

# FCC RADIO TEST REPORT


FCC ID : 2AJN7-TP00109A  
Equipment : Notebook Computer  
Brand Name : Lenovo  
Model Name : TP00109A  
Applicant : LC Future Center Limited Taiwan Branch  
7F., No. 780, Bei'an Rd., Zhongshan Dist.,  
Taipei City 104, Taiwan (R.O.C.)  
Manufacturer : LC Future Center Limited Taiwan Branch  
7F., No. 780, Bei'an Rd., Zhongshan Dist.,  
Taipei City 104, Taiwan (R.O.C.)  
Standard : FCC 47 CFR Part 2, 90(R)

Equipment: Fibocom L860-GL and Intel 9560D2W tested inside of Lenovo Notebook Computer.

The product was received on Mar. 13, 2019 and testing was started from Mar. 23, 2019 and completed on Mar. 28, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this partial report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Jones Tsai

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**  
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

## Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
<b>1 General Description .....</b>	<b>5</b>
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	5
1.3 Modification of EUT .....	5
1.4 Testing Site .....	6
1.5 Applied Standards .....	6
<b>2 Test Configuration of Equipment Under Test .....</b>	<b>7</b>
2.1 Test Mode.....	7
2.2 Connection Diagram of Test System.....	7
2.3 Support Unit used in test configuration and system .....	8
2.4 Frequency List of Low/Middle/High Channels .....	8
<b>3 Conducted Test Items .....</b>	<b>9</b>
3.1 Measuring Instruments .....	9
3.2 Conducted Output Power Measurement and ERP .....	10
<b>4 Radiated Test Items .....</b>	<b>11</b>
4.1 Measuring Instruments .....	11
4.2 Radiated Spurious Emission .....	12
<b>5 List of Measuring Equipment.....</b>	<b>13</b>
<b>6 Uncertainty of Evaluation .....</b>	<b>14</b>
<b>Appendix A. Test Results of Conducted Test</b>	
<b>Appendix B. Test Results of ERP and Radiated Test</b>	
<b>Appendix C. Test Setup Photographs</b>	



## History of this test report

Report No.	Version	Description	Issued Date
FG931312E	01	Initial issue of report	May 02, 2019

## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Reporting only	-
	§90.542 (a)(7)	Effective Radiated Power	Pass	-
4.2	§2.1053 §90.543 (e)(3) §90.543 (f)	Radiated Spurious Emission	Pass	Under limit 2.25 dB at 1576.000 MHz

<b>Declaration of Conformity:</b>
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
<b>Comments and Explanations:</b>
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

**Reviewed by: Wii Chang**

**Report Producer: Polly Tsai**

# 1 General Description

## 1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Notebook Computer
Brand Name	Lenovo
Model Name	TP00109A
FCC ID	2AJN7-TP00109A
Sample 1	EUT with Amphenol Antenna
Sample 2	EUT with SPEEDWIRE Antenna
EUT supports Radios application	WCDMA/HSPA/LTE/GNSS WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80/VHT160 Bluetooth BR/EDR/LE
EUT Stage	Production Unit

### Remark:

1. The above EUT's information was declared by manufacturer.
2. Equipment: Fibocom L860-GL and Intel 9560D2W tested inside of Lenovo Notebook Computer.
3. All test items were performed with Sample 2.

Antenna Information				
WWAN				3G&LTE (dBi)
Antenna 1	Manufacturer	Amphenol	Peak gain	1.12
	Part number	LXA113-16-000-C	Type	PIFA
Antenna 2	Manufacturer	SPEEDWIRE	Peak gain	1.63
	Part number	F.0G.ZV-0009-001-00	Type	PIFA

## 1.2 Product Specification of Equipment Under Test

Product Feature	
Tx Frequency	LTE Band 14 :790.5 MHz ~ 795.5 MHz
Rx Frequency	LTE Band 14 :760.5 MHz ~ 765.5 MHz
Bandwidth	5MHz / 10MHz
Maximum Output Power to Antenna	22.51 dBm
Type of Modulation	QPSK / 16QAM / 64QAM

## 1.3 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.4 Testing Site

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)
Test Site No.	<b>Sporton Site No.</b>
	TH05-HY
Test Engineer	Lemon Su
Temperature	23°C
Relative Humidity	58%

**Note:** The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)
Test Site No.	<b>Sporton Site No.</b>
	03CH12-HY
Test Engineer	Jack Cheng, Lance Chiang, and Chuan Chu
Temperature	23~24°C
Relative Humidity	63~66%

**Note:** The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW0007

## 1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ 47 CFR Part 2, Part 90(R)
- ♦ ANSI / TIA-603-E
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.


## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Conducted Test Cases	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	14	-	-	V	V	-	-	V	V	V	V	V	V	V	V	V
E.R.P	14	-	-	V	V	-	-	V	V	V	V			V	V	V
Radiated Spurious Emission	14	Worst Case											V	V	V	
Remark	1. The mark “V ” means that this configuration is chosen for testing 2. The mark “-” means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 4. All the radiated test cases were performed with Adapter 3.															

### 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Earphone	zyia	N/A	N/A	Unshielded, 1.2 m	N/A

## 2.4 Frequency List of Low/Middle/High Channels

LTE Band 14 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	-	23330	-
	Frequency	-	793	-
5	Channel	23305	23330	23355
	Frequency	790.5	793	795.5




### 3 Conducted Test Items

#### 3.1 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.1 Test Setup

##### 3.1.2 Conducted Output Power



##### 3.1.3 Test Result of Conducted Test

Please refer to Appendix A.

## 3.2 Conducted Output Power Measurement and ERP

### 3.2.1 Description of the Conducted Output Power Measurement and ERP Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 14.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$ ,  $ERP = EIRP - 2.15$ , where

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB

### 3.2.2 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.


## 4 Radiated Test Items

### 4.1 Measuring Instruments


See list of measuring instruments of this test report.

#### 4.1.1 Test Setup

For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



#### 4.1.2 Test Result of Radiated Test

Please refer to Appendix B.

## 4.2 Radiated Spurious Emission

### 4.2.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 4.2.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 5.8 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from  $43 + 10\log(P)$ dB below the transmitter power P(Watts)



## 5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
LTE Base Station	Anritsu	MT8820C	6201432821	-	Oct. 14, 2018	Mar. 28, 2019	Oct. 13, 2019	Conducted (TH05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 07, 2019	Mar. 23, 2019~ Mar. 28, 2019	Jan. 06, 2020	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	37059&01	30MHz~1GHz	Oct. 13, 2018	Mar. 23, 2019~ Mar. 28, 2019	Oct. 12, 2019	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1328	1GHz ~ 18GHz	Oct. 19, 2018	Mar. 23, 2019~ Mar. 28, 2019	Oct. 18, 2019	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	May 21, 2018	Mar. 23, 2019~ Mar. 28, 2019	May 20, 2019	Radiation (03CH12-HY)
Preamplifier	Jet-Power	JPA0118-55-303K	1710001800054002	1GHz~18GHz	Apr. 17, 2018	Mar. 23, 2019~ Mar. 28, 2019	Apr. 16, 2019	Radiation (03CH12-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 06, 2018	Mar. 23, 2019~ Mar. 28, 2019	Dec. 05, 2019	Radiation (03CH12-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100390	20Hz~26.5GHz	Dec. 26, 2018	Mar. 23, 2019~ Mar. 28, 2019	Dec. 25, 2019	Radiation (03CH12-HY)
Signal Generator	Rohde & Schwarz	SMF100A	101107	100kHz~40GHz	May 21, 2018	Mar. 23, 2019~ Mar. 28, 2019	May 20, 2019	Radiation (03CH12-HY)
Filter	Wainwright	WLK4-1000-1530-6000-40SS	SN11	1 GHz Low pass	Sep. 16, 2018	Mar. 23, 2019~ Mar. 28, 2019	Sep. 15, 2019	Radiation (03CH12-HY)
Filter	Wainwright	WHKX12-1080-1200-1500-60SS	SN2	1.2G High Pass	Sep. 16, 2018	Mar. 23, 2019~ Mar. 28, 2019	Sep. 15, 2019	Radiation (03CH12-HY)
Filter	Wainwright	WHKX12-2700-3000-18000-60ST	SN3	3GHz High Pass	Jul. 05, 2018	Mar. 23, 2019~ Mar. 28, 2019	Jul. 04, 2019	Radiation (03CH12-HY)
Filter	Woken	WHKX8-5272.5-6750-18000-40ST	SN2	6.75G High pass	Sep. 17, 2018	Mar. 23, 2019~ Mar. 28, 2019	Sep.16, 2019	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0058/126E	30M-18G	Mar. 13, 2019	Mar. 23, 2019~ Mar. 28, 2019	Mar. 12, 2020	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30M~40GHz	Oct. 16, 2018	Mar. 23, 2019~ Mar. 28, 2019	Oct. 15, 2019	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30M~40GHz	Oct. 16, 2018	Mar. 23, 2019~ Mar. 28, 2019	Oct. 15, 2019	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Mar. 23, 2019~ Mar. 28, 2019	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Mar. 23, 2019~ Mar. 28, 2019	N/A	Radiation (03CH12-HY)
Software	Audix	E3 6.2009-8-24	RK-000989	N/A	N/A	Mar. 23, 2019~ Mar. 28, 2019	N/A	Radiation (03CH12-HY)

## 6 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	3.36
--	------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	3.70
--	------

### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	3.98
--	------



## Appendix A. Test Results of Conducted Test

### Conducted Output Power(Average power)

LTE Band 14 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	-	22.51	-
10	1	25			22.38	
10	1	49			22.47	
10	25	0			21.46	
10	25	12			21.39	
10	25	25			21.41	
10	50	0			21.43	
10	1	0	16-QAM		21.95	
10	1	25			21.61	
10	1	49			21.70	
10	25	0			20.64	
10	25	12			20.50	
10	25	25			20.56	
10	50	0			20.43	
10	1	0	64-QAM		20.95	
10	1	25			20.98	
10	1	49			20.92	
10	25	0			19.76	
10	25	12			19.77	
10	25	25			19.98	
10	50	0			19.78	
5	1	0	QPSK	22.39	22.40	22.26
5	1	12		22.43	22.39	22.44
5	1	24		22.40	22.37	22.47
5	12	0		21.48	21.44	21.28
5	12	7		21.52	21.35	21.26
5	12	13		21.43	21.50	21.52
5	25	0		21.66	21.35	21.36
5	1	0	16-QAM	21.53	21.97	21.62
5	1	12		21.80	21.53	21.94
5	1	24		21.67	21.95	21.98
5	12	0		20.43	20.65	20.57
5	12	7		20.51	20.59	20.51
5	12	13		20.43	20.64	20.60
5	25	0		20.46	20.49	20.54
5	1	0	64-QAM	20.94	20.94	20.96
5	1	12		20.90	20.98	20.90
5	1	24		20.84	20.99	20.94
5	12	0		19.68	19.91	19.85
5	12	7		19.63	19.89	19.87
5	12	13		19.92	19.69	19.73
5	25	0		19.67	19.73	19.87

**Appendix B. Test Results of ERP and Radiated Test****ERP**

LTE Band 14 / 5MHz (Average) (GT - LC = 1 dB)							
Channel	Mode	RB		Conducted		ERP	
		Size	Offset	Power (dBm)	Power (Watts)	ERP(dBm)	ERP(W)
Lowest	QPSK	1	24	22.40	0.1738	21.25	0.1334
Middle		1	24	22.37	0.1726	21.22	0.1324
Highest		1	24	22.47	0.1766	21.32	0.1355
Lowest	16QAM	1	24	21.67	0.1469	20.52	0.1127
Middle		1	24	21.95	0.1567	20.80	0.1202
Highest		1	24	21.98	0.1578	20.83	0.1211
Lowest	64QAM	1	24	20.84	0.1213	19.69	0.0931
Middle		1	24	20.99	0.1256	19.84	0.0964
Highest		1	24	20.94	0.1242	19.79	0.0953
Limit	ERP < 3W			Result		PASS	

LTE Band 14 / 10MHz (Average) (GT - LC = 1 dB)							
Channel	Mode	RB		Conducted		ERP	
		Size	Offset	Power (dBm)	Power (Watts)	ERP(dBm)	ERP(W)
Lowest	QPSK	-	-	-	-	-	-
Middle		1	0	22.51	0.1782	21.36	0.1368
Highest		-	-	-	-	-	-
Lowest	16QAM	-	-	-	-	-	-
Middle		1	0	21.95	0.1567	20.80	0.1202
Highest		-	-	-	-	-	-
Lowest	64QAM	-	-	-	-	-	-
Middle		1	25	20.98	0.1253	19.83	0.0962
Highest		-	-	-	-	-	-
Limit	ERP < 3W			Result		PASS	



**Radiated Spurious Emission****LTE Band 14**

LTE Band 14 / 5MHz / QPSK									
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1584	-45.36	-42.15	-3.21	-55.44	-50.73	0.90	8.42	H
	2376	-36.91	-13	-23.91	-51.40	-44.16	1.12	10.53	H
	3162	-53.76	-13	-40.76	-69.62	-62.00	1.30	11.69	H
									H
	1584	-46.49	-42.15	-4.34	-56.10	-51.86	0.90	8.42	V
	2376	-40.94	-13	-27.94	-55.20	-48.19	1.12	10.53	V
	3162	-53.39	-13	-40.39	-69.69	-61.63	1.30	11.69	V
									V
Middle	1592	-45.64	-42.15	-3.49	-55.57	-51.04	0.90	8.45	H
	2384	-38.29	-13	-25.29	-52.77	-45.55	1.12	10.54	H
	3172	-54.35	-13	-41.35	-70.23	-62.61	1.30	11.71	H
									H
	1592	-46.54	-42.15	-4.39	-56.12	-51.94	0.90	8.45	V
	2384	-41.79	-13	-28.79	-56.12	-49.05	1.12	10.54	V
	3172	-53.96	-13	-40.96	-70.31	-62.22	1.30	11.71	V
									V
Highest	1592	-46.56	-42.15	-4.41	-56.49	-51.96	0.90	8.45	H
	2392	-39.49	-13	-26.49	-53.85	-46.76	1.13	10.55	H
	3182	-54.69	-13	-41.69	-70.57	-62.97	1.30	11.74	H
									H
	1592	-48.27	-42.15	-6.12	-57.85	-53.67	0.90	8.45	V
	2392	-42.41	-13	-29.41	-56.73	-49.68	1.13	10.55	V
	3182	-54.32	-13	-41.32	-70.67	-62.60	1.30	11.74	V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



LTE Band 14 / 10MHz / QPSK									
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1576	-44.40	-42.15	-2.25	-54.47	-49.74	0.90	8.39	H
	2368	-36.34	-13	-23.34	-50.95	-43.58	1.12	10.52	H
	3172	-54.51	-13	-41.51	-70.39	-62.77	1.30	11.71	H
									H
	1576	-46.81	-42.15	-4.66	-56.41	-52.15	0.90	8.39	V
	2368	-38.17	-13	-25.17	-52.52	-45.41	1.12	10.52	V
	3172	-53.75	-13	-40.75	-70.1	-62.01	1.30	11.71	V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.