

FCC Test Report

Report No.: AGC1690950301FE01

FCC ID 2BN9AUV8000

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: Amateur Radio

BRAND NAME : Bintolk, BinTe radio

MODEL NAME : RT-900, UV8000, UV8100, UV8200, UV8300, UV8500,

UV8600, UV8700, UV8800, UV8900, UV9000

APPLICANT: Quanzhou Binte Electronic Technology Co., Ltd.

DATE OF ISSUE : Apr. 07, 2025

STANDARD(S) : FCC Part 15 Subpart B

REPORT VERSION: V1.0

Attestation of Global Chence (Shenzhen) Co., Ltd



Page 2 of 21

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Apr. 07, 2025	Valid	Initial Release







Table of Contents

1. General Information	4
2. Product Information	5
2.1 Product Technical Description	5
2.2 Auxiliary Surrounding Description	5
2.2 Test Methodology	6
2.3 Description of Test Modes	6
3. Test Environment	7
3.1 Address of The Test Laboratory	7
3.2 Test Facility	7
3.3 Environmental Conditions	8
3.4 Measurement Uncertainty	8
3.5 List of Equipment Used	<u>e</u>
4. Summary of Test Results	10
5. Radiated Emission Measurements	11
5.1 Provisions Applicable	11
5.2 Measurement Setup	11
5.3 Measurement Procedure	12
5.4 Measurement Resul	13
6. Conducted Emission Measurements	17
6.1 Provisions Applicable	17
6.2 Measurement Setup	17
6.3 Measurement Procedure	18
6.4 Measurement Result	19
Appendix I: Photographs of Test Setup	21
Appendix II: Photographs of Test EUT	21





1. General Information

Quanzhou Binte Electronic Technology Co., Ltd.	
No. 1 Industrial Road, Chengbei Industrial Zone, Luocheng Town, Hui'an County Quanzhou City, Fujian Province,China	
Quanzhou Binte Electronic Technology Co., Ltd.	
No. 1 Industrial Road, Chengbei Industrial Zone, Luocheng Town, Hui'an County, Quanzhou City, Fujian Province, China	
Quanzhou Binte Electronic Technology Co., Ltd.	
No. 1 Industrial Road, Chengbei Industrial Zone, Luocheng Town, Hui'an County, Quanzhou City, Fujian Province, China	
Amateur Radio	
Bintolk, BinTe radio	
RT-900	
UV8000, UV8100, UV8200, UV8300, UV8500, UV8600, UV8700, UV8800, UV8900, UV9000	
All the same except for model name, Keypad PCB board and front shell style design	
Mar. 03, 2025	
Apr. 07, 2025	
No any deviation from the test method	
Normal	
Pass	
AGCTR-ER-FCC-CSR-V1.0	

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By	Bibo zhang	
	Bibo Zhang (Project Engineer)	Apr. 07, 2025
Reviewed By	Colvin Lin	
	Calvin Liu (Reviewer)	Apr. 07, 2025
Approved By	Angole li	
	Angela Li (Authorized Officer)	Apr. 07, 2025



Page 5 of 21

2. Product Information

2.1 Product Technical Description

Housing Type	Plastic and metal
Receive Frequency Range	0-999MHz
Highest Operating Frequency	☑Greater than 108MHz ☐Less than 108MHz
Equipment Type	Table-Top
Hardware Version	V1.0
Software Version	V1.0
Power Supply	DC 7.4V 2200mAh by battery or DC 5V from adapter

I/O Port of EUT				
I/O Port Type	Q'TY	Cable	Tested with	
Earphone Port	1	0	1	
Type C Port	1	0	1	

2.2 Auxiliary Surrounding Description

The Following Peripheral Devices and Interface Cables Were Connected During the Measurement:

☐ Test Accessories Come From The Laboratory

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1	Adapter	Huawei	HW-200440C00	AC100-240V,50-60Hz,0.35A, DC5V/3A	1.0m unshielded

☐ Test Accessories Come From The Manufacturer

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1	Battery	18650	Quanzhou Binte Electronic Technology Co., Ltd.	DC 7.4V 2200mAh	N/A



Page 6 of 21

2.2 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 15	Radio Frequency Devices
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

2.3 Description of Test Modes

No.	Test Mode	Remark
1	Receiving at low channel of 0 to 999 MHz	Worst
2	Receiving at middle channel of 0 to 999 MHz	
3	Receiving at high channel of 0 to 999 MHz	

Note: Only the result of the worst case was recorded in the report.



Page 7 of 21

3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



Page 8 of 21

3.3 Environmental Conditions

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106

3.4 Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

ancontainty mattiplied by a coverage laster of it 2, prov	iding a level of confidence of approximately coron
Item	Measurement Uncertainty
Uncertainty of Conducted Emission	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$



Page 9 of 21

3.5 List of Equipment Used

•	Radiated Emiss	sion					
Used	Equipment No.	Test Equipment	Test Equipment Manufacturer Model No. Serial No		Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
\boxtimes	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2025-01-14	2026-01-13
\boxtimes	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23
\boxtimes	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10
\boxtimes	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2025-03-29	2026-03-28
\boxtimes	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23

•	AC Power Line Conducted Emission												
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)						
\boxtimes	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2024-05-28	2025-05-27						
\boxtimes	AGC-EM-A130	6dB Attenuator	Eeatsheep	LM-XX-6-5W	DC-6GZ	2023-06-09	2025-06-08						
\boxtimes	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2024-05-28	2025-05-27						

Te	Test Software												
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information								
\boxtimes	AGC-EM-S004	RE Test System	Tonscend	TS ⁺ Ver2.1(JS32-RE)	4.0.0.0								
	AGC-EM-S003	RE Test System	FARA	EZ-EMC	V.RA-03A								
\boxtimes	AGC-EM-S011	RSE Test System	Tonscend	TS ⁺ Ver2.1(JS36-RSE)	4.0.0.0								
	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71								



Page 10 of 21

4. Summary of Test Results

Item	FCC Rules	Description Of Test	Class/Severity	Result
1	Section 15.107	Radiated Emission	Class B	Pass
2	Section 15.109	Conducted Emission	Class B	Pass




5. Radiated Emission Measurements

5.1 Provisions Applicable


FCC CFR Title 47 Part 15 Subpart B Section 15.109:

Frequency Range	Class B Limit (dBuV/m @3m)	Class A Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	50.00	Quasi-peak
88MHz-216MHz	43.50	53.50	Quasi-peak
216MHz-960MHz	46.00	56.00	Quasi-peak
960MHz-1GHz	54.00	64.00	Quasi-peak
Above 1GHz	54.00	60.00	Average
Above IGHZ	74.00	80.00	Peak

5.2 Measurement Setup



Radiated Emission Measurements Test Setup for 30MHz to 1GHz



Radiated Emission Measurements Test Setup for above 1GHz



Page 12 of 21


5.3 Measurement Procedure

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. The EUT received power by AC 120V/60Hz.
- 5. The antenna was placed at 3 meter away from the EUT as stated in FCC Part 15. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
- 6. The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 7. The test mode(s) were scanned during the test:
- 8. Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and Q.P./Peak reading is presented. For emissions below 1GHz, use 120KHz RBW and VBW>=3RBW for QP reading.
- 9. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 10. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 11. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the guasi-peak method for below 1GHz.
- 12. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 13. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.
- 14. The test data of the worst case condition (mode 1) was reported on the following Data page.

EMI Test Receiver Setup:


During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Abovo 1 CHz	1MHz	3 MHz	/	PK
Above 1 GHz	1MHz	10 Hz	/	Ave.







5.4 Measurement Resul




RESULT: PASS








RESULT: PASS









Final Data List

NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1247.04941	33.71	-17.95	74.00	40.29	100	210	Vertical
2	1716.143229	36.35	-15.76	74.00	37.65	100	260	Vertical
3	2566.313263	39.70	-12.17	74.00	34.30	100	80	Vertical
4	3266.453291	37.19	-11.26	74.00	36.81	100	240	Vertical
5	3904.580916	38.03	-10.10	74.00	35.97	100	150	Vertical
6	5574.914983	41.29	-6.66	74.00	32.71	100	100	Vertical

RESULT: PASS







Final Data List

NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1252.05041	33.83	-17.93	74.00	40.17	100	100	Horizontal
2	1600.120024	35.52	-16.71	74.00	38.48	100	70	Horizontal
3	2142.228446	38.12	-13.06	74.00	35.88	100	30	Horizontal
4	3113.422685	37.46	-11.66	74.00	36.54	100	210	Horizontal
5	4243.64873	38.06	-8.95	74.00	35.94	100	180	Horizontal
6	5741.94839	41.57	-6.16	74.00	32.43	100	140	Horizontal

RESULT: PASS

Note:

- 1. Factor=Antenna Factor + Cable loss Amplifier gain, Margin= -Limit-Measurement.
- 2. The "Factor" value can be calculated automatically by software of measurement system.



Page 17 of 21

6. Conducted Emission Measurements

6.1 Provisions Applicable

FCC CFR Title 47 Part 15 Subpart B Section 15.107:


For Class B Limits:

Fraguenay	Maximum RF	Line Voltage
Frequency	Q.P. (dBμV)	Average (dBµV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

For Class A Limits:

Fraguenay	Maximum RF Line Voltage						
Frequency	Q.P. (dBµV)	Average (dBµV)					
150kHz~500kHz	79	66					
500kHz~30MHz	73	60					

6.2 Measurement Setup





Page 18 of 21

6.3 Measurement Procedure

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. The EUT received AC 120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5. All support equipment received AC power from a second LISN, if any.
- 6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. A conducted emission is calculated by the following equation:
 - Measurement Level (dBµV) = Receiver reading (dBµV) + Transd (dB)
 - Transd (dB)= AMN Factor(dB)+Cable Loss(dB)+Attenuation(dB)
 - Margin= Limit-Level
- 10. The test data of the worst case condition (Mode 1) was reported on the following Data page.



6.4 Measurement Result

	_										1								
t Mode	M	ode 1									LISN Line						Hot Side		
																	1		
Lev	el [dE	βµV]																	
80 F	_i				_i		-,					,							
70 -	;		·			¦-	-¦	-		. _				╣	-				
60			<u> </u>	. <u>L</u>	 		-	<u> </u>		.	!		-	!				!	
50			_		- !		-!	1-1						!				!	
40 -			!		 	+	+	++		!	+		-						
	:						-											1	
30 5	w/	Mora	mm	month	A.W.	М.,	, miles	<u> </u>	na di dingena di di	·i	·						أأأ أأأسا		
20	~~~		·	~~~	+	X.	-1-	+ - F	X	- Mary and property and			and the co	المال	adh			Halabidigi	
10 -	Ì		. <u>i</u>	- 	<u> </u>	<u> </u> -	-	ļ-Ļ		-	4	لــ	-	3-1		علىلسلسا			
0-			<u></u>			¦-				<u></u>	-				ii	 -			
-10			!	!		_				!		-		1				1	
1 1	50k	30	00k 4	00k	60	Ok (B00k	11		?M iency [H:	3M	4M	5M 6	6M	8M	10M	2	0M 30M	

MEASUREMENT RESULT: "agc fin"


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.650000	19.10	6.2	56	36.9	QP	L1
1.174000	20.50	6.2	56	35.5	QP	L1
23.446000	26.00	7.7	60	34.0	QP	L1
25.970000	30.00	8.0	60	30.0	QP	L1
27.634000	30.40	8.2	60	29.6	QP	L1
29.302000	26.40	8.3	60	33.6	QP	L1

MEASUREMENT RESULT: "agc_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
21.762000 23.446000 25.118000 25.962000 27.626000	11.00 17.40 6.10 24.60 14.60	7.4 7.7 8.0 8.0	50 50 50 50	32.6 43.9 25.4 35.4	AV AV	L1 L1 L1 L1
29.302000	12.80	8.3	50	37.2	AV	L1

RESULT: PASS





MEASUREMENT RESULT: "agc_fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.778000	25.50	6.2	56	30.5	QP	N
20.958000	29.70	7.3	60	30.3	QP	N
22.642000	28.10	7.6	60	31.9	QP	N
25.162000	32.30	8.0	60	27.7	QP	N
26.818000	29.30	8.1	60	30.7	QP	N
29.350000	32.60	8.3	60	27.4	QP	N

MEASUREMENT RESULT: "agc_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
20.954000	20.20	7.3	50	29.8	AV	N
22.646000	17.50	7.6	50	32.5	AV	N
25.138000	19.10	8.0	50	30.9	AV	N
25.162000	24.00	8.0	50	26.0	AV	N
26.818000	15.50	8.1	50	34.5	AV	N
29.342000	23.80	8.3	50	26.2	AV	N

RESULT: PASS



Page 21 of 21

Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC1690950301AP01

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC1690950301AP01

----End of Report----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.