




# TEST REPORT

Report Reference No. .... : CHTEW19020099 Report verification: 

Project No. .... : SHT1812060301EW

FCC ID. .... : ZSW-30-079

Applicant's name ..... : b mobile HK Limited

Address ..... : Flat 18; 14/F Block 1; Golden Industrial Building; 16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong

Manufacturer ..... : b mobile HK Limited

Address ..... : Flat 18; 14/F Block 1; Golden Industrial Building; 16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong

Test item description ..... : Mobile Phone

Trade Mark ..... : Bmobile

Model/Type reference ..... : AX1077

Listed Model(s) ..... : -

Standard ..... : FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of receipt of test sample ..... : Dec 27, 2018

Date of testing ..... : Dec 28, 2018- Feb 21, 2019

Date of issue ..... : Feb 22, 2019

Result ..... : PASS

Compiled by  
( position+printedname+signature).... : File administrators Silvia Li

Supervised by  
(position+printedname+signature).... : Project Engineer Aaron Fang

Approved by  
(position+printedname+signature).... : RF Manager Hans Hu

*Silvia Li*

*Aaron Fang*

*Hans Hu*

Testing Laboratory Name ..... : Shenzhen Huatongwei International Inspection Co., Ltd.

Address ..... : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

**Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

*The test report merely correspond to the test sample.*

## Contents

<b><u>1.</u></b>	<b><u>TEST STANDARDS AND REPORT VERSION</u></b>	<b><u>3</u></b>
1.1.	Test Standards	3
1.2.	Report version	3
<b><u>2.</u></b>	<b><u>TEST DESCRIPTION</u></b>	<b><u>4</u></b>
<b><u>3.</u></b>	<b><u>SUMMARY</u></b>	<b><u>5</u></b>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Operation state	6
3.4.	EUT configuration	6
3.5.	Modifications	6
<b><u>4.</u></b>	<b><u>TEST ENVIRONMENT</u></b>	<b><u>7</u></b>
4.1.	Address of the test laboratory	7
4.2.	Test Facility	7
4.3.	Environmental conditions	8
4.4.	Statement of the measurement uncertainty	8
4.5.	Equipments Used during the Test	9
<b><u>5.</u></b>	<b><u>TEST CONDITIONS AND RESULTS</u></b>	<b><u>11</u></b>
5.1.	Antenna requirement	11
5.2.	Conducted Emissions (AC Main)	12
5.3.	Conducted Peak Output Power	15
5.4.	Power Spectral Density	16
5.5.	6dB bandwidth	20
5.6.	Restricted band	24
5.7.	Band edge and Spurious Emissions (conducted)	28
5.8.	Spurious Emissions (radiated)	41
<b><u>6.</u></b>	<b><u>TEST SETUP PHOTOS</u></b>	<b><u>47</u></b>
<b><u>7.</u></b>	<b><u>EXTERANAL AND INTERNAL PHOTOS</u></b>	<b><u>48</u></b>

## 1. TEST STANDARDS AND REPORT VERSION

### 1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10:2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 558074 D01 15.247 Meas Guidance v05](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

### 1.2. Report version

Revision No.	Date of issue	Description
N/A	2019-02-22	Original

## 2. TEST DESCRIPTION

Test Item	FCC Rule	Result	Test Engineer
Antenna requirement	15.203/15.247(c)	PASS	Xiaokang Tan
Line Conducted Emissions (AC Main)	15.207	PASS	Tony Duan
Conducted Peak Output Power	15.247(b)(3)	PASS	Xiaokang Tan
Power Spectral Density	15.247(e)	PASS	Xiaokang Tan
6dB Bandwidth	15.247(a)(2)	PASS	Xiaokang Tan
Restricted band	15.247(d)/15.205	PASS	Shower Dai
Spurious Emissions	15.247(d)/15.209	PASS	Shower Dai

Note: The measurement uncertainty is not included in the test result.

### 3. SUMMARY

#### 3.1. Client Information

Applicant:	b mobile HK Limited
Address:	Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong
Manufacturer:	b mobile HK Limited
Address:	Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong

#### 3.2. Product Description

Name of EUT:	Mobile Phone
Trade Mark:	Bmobile
Model No.:	AX1077
Listed Model(s):	-
IMEI:	Conducted: 867400020317123 Radiated: 867400020317115
Power supply:	DC3.8V
Adapter information:	Input:100-240Va.c. 50/60Hz 0.2A Output:5.0Vd.c. 1000mA
Hardware version:	V1.0
Software version:	Bmobile_AX1077_TIGO_LTM_V005
<b>WIFI</b>	
Supported type:	802.11b/802.11g/802.11n(HT20)
Modulation:	DSSS for 802.11b OFDM for 802.11g/802.11n(HT20)
Operation frequency:	2412MHz~2462MHz
Channel number:	11
Channel separation:	5MHz
Antenna type:	FPC Antenna
Antenna gain:	0.5dBi

### 3.3. Operation state

#### ➤ Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

802.11b/g/n(HT20)	
Channel	Frequency (MHz)
01	2412
02	2417
...	...
06	2437
...	...
10	2457
11	2462

#### ➤ Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit (duty cycle>98%).
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated suprious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit(duty cycle>98%). The EUT in each of three orthogonal axis emissions had been tested ,but only the worst case (X axis) data Recorded in the report.

### 3.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

○	/	Manufacturer:	/
		Model No.:	/
○	/	Manufacturer:	/
		Model No.:	/

### 3.5. Modifications

No modifications were implemented to meet testing criteria.

## **4. TEST ENVIRONMENT**

### **4.1. Address of the test laboratory**

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

### **4.2. Test Facility**

#### **CNAS-Lab Code: L1225**

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

#### **A2LA-Lab Cert. No.: 3902.01**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### **FCC-Registration No.: 762235**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files.

#### **IC-Registration No.:5377B-1**

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No.: 5377B-1.

#### **ACA**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

### 4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

### 4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors in calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd. quality system according to ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Here after the best measurement capability for Shenzhen Huatongwei International Inspection Co., Ltd. is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.63 dB	(1)
Conducted spurious emissions 9kHz~40GHz	0.63 dB	(1)
Conducted Disturbance 150kHz~30MHz	3.35 dB	(1)
Radiated Emissions below 1GHz	4.28 dB	(1)
Radiated Emissions above 1GHz	5.16 dB	(1)
Occupied Bandwidth	69 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=1.96$ .



#### 4.5. Equipments Used during the Test

Conducted Emissions						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	EMI Test Receiver	R&S	ESCI	101247	10/27/2018	10/26/2019
2	Artificial Mains	SCHWARZBECK	NNLK 8121	573	10/27/2018	10/26/2019
3	Pulse Limiter	R&S	ESH3-Z2	101488	10/27/2018	10/26/2019
4	RF Connection Cable	HUBER+SUHNER	EF400	N/A	11/14/2017	11/13/2019
5	Test Software	R&S	ES-K1	N/A	N/A	N/A
6	Temperature and Humidity Meter	MIAOXIN	TH10R	N/A	10/30/2018	10/29/2019

Radiated Emissions(Below 1GHz)						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	Semi-Anechoic Chamber	Albatross projects	SAC-3m-02	C11121	09/30/2018	09/29/2021
2	EMI Test Receiver	R&S	ESCI	100900	10/28/2018	10/27/2019
3	Loop Antenna	R&S	HFH2-Z2	100020	04/02/2018	04/02/2021
4	Ultra-Broadband Antenna	SCHWARZBECK	VULB9163	546	04/05/2017	04/04/2020
5	RF Connection Cable	HUBER+SUHNER	N/A	N/A	09/28/2018	09/27/2019
6	RF Connection Cable	HUBER+SUHNER	SUCOFLEX104	501184/4	09/28/2018	09/27/2019
7	Test Software	R&S	ES-K1	N/A	N/A	N/A
8	Turntable	Maturo Germany	TT2.0-1T	N/A	N/A	N/A
9	Antenna Mast	Maturo Germany	TAM-4.0-P	N/A	N/A	N/A
10	Temperature and Humidity Meter	KEJIAN	KJ03	N/A	10/30/2018	10/29/2019

Radiated Emissions(Above 1GHz)						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	Anechoic Chamber	Albatross projects	SAC-3m-01	C11121	09/30/2018	09/29/2021
2	Horn Antenna	SCHWARZBECK	9120D	1011	03/27/2017	03/26/2020
3	Preamplifier	BONN	BLWA0160-2M	1811887	11/14/2018	11/13/2019
4	Pre-amplifier	SCHWARZBECK	BBV 9743	9743-0022	10/17/2018	10/16/2019
5	Broadband Pre-amplifier	SCHWARZBECK	BBV 9718	9718-248	04/28/2018	04/27/2019
6	Spectrum Analyzer	R&S	FSP40	100597	10/27/2018	10/26/2019
7	RF Connection Cable	HUBER+SUHNER	RE-7-FL	N/A	11/15/2018	11/14/2019
8	RF Connection Cable	HUBER+SUHNER	RE-7-FH	N/A	11/15/2018	11/14/2019
9	Test Software	Audix	E3	N/A	N/A	N/A
10	Turntable	Maturo Germany	TT2.0-1T	N/A	N/A	N/A
11	Antenna Mast	Maturo Germany	CAM-4.0-P-12	N/A	N/A	N/A
12	Temperature and Humidity Meter	MINGLE	YH101	N/A	10/30/2018	10/29/2019

RF Conducted Test						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	Spectrum Analyzer	R&S	FSV40	100048	10/28/2018	10/27/2019
2	EXA Signal Analyzer	Agilent	N9020A	MY5050187	09/29/2018	09/28/2019
3	Power Meter	Anritsu	ML249A	N/A	09/29/2018	09/28/2019
4	OSP	R&S	OSP120	101317	N/A	N/A

## 5. TEST CONDITIONS AND RESULTS

### 5.1. Antenna requirement

#### REQUIREMENT:

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):**

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

#### TEST RESULTS

☒ Passed      ☐ Not Applicable

The directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



## 5.2. Conducted Emissions (AC Main)


### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

### TEST MODE:

Please refer to the clause 3.3

### TEST RESULTS


☒ Passed      ☐ Not Applicable

Note:

- 1) Transd=Cable lose+ Pulse Limiter Factor + Artificial Mains Factor
- 2) Margin= Limit -Level

Test Line:

L

**MEASUREMENT RESULT: "GM1902185036\_fin"**

2/18/2019 4:37PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.294000	42.50	10.2	60	17.9	QP	L1	GND
0.411000	49.80	10.1	58	7.8	QP	L1	GND
0.964500	41.20	9.9	56	14.8	QP	L1	GND
2.557500	38.00	10.0	56	18.0	QP	L1	GND
6.094500	32.70	10.0	60	27.3	QP	L1	GND
12.484500	31.50	10.2	60	28.5	QP	L1	GND


**MEASUREMENT RESULT: "GM1902185036\_fin2"**

2/18/2019 4:37PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.280500	35.60	10.2	51	15.2	AV	L1	GND
0.402000	35.60	10.1	48	12.2	AV	L1	GND
0.465000	37.30	10.1	47	9.3	AV	L1	GND
1.563000	30.10	10.0	46	15.9	AV	L1	GND
2.481000	30.00	10.0	46	16.0	AV	L1	GND
6.508500	24.00	10.0	50	26.0	AV	L1	GND

Test Line:

N

**MEASUREMENT RESULT: "GM1902185037\_fin"**

2/18/2019 4:40PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.285000	38.80	10.2	61	21.9	QP	N	GND
0.469500	43.90	10.1	57	12.6	QP	N	GND
0.856500	36.90	9.9	56	19.1	QP	N	GND
2.436000	34.20	10.0	56	21.8	QP	N	GND
5.941500	28.40	10.0	60	31.6	QP	N	GND
13.771500	27.90	10.2	60	32.1	QP	N	GND

**MEASUREMENT RESULT: "GM1902185037\_fin2"**

2/18/2019 4:40PM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.285000	27.90	10.2	51	22.8	AV	N	GND
0.474000	29.30	10.1	46	17.1	AV	N	GND
1.140000	23.40	10.0	46	22.6	AV	N	GND
4.182000	23.70	10.0	46	22.3	AV	N	GND
5.230500	18.80	10.0	50	31.2	AV	N	GND
23.068500	21.70	10.4	50	28.3	AV	N	GND

### 5.3. Conducted Peak Output Power

#### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): 30dBm

#### TEST CONFIGURATION



#### TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10: 2013 and KDB 558074 D01 for compliance to FCC 47 CFR 15.247 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector
4. Record the measurement data.

#### TEST MODE:

Please refer to the clause 3.3

#### TEST RESULTS

☒ Passed ☐ Not Applicable

Type	Channel	Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
802.11b	01	16.46	14.05	≤30.00	Pass
	06	15.04	12.76		
	11	15.95	13.55		
802.11g	01	14.91	10.76	≤30.00	Pass
	06	13.40	9.23		
	11	14.11	9.95		
802.11n(HT20)	01	12.80	8.95	≤30.00	Pass
	06	12.07	8.33		
	11	12.86	9.16		


## 5.4. Power Spectral Density

### LIMIT

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### TEST CONFIGURATION



### TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:  
Center frequency=DTS channel center frequency  
Span =1.5 times the DTS bandwidth  
RBW = 3 kHz ≤ RBW ≤ 100 kHz, VBW ≥ 3 × RBW  
Sweep time = auto couple  
Detector = peak  
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### TEST MODE:

Please refer to the clause 3.3


### TEST RESULTS


☒ Passed      ☐ Not Applicable


Type	Channel	Power Spectral Density (dBm/30KHz)	Limit (dBm/3KHz)	Result
802.11b	01	2.71	≤8.00	Pass
	06	1.55		
	11	2.41		
802.11g	01	-9.41	≤8.00	Pass
	06	-10.39		
	11	-9.62		
802.11n(HT20)	01	-11.57	≤8.00	Pass
	06	-12.50		
	11	-11.13		

Test plot as follows:










## 5.5. 6dB bandwidth

### LIMIT

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):**

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

### TEST CONFIGURATION



### TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).  
 Center Frequency = DTS channel center frequency  
 Span = 2 x DTS bandwidth  
 RBW = 100 kHz, VBW ≥ 3 x RBW  
 Sweep time = auto couple  
 Detector = Peak  
 Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

### TEST MODE:


Please refer to the clause 3.3


### TEST RESULTS


☒ Passed      ☐ Not Applicable

Type	Channel	6dB Bandwidth (MHz)	Limit (kHz)	Result
802.11b	01	9.12	≥500	Pass
	06	8.64		
	11	8.64		
802.11g	01	16.38	≥500	Pass
	06	16.41		
	11	16.35		
802.11n(HT20)	01	17.22	≥500	Pass
	06	17.64		
	11	16.62		

Test plot as follows:








## 5.6. Restricted band

### LIMIT

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

### TEST CONFIGURATION



### TEST PROCEDURE

- 1) The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
- 2) The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- 3) The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
- 4) The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
- 5) The receiver set as follow:  
 RBW=1MHz, VBW=3MHz PEAK detector for Peak value.  
 RBW=1MHz, VBW=3MHz RMS detector for Average value.

### TEST MODE:

Please refer to the clause 3.3

### TEST RESULTS

☒ Passed      ☐ Not Applicable

Note:

- 1) Final level= Read level + Antenna Factor+ Cable Loss- Preamp Factor



802.11b					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	17.09	28.05	6.62	0.00	51.76	74.00	-22.24	Vertical	Peak
2390.01	17.31	27.65	6.75	0.00	51.71	74.00	-22.29	Vertical	Peak
2310.00	17.62	28.05	6.62	0.00	52.29	74.00	-21.71	Horizontal	Peak
2390.01	18.32	27.65	6.75	0.00	52.72	74.00	-21.28	Horizontal	Peak
2310.00	10.81	28.05	6.62	0.00	45.48	54.00	-8.52	Vertical	Average
2390.01	10.52	27.65	6.75	0.00	44.92	54.00	-9.08	Vertical	Average
2310.00	10.81	28.05	6.62	0.00	45.48	54.00	-8.52	Horizontal	Average
2390.01	10.49	27.65	6.75	0.00	44.89	54.00	-9.11	Horizontal	Average

802.11b					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.49	17.79	27.26	6.83	0.00	51.88	74.00	-22.12	Vertical	Peak
2500.00	16.90	27.20	6.84	0.00	50.94	74.00	-23.06	Vertical	Peak
2483.49	18.54	27.26	6.83	0.00	52.63	74.00	-21.37	Horizontal	Peak
2500.00	18.56	27.20	6.84	0.00	52.60	74.00	-21.40	Horizontal	Peak
2483.49	10.52	27.26	6.83	0.00	44.61	54.00	-9.39	Vertical	Average
2500.00	10.37	27.20	6.84	0.00	44.41	54.00	-9.59	Vertical	Average
2483.49	10.54	27.26	6.83	0.00	44.63	54.00	-9.37	Horizontal	Average
2500.00	10.37	27.20	6.84	0.00	44.41	54.00	-9.59	Horizontal	Average

802.11g					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	18.80	28.05	6.62	0.00	53.47	74.00	-20.53	Vertical	Peak
2390.01	18.97	27.65	6.75	0.00	53.37	74.00	-20.63	Vertical	Peak
2310.00	17.94	28.05	6.62	0.00	52.61	74.00	-21.39	Horizontal	Peak
2390.01	17.97	27.65	6.75	0.00	52.37	74.00	-21.63	Horizontal	Peak
2310.00	10.81	28.05	6.62	0.00	45.48	54.00	-8.52	Vertical	Average
2390.01	10.92	27.65	6.75	0.00	45.32	54.00	-8.68	Vertical	Average
2310.00	10.81	28.05	6.62	0.00	45.48	54.00	-8.52	Horizontal	Average
2390.01	11.16	27.65	6.75	0.00	45.56	54.00	-8.44	Horizontal	Average

802.11g					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.49	17.40	27.26	6.83	0.00	51.49	74.00	-22.51	Vertical	Peak
2500.00	18.75	27.20	6.84	0.00	52.79	74.00	-21.21	Vertical	Peak
2483.49	17.79	27.26	6.83	0.00	51.88	74.00	-22.12	Horizontal	Peak
2500.00	17.86	27.20	6.84	0.00	51.90	74.00	-22.10	Horizontal	Peak
2483.49	12.21	27.26	6.83	0.00	46.30	54.00	-7.70	Vertical	Average
2500.00	10.35	27.20	6.84	0.00	44.39	54.00	-9.61	Vertical	Average
2483.49	12.21	27.26	6.83	0.00	46.30	54.00	-7.70	Horizontal	Average
2500.00	10.38	27.20	6.84	0.00	44.42	54.00	-9.58	Horizontal	Average

802.11n(HT20)					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	18.20	28.05	6.62	0.00	52.87	74.00	-21.13	Vertical	Peak
2390.01	17.05	27.65	6.75	0.00	51.45	74.00	-22.55	Vertical	Peak
2310.00	18.61	28.05	6.62	0.00	53.28	74.00	-20.72	Horizontal	Peak
2390.01	18.19	27.65	6.75	0.00	52.59	74.00	-21.41	Horizontal	Peak
2310.00	10.78	28.05	6.62	0.00	45.45	54.00	-8.55	Vertical	Average
2390.01	11.17	27.65	6.75	0.00	45.57	54.00	-8.43	Vertical	Average
2310.00	10.80	28.05	6.62	0.00	45.47	54.00	-8.53	Horizontal	Average
2390.01	11.56	27.65	6.75	0.00	45.96	54.00	-8.04	Horizontal	Average

802.11n(HT20)					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.49	17.86	27.26	6.83	0.00	51.95	74.00	-22.05	Vertical	Peak
2500.00	17.32	27.20	6.84	0.00	51.36	74.00	-22.64	Vertical	Peak
2483.49	18.74	27.26	6.83	0.00	52.83	74.00	-21.17	Horizontal	Peak
2500.00	17.78	27.20	6.84	0.00	51.82	74.00	-22.18	Horizontal	Peak
2483.49	11.65	27.26	6.83	0.00	45.74	54.00	-8.26	Vertical	Average
2500.00	10.38	27.20	6.84	0.00	44.42	54.00	-9.58	Vertical	Average
2483.49	12.06	27.26	6.83	0.00	46.15	54.00	-7.85	Horizontal	Average
2500.00	10.39	27.20	6.84	0.00	44.43	54.00	-9.57	Horizontal	Average


## 5.7. Band edge and Spurious Emissions (conducted)

### LIMIT

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### TEST CONFIGURATION



### TEST PROCEDURE


1. Connect the antenna port(s) to the spectrum analyzer input.
2. Establish a reference level by using the following procedure  
Center frequency=DTS channel center frequency  
The span = 1.5 times the DTS bandwidth.  
RBW = 100 kHz, VBW  $\geq 3 \times$  RBW  
Detector = peak, Sweep time = auto couple, Trace mode = max hold  
Allow trace to fully stabilize  
Use the peak marker function to determine the maximum PSD level  
  
Note: the channel found to contain the maximum PSD level can be used to establish the reference level.
3. Emission level measurement  
Set the center frequency and span to encompass frequency range to be measured  
RBW = 100 kHz, VBW  $\geq 3 \times$  RBW  
Detector = peak, Sweep time = auto couple, Trace mode = max hold  
Allow trace to fully stabilize  
Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.


### TEST MODE:


Please refer to the clause 3.3




### TEST RESULTS

☒ Passed      ☐ Not Applicable









Test Item:	SE	Type:	802.11 b
CH01 Reference level			
CH01 30MHz~1000MHz			
CH01 1GHz~26GHz			




CH06  
Reference level




CH06  
30MHz~1000MHz




CH06  
1GHz~26GHz




CH11  
Reference level






CH11  
30MHz~1000MHz




CH11  
1GHz~26GHz




Test Item:	SE	Type:	802.11 g
CH01 Reference level			
CH01 30MHz~1000MHz			
CH01 1GHz~26GHz			


CH06  
Reference level




CH06  
30MHz~1000MHz




CH06  
1GHz~26GHz




CH11  
Reference level






CH11  
30MHz~1000MHz




CH11  
1GHz~26GHz




Test Item:	SE	Type:	802.11 n(HT20)
CH01 Reference level			
CH01 30MHz~1000MHz			
CH01 1GHz~26GHz			


CH06  
Reference level






CH06  
30MHz~1000MHz



CH06  
1GHz~26GHz



CH11  
Reference levelCH11  
30MHz~1000MHzCH11  
1GHz~26GHz



## 5.8. Spurious Emissions (radiated)


### LIMIT

#### FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

### TEST CONFIGURATION


#### ➤ 9kHz ~30MHz



#### ➤ 30MHz ~ 1GHz



#### ➤ Above 1GHz



**TEST PROCEDURE**

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Below 1 GHz:  
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;  
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
  - (3) From 1 GHz to 10<sup>th</sup> harmonic:  
RBW=1MHz, VBW=3MHz Peak detector for Peak value.  
RBW=1MHz, VBW=3MHz RMS detector for Average value.

**TEST MODE:**

Please refer to the clause 3.3

**TEST RESULTS**

☒ **Passed**      ☐ **Not Applicable**

Note:

- 1) Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2) The emission levels of other frequencies are very lower than the limit and not show in test report.

➤ **9kHz ~ 30MHz**


The EUT was pre-scanned the frequency band (9kHz~30MHz), found the radiated level lower than the limit, so don't show on the report.

➤ **30MHz ~1000MHz**

Have pre-scan all modulation mode, found the 802.11b mode CH01 which it was worst case, so only the worst case's data on the test report.

## ➤ 30MHz ~ 1GHz


Polarization: Vertical

**MEASUREMENT RESULT: "GM1901186094\_red"**

1/18/2019 6:32PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
43.580000	20.00	-9.0	40.0	20.0	QP	100.0	10.00	VERTICAL
57.160000	18.20	-9.3	40.0	21.8	QP	100.0	239.00	VERTICAL
99.840000	16.90	-10.3	43.5	26.6	QP	100.0	134.00	VERTICAL
200.720000	18.20	-9.6	43.5	25.3	QP	100.0	330.00	VERTICAL
546.040000	27.40	-0.2	46.0	18.6	QP	100.0	149.00	VERTICAL
934.040000	35.40	8.0	46.0	10.6	QP	100.0	55.00	VERTICAL

Polarization: Horizontal

**MEASUREMENT RESULT: "GM1901186093\_red"**

1/18/2019 6:30PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
47.460000	19.10	-8.7	40.0	20.9	QP	100.0	26.00	HORIZONTAL
57.160000	18.50	-9.3	40.0	21.5	QP	100.0	62.00	HORIZONTAL
107.600000	18.20	-10.5	43.5	25.3	QP	300.0	14.00	HORIZONTAL
212.360000	20.10	-10.1	43.5	23.4	QP	100.0	151.00	HORIZONTAL
547.980000	28.20	-0.1	46.0	17.8	QP	100.0	353.00	HORIZONTAL
953.440000	35.70	8.2	46.0	10.3	QP	100.0	116.00	HORIZONTAL

## ➤ 1 GHz ~ 25 GHz

802.11b					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3662.78	33.43	29.30	8.34	37.01	34.06	74.00	-39.94	Vertical	Peak
5217.66	31.73	31.46	9.86	34.95	38.10	74.00	-35.90	Vertical	Peak
6628.18	30.88	34.20	11.39	33.69	42.78	74.00	-31.22	Vertical	Peak
8549.59	31.54	37.10	12.88	32.92	48.60	74.00	-25.40	Vertical	Peak
4045.06	32.54	29.79	8.82	36.72	34.43	74.00	-39.57	Horizontal	Peak
5617.41	31.42	31.76	10.30	34.35	39.13	74.00	-34.87	Horizontal	Peak
7209.02	30.12	36.21	11.87	33.51	44.69	74.00	-29.31	Horizontal	Peak
8187.50	31.48	36.74	12.74	33.01	47.95	74.00	-26.05	Horizontal	Peak

802.11b					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3863.90	32.86	29.66	8.59	36.86	34.25	74.00	-39.75	Vertical	Peak
4871.10	35.97	31.46	9.59	35.61	41.41	74.00	-32.59	Vertical	Peak
6903.71	30.28	34.72	11.73	33.83	42.90	74.00	-31.10	Vertical	Peak
8002.06	31.62	37.10	12.30	33.07	47.95	74.00	-26.05	Vertical	Peak
3570.71	34.48	29.21	8.22	37.08	34.83	74.00	-39.17	Horizontal	Peak
4871.10	33.83	31.46	9.59	35.61	39.27	74.00	-34.73	Horizontal	Peak
6363.65	31.65	33.23	10.99	33.76	42.11	74.00	-31.89	Horizontal	Peak
7981.72	31.30	37.03	12.39	33.07	47.65	74.00	-26.35	Horizontal	Peak

802.11b					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3709.69	33.52	29.33	8.40	36.97	34.28	74.00	-39.72	Vertical	Peak
4920.96	35.12	31.42	9.62	35.52	40.64	74.00	-33.36	Vertical	Peak
6662.01	31.02	34.20	11.43	33.71	42.94	74.00	-31.06	Vertical	Peak
8681.17	31.88	37.79	12.98	32.95	49.70	74.00	-24.30	Vertical	Peak
3128.01	33.98	28.80	7.63	37.46	32.95	74.00	-41.05	Horizontal	Peak
4920.96	34.16	31.42	9.62	35.52	39.68	74.00	-34.32	Horizontal	Peak
5850.92	31.61	32.20	10.61	34.23	40.19	74.00	-33.81	Horizontal	Peak
7981.72	31.46	37.03	12.39	33.07	47.81	74.00	-26.19	Horizontal	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.

802.11g					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3728.63	33.64	29.39	8.42	36.96	34.49	74.00	-39.51	Vertical	Peak
5099.49	31.44	31.90	9.75	35.18	37.91	74.00	-36.09	Vertical	Peak
6544.35	30.38	34.09	11.26	33.64	42.09	74.00	-31.91	Vertical	Peak
7840.75	31.15	36.35	13.06	33.05	47.51	74.00	-26.49	Vertical	Peak
3786.01	34.48	29.56	8.48	36.92	35.60	74.00	-38.40	Horizontal	Peak
5271.06	31.89	31.36	9.94	34.85	38.34	74.00	-35.66	Horizontal	Peak
6662.01	30.95	34.20	11.43	33.71	42.87	74.00	-31.13	Horizontal	Peak
7840.75	31.39	36.35	13.06	33.05	47.75	74.00	-26.25	Horizontal	Peak

802.11g					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3570.71	33.79	29.21	8.22	37.08	34.14	74.00	-39.86	Vertical	Peak
5476.22	31.16	31.81	10.18	34.46	38.69	74.00	-35.31	Vertical	Peak
7547.01	30.73	36.15	12.55	33.02	46.41	74.00	-27.59	Vertical	Peak
9228.06	31.05	38.77	13.53	33.40	49.95	74.00	-24.05	Vertical	Peak
3700.26	33.30	29.30	8.39	36.98	34.01	74.00	-39.99	Horizontal	Peak
5244.30	31.54	31.41	9.90	34.90	37.95	74.00	-36.05	Horizontal	Peak
7172.41	31.87	36.04	11.86	33.58	46.19	74.00	-27.81	Horizontal	Peak
7941.19	31.18	36.87	12.58	33.06	47.57	74.00	-26.43	Horizontal	Peak

802.11g					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3507.65	32.98	29.02	8.13	37.13	33.00	74.00	-41.00	Vertical	Peak
4736.60	31.94	31.35	9.51	35.85	36.95	74.00	-37.05	Vertical	Peak
6283.16	30.68	33.07	11.00	33.84	40.91	74.00	-33.09	Vertical	Peak
8125.22	31.71	36.92	12.59	33.03	48.19	74.00	-25.81	Vertical	Peak
3993.90	32.54	29.70	8.77	36.76	34.25	74.00	-39.75	Horizontal	Peak
5476.22	30.27	31.81	10.18	34.46	37.80	74.00	-36.20	Horizontal	Peak
6628.18	31.15	34.20	11.39	33.69	43.05	74.00	-30.95	Horizontal	Peak
7981.72	31.24	37.03	12.39	33.07	47.59	74.00	-26.41	Horizontal	Peak

## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.

802.11n(HT20)					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3690.85	33.84	29.30	8.37	36.99	34.52	74.00	-39.48	Vertical	Peak
5271.06	31.63	31.36	9.94	34.85	38.08	74.00	-35.92	Vertical	Peak
7508.69	31.10	36.11	12.42	33.02	46.61	74.00	-27.39	Vertical	Peak
9275.16	31.84	39.05	13.57	33.48	50.98	74.00	-23.02	Vertical	Peak
3588.94	34.19	29.27	8.25	37.07	34.64	74.00	-39.36	Horizontal	Peak
4821.76	32.34	31.56	9.55	35.69	37.76	74.00	-36.24	Horizontal	Peak
6203.70	32.29	32.91	11.01	33.93	42.28	74.00	-31.72	Horizontal	Peak
7394.88	31.54	36.30	12.06	33.20	46.70	74.00	-27.30	Horizontal	Peak

802.11n(HT20)					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
4014.29	32.76	29.73	8.79	36.75	34.53	74.00	-39.47	Vertical	Peak
5112.49	31.60	31.85	9.76	35.16	38.05	74.00	-35.95	Vertical	Peak
7319.96	30.54	36.30	11.99	33.32	45.51	74.00	-28.49	Vertical	Peak
9251.58	31.49	38.91	13.55	33.44	50.51	74.00	-23.49	Vertical	Peak
3570.71	34.78	29.21	8.22	37.08	35.13	74.00	-38.87	Horizontal	Peak
5009.43	32.00	31.54	9.68	35.36	37.86	74.00	-36.14	Horizontal	Peak
6379.86	31.84	33.26	10.99	33.74	42.35	74.00	-31.65	Horizontal	Peak
9275.16	31.81	39.05	13.57	33.48	50.95	74.00	-23.05	Horizontal	Peak

802.11n(HT20)					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
4700.57	32.80	31.20	9.50	35.91	37.59	74.00	-36.41	Vertical	Peak
5762.24	31.99	31.91	10.53	34.28	40.15	74.00	-33.85	Vertical	Peak
8022.46	31.98	37.08	12.35	33.06	48.35	74.00	-25.65	Vertical	Peak
9370.08	31.92	39.06	13.66	33.63	51.01	74.00	-22.99	Vertical	Peak
3644.18	33.25	29.30	8.32	37.03	33.84	74.00	-40.16	Horizontal	Peak
5151.68	31.82	31.69	9.79	35.08	38.22	74.00	-35.78	Horizontal	Peak
7432.62	31.76	36.23	12.18	33.13	47.04	74.00	-26.96	Horizontal	Peak
9204.60	32.31	38.63	13.50	33.37	51.07	74.00	-22.93	Horizontal	Peak


## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.



## 6. TEST SETUP PHOTOS

### Conducted Emissions (AC Mains)



### Radiated Emissions





## **7. EXTERANAL AND INTERNAL PHOTOS**

Reference to the test report No.: CHTEW19020094

-----End of Report-----