
INCLUDED ELEMENTS



with (4) Mounting Screws

C. Car Adapter

D. Cable Clips (2)

DEVICE SETUP

SECTION A - Universal AMPS Pattern Adapter

SECTION B - Integrated Cable Management System

SECTION C - Connection & Charging


SECTION **D** - Charging Head Adjustment

SECTION A




Note: The Universal AMPS Pattern Adapter should be installed disassembled from the MagicMount Charge Elite.

- 1. Remove the ball collar from adapter plate and remove the MagicMount.
- 2. Position the adapter plate on the AMPS Mounting Location.
- 3. Use a Phillips Head screwdriver to attach the adapter plate with (4) self-driving screws, included.
- 4. Replace the MagicMount. Place the ball connector through the collar into the ball socket. Note: Make sure the "Scosche" side of the collar is facing outward (toward the MagicMount).
- 5. Tighten the collar onto the ball socket.











SCOSCHE

MAGICMOUNT

CHARGE ELITE


Integrated Cable Management System

1. Kelease the cable from the output slot (A)

Z Via rually unwind the cable from the Internal storage red (B) or which the cable onto the storage cel (C) to adjust the length of expused cable

> Minimum Length. 1 ft Vlaxl nu n Le 19th. 4tt


3 At the destred length, culace the cable In the output slot (D)







Loosen ball joint collar (A) to adjust charging head angle (B) or rotate device 360°(C)





Scosche Industries 1550 Pacific Avenue Oxnard, California 93033 Pnone 800 363 4490 x1 / 805-486-4450 x1 www.scosche.com

©2024 Scosche Industries

Scosche & MagicMount are trademarks of Scosche Industries. Other marks or brands are the property of their respective owners Devices and or appearance may vary.

Designed in Oxnard, California

SI MEQMRAMPS: 7/24