




11N20SISO_Ant1_2437_1000~26500



11N20SISO_Ant1_2462_0~Reference




11N20SISO_Ant1_2462_30~1000




Date: 22 AUG 2024 16:28:32

11N20SISO_Ant1_2462_1000~26500




Date: 22 AUG 2024 16:28:54


11N40SISO_Ant1_2422_0~Reference




11N40SISO_Ant1_2422_30~1000



11N40SISO_Ant1_2422_1000~26500




11N40SISO_Ant1_2437_0~Reference




Date: 22 AUG 2024 16:32:28

11N40SISO_Ant1_2437_30~1000




Date: 22 AUG 2024 16:32:35


11N40SISO_Ant1_2437_1000~26500




11N40SISO_Ant1_2452_0~Reference



11N40SISO_Ant1_2452_30~1000





Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

5.7 Radiated Spurious Emissions

| | | | | | |
|-------------------|---|-------------------------------------|-------------------|------------|-----------------------------|
| Test Requirement: | 47 CFR Part 15C Section 15.209 and 15.205 | | | | |
| Test Method: | ANSI C63.10 2013 | | | | |
| Test Site: | Measurement Distance: 3m (Semi-Anechoic Chamber) | | | | |
| Receiver Setup: | Frequency | Detector | RBW | VBW | Remark |
| | 0.009MHz-0.090MHz | Peak | 10kHz | 30kHz | Peak |
| | 0.009MHz-0.090MHz | Average | 10kHz | 30kHz | Average |
| | 0.090MHz-0.110MHz | Quasi-peak | 10kHz | 30kHz | Quasi-peak |
| | 0.110MHz-0.490MHz | Peak | 10kHz | 30kHz | Peak |
| | 0.110MHz-0.490MHz | Average | 10kHz | 30kHz | Average |
| | 0.490MHz -30MHz | Quasi-peak | 10kHz | 30kHz | Quasi-peak |
| | 30MHz-1GHz | Quasi-peak | 100 kHz | 300kHz | Quasi-peak |
| | Above 1GHz | Peak | 1MHz | 3MHz | Peak |
| | | Peak | 1MHz | 10Hz | Average |
| Limit: | Frequency | Field strength (microvolt/meter) | Limit (dBuV/m) | Remark | Measurement distance (m) |
| | 0.009MHz-0.490MHz | 2400/F(kHz) | - | - | 300 |
| | 0.490MHz-1.705MHz | 24000/F(kHz) | - | - | 30 |
| | 1.705MHz-30MHz | 30 | - | - | 30 |
| | 30MHz-88MHz | 100 | 40.0 | Quasi-peak | 3 |
| | 88MHz-216MHz | 150 | 43.5 | Quasi-peak | 3 |
| | 216MHz-960MHz | 200 | 46.0 | Quasi-peak | 3 |
| | 960MHz-1GHz | 500 | 54.0 | Quasi-peak | 3 |
| | Above 1GHz | 500 | 54.0 | Average | 3 |
| | Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device. | | | | |

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz


Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
Note: For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

| | |
|------------------------|---|
| | <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel, the middle channel, the Highest channel.</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case .</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p> |
| Exploratory Test Mode: | Transmitting with all kind of modulations, data rates at lowest, middle and highest channel. |
| Final Test Mode: | Only the worst case is recorded in the report. |
| Test Results: | Pass |

5.7.1 Radiated emission below 1GHz

| |
|------------|
| 30MHz~1GHz |
| Vertical |



| | Read Freq | Level | Factor | Level | Limit Line | Over Limit | Remark | Pol/Phase |
|------|--------------|-------|--------|--------|---------------|---------------|--------|-----------|
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | |
| 1 | 35.38 | 11.00 | 14.90 | 25.90 | 40.00 | -14.10 | Peak | VERTICAL |
| 2 | 77.87 | 12.37 | 10.36 | 22.73 | 40.00 | -17.27 | Peak | VERTICAL |
| 3 | 119.44 | 9.82 | 11.86 | 21.68 | 43.50 | -21.82 | Peak | VERTICAL |
| 4 | 245.09 | 9.89 | 13.46 | 23.35 | 46.00 | -22.65 | Peak | VERTICAL |
| 5 | 501.18 | 10.24 | 20.31 | 30.55 | 46.00 | -15.45 | Peak | VERTICAL |
| 6 pp | 881.41 | 9.12 | 26.75 | 35.87 | 46.00 | -10.13 | Peak | VERTICAL |

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

Horizontal



| | | Read | | Limit | Over | | |
|---|------|---------|--------|--------|--------|-------|-------------|
| | Freq | Level | Factor | Level | Line | Limit | Remark |
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | Pol/Phase |
| 1 | pp | 34.04 | 9.42 | 15.23 | 24.65 | 40.00 | -15.35 Peak |
| 2 | | 89.59 | 11.62 | 10.99 | 22.61 | 43.50 | -20.89 Peak |
| 3 | | 116.54 | 11.25 | 11.70 | 22.95 | 43.50 | -20.55 Peak |
| 4 | | 366.82 | 8.43 | 17.04 | 25.47 | 46.00 | -20.53 Peak |
| 5 | | 574.63 | 8.38 | 21.24 | 29.62 | 46.00 | -16.38 Peak |
| 6 | | 1000.00 | 10.88 | 27.71 | 38.59 | 54.00 | -15.41 Peak |

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

5.7.2 Transmitter emission above 1GHz

| Test mode: | | 802.11b(1Mbps) | | Test channel: | | Lowest | |
|------------|---------------|----------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 4824.000 | 52.35 | -4.26 | 48.09 | 74 | -25.91 | peak | H |
| 4824.000 | 36.86 | -4.26 | 32.60 | 54 | -21.40 | AVG | H |
| 7236.000 | 51.86 | 1.18 | 53.04 | 74 | -20.96 | peak | H |
| 7236.000 | 38.53 | 1.18 | 39.71 | 54 | -14.29 | AVG | H |
| 4824.000 | 54.81 | -4.26 | 50.55 | 74 | -23.45 | peak | V |
| 4824.000 | 39.01 | -4.26 | 34.75 | 54 | -19.25 | AVG | V |
| 7236.000 | 50.25 | 1.18 | 51.43 | 74 | -22.57 | peak | V |
| 7236.000 | 35.50 | 1.18 | 36.68 | 54 | -17.32 | AVG | V |

| Test mode: | | 802.11b(1Mbps) | | Test channel: | | Middle | |
|------------|---------------|----------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 4874.000 | 52.91 | -4.12 | 48.79 | 74 | -25.21 | peak | H |
| 4874.000 | 37.67 | -4.12 | 33.55 | 54 | -20.45 | AVG | H |
| 7311.000 | 50.06 | 1.46 | 51.52 | 74 | -22.48 | peak | H |
| 7311.000 | 35.69 | 1.46 | 37.15 | 54 | -16.85 | AVG | H |
| 4874.000 | 53.22 | -4.12 | 49.10 | 74 | -24.90 | peak | V |
| 4874.000 | 37.20 | -4.12 | 33.08 | 54 | -20.92 | AVG | V |
| 7311.000 | 49.09 | 1.46 | 50.55 | 74 | -23.45 | peak | V |
| 7311.000 | 36.29 | 1.46 | 37.75 | 54 | -16.25 | AVG | V |

| Test mode: | | 802.11b(1Mbps) | | Test channel: | | Highest | |
|------------|---------------|----------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 4924.000 | 52.44 | -4.03 | 48.41 | 74 | -25.59 | peak | H |
| 4924.000 | 37.94 | -4.03 | 33.91 | 54 | -20.09 | AVG | H |
| 7386.000 | 49.70 | 1.66 | 51.36 | 74 | -22.64 | peak | H |
| 7386.000 | 37.52 | 1.66 | 39.18 | 54 | -14.82 | AVG | H |
| 4924.000 | 53.60 | -4.03 | 49.57 | 74 | -24.43 | peak | V |
| 4924.000 | 38.78 | -4.03 | 34.75 | 54 | -19.25 | AVG | V |
| 7386.000 | 50.13 | 1.66 | 51.79 | 74 | -22.21 | peak | V |
| 7386.000 | 37.81 | 1.66 | 39.47 | 54 | -14.53 | AVG | V |

Remark:

- 1) The 1Mbps of rate of 802.11b is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
 Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

| Test mode: | | 802.11g(6Mbps) | | Test channel: | | Lowest | |
|------------|---------------|----------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 4824.000 | 54.19 | -4.26 | 49.93 | 74 | -24.07 | peak | H |
| 4824.000 | 36.00 | -4.26 | 31.74 | 54 | -22.26 | AVG | H |
| 7236.000 | 51.14 | 1.18 | 52.32 | 74 | -21.68 | peak | H |
| 7236.000 | 38.40 | 1.18 | 39.58 | 54 | -14.42 | AVG | H |
| 4824.000 | 54.76 | -4.26 | 50.50 | 74 | -23.50 | peak | V |
| 4824.000 | 39.64 | -4.26 | 35.38 | 54 | -18.62 | AVG | V |
| 7236.000 | 51.10 | 1.18 | 52.28 | 74 | -21.72 | peak | V |
| 7236.000 | 35.39 | 1.18 | 36.57 | 54 | -17.43 | AVG | V |

| Test mode: | | 802.11g(6Mbps) | | Test channel: | | Middle | |
|------------|---------------|----------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 4874.000 | 51.71 | -4.12 | 47.59 | 74 | -26.41 | peak | H |
| 4874.000 | 36.51 | -4.12 | 32.39 | 54 | -21.61 | AVG | H |
| 7311.000 | 49.04 | 1.46 | 50.50 | 74 | -23.50 | peak | H |
| 7311.000 | 36.71 | 1.46 | 38.17 | 54 | -15.83 | AVG | H |
| 4874.000 | 52.45 | -4.12 | 48.33 | 74 | -25.67 | peak | V |
| 4874.000 | 37.13 | -4.12 | 33.01 | 54 | -20.99 | AVG | V |
| 7311.000 | 48.38 | 1.46 | 49.84 | 74 | -24.16 | peak | V |
| 7311.000 | 36.44 | 1.46 | 37.90 | 54 | -16.10 | AVG | V |

| Test mode: | | 802.11g(6Mbps) | | Test channel: | | Highest | |
|------------|---------------|----------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 4924.000 | 53.13 | -4.03 | 49.10 | 74 | -24.90 | peak | H |
| 4924.000 | 38.77 | -4.03 | 34.74 | 54 | -19.26 | AVG | H |
| 7386.000 | 49.47 | 1.66 | 51.13 | 74 | -22.87 | peak | H |
| 7386.000 | 37.58 | 1.66 | 39.24 | 54 | -14.76 | AVG | H |
| 4924.000 | 53.45 | -4.03 | 49.42 | 74 | -24.58 | peak | V |
| 4924.000 | 38.75 | -4.03 | 34.72 | 54 | -19.28 | AVG | V |
| 7386.000 | 50.58 | 1.66 | 52.24 | 74 | -21.76 | peak | V |
| 7386.000 | 37.28 | 1.66 | 38.94 | 54 | -15.06 | AVG | V |

Remark:

- 1) The 6Mbps of rate of 802.11g is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

| Test mode: | | 802.11n20(mcs0) | | Test channel: | | Lowest | |
|------------|---------------|-----------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 4824.000 | 53.13 | -4.26 | 48.87 | 74 | -25.13 | peak | H |
| 4824.000 | 35.99 | -4.26 | 31.73 | 54 | -22.27 | AVG | H |
| 7236.000 | 50.46 | 1.18 | 51.64 | 74 | -22.36 | peak | H |
| 7236.000 | 38.23 | 1.18 | 39.41 | 54 | -14.59 | AVG | H |
| 4824.000 | 55.36 | -4.26 | 51.10 | 74 | -22.90 | peak | V |
| 4824.000 | 39.81 | -4.26 | 35.55 | 54 | -18.45 | AVG | V |
| 7236.000 | 51.19 | 1.18 | 52.37 | 74 | -21.63 | peak | V |
| 7236.000 | 36.77 | 1.18 | 37.95 | 54 | -16.05 | AVG | V |

| Test mode: | | 802.11n20(mcs0) | | Test channel: | | Middle | |
|------------|---------------|-----------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 4874.000 | 52.21 | -4.12 | 48.09 | 74 | -25.91 | peak | H |
| 4874.000 | 36.54 | -4.12 | 32.42 | 54 | -21.58 | AVG | H |
| 7311.000 | 48.89 | 1.46 | 50.35 | 74 | -23.65 | peak | H |
| 7311.000 | 35.24 | 1.46 | 36.70 | 54 | -17.30 | AVG | H |
| 4874.000 | 52.87 | -4.12 | 48.75 | 74 | -25.25 | peak | V |
| 4874.000 | 36.97 | -4.12 | 32.85 | 54 | -21.15 | AVG | V |
| 7311.000 | 50.12 | 1.46 | 51.58 | 74 | -22.42 | peak | V |
| 7311.000 | 35.96 | 1.46 | 37.42 | 54 | -16.58 | AVG | V |

| Test mode: | | 802.11n20(mcs0) | | Test channel: | | Highest | |
|------------|---------------|-----------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 4924.000 | 51.93 | -4.03 | 47.90 | 74 | -26.10 | peak | H |
| 4924.000 | 37.35 | -4.03 | 33.32 | 54 | -20.68 | AVG | H |
| 7386.000 | 49.66 | 1.66 | 51.32 | 74 | -22.68 | peak | H |
| 7386.000 | 36.63 | 1.66 | 38.29 | 54 | -15.71 | AVG | H |
| 4924.000 | 54.38 | -4.03 | 50.35 | 74 | -23.65 | peak | V |
| 4924.000 | 38.84 | -4.03 | 34.81 | 54 | -19.19 | AVG | V |
| 7386.000 | 50.35 | 1.66 | 52.01 | 74 | -21.99 | peak | V |
| 7386.000 | 36.42 | 1.66 | 38.08 | 54 | -15.92 | AVG | V |

Remark:

- 1) The MCS0 of rate of 802.11n20 is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

| Test mode: | | 802.11n40(mcs0) | | Test channel: | | Lowest | |
|------------|---------------|-----------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 4844.000 | 53.46 | -4.24 | 49.22 | 74 | -24.78 | peak | H |
| 4844.000 | 37.75 | -4.24 | 33.51 | 54 | -20.49 | AVG | H |
| 7266.000 | 50.45 | 1.2 | 51.65 | 74 | -22.35 | peak | H |
| 7266.000 | 37.98 | 1.2 | 39.18 | 54 | -14.82 | AVG | H |
| 4844.000 | 54.69 | -4.24 | 50.45 | 74 | -23.55 | peak | V |
| 4844.000 | 39.51 | -4.24 | 35.27 | 54 | -18.73 | AVG | V |
| 7266.000 | 51.99 | 1.2 | 53.19 | 74 | -20.81 | peak | V |
| 7266.000 | 35.95 | 1.2 | 37.15 | 54 | -16.85 | AVG | V |

| Test mode: | | 802.11n40(mcs0) | | Test channel: | | Middle | |
|------------|---------------|-----------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 4874.000 | 52.44 | -4.12 | 48.32 | 74 | -25.68 | peak | H |
| 4874.000 | 36.15 | -4.12 | 32.03 | 54 | -21.97 | AVG | H |
| 7311.000 | 48.88 | 1.46 | 50.34 | 74 | -23.66 | peak | H |
| 7311.000 | 35.22 | 1.46 | 36.68 | 54 | -17.32 | AVG | H |
| 4874.000 | 53.74 | -4.12 | 49.62 | 74 | -24.38 | peak | V |
| 4874.000 | 37.16 | -4.12 | 33.04 | 54 | -20.96 | AVG | V |
| 7311.000 | 49.97 | 1.46 | 51.43 | 74 | -22.57 | peak | V |
| 7311.000 | 36.81 | 1.46 | 38.27 | 54 | -15.73 | AVG | V |

| Test mode: | | 802.11n40(mcs0) | | Test channel: | | Highest | |
|------------|---------------|-----------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 4904.000 | 53.78 | -4.05 | 49.73 | 74 | -24.27 | peak | H |
| 4904.000 | 37.65 | -4.05 | 33.60 | 54 | -20.40 | AVG | H |
| 7356.000 | 50.63 | 1.64 | 52.27 | 74 | -21.73 | peak | H |
| 7356.000 | 37.98 | 1.64 | 39.62 | 54 | -14.38 | AVG | H |
| 4904.000 | 55.31 | -4.05 | 51.26 | 74 | -22.74 | peak | V |
| 4904.000 | 38.80 | -4.05 | 34.75 | 54 | -19.25 | AVG | V |
| 7356.000 | 51.42 | 1.64 | 53.06 | 74 | -20.94 | peak | V |
| 7356.000 | 35.12 | 1.64 | 36.76 | 54 | -17.24 | AVG | V |

Remark:

- 1) The MCS0 of rate of 802.11n40 is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

5.8 Restricted bands around fundamental frequency

| | | | |
|-------------------|--|--------------------|------------------|
| Test Requirement: | 47 CFR Part 15C Section 15.209 and 15.205 | | |
| Test Method: | ANSI C63.10 2013 | | |
| Test Site: | Measurement Distance: 3m (Semi-Anechoic Chamber) | | |
| Limit: | Frequency | Limit (dBuV/m @3m) | Remark |
| | 30MHz-88MHz | 40.0 | Quasi-peak Value |
| | 88MHz-216MHz | 43.5 | Quasi-peak Value |
| | 216MHz-960MHz | 46.0 | Quasi-peak Value |
| | 960MHz-1GHz | 54.0 | Quasi-peak Value |
| | Above 1GHz | 54.0 | Average Value |
| | | 74.0 | Peak Value |

Test Setup:




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

Test Procedure:

- 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- Note: For the radiated emission test above 1GHz:
- Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
 - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
 - For each suspected emission, the EUT was arranged to its worst case and

| | |
|------------------------|--|
| | <p>then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel</p> <p>g. Test the EUT in the lowest channel, the middle channel, the Highest channel.</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case .</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p> |
| Exploratory Test Mode: | <p>Transmitting with all kind of modulations, data rates.</p> <p>Transmitting mode.</p> |
| Final Test Mode: | <p>Pretest the EUT at Transmitting mode, found the Transmitting mode which it is worse case.</p> <p>Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).</p> <p>Only the worst case is recorded in the report.</p> |
| Test Results: | Pass |

Test data:

| Worse case mode: | | 802.11b(1Mbps) | | Test channel: | | Lowest | |
|------------------|---------------|----------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 2390.000 | 58.81 | -9.2 | 49.61 | 74 | -24.39 | peak | H |
| 2390.000 | 44.33 | -9.2 | 35.13 | 54 | -18.87 | AVG | H |
| 2400.000 | 59.55 | -9.39 | 50.16 | 74 | -23.84 | peak | H |
| 2400.000 | 46.06 | -9.39 | 36.67 | 54 | -17.33 | AVG | H |
| 2390.000 | 58.96 | -9.2 | 49.76 | 74 | -24.24 | peak | V |
| 2390.000 | 44.97 | -9.2 | 35.77 | 54 | -18.23 | AVG | V |
| 2400.000 | 60.08 | -9.39 | 50.69 | 74 | -23.31 | peak | V |
| 2400.000 | 46.30 | -9.39 | 36.91 | 54 | -17.09 | AVG | V |

| Worse case mode: | | 802.11b(1Mbps) | | Test channel: | | Highest | |
|------------------|---------------|----------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 2483.500 | 57.84 | -9.29 | 48.55 | 74 | -25.45 | peak | H |
| 2483.500 | 44.07 | -9.29 | 34.78 | 54 | -19.22 | AVG | H |
| 2483.500 | 57.77 | -9.29 | 48.48 | 74 | -25.52 | peak | V |
| 2483.500 | 45.65 | -9.29 | 36.36 | 54 | -17.64 | AVG | V |

| Worse case mode: | | 802.11g(6Mbps) | | Test channel: | | Lowest | |
|------------------|---------------|----------------|----------------|---------------|--------|----------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | Type | H/V |
| 2390.000 | 58.93 | -9.2 | 49.73 | 74 | -24.27 | peak | H |
| 2390.000 | 44.61 | -9.2 | 35.41 | 54 | -18.59 | AVG | H |
| 2400.000 | 59.84 | -9.39 | 50.45 | 74 | -23.55 | peak | H |
| 2400.000 | 46.46 | -9.39 | 37.07 | 54 | -16.93 | AVG | H |
| 2390.000 | 58.29 | -9.2 | 49.09 | 74 | -24.91 | peak | V |
| 2390.000 | 44.09 | -9.2 | 34.89 | 54 | -19.11 | AVG | V |
| 2400.000 | 60.13 | -9.39 | 50.74 | 74 | -23.26 | peak | V |
| 2400.000 | 46.92 | -9.39 | 37.53 | 54 | -16.47 | AVG | V |

| Worse case mode: | | 802.11g(6Mbps) | | Test channel: | | Highest | |
|------------------|---------------|----------------|----------------|---------------|--------|----------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | Type | H/V |
| 2483.500 | 58.23 | -9.29 | 48.94 | 74 | -25.06 | peak | H |
| 2483.500 | 44.12 | -9.29 | 34.83 | 54 | -19.17 | AVG | H |
| 2483.500 | 58.20 | -9.29 | 48.91 | 74 | -25.09 | peak | V |
| 2483.500 | 45.51 | -9.29 | 36.22 | 54 | -17.78 | AVG | V |

| Worse case mode: | | 802.11n(HT20)(6.5Mbps) | | Test channel: | | Lowest | |
|------------------|---------------|------------------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 2390.000 | 59.02 | -9.2 | 49.82 | 74 | -24.18 | peak | H |
| 2390.000 | 44.36 | -9.2 | 35.16 | 54 | -18.84 | AVG | H |
| 2400.000 | 59.74 | -9.39 | 50.35 | 74 | -23.65 | peak | H |
| 2400.000 | 46.72 | -9.39 | 37.33 | 54 | -16.67 | AVG | H |
| 2390.000 | 58.26 | -9.2 | 49.06 | 74 | -24.94 | peak | V |
| 2390.000 | 44.29 | -9.2 | 35.09 | 54 | -18.91 | AVG | V |
| 2400.000 | 60.05 | -9.39 | 50.66 | 74 | -23.34 | peak | V |
| 2400.000 | 46.00 | -9.39 | 36.61 | 54 | -17.39 | AVG | V |

| Worse case mode: | | 802.11n(HT20)(6.5Mbps) | | Test channel: | | Highest | |
|------------------|---------------|------------------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 2483.500 | 57.71 | -9.29 | 48.42 | 74 | -25.58 | peak | H |
| 2483.500 | 43.65 | -9.29 | 34.36 | 54 | -19.64 | AVG | H |
| 2483.500 | 57.90 | -9.29 | 48.61 | 74 | -25.39 | peak | V |
| 2483.500 | 45.67 | -9.29 | 36.38 | 54 | -17.62 | AVG | V |

| Worse case mode: | | 802.11n(HT40)(13.5Mbps) | | Test channel: | | Lowest | |
|------------------|---------------|-------------------------|----------------|---------------|--------|----------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | Type | H/V |
| 2390.000 | 58.93 | -9.2 | 49.73 | 74 | -24.27 | peak | H |
| 2390.000 | 44.60 | -9.2 | 35.40 | 54 | -18.60 | AVG | H |
| 2400.000 | 60.15 | -9.39 | 50.76 | 74 | -23.24 | peak | H |
| 2400.000 | 46.13 | -9.39 | 36.74 | 54 | -17.26 | AVG | H |
| 2390.000 | 58.73 | -9.2 | 49.53 | 74 | -24.47 | peak | V |
| 2390.000 | 44.30 | -9.2 | 35.10 | 54 | -18.90 | AVG | V |
| 2400.000 | 59.56 | -9.39 | 50.17 | 74 | -23.83 | peak | V |
| 2400.000 | 46.37 | -9.39 | 36.98 | 54 | -17.02 | AVG | V |

| Worse case mode: | | 802.11n(HT40)(13.5Mbps) | | Test channel: | | Highest | |
|------------------|---------------|-------------------------|----------------|---------------|--------|----------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | Type | H/V |
| 2483.500 | 57.74 | -9.29 | 48.45 | 74 | -25.55 | peak | H |
| 2483.500 | 43.66 | -9.29 | 34.37 | 54 | -19.63 | AVG | H |
| 2483.500 | 57.75 | -9.29 | 48.46 | 74 | -25.54 | peak | V |
| 2483.500 | 45.94 | -9.29 | 36.65 | 54 | -17.35 | AVG | V |

Note:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor


6 Photographs - EUT Test Setup

6.1 Radiated Spurious Emission

9kHz~30MHz:



30MHz~1GHz:



Above 1GHz:



7 Photographs - EUT Constructional Details

Refer to PHOTOGRAPHS OF EUT for CQASZ20240801695E-01.

*** END OF REPORT ***