

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is an 1:24 R/C Asst.(1:24 Radio Control Vehicle (2.4GHz Version) ~ Volkswagen Van "Samba") operating at 2.4G Band. The EUT can be powered by DC 3.0V (2 x 1.5V AAA batteries). For more details information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -1.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -1.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 96.9dBμV/m at 3m in the frequency 2421MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = 1.67dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 91.9dBμV/m at 3m in the frequency 2478MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -3.33dBm

which is within the production variation.

The maximum conducted output power specified is 2.0dBm= 1.585mW

The source- based time-averaging conducted output power
=1.585mW

The SAR Exclusion Threshold Level:

= $3.0 \cdot (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$

= $3.0 \cdot 5 / \sqrt{2.478}$ mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.