

EMC TEST REPORT

FCC ID: 2BF55-MINI-2

Report No. : SSP24040253-1E

Applicant : Anshan Xupu Trading Co., Ltd

Product Name : LED BULB

Model Name : MINI-2

Test Standard : FCC Part 15 Subpart B

Date of Issue : 2024-05-15



Shenzhen CCUT Quality Technology Co., Ltd.

1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen,
Guangdong, China; (Tel.:+86-755-23406590 website: www.ccuttest.com)

This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

Test Report Basic Information

Applicant:	Anshan Xupu Trading Co., Ltd
Address of Applicant:	46, Floor 4,128 B, Jiefang East Road,Tiedong, Anshan, Liaoning
Manufacturer:	Anshan Xupu Trading Co., Ltd
Address of Manufacturer:	46, Floor 4,128 B, Jiefang East Road,Tiedong, Anshan, Liaoning
Product Name:	LED BULB
Brand Name:	PIBAOGU
Main Model:	MINI-2
Series Models:	AP-1-1w, AP-2-2w, AP-3-3w, AP-4-4w, AP-5-5w, AP-6-6w, leida-1-7W, leida-8-9W, leida-2-8W, leida-3-10W, leida-4-11W, leida-5-12W, leida-6-13W, leida-7-14W, FJ-2-15W, JG-1-16W, JG-2-17W, JG-3-18W, mi4-1-19W, mini-2-20w, mini-3-21w, mini-5-24w, mini-4-28w, HW-6-30W
Test Standard:	FCC Part 15 Subpart B ANSI C63.4-2014
Date of Test	2024-05-08 to 2024-05-09
Test Result:	PASS
Tested By	<u>Choco Qiu</u> (Choco Qiu)
Reviewed By:	<u>Lieber Ouyang</u> (Lieber Ouyang)
Authorized Signatory:	<u>Lahm Peng</u> (Lahm Peng)
Note : This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.	



CONTENTS

1. General Information.....5

 1.1 Product Information5

 1.2 Test Setup Information.....5

 1.3 Compliance Standards.....6

 1.4 Test Facilities.....6

 1.5 Measurement Uncertainty.....6

 1.6 List of Test and Measurement Instruments7

2. Summary of Test Results8

3. Conducted Emissions9

 3.1 Standard and Limit.....9

 3.2 Test Procedure.....9

 3.3 Test Data and Results9

4. Radiated Disturbance.....12

 4.1 Standard and Limit.....12

 4.2 Test Procedure.....12

 4.3 Test Data and Results12

Revision History

Revision	Issue Date	Description	Revised By
V1.0	2024-05-15	Initial Release	Lahm Peng

1. General Information

1.1 Product Information

Product Name:	LED BULB
Trade Name:	PIBAOGU
Main Model:	MINI-2
Series Models:	AP-1-1w, AP-2-2w, AP-3-3w, AP-4-4w, AP-5-5w, AP-6-6w, leida-1-7W, leida-8-9W, leida-2-8W, leida-3-10W, leida-4-11W, leida-5-12W, leida-6-13W, leida-7-14W, FJ-2-15W, JG-1-16W, JG-2-17W, JG-3-18W, mini4-1-19W, mini-2-20w, mini-3-21w, mini-5-24w, mini-4-28w, HW-6-30W
Class of Equipment:	☐ Class A ☒ Class B
Highest Internal Frequency:	<108MHz
Rated Voltage:	Input: AC 120V/60Hz
Note 1: The test data is gathered from a production sample, provided by the manufacturer.	
Note 2: The color of appearance and model name of series models listed are different from the main model, but the circuit and the electronic construction are the same, declared by the manufacturer.	

1.2 Test Setup Information

List of Test Modes			
Test Mode	Description	Remark	
TM1	Working	AC 120V/60Hz	
TM2	-	-	
TM3	-	-	
TM4	-	-	
List and Details of Auxiliary Cable			
Description	Length (cm)	Shielded/Unshielded	With/Without Ferrite
-	-	-	-
-	-	-	-
-	-	-	-
List and Details of Auxiliary Equipment			
Description	Manufacturer	Model	Serial Number
-	-	-	-
-	-	-	-
-	-	-	-
The equipment under test (EUT) was configured to measure its highest possible emission and immunity level. The test modes were adapted according to the operation manual for use.			

1.3 Compliance Standards

Compliance Standards	
FCC Part 15 Subpart B	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Unintentional Radiators
All measurements contained in this report were conducted with all above standards	
According to standards for test methodology	
FCC Part 15 Subpart B	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Unintentional Radiators
ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.
Maintenance of compliance is the responsibility of the manufacturer or applicant. Any modification of the product, which result is lowering the emission, should be checked to ensure compliance has been maintained.	

1.4 Test Facilities

Laboratory Name:	Shenzhen CCUT Quality Technology Co., Ltd. 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China
CNAS Laboratory No.:	L18863
A2LA Certificate No.:	6893.01
FCC Registration No.:	583813
ISED Registration No.:	CN0164
All measurement facilities used to collect the measurement data are located at 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China.	

1.5 Measurement Uncertainty

Test Item	Conditions	Uncertainty
Conducted Disturbance	9kHz ~30MHz	±1.64 dB
Radiated Disturbance	30MHz ~ 1GHz	±3.32 dB
Radiated Disturbance	1GHz ~ 18GHz	±3.50 dB

1.6 List of Test and Measurement Instruments

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Conducted Emissions					
AMN	ROHDE&SCHWARZ	ENV216	101097	2023-10-21	2024-10-20
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100242	2023-07-31	2024-07-30
EMI Test Software	FARA	EZ-EMC	EMEC-3A1+	N/A	N/A
Radiated Emissions					
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100154	2023-07-31	2024-07-30
Spectrum Analyzer	KEYSIGHT	N9020A	MY48030972	2023-07-31	2024-07-30
Amplifier	SCHWARZBECK	BBV 9743B	00251	2023-07-31	2024-07-30
Amplifier	HUABO	YXL0518-2.5-45	--	2023-07-31	2024-07-30
Loop Antenna	DAZE	ZN30900C	21104	2023-08-07	2024-08-06
Broadband Antenna	SCHWARZBECK	VULB 9168	01320	2023-08-07	2024-08-06
Horn Antenna	SCHWARZBECK	BBHA 9120D	02553	2023-08-07	2024-08-06
EMI Test Software	FARA	EZ-EMC	FA-03A2 RE+	N/A	N/A

2. Summary of Test Results

FCC Rule	Description of Test Item	Result
FCC Part 15.107	Conducted Emissions	Passed
FCC Part 15.109	Radiated Emissions	Passed
Passed: The EUT complies with the essential requirements in the standard Failed: The EUT does not comply with the essential requirements in the standard N/A: Not applicable		

3. Conducted Emissions

3.1 Standard and Limit


According to the rule FCC Part 15.107, Conducted limit, the limit for a class A and class B device as below:

Frequency of Emission (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15-0.5	79	66	66 to 56	56 to 46
0.5-5	73	60	56	46
5-30	73	60	60	50

Note 1: Decreases with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz
Note 2: The lower limit applies at the band edges

3.2 Test Procedure

Test is conducting under the description of ANSI C63.4-2014 American National Standard for Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.



Test Setup Block Diagram

3.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.107 standard limit for a Class B device, and with the worst case as below:

Remark: Level = Reading + Factor, Margin = Level - Limit

Test Plots and Data of Conducted Emissions


Tested Model: MINI-2

Tested Mode: TM1

Test Voltage: AC 120V/60Hz

Test Power Line: Neutral

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2040	48.40	9.60	58.00	63.45	-5.45	QP	P	
2	0.2040	32.38	9.60	41.98	53.45	-11.47	AVG	P	
3	0.3570	45.85	9.44	55.29	58.80	-3.51	QP	P	
4	0.3570	25.56	9.44	35.00	48.80	-13.80	AVG	P	
5	0.4335	43.06	9.94	53.00	57.19	-4.19	QP	P	
6	0.4335	25.51	9.94	35.45	47.19	-11.74	AVG	P	
7	1.0590	31.56	9.77	41.33	56.00	-14.67	QP	P	
8	1.0590	15.06	9.77	24.83	46.00	-21.17	AVG	P	
9 *	3.7590	42.56	10.14	52.70	56.00	-3.30	QP	P	
10	3.7590	1.85	10.14	11.99	46.00	-34.01	AVG	P	
11	25.4310	23.90	10.42	34.32	60.00	-25.68	QP	P	
12	25.4310	20.41	10.42	30.83	50.00	-19.17	AVG	P	

Test Plots and Data of Conducted Emissions


Tested Model: MINI-2

Tested Mode: TM1

Test Voltage: AC 120V/60Hz

Test Power Line: Live

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1 *	0.2490	49.21	9.52	58.73	61.79	-3.06	QP	P	
2	0.2490	30.83	9.52	40.35	51.79	-11.44	AVG	P	
3	0.3074	45.68	9.78	55.46	60.04	-4.58	QP	P	
4	0.3074	26.17	9.78	35.95	50.04	-14.09	AVG	P	
5	0.4425	43.33	9.93	53.26	57.01	-3.75	QP	P	
6	0.4425	22.70	9.93	32.63	47.01	-14.38	AVG	P	
7	6.1844	27.68	10.25	37.93	60.00	-22.07	QP	P	
8	6.1844	-6.48	10.25	3.77	50.00	-46.23	AVG	P	
9	10.5854	35.30	10.08	45.38	60.00	-14.62	QP	P	
10	10.5854	-4.56	10.08	5.52	50.00	-44.48	AVG	P	
11	25.4355	22.42	10.28	32.70	60.00	-27.30	QP	P	
12	25.4355	15.52	10.28	25.80	50.00	-24.20	AVG	P	

4. Radiated Disturbance

4.1 Standard and Limit


According to the rule FCC Part 15.109, Radiated emission limit for a class A and class B device as below:

Frequency of Emission (MHz)	Class A (3m)	Class B (3m)
	Quasi-peak (dBuV/m)	Quasi-peak (dBuV/m)
30-88	50	40
88-216	54.0	43.5
216-960	57.0	46
Above 960	60	54

Note: The more stringent limit applies at transition frequencies.

4.2 Test Procedure

Test is conducting under the description of ANSI C63.4-2014 American National Standard for Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.



Test Setup Block Diagram

4.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.109 standard limit for a Class B device, and with the worst case as below:

Remark: Level = Reading + Factor, Margin = Level - Limit

