



RF EXPOSURE Test Report

Report No.: MTi240509008-08E3

Date of issue: 2024-06-03

Applicant: Shenzhen Baseus Technology Co., Ltd.

Product: Baseus SafeJourney Series Wireless CarPlay Adapter

Model(s): BS-CG027

FCC ID: 2A482-BSCG027

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.cn>

Instructions

1. The report shall not be partially reproduced without the written consent of the laboratory;
2. The test results of this report are only responsible for the samples submitted;
3. This report is invalid without the seal and signature of the laboratory;
4. This report is invalid if transferred, altered or tampered with in any form without authorization;
5. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.



Test Result Certification	
Applicant:	Shenzhen Baseus Technology Co., Ltd.
Address:	2nd Floor, Building B, Baseus Intelligence Park, No.2008, Xuegang Rd, Gangtou Community, Bantian Street, Longgang District, Shenzhen, China.
Manufacturer:	Shenzhen Baseus Technology Co., Ltd.
Address:	2nd Floor, Building B, Baseus Intelligence Park, No.2008, Xuegang Rd, Gangtou Community, Bantian Street, Longgang District, Shenzhen, China.
Factory:	Shenzhen Anaijia Electronics Co. , Ltd.
Address:	Shenzhen Longhua district, Dalong Street, Hua Fan road, Quanxinyuan industrial zone, building 3
Product description	
Product name:	Baseus SafeJourney Series Wireless CarPlay Adapter
Trademark:	baseus
Model name:	BS-CG027
Series Model:	N/A
Standards:	N/A
Test procedure:	KDB 447498 D01 v06
Date of Test	
Date of test:	2024-05-21 to 2024-05-31
Test result:	Pass

Test Engineer	:	Yanice Xie
		(Yanice.Xie)
Reviewed By	:	David. Lee
		(David Lee)
Approved By	:	Leon Chen
		(Leon Chen)



RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm(20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

BT:

Operation Frequency: 2402-2480MHz,

Power density limited: 1mW/ cm²

Antenna Type: PCB Antenna

Antenna gain: -1.63 dBi

R=20cm

$mW=10^{(dBm/10)}$

Antenna gain Numeric= $10^{(dBi/10)}=10^{(-1.63/10)}=0.69$

5GWiFi:

802.11a: 20 MHz

802.11n: 20 MHz, 40 MHz

Antenna Type: PCB Antenna

Antenna gain:

U-NII 1: 2.27dBi

R=20cm

$mW=10^{(dBm/10)}$

U-NII 1: antenna gain Numeric= $10^{(dBi/10)}=10^{(2.27/10)}=1.69$

BT:

Channe l Freq. (MHz)	modulation	conducted power	Tune- up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm ²)	(mW/cm ²)
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	5.88	5±1	6	3.981	-1.63	0.69	0.0005	1
2441		5.94	5±1	6	3.981	-1.63	0.69	0.0005	1
2480		4.78	5±1	6	3.981	-1.63	0.69	0.0005	1
2402	π/4- DQPSK	6.16	6±1	7	5.012	-1.63	0.69	0.0007	1
2441		6.36	6±1	7	5.012	-1.63	0.69	0.0007	1
2480		5.15	6±1	7	5.012	-1.63	0.69	0.0007	1
2402	8DPSK	7.18	7±1	8	6.310	-1.63	0.69	0.0009	1
2441		6.75	6±1	7	5.012	-1.63	0.69	0.0007	1
2480		5.55	6±1	7	5.012	-1.63	0.69	0.0007	1



5G WIFI: UNII-1

Channel Freq. (MHz)	modulation	Conducted power	Tune- up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm ²)	(mW/cm ²)
				(dBm)	(mW)	Numeric		
5180	11a	13.89	13±1	14	25.119	1.69	0.00843	1
5200	11a	14.03	14±1	15	31.623	1.69	0.01061	1
5240	11a	14.08	14±1	15	31.623	1.69	0.01061	1
5180	11n (VHT20)	13.88	13±1	14	25.119	1.69	0.00843	1
5200	11n (VHT20)	13.83	13±1	14	25.119	1.69	0.00843	1
5240	11n (VHT20)	14.23	14±1	15	31.623	1.69	0.01061	1
5190	11n (VHT40)	13.60	13±1	14	25.119	1.69	0.00843	1
5230	11n (VHT40)	13.71	13±1	14	25.119	1.69	0.00843	1

Conclusion:

For the max result: $0.1061 \leq 1.0$ test exclusion threshold, No SAR is required.

----END OF REPORT----