



TEST REPORT

No. I20N00718-BLE

for

Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd

smartphone

CP3706AS

With

Hardware Version: P1

Software Version: 3706AS.SPRINT.191220.2D

FCC ID: R38YLC3706AS

Issued Date: 2020-04-14

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of SAICT.

Test Laboratory:

SAICT, Shenzhen Academy of Information and Communications Technology

Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China 518026.

Tel:+86(0)755-33322000, Fax:+86(0)755-33322001

Email: yewu@caict.ac.cn. www.saict.ac.cn

CONTENTS

CONTENTS	2
1. SUMMARY OF TEST REPORT.....	3
1.1. TEST ITEMS.....	3
1.2. TEST STANDARDS	3
1.3. TEST RESULT	3
1.4. TESTING LOCATION	3
1.5. PROJECT DATA	3
1.6. SIGNATURE	3
2. CLIENT INFORMATION.....	4
2.1. APPLICANT INFORMATION	4
2.2. MANUFACTURER INFORMATION	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
3.4. GENERAL DESCRIPTION.....	6
4. REFERENCE DOCUMENTS.....	7
4.1. DOCUMENTS SUPPLIED BY APPLICANT	7
4.2. REFERENCE DOCUMENTS FOR TESTING.....	7
5. TEST RESULTS	8
5.1. TESTING ENVIRONMENT.....	8
5.2. TEST RESULTS	8
5.3. STATEMENTS.....	8
6. TEST EQUIPMENTS UTILIZED.....	9
7. LABORATORY ENVIRONMENT.....	10
8. MEASUREMENT UNCERTAINTY	11
ANNEX A: DETAILED TEST RESULTS.....	12
A.0 ANTENNA REQUIREMENT	12
A.1 MAXIMUM PEAK OUTPUT POWER	13
A.2 PEAK POWER SPECTRAL DENSITY	14
A.3 6dB BANDWIDTH.....	19
A.4 BAND EDGES COMPLIANCE	24
A.5 TRANSMITTER SPURIOUS EMISSION - CONDUCTED	28
A.6 TRANSMITTER SPURIOUS EMISSION - RADIATED	46
A.7 AC POWER LINE CONDUCTED EMISSION	70

1. Summary of Test Report

1.1. Test Items

Description	smartphone
Model Name	CP3706AS
Applicant's name	Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd
Manufacturer's Name	Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd

1.2. Test Standards

FCC Part15-2018; ANSI C63.10-2013

1.3. Test Result

Pass

1.4. Testing Location

Address: Building G, Shenzhen International Innovation Center, No.1006 Shennan Road,
Futian District, Shenzhen, Guangdong, P. R. China

1.5. Project data

Testing Start Date:	2019-11-25
Testing End Date:	2020-04-13

1.6. Signature



Lin Zechuang
(Prepared this test report)



Tang Weisheng
(Reviewed this test report)



Zhang Bojun
(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name:	Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd
Address:	Building B, Boton Science Park, Chaguang Road, Xili Town, Nanshan District, Shenzhen
Contact Person	Emily zhang
E-Mail	zhangxuzhu@yulong.com
Telephone:	15089742056
Fax:	/

2.2. Manufacturer Information

Company Name:	Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd
Address:	Building B, Boton Science Park, Chaguang Road, Xili Town, Nanshan District, Shenzhen
Contact Person	Emily zhang
E-Mail	zhangxuzhu@yulong.com
Telephone:	15089742056
Fax:	/

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	smartphone
Model Name	CP3706AS
Brand Name	coolpad
Frequency Range	2400MHz~2483.5MHz
Type of Modulation	GFSK
Number of Channels	40
Antenna Type	Integrated
Antenna Gain	0.52dBi
Power Supply	3.85V DC by Battery
FCC ID	R38YLCP3706AS
Condition of EUT as received	No abnormality in appearance

Note1: According to the customer's description, the EUT is a variant of the CP3706AS. It just changed the model of charger, battery and USB cable. The part of AC Power line Conducted Emission have been rested, other test items results were from the initial model. The initial model report number is I20N02705-BLE.

Note2: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Shenzhen Academy of Information and Communications Technology.

3.2. Internal Identification of EUT used during the test

EUT ID*	IMEI	HW Version	SW Version	Receive Date
EUT1	990015570002451	P1	3706AS.SPRINT.191 220.2D	2019-11-25
EUT2	990015570014472	P1	3706AS.SPRINT.191 220.2D	2020-11-25

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	AE ID*
AE1	Charger	Aa01a
AE2	Battery	/
AE3	Type C Cable	Ca01a

AE1

Model	619043
Manufacturer	Kosun
Length of DC line	/cm

AE2

Model	1.1.0LS0025001
-------	----------------



Manufacturer	Lishen
Capacitance	3980mAh
Nominal Voltage	3.85V
AE3	
Model	SYL-A147A
Manufacturer	Saibao

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment under Test (EUT) is a model of smartphone with integrated antenna and battery.

It consists of normal options: Lithium Battery, Charger and USB Cable.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.



4. Reference Documents

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz	2018
ANSI C63.10	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices	2013

5. Test Results

5.1. Testing Environment

Normal Temperature: 15~35°C

Relative Humidity: 20~75%

5.2. Test Results

No	Test cases	Sub-clause of Part 15C	Verdict
0	Antenna Requirement	15.203	P
1	Maximum Peak Output Power	15.247 (b)	P
2	Peak Power Spectral Density	15.247 (e)	P
3	Occupied 6dB Bandwidth	15.247 (a)	P
4	Band Edges Compliance	15.247 (d)	P
5	Transmitter Spurious Emission - Conducted	15.247 (d)	P
6	Transmitter Spurious Emission - Radiated	15.247, 15.205, 15.209	P
7	AC Power line Conducted Emission	15.107, 15.207	P

See **ANNEX A** for details.

5.3. Statements

SAICT has evaluated the test cases requested by the applicant/manufacture as listed in section 5.2 of this report, for the EUT specified in section 3, according to the standards or reference documents listed in section 4.2.

6. Test Equipments Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date	Calibration Period
1	Vector Signal Analyzer	FSV40	100903	Rohde & Schwarz	2021-01-01	1 year
2	Test Receiver	ESCI	100702	Rohde & Schwarz	2021-01-14	1 year
3	LISN	ENV216	102067	Rohde & Schwarz	2020-07-17	1 year

Radiated emission test system

NO.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date	Calibration Period
1	Loop Antenna	HLA6120	35779	TESEQ	2022-04-25	3 years
2	BiLog Antenna	3142E	00224831	ETS-Lindgren	2021-05-17	3 years
3	Horn Antenna	3117	00066577	ETS-Lindgren	2022-04-02	3 years
4	Test Receiver	ESR7	101676	Rohde & Schwarz	2020-11-27	1 year
5	Spectrum Analyser	FSV40	101192	Rohde & Schwarz	2021-01-14	1 year
6	Chamber	FACT3-2.0	1285	ETS-Lindgren	2021-07-19	3 years
7	Antenna	QSH-SL-18-26-S-20	17013	Q-par	2023-01-06	3 years
8	Antenna	QSH-SL-26-40-K-20	17014	Q-par	2023-01-06	3 years

Test software

No.	Equipment	Manufacturer	Version
1	TechMgr Software	CAICT	2.1.1
2	EMC32	Rohde & Schwarz	8.53.0
3	EMC32	Rohde & Schwarz	10.01.00

EUT is engineering software provided by the customer to control the transmitting signal.
The EUT was programmed to be in continuously transmitting mode.

Anechoic chamber

Fully anechoic chamber by ETS-Lindgren

7. Laboratory Environment

Semi-anechoic chambe

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz> 60 dB; 1MHz-18000MHz>90 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	< ± 4 dB, 3 m distance, from 30 to 1000 MHz

Shielded room

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz> 60 dB; 1MHz-1000MHz>90 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4 Ω

Fully-anechoic chamber

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz> 60 dB; 1MHz-18000MHz>90 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4 Ω
Voltage Standing Wave Ratio (VSWR)	≤ 6 dB, from 1 to 18 GHz, 3 m distance
Uniformity of field strength	Between 0 and 6 dB, from 80 to 6000 MHz

8. Measurement Uncertainty

Test Name	Uncertainty ($k=2$)	
1. RF Output Power - Conducted	1.32dB	
2. Power Spectral Density - Conducted	2.32dB	
3. Occupied channel bandwidth - Conducted	66Hz	
4 Transmitter Spurious Emission - Conducted	$30\text{MHz} \leq f \leq 1\text{GHz}$	1.41dB
	$1\text{GHz} \leq f \leq 7\text{GHz}$	1.92dB
	$7\text{GHz} \leq f \leq 13\text{GHz}$	2.31dB
	$13\text{GHz} \leq f \leq 26\text{GHz}$	2.61dB
5. Transmitter Spurious Emission - Radiated	$9\text{kHz} \leq f \leq 30\text{MHz}$	1.70dB
	$30\text{MHz} \leq f \leq 1\text{GHz}$	4.90dB
	$1\text{GHz} \leq f \leq 18\text{GHz}$	4.60dB
	$18\text{GHz} \leq f \leq 40\text{GHz}$	4.10dB
6. AC Power line Conducted Emission	$150\text{kHz} \leq f \leq 30\text{MHz}$	3.00dB

ANNEX A: Detailed Test Results

A.0 Antenna requirement

Measurement Limit:

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

**Conclusion: The Directional gains of antenna used for transmitting is 0.52 dBi.
The RF transmitter uses an integrate antenna without connector.**

A.1 Maximum Peak Output Power

Method of Measurement: See ANSI C63.10-clause 11.9.1.1

Use the following spectrum analyzer settings:

- a) Set the RBW = 1 MHz.
- b) Set VBW = 3 MHz.
- c) Set span = 3 MHz.
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

Measurement Limit:

Standard	Limit (dBm)
FCC 47 CRF Part 15.247(b)	< 30

Measurement Results:

Mode	RF output power (dBm)		
	2402MHz (Ch0)	2440MHz(Ch19)	2480MHz(Ch39)
LE 1M	2.13	3.54	5.25
LE 2M	2.31	3.66	5.47
LE Coded	2.44	3.80	5.49

Conclusion: Pass

A.2 Peak Power Spectral Density

Method of Measurement: See ANSI C63.10-clause 11.10.2

Measurement Limit:

Standard	Limit
FCC 47 CRF Part 15.247(e)	< 8 dBm/3 kHz

Measurement Results:

Mode	Frequency (MHz)	Peak Power Spectral Density (dBm)		Conclusion
LE 1M	2402 (CH0)	Fig.1	-11.16	P
	2440 (CH19)	Fig.2	-10.40	P
	2480 (CH39)	Fig.3	-8.78	P
LE 2M	2402 (CH0)	Fig.4	-15.11	P
	2440 (CH19)	Fig.5	-14.47	P
	2480 (CH39)	Fig.6	-12.83	P
LE Coded	2402 (CH0)	Fig.7	-2.50	P
	2440 (CH19)	Fig.8	-1.81	P
	2480 (CH39)	Fig.9	-0.25	P

See below for test graphs.

Conclusion: PASS




Fig.1 Power Spectral Density (Ch 0), LE 1M




Fig.2 Power Spectral Density (Ch 19), LE 1M




Fig.3 Power Spectral Density (Ch 39), LE 1M




Fig.4 Power Spectral Density (Ch 0), LE 2M




Fig.5 Power Spectral Density (Ch 19), LE 2M




Fig.6 Power Spectral Density (Ch 39), LE 2M




Fig.7 Power Spectral Density (Ch 0), LE Coded




Fig.8 Power Spectral Density (Ch 19), LE Coded




Fig.9 Power Spectral Density (Ch 39), LE Coded

A.3 6dB Bandwidth

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.247 (a)	≥ 500

Measurement Result:

Mode	Frequency (MHz)	Test Results (kHz)		Conclusion
LE 1M	2402(CH0)	Fig.10	663.50	P
	2440(CH19)	Fig.11	670.50	P
	2480(CH39)	Fig.12	660.50	P
LE 2M	2402(CH0)	Fig.13	1129.50	P
	2440(CH19)	Fig.14	1136.00	P
	2480(CH39)	Fig.15	1134.00	P
LE Coded	2402(CH0)	Fig.16	602.00	P
	2440(CH19)	Fig.17	603.50	P
	2480(CH39)	Fig.18	602.50	P

See below for test graphs.

Conclusion: PASS



Fig.10 6dB Bandwidth (Ch 0), LE 1M




Fig.11 6dB Bandwidth (Ch 19), LE 1M




Fig.12 6dB Bandwidth (Ch 39), LE 1M




Fig.13 6dB Bandwidth (Ch 0), LE 2M




Fig.14 6dB Bandwidth (Ch 19), LE 2M




Fig.15 6dB Bandwidth (Ch 39), LE 2M




Fig.16 6dB Bandwidth (Ch 0), LE Coded




Fig.17 6dB Bandwidth (Ch 19), LE Coded




Fig.18 6dB Bandwidth (Ch 39), LE Coded

A.4 Band Edges Compliance

Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	> 20

Measurement Result:

Mode	Frequency (MHz)	Test Results		Conclusion
LE 1M	2402(CH0)	Fig.19	56.19	P
	2480(CH39)	Fig.20	63.85	P
LE 2M	2402(CH0)	Fig.21	47.85	P
	2480(CH39)	Fig.22	62.08	P
LE Coded	2402(CH0)	Fig.23	56.84	P
	2480(CH39)	Fig.24	64.24	P

See below for test graphs.

Conclusion: PASS




Fig.19 Band Edges (Ch 0), LE 1M




Fig.20 Band Edges (Ch 39), LE 1M




Fig.21 Band Edges (Ch 0), LE 2M




Fig.22 Band Edges (Ch 39), LE 2M




Fig.23 Band Edges (Ch 0), LE Coded




Fig.24 Band Edges (Ch 39), LE Coded

A.5 Transmitter Spurious Emission - Conducted

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

Measurement Results:

MODE	Channel	Frequency Range	Test Results	Conclusion
LE 1M	0	2.402 GHz	Fig.25	P
		1GHz -3GHz	Fig.26	P
		3GHz-10GHz	Fig.27	P
	19	2.440 GHz	Fig.28	P
		1GHz -3GHz	Fig.29	P
		3GHz-10GHz	Fig.30	P
	39	2.480 GHz	Fig.31	P
		1GHz -3GHz	Fig.32	P
		3GHz-10GHz	Fig.33	P
	All channels	30MHz-1GHz	Fig.34	P
		10GHz-26GHz	Fig.35	P
LE 2M	0	2.402 GHz	Fig.36	P
		1GHz -3GHz	Fig.37	P
		3GHz-10GHz	Fig.38	P
	19	2.440 GHz	Fig.39	P
		1GHz -3GHz	Fig.40	P
		3GHz-10GHz	Fig.41	P
	39	2.480 GHz	Fig.42	P
		1GHz -3GHz	Fig.43	P
		3GHz-10GHz	Fig.44	P
	All channels	30MHz-1GHz	Fig.45	P
		10GHz-26GHz	Fig.46	P
LE Coded	0	2.402 GHz	Fig.47	P
		1GHz -3GHz	Fig.48	P
		3GHz-10GHz	Fig.49	P
	19	2.440 GHz	Fig.50	P
		1GHz -3GHz	Fig.51	P
		3GHz-10GHz	Fig.52	P
	39	2.480 GHz	Fig.53	P
		1GHz -3GHz	Fig.54	P
		3GHz-10GHz	Fig.55	P
	All channels	30MHz-1GHz	Fig.56	P
		10GHz-26GHz	Fig.57	P

See below for test graphs.

Conclusion: Pass



Fig.25 Conducted Spurious Emission (Ch0, Center Frequency), LE 1M




Fig.26 Conducted Spurious Emission (Ch0, 1 GHz-3 GHz), LE 1M




Fig.27 Conducted Spurious Emission (Ch0, 3 GHz-10 GHz), LE 1M




Fig.28 Conducted Spurious Emission (Ch19, Center Frequency), LE 1M




Fig.29 Conducted Spurious Emission (Ch19, 1 GHz-3 GHz), LE 1M




Fig.30 Conducted Spurious Emission (Ch19, 3 GHz-10 GHz), LE 1M




Fig.31 Conducted Spurious Emission (Ch39, Center Frequency), LE 1M




Fig.32 Conducted Spurious Emission (Ch39, 1 GHz-3 GHz), LE 1M




Fig.33 Conducted Spurious Emission (Ch39, 3 GHz-10 GHz), LE 1M




Fig.34 Conducted Spurious Emission (All channels, 30 MHz-1 GHz), LE 1M




Fig.35 Conducted Spurious Emission (All channels, 10 GHz-26 GHz), LE 1M




Fig.36 Conducted Spurious Emission (Ch0, Center Frequency), LE 2M




Fig.37 Conducted Spurious Emission (Ch0, 1 GHz-3 GHz), LE 2M




Fig.38 Conducted Spurious Emission (Ch0, 3 GHz-10 GHz), LE 2M




Fig.39 Conducted Spurious Emission (Ch19, Center Frequency), LE 2M




Fig.40 Conducted Spurious Emission (Ch19, 1 GHz-3 GHz), LE 2M




Fig.41 Conducted Spurious Emission (Ch19, 3 GHz-10 GHz), LE 2M




Fig.42 Conducted Spurious Emission (Ch39, Center Frequency), LE 2M




Fig.43 Conducted Spurious Emission (Ch39, 1 GHz-3 GHz), LE 2M




Fig.44 Conducted Spurious Emission (Ch39, 3 GHz-10 GHz), LE 2M




Fig.45 Conducted Spurious Emission (All channels, 30 MHz-1 GHz), LE 2M




Fig.46 Conducted Spurious Emission (All channels, 10 GHz-26 GHz), LE 2M




Fig.47 Conducted Spurious Emission (Ch0, Center Frequency), LE Coded




Fig.48 Conducted Spurious Emission (Ch0, 1 GHz-3 GHz), LE Coded




Fig.49 Conducted Spurious Emission (Ch0, 3 GHz-10 GHz), LE Coded




Fig.50 Conducted Spurious Emission (Ch19, Center Frequency), LE Coded




Fig.51 Conducted Spurious Emission (Ch19, 1 GHz-3 GHz), LE Coded




Fig.52 Conducted Spurious Emission (Ch19, 3 GHz-10 GHz), LE Coded




Fig.53 Conducted Spurious Emission (Ch39, Center Frequency), LE Coded




Fig.54 Conducted Spurious Emission (Ch39, 1 GHz-3 GHz), LE Coded




Fig.55 Conducted Spurious Emission (Ch39, 3 GHz-10 GHz), LE Coded




Fig.56 Conducted Spurious Emission (All channels, 30 MHz-1 GHz), LE Coded




Fig.57 Conducted Spurious Emission (All channels, 10 GHz-26 GHz), LE Coded

A.6 Transmitter Spurious Emission - Radiated

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency of emission (MHz)	Field strength(μ V/m)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Condition:

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	120kHz/300kHz	5
1000-4000	1MHz/3MHz	15
4000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

Note: According to the performance evaluation, the radiated emission margin of EUT is over 20dB in the band from 9kHz to 30MHz. Therefore, the measurement starts from 30MHz to tenth harmonic. The measurement results include the horizontal polarization and vertical polarization measurements.

Measurement Results:

Mode	Channel	Frequency Range	Test Results	Conclusion
LE 1M	0	1 GHz ~3 GHz	Fig.58	P
		3 GHz ~18 GHz	Fig.59	P
	19	1 GHz ~3 GHz	Fig.60	P
		3 GHz ~18 GHz	Fig.61	P
	39	1 GHz ~3 GHz	Fig.62	P
		3 GHz ~18 GHz	Fig.63	P
	Restricted Band(CH0)	2.38 GHz ~ 2.45 GHz	Fig.64	P
	Restricted Band(CH39)	2.45 GHz ~ 2.5 GHz	Fig.65	P
	All channels	9 kHz ~30 MHz	Fig.66	P
		30 MHz ~1 GHz	Fig.67	P
		1 GHz ~18 GHz	Fig.68	P
LE 2M	0	1 GHz ~3 GHz	Fig.69	P
		3 GHz ~18 GHz	Fig.70	P
	19	1 GHz ~3 GHz	Fig.71	P
		3 GHz ~18 GHz	Fig.72	P
	39	1 GHz ~3 GHz	Fig.73	P
		3 GHz ~18 GHz	Fig.74	P
	Restricted Band(CH0)	2.38 GHz ~ 2.45 GHz	Fig.75	P
	Restricted Band(CH39)	2.45 GHz ~ 2.5 GHz	Fig.76	P
	All channels	9 kHz ~30 MHz	Fig.77	P
		30 MHz ~1 GHz	Fig.78	P
		1 GHz ~18 GHz	Fig.79	P
LE Coded	0	1 GHz ~3 GHz	Fig.80	P
		3 GHz ~18 GHz	Fig.81	P
	19	1 GHz ~3 GHz	Fig.82	P
		3 GHz ~18 GHz	Fig.83	P
	39	1 GHz ~3 GHz	Fig.84	P
		3 GHz ~18 GHz	Fig.85	P
	Restricted Band(CH0)	2.38 GHz ~ 2.45 GHz	Fig.86	P
	Restricted Band(CH39)	2.45 GHz ~ 2.5 GHz	Fig.87	P
	All channels	9 kHz ~30 MHz	Fig.88	P
		30 MHz ~1 GHz	Fig.89	P
		1 GHz ~18 GHz	Fig.90	P

Worst Case Result

LE 1M:

GFSK CH0 (1-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
12072.5000	46.81	---	74.00	27.19	H	7.3
13325.0000	47.18	---	74.00	26.82	V	8.9
15556.5000	48.72	---	74.00	25.28	V	11.8
14490.0000	49.40	---	74.00	24.60	H	11.4
16565.0000	50.59	---	74.00	23.41	H	14.8
17930.0000	51.66	---	74.00	22.34	V	16.1
11635.5000	---	37.36	54.00	16.64	V	6.9
12523.5000	---	37.47	54.00	16.53	H	8.0
13288.5000	---	38.13	54.00	15.87	V	8.9
14884.5000	---	39.06	54.00	14.94	V	11.1
16683.0000	---	41.30	54.00	12.70	V	14.9
17926.0000	---	42.50	54.00	11.50	H	16.1

GFSK CH19 (1-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
10640.0000	45.60	---	74.00	28.40	H	4.9
11711.0000	46.88	---	74.00	27.12	V	6.9
12932.5000	46.97	---	74.00	27.03	V	8.6
14511.5000	49.18	---	74.00	24.82	H	11.5
16120.0000	50.89	---	74.00	23.11	V	14.1
17893.0000	51.56	---	74.00	22.44	H	16.2
11699.0000	---	37.57	54.00	16.43	V	7.0
12505.5000	---	37.37	54.00	16.63	V	8.0
13310.0000	---	37.82	54.00	16.18	V	9.0
14517.5000	---	39.99	54.00	14.01	V	11.5
16748.0000	---	41.45	54.00	12.55	H	14.9
17913.5000	---	42.40	54.00	11.60	V	16.3

GFSK CH39 (1-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
10835.5000	46.08	---	74.00	27.92	V	5.3
11855.5000	46.95	---	74.00	27.05	H	6.8
13073.5000	47.01	---	74.00	26.99	V	8.4
14496.0000	48.63	---	74.00	25.37	V	11.4
16225.0000	50.65	---	74.00	23.35	V	14.3
17914.0000	52.25	---	74.00	21.75	H	16.3
10585.5000	---	36.06	54.00	17.94	H	5.0
12034.0000	---	37.46	54.00	16.54	V	7.2
13312.0000	---	37.65	54.00	16.35	V	8.9
14519.5000	---	39.43	54.00	14.57	H	11.5
16689.0000	---	41.41	54.00	12.59	H	14.9
17916.5000	---	41.87	54.00	12.13	H	16.2

LE 2M:
GFSK CH0 (1-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
10235.5000	46.10	---	74.00	27.90	H	5.2
11663.0000	47.17	---	74.00	26.83	H	6.9
12793.5000	47.71	---	74.00	26.29	V	7.8
14458.5000	48.73	---	74.00	25.27	V	11.2
16352.5000	50.52	---	74.00	23.48	H	14.4
17873.5000	50.98	---	74.00	23.02	V	16.3
10458.5000	---	36.21	54.00	17.79	H	5.0
11899.5000	---	36.76	54.00	17.24	V	7.1
13309.5000	---	37.99	54.00	16.01	V	9.0
14631.0000	---	39.85	54.00	14.15	V	11.3
16564.0000	---	41.50	54.00	12.50	V	14.8
17957.5000	---	41.97	54.00	12.03	V	16.1

GFSK CH19 (1-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
10181.0000	45.34	---	74.00	28.66	V	5.1
11685.5000	46.60	---	74.00	27.40	V	7.1
13376.5000	47.67	---	74.00	26.33	V	8.5
14875.0000	48.91	---	74.00	25.09	H	11.0
16382.5000	50.75	---	74.00	23.25	V	14.0
17881.5000	51.69	---	74.00	22.31	V	16.2
10596.5000	---	36.26	54.00	17.74	H	4.9
12110.0000	---	37.33	54.00	16.67	V	7.3
13308.0000	---	37.66	54.00	16.34	H	9.0
14500.0000	---	39.11	54.00	14.89	V	11.5
16684.5000	---	41.68	54.00	12.32	H	14.9
17907.0000	---	42.02	54.00	11.98	H	16.3

GFSK CH39 (1-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
10641.0000	45.32	---	74.00	28.68	H	4.9
13295.0000	47.38	---	74.00	26.62	V	8.9
11685.5000	47.42	---	74.00	26.58	V	7.1
14498.5000	48.73	---	74.00	25.27	H	11.4
16315.0000	50.87	---	74.00	23.13	V	14.3
17899.5000	51.57	---	74.00	22.43	H	16.3
10982.0000	---	35.97	54.00	18.03	V	5.1
12101.0000	---	37.15	54.00	16.85	V	7.4
13279.5000	---	37.94	54.00	16.06	V	8.8
14506.5000	---	39.14	54.00	14.86	H	11.5
16316.0000	---	41.37	54.00	12.63	V	14.3
17899.0000	---	42.24	54.00	11.76	H	16.3

LE Coded:

GFSK CH0 (1-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
10450.00	45.93	---	74.00	28.07	V	5
12114.00	47.14	---	74.00	26.86	V	7.3
13221.00	47.67	---	74.00	26.33	V	8.6
14472.50	49.72	---	74.00	24.28	V	11.3
17923.50	51.18	---	74.00	22.82	V	16.2
16871.50	51.32	---	74.00	22.68	V	14.9
10427.50	---	36.53	54.00	17.47	V	5.1
11708.00	---	37.34	54.00	16.66	H	6.9
12934.50	---	37.64	54.00	16.36	V	8.6
14488.50	---	39.67	54.00	14.33	V	11.3
16684.00	---	41.68	54.00	12.32	V	14.9
17908.00	---	41.81	54.00	12.19	V	16.3

GFSK CH19 (1-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
11549.50	46.40	---	74.00	27.60	V	6.4
12332.50	46.89	---	74.00	27.11	V	7.3
13238.00	47.28	---	74.00	26.72	V	8.7
14504.50	49.06	---	74.00	24.94	H	11.5
16733.00	51.17	---	74.00	22.83	H	14.9
17833.50	51.40	---	74.00	22.60	V	16.3
11405.50	---	36.60	54.00	17.40	V	5.6
12541.00	---	37.87	54.00	16.13	V	8.1
13292.00	---	38.10	54.00	15.90	H	8.9
14544.00	---	39.57	54.00	14.43	H	11.4
16218.00	---	40.96	54.00	13.04	V	14.3
17923.50	---	42.31	54.00	11.69	H	16.2

GFSK CH39 (1-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Corr. (dB)
11658.00	46.92	---	74.00	27.08	H	6.9
12526.50	47.68	---	74.00	26.32	H	8
13309.00	48.42	---	74.00	25.58	H	9
15251.00	48.67	---	74.00	25.33	H	11.2
17953.50	51.91	---	74.00	22.09	V	16.1
16930.50	52.31	---	74.00	21.69	H	14.9
12316.00	---	37.48	54.00	16.52	V	7.2
12916.50	---	37.71	54.00	16.29	V	8.6
14503.00	---	39.53	54.00	14.47	V	11.5
15883.00	---	39.89	54.00	14.11	H	13.1
16645.00	---	41.36	54.00	12.64	H	14.9
17897.00	---	42.15	54.00	11.85	H	16.3

Note:

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and Antenna Factor, the gain of the preamplifier, the cable loss. P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result= P_{Mea} +Cable Loss +Antenna Factor-Gain of the preamplifier.

See below for test graphs.

Conclusion: Pass




Fig.58 Radiated Spurious Emission, LE 1M (GFSK, Ch0, 1 GHz ~3 GHz)




Fig.59 Radiated Spurious Emission , LE 1M (GFSK, Ch0, 3 GHz ~18 GHz)