

FCC Test Report

Report No.: AGC01689241119FR03

FCC ID : 2A2UU-B1796

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: POS Terminal

BRAND NAME : Kozen

MODEL NAME : P3

APPLICANT: Shanghai Xiangcheng Communication Technology Co., Ltd

DATE OF ISSUE : Feb. 17, 2025

STANDARD(S) : FCC Part 15 Subpart C §15.247

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Page 2 of 84

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Feb. 17, 2025	Valid	Initial Release



Table of Contents

1. General Information	5
2. Product Information	6
2.1 Product Technical Description	6
2.2 Table of Carrier Frequency	7
2.3 IEEE 802.11n Modulation Scheme	
2.4 Related Submittal(S) / Grant (S)	9
2.5 Test Methodology	9
2.6 Special Accessories	9
2.7 Equipment Modifications	9
2.8 Antenna Requirement	9
2.9 Description of Test Software	10
3. Test Environment	11
3.1 Address of The Test Laboratory	11
3.2 Test Facility	11
3.3 Environmental Conditions	12
3.4 Measurement Uncertainty	12
3.5 List of Equipment Used	13
4.System Test Configuration	15
4.1 EUT Configuration	15
4.2 EUT Exercise	15
4.3 Configuration of Tested System	15
4.4 Equipment Used in Tested System	15
4.5 Summary of Test Results	15
5. Description of Test Modes	17
6. Duty Cycle Measurement	18
7. RF Output Power Measurement	
7.1 Provisions Applicable	20
7.2 Measurement Procedure	20
7.3 Measurement Setup (Block Diagram of Configuration)	20
7.4 Measurement Result	21
8. 6dB Bandwidth Measurement	22
8.1 Provisions Applicable	22
8.2 Measurement Procedure	22
8.3 Measurement Setup (Block Diagram of Configuration)	22
8.4 Measurement Result	23
9. Power Spectral Density Measurement	36





	9.1 Provisions Applicable	36
	9.2 Measurement Procedure	36
	9.3 Measurement Setup (Block Diagram of Configuration)	37
	9.4 Measurement Result	37
10	. Conducted Band Edge and Out-of-Band Emissions	44
	10.1 Provisions Applicable	44
	10.2 Measurement Procedure	44
	10.3 Measurement Setup (Block Diagram of Configuration)	44
	10.4 Measurement Result	45
11	. Radiated Spurious Emission	59
	11.1 Measurement Limits	59
	11.2 Measurement Procedure	59
	11.3 Measurement Setup (Block Diagram of Configuration)	62
	11.4 Measurement Result	63
12	AC Power Line Conducted Emission	80
	12.1 Measurement Limits	80
	12.2 Block Diagram of Line Conducted Emission Test	80
	12.3 Preliminary Procedure of Line Conducted Emission Test	81
	12.4 Final Procedure of Line Conducted Emission Test	81
	12.5 Test Result of Line Conducted Emission Test	81
Αŗ	ppendix I: Photographs of Test Setup	84
Αŗ	ppendix II: Photographs of Test EUT	84




1. General Information

Applicant	Shanghai Xiangcheng Communication Technology Co., Ltd
Address	6th Floor, Building 10, No.3000 Longdong Avenue, Pudong New District, Shanghai, China
Manufacturer	Sichuan Xiangcheng Intelligent Technology Co., Ltd.
Address	Factory No. 2 and 7 Zone A, Intelligent Terminal Demonstration Park, West Section of Gangyuan Road, Lingang Economic Development Zone, Yibin City, Sichuan Province China
Factory	Sichuan Xiangcheng Intelligent Technology Co., Ltd.
Address	Factory No. 2 and 7 Zone A, Intelligent Terminal Demonstration Park, West Section of Gangyuan Road, Lingang Economic Development Zone, Yibin City, Sichuan Province China
Product Designation	POS Terminal
Brand Name	Kozen
Test Model	P3
Series Model(s)	N/A
Difference Description	N/A
Date of receipt of test item	Nov. 18, 2024
Date of Test	Nov. 18, 2024~Jan. 15, 2025
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-2.4GWLAN-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By	Bibo Zhang	
	Bibo Zhang (Project Engineer)	Feb. 17, 2025
Reviewed By	Calin Lin	
	Calvin Liu (Reviewer)	Feb. 17, 2025
Approved By	Angole li	
•	Angela Li (Authorized Officer)	Feb. 17, 2025





2. Product Information

2.1 Product Technical Description

Equipment Type	WLAN 2.4G		
Frequency Band	2400MHz ~ 2483.5MHz		
Operation Frequency	2412MHz ~ 2462MHz		
Output Power (Average)	IEEE 802.11b:16.85dBm; IEEE 802.11g:14.75dBm;		
Output Fower (Average)	IEEE 802.11n(HT20):13.114dBm; IEEE 802.11n(HT40):12.87dBm		
Output Power (Peak)	IEEE 802.11b:19.48dBm; IEEE 802.11g:22.12dBm;		
Output Fower (Feak)	IEEE 802.11n(HT20):20.68dBm; IEEE 802.11n(HT40):21.00dBm		
Modulation	802.11b:(DQPSK, DBPSK, CCK) DSSS		
iviodulation	802.11g/n:(64-QAM,16-QAM, QPSK, BPSK) OFDM		
	802.11b:1/2/5.5/11Mbps		
Data Rate	802.11g: 6/9/12/18/24/36/48/54Mbps		
	802.11n: up to 300Mbps		
Number of channels	11		
Hardware Version	V1.0A		
Software Version	b1796_kozen_combo_202408061611		
Antenna Designation	PIFA Antenna		
Antenna Gain	0.12dBi		
Power Supply	DC 7.4V 2600mAh by battery or DC 5V from adapter		



2.2 Table of Carrier Frequency

For 2412-2462MHz:

11 channels are provided for 802.11b/g/n(HT20):

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz		

7 channels are provided for 802.11n(HT40):

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	-	02	-	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	1	11	-		



2.3 IEEE 802.11n Modulation Scheme

					N _{CBPS}		N _{CBPS} N _{DBPS}		Data Ra	te(Mbps)
MCS Index	Nss	Modulation	R	N _{BPSC}					800nsGI	
Huex					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0
6	1	64-QAM	3/4	6	312	648	234	489	58.5	121.5
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	Guard interval



Page 9 of 84

2.4 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **2A2UU-B1796**, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.5 Test Methodology

The tests were performed according to following standards:

	No. Identity		Document Title		
	1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations		
	2	FCC 47 CFR Part 15	Radio Frequency Devices		
•	3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices		

2.6 Special Accessories

Refer to section 4.4.

2.7 Equipment Modifications

Not available for this EUT intended for grant.

2.8 Antenna Requirement

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 0.9dBi.



Page 10 of 84

2.9 Description of Test Software

For IEEE 802.11 mode:

The test software is through engineering commands, EUT can be set to a separate test mode.

	·	•
Test Mode	Channel	Power Index
802.11b	L/M/H	18
802.11g	L/M/H	16
802.11n-HT20	L/M/H	14
802.11n-HT40	L/M/H	14



Page 11 of 84

3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories).

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



3.3 Environmental Conditions

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106

3.4 Measurement Uncertainty

The reported uncertainty of measurement y±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	U _c = ±2 %
Uncertainty of Occupied Channel Bandwidth	U _c = ±2 %




3.5 List of Equipment Used

• R	RF Conducted Test System								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2024-05-24	2025-05-23		
\boxtimes	AGC-ER-E062	Power Sensor	Agilent	U2021XA	MY54110007	2024-02-01	2025-01-31		
\boxtimes	AGC-ER-E063	Power Sensor	Agilent	U2021XA	MY54110009	2024-02-01	2025-01-31		
\boxtimes	AGC-ER-A001	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-09-21	2025-09-20		
\boxtimes	AGC-ER-E083	Signal Generator	Agilent	E4421B	US39340815	2024-05-23	2025-05-22		
	N/A	RF Connection Cable	N/A	1#	N/A	Each time	N/A		
	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A		

• F	Radiated Spurious Emission								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
\boxtimes	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31		
\boxtimes	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23		
\boxtimes	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27		
\boxtimes	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04		
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10		
\boxtimes	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2024-03-31	2025-03-30		
\boxtimes	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23		
\boxtimes	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23		
	AGC-EM-A119	2.4G Filter	SongYi	N/A	N/A	2024-05-23	2025-05-22		
\boxtimes	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08		
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08		

A	AC Power Line Conducted Emission								
Used	sed Equipment No. Test Equipment Manufacturer Model No. Serial No. Last Cal. Date (YY-MM-DD) (YY-MM-DD)								
\boxtimes	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2024-05-28	2025-05-27		
\boxtimes	AGC-EM-A130	6dB Attenuator	Eeatsheep	LM-XX-6-5W	DC-6GZ	2023-06-09	2025-06-08		
\boxtimes	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2024-05-28	2025-05-27		





• Te:	Test Software							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information			
\boxtimes	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71			
\boxtimes	AGC-EM-S003	RE Test System	FARA	EZ-EMC	VRA-03A			
\boxtimes	AGC-ER-S012	BT/WIFI Test System	Tonscend	JS1120-2	2.6			
\boxtimes	AGC-EM-S011	RSE Test System	Tonscend	TS+-Ver2.1(JS36-RSE)	4.0.0.0			



4.System Test Configuration


4.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System



4.4 Equipment Used in Tested System

The following peripheral devices and interface cables were connected during the measurement:

☐ Test Accessories Come From The Laboratory

□ Test Accessories Come From The Manufacturer

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	Adapter	Shenzhen Tianyin Electronics Co.,Ltd	LM-603U-050200U02UL	Input: AC 100-240V 50/60Hz, 0.35A Output: DC 5V 2A	1.0m unshielded
2	Battery	DongGuan Hongde Battery Co.,Ltd.	B1791	DC 7.4V 2600mAh	



4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.203&15.247(b)(4)	Antenna Equipment	Pass
2	§15.247 (b)(1)	RF Output Power	Pass
3	§15.247 (a)(1)	6 dB Bandwidth	Pass
4	§15.247 (e)	Power Spectral Density	Pass
5	§15.247 (d)	Conducted Band Edge and Out-of-Band Emissions	Pass
6	§15.247 (d)&15.209	Radiated Spurious Emission	Pass
7	§15.207	AC Power Line Conducted Emission	Pass



5. Description of Test Modes

	Summary table of Test Cases					
Toot Itom	Data Rate / Modulation					
Test Item -	2.4G WLAN - 802.11b/g/n/ax (DSSS/OFDM/OFDMA)					
	Mode 1: 802.11b_TX CH01_2412 MHz_1 Mbps					
	Mode 2: 802.11b_TX CH06_2437 MHz_1 Mbps					
	Mode 3: 802.11b_TX CH11_2462 MHz_1 Mbps					
	Mode 4: 802.11g_TX CH01_2412 MHz_6 Mbps					
	Mode 5: 802.11g_TX CH06_2437 MHz_6 Mbps					
	Mode 6: 802.11g_TX CH11_2462 MHz_6 Mbps					
Radiated & Conducted	Mode 7: 802.11n-HT20_TX CH01_2412 MHz_MCS0 Mbps					
Test Cases	Mode 8: 802.11n-HT20_TX CH06_2437 MHz_ MCS0 Mbps					
	Mode 9: 802.11n-HT20_TX CH11_2462 MHz_ MCS0 Mbps					
	Mode 10: 802.11n-HT40_TX CH03_2422 MHz_MCS0 Mbps					
	Mode 11: 802.11n-HT40_TX CH06_2437 MHz_ MCS0 Mbps					
	Mode 12: 802.11n-HT40_TX CH09_2452 MHz_ MCS0 Mbps					
AC Conducted Emission	Mode 1: 2.4G WLAN Link + Battery + USB Cable (Charging from AC Adapter)					

Note:

- 1. The battery is full-charged during the test.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.



Page 18 of 84

6. Duty Cycle Measurement

2.4GHz WLAN (DTS) operation is possible in 20MHz, and 40MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = Average. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:


Operating mode	Data rates (Mbps)	Duty Cycle (%)	Duty Cycle Factor (dB)
IEEE 802.11b	1	100	/
IEEE 802.11g	6	97	0.13
IEEE 802.11n-HT20	MCS0	97	0.13
IEEE 802.11n-HT40	MCS0	95	0.22

Remark:

- 1. Duty Cycle factor = 10 * log (1/ Duty cycle)
- 2. The duty cycle of each frequency band mode reflects the determination requirements of the Middle channel measurement value.



The test plots as follows:





7. RF Output Power Measurement

7.1 Provisions Applicable

For DTSs employing digital modulation techniques operating in the bands 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W.

7.2 Measurement Procedure


Method PM is Measurement using an RF Peak power meter. The procedure for this method is as follows:

- 1. The testing follows the ANSI C63.10 Section 11.9.1.3
- 2. The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

Method PM is Measurement using an RF AV power meter. The procedure for this method is as follows:

- 1. The testing follows the ANSI C63.10 Section 11.9.2.3
- 2. Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the following conditions are satisfied:
- 3. The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
- 4. At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
- 5. The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- 6. Determine according to the duty cycle of the equipment: when it is less than 98%, follow the steps below.
- 7. Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
- 8. Adjust the measurement in dBm by adding [10 log (1 / D)], where D is the duty cycle {e.g., [10 log (1 / 0.25)], if the duty cycle is 25%}.
- 9. Record the test results in the report.

7.3 Measurement Setup (Block Diagram of Configuration)





7.4 Measurement Result

	Test Data of Conducted Output Power							
Test Mode	Test Frequency (MHz)	Average Power (dBm)	Peak Power (dBm)	Limits (dBm)	Pass or Fail			
	2412	16.73	19.35	≤30	Pass			
802.11b	2437	16.85	19.48	≤30	Pass			
	2462	16.66	19.23	≤30	Pass			
	2412	13.82	21.21	≤30	Pass			
802.11g	2437	14.75	21.76	≤30	Pass			
	2462	14.44	22.12	≤30	Pass			
	2412	13.11	20.68	≤30	Pass			
802.11n20	2437	12.80	20.66	≤30	Pass			
	2462	12.69	20.41	≤30	Pass			
	2422	12.83	20.94	≤30	Pass			
802.11n40	2437	12.67	20.48	≤30	Pass			
1	2452	12.87	21.00	≤30	Pass			



8. 6dB Bandwidth Measurement


8.1 Provisions Applicable

The minimum 6dB bandwidth shall be 500 kHz.

8.2 Measurement Procedure

- The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- 3. For 6dB Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement.
- For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the OBW and set the Video bandwidth (VBW) ≥ 3 * RBW.
- 5. Detector = peak
- 6. Trace mode = max hold.
- 7. Sweep = auto couple.
- 8. Allow the trace to stabilize.
- 9. Measure and record the results in the test report.

8.3 Measurement Setup (Block Diagram of Configuration)






8.4 Measurement Result

	Test Data of Occupied Bandwidth and DTS Bandwidth								
Test Mode	Test Frequency (MHz)	99% Occupied Bandwidth (MHz)	DTS Bandwidth (MHz)	DTS Bandwidth Limits (MHz)	Result				
	2412	12.391	9.095	≥0.5	Pass				
802.11b	2437	12.389	9.600	≥0.5	Pass				
	2462	12.398	9.063	≥0.5	Pass				
	2412	16.543	15.328	≥0.5	Pass				
802.11g	2437	16.463	13.888	≥0.5	Pass				
	2462	16.468	15.478	≥0.5	Pass				
	2412	17.728	17.597	≥0.5	Pass				
802.11n20	2437	17.720	17.654	≥0.5	Pass				
	2462	17.708	17.599	≥0.5	Pass				
	2422	35.917	35.202	≥0.5	Pass				
802.11n40	2437	35.928	33.945	≥0.5	Pass				
	2452	35.933	35.111	≥0.5	Pass				




Test Graphs of Occupied Bandwidth




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.




























Test Graphs of DTS Bandwidth




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


























Page 36 of 84

9. Power Spectral Density Measurement

9.1 Provisions Applicable

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

9.2 Measurement Procedure

⊠For Peak power spectral density test:


- 1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 3. Set the RBW = 20 kHz.
- 4. Set the VBW \geq [3 × RBW].
- 5. Set the Span ≥ [1.5 × DTS bandwidth].
- 6. Sweep time=Auto couple.
- 7. Detector function=Peak.
- 8. Trace Mode=Max hold.
- 9. When the measurement bandwidth of the maximum PSD is 3 kHz, a constant factor of 10*log(3kHz/20kHz) = -8.23 dB is added to the measurement result.
- 10. Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission.
- 11. The indicated level is the peak output power, after any corrections for external attenuators and cables.

☐ For Average power spectral density test:

- 1. The testing follows the ANSI C63.10 Section 11.10.5 Method AVPSD.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator.
- 3. Set Span to at least 1.5 times the OBW.
- 4. Set RBW to:3 kHz ≤ RBW ≤ 100 kHz.
- 5. Set VBW≥[3×RBW].
- 6. Sweep Time=Auto couple.
- 7. Detector function=RMS (i.e., power averaging).
- 8. Trace average at least 100 traces in power averaging (rms) mode.
- 9. When the measurement bandwidth of the maximum PSD is 3 kHz, a constant factor of 10*log(3kHz/20kHz) = -8.23 dB is added to the measurement result.
- 10. Determine according to the duty cycle of the equipment: when it is less than 98%, follow the steps below.
- 11. Add [10 log (1 / D)], where D is the duty cycle, to the measured power to compute the average power during the actual transmission times (because the measurement represents an average over both the ON and OFF times of the transmission). For example, add [10 log (1/0.25)] = 6 dB if the duty cycle is 25%.
- 12. Record the test results in the report.



9.3 Measurement Setup (Block Diagram of Configuration)



9.4 Measurement Result

	Test Data of Conducted Output Power Spectral Density						
Test Mode	Test Frequency (MHz)	Power Spectral density (dBm/20kHz)	Power Spectral density (dBm/3kHz)	Limit (dBm/3kHz)	Result		
	2412	3.478	-4.761	≪8	Pass		
802.11b	2437	3.052	-5.187	≪8	Pass		
	2462	3.438	-4.801	≪8	Pass		
	2412	-2.036	-10.275	≪8	Pass		
802.11g	2437	-0.753	-8.992	≪8	Pass		
	2462	-0.988	-9.227	≪8	Pass		
	2412	-4.259	-12.498	≪8	Pass		
802.11n20	2437	-4.200	-12.439	≤8	Pass		
	2462	-4.400	-12.639	≤8	Pass		
	2422	-6.538	-14.777	≤8	Pass		
802.11n40	2437	-7.063	-15.302	≤8	Pass		
	2452	-7.196	-15.435	≪8	Pass		




Test Graphs of Conducted Output Power Spectral Density




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_802.11b_ANT1_2437_1Mbps_PSD


























10. Conducted Band Edge and Out-of-Band Emissions

10.1 Provisions Applicable

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

10.2 Measurement Procedure


Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Use the following spectrum analyzer settings:

- Step 1: Measurement Procedure In-Band Reference Level
 - 1. Set instrument center frequency to DTS channel center frequency.
 - 2. Set the span to \geq 1.5 times the DTS bandwidth.
 - 3. Set the RBW = 100 kHz.
 - 4. Set the VBW \geq 3 x RBW.
 - 5. Detector = peak.
 - 6. Sweep time = auto couple.
 - 7. Trace mode = max hold.
 - 8. Allow trace to fully stabilize.
 - Use the peak marker function to determine the maximum PSD level.
 - 10. Note that the channel found to contain the maximum PSD level can be used to establish the reference level.
 - 11. For reference level values, please refer to DTS bandwidth test.
- Step 2: Measurement Procedure Out of Band Emission
 - 1. Set RBW = 100 kHz.
 - 2. Set VBW ≥ 300 kHz.
 - 3. Detector = peak.
 - 4. Sweep = auto couple.
 - 5. Trace Mode = max hold.
 - 6. Allow trace to fully stabilize.
 - 7. Use the peak marker function to determine the maximum amplitude level.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

10.3 Measurement Setup (Block Diagram of Configuration)




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/




10.4 Measurement Result

Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.






Test_Graph_802.11b_ANT1_2437_1Mbps_Higher Band Emissions


#VBW 300 kHz





Test_Graph_802.11b_ANT1_2462_1Mbps_Higher Band Emissions






Test_Graph_802.11g_ANT1_2412_6Mbps_Higher Band Emissions

#VBW 300 kHz

Span 22.52 GHz Sweep 2.152 s (30000 pts)


Center 13.74 GHz #Res BW 100 kHz





Test_Graph_802.11g_ANT1_2437_6Mbps_Higher Band Emissions






Test_Graph_802.11g_ANT1_2462_6Mbps_Higher Band Emissions

#VBW 300 kHz

Span 22.50 GHz Sweep 2.152 s (30000 pts)

Center 13.75 GHz #Res BW 100 kHz






Test Graph 802.11n20 ANT1 2412 MCS0 Higher Band Emissions


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/






Test_Graph_802.11n20_ANT1_2437_MCS0_Higher Band Emissions





Test Graph 802.11n20 ANT1 2462 MCS0 Higher Band Emissions






Test Graph 802.11n40 ANT1 2422 MCS0 Higher Band Emissions

Scale Type

Span 22.52 GHz Sweep 2.152 s (30000 pts)






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_802.11n40_ANT1_2437_MCS0_Higher Band Emissions

#VBW 300 kHz

Center 13.74 GHz #Res BW 100 kHz





Test Graph 802.11n40 ANT1 2452 MCS0 Higher Band Emissions

#VBW 300 kHz

Span 22.50 GHz Sweep 2.152 s (30000 pts)

Center 13.75 GHz #Res BW 100 kHz




Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_802.11g_ANT1_2412_6Mbps_Lower Band Edge Emissions







11. Radiated Spurious Emission

11.1 Measurement Limits

15.209(a) Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

11.2 Measurement Procedure


- The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the



- pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.
- ◆ The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9kHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/3MHz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9kHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP





Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

Peak Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize


Average Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW ≥ [3 × RBW]
- 4. Detector = Power averaging (rms)
- 5. Averaging type = power (i.e., rms)
- 6. Sweep time = auto
- 7. Perform a trace average of at least 100 traces.
- 8. The applicable correction factor is [10*log (1 / D)], where D is the duty cycle. The factor had been edited in the "Input Correction" of the Spectrum Analyzer.




11.3 Measurement Setup (Block Diagram of Configuration)


Radiated Emission Test Setup 9kHz-30MHz



Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz






11.4 Measurement Result

Radiated Emission at 9kHz-30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.


Radiated Emission Test Results at 30MHz-1GHz						
EUT Name	POS Terminal	Model Name	P3			
Temperature	22.9°C	Relative Humidity	56.4%			
Pressure	960hPa	Test Voltage	DC 7.4V by battery			
Test Mode	Mode 2	Antenna Polarity	Horizontal			



Final	Data List							
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	45.6948	19.72	13.50	40.00	20.28	100	196	Horizontal
2	99.5281	23.21	16.13	43.50	20.29	100	288	Horizontal
3	130.3789	22.65	15.78	43.50	20.85	100	360	Horizontal
4	455.9058	30.93	24.54	46.00	15.07	100	270	Horizontal
5	545.1826	32.85	23.98	46.00	13.15	100	180	Horizontal
6	900.1474	37.21	31.78	46.00	8.79	100	50	Horizontal



Radiated Emission Test Results at 30MHz-1GHz						
EUT Name	POS Terminal	Model Name	P3			
Temperature	22.9°C	Relative Humidity	56.4%			
Pressure	960hPa	Test Voltage	DC 7.4V by battery			
Test Mode	Mode 2	Antenna Polarity	Vertical			



Final Data List Freq. Level Factor Limit Margin Height Angle NO. Polarity [MHz] [dBµV/m] [dB] [dBµV/m] [dB] [cm] [°] 1 42.0065 22.98 16.92 40.00 17.02 100 Vertical 260 2 64.6594 24.46 17.05 40.00 15.54 100 333 Vertical 159.2250 17.84 100 3 25.66 18.20 43.50 178 Vertical 435.5898 25.39 14.73 4 31.27 46.00 100 200 Vertical 5 758.0407 34.88 28.07 46.00 11.12 100 194 Vertical 6 958.7943 36.27 30.25 9.73 100 46.00 280 Vertical

RESULT: Pass

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. All test modes had been pre-tested. The mode 2 is the worst case and recorded in the report.



Radiated Emissions Test Results above 1 GHz

EUT Name	POS Terminal	Model Name	P3
Temperature	22.9°C	Relative Humidity	56.4%
Pressure	960hPa	Test Voltage	DC 7.4V by battery
Test Mode	Mode 1	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
4824.000	50.34	80.0	50.42	74.00	-23.58	peak
4824.000	39.55	80.0	39.63	54.00	-14.37	AVG
7236.000	48.74	2.21	50.95	74.00	-23.05	peak
7236.000	39.12	2.21	41.33	54.00	-12.67	AVG
Remark:						

Remark

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

EUT Name	POS Terminal	Model Name	P3
Temperature	22.9°C	Relative Humidity	56.4%
Pressure	960hPa	Test Voltage	DC 7.4V by battery
Test Mode	Mode 1	Antenna Polarity	Vertical

Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
49.89	0.08	49.97	74.00	-24.03	peak
40.15	0.08	40.23	54.00	-13.77	AVG
49.37	2.21	51.58	74.00	-22.42	peak
38.77	2.21	40.98	54.00	-13.02	AVG
	Reading (dBµV) 49.89 40.15 49.37	Reading Factor (dBμV) (dB) 49.89 0.08 40.15 0.08 49.37 2.21	Reading Factor Level (dBμV) (dB) (dBμV/m) 49.89 0.08 49.97 40.15 0.08 40.23 49.37 2.21 51.58	Reading Factor Level Limits (dBμV) (dB) (dBμV/m) (dBμV/m) 49.89 0.08 49.97 74.00 40.15 0.08 40.23 54.00 49.37 2.21 51.58 74.00	Reading Factor Level Limits Margin (dBμV) (dB) (dBμV/m) (dBμV/m) (dB) 49.89 0.08 49.97 74.00 -24.03 40.15 0.08 40.23 54.00 -13.77 49.37 2.21 51.58 74.00 -22.42

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

RESULT: Pass