

## MPE Calculation

Product:	Persee 2
Model no.:	P53300-0111
FCC ID:	2A2CLP53300-0111
Rating:	Input: 12.0VDC, 2.0A
RF Transmission Frequency:	Bluetooth BR+EDR: 2402-2480MHz Bluetooth LE: 2402-2480MHz Wi-Fi 2.4G: 2412-2462MHz Wi-Fi 5G: 5150MHz – 5250MHz; Wi-Fi 5G: 5725MHz – 5850MHz.
Antenna Type:	Internal Antenna
Max Antenna Gain:	Bluetooth: 2.8dBi max Wi-Fi 2.4G: 2.8dBi max Wi-Fi 5G 5150MHz – 5250MHz: 4.2dBi max, 5725MHz – 5850MHz: 3.3dBi max
Description of the EUT:	EUT is a Persee 2 with Bluetooth Low Energy/Bluetooth BDR+EDR, 2.4GHz Wi-Fi and 5GHz Wi-Fi functions

According to subpart 15.247(i) and subpart §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091, KDB447498 D01 General RF Exposure Guidance v06)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1,500	/	/	f/1500	30
1,500–100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

## Calculated Data:

## For 5G Wi-Fi

Maximum peak output power at antenna input terminal (dBm):	<b>14.2</b>
Maximum peak output power at antenna input terminal (mW):	<b>26.30</b>
Prediction distance (cm):	<b>20</b>
Antenna Gain, typical (dBi):	<b>3.3</b>
Maximum Antenna Gain (numeric):	<b>2.14</b>
The worst case is power density at predication frequency at 20 cm (mW/cm <sup>2</sup> ):	<b>0.0112</b>
MPE limit for general population exposure at prediction frequency (mW/cm <sup>2</sup> ):	1.0

## For 2.4G Wi-Fi

Maximum peak output power at antenna input terminal (dBm):	<b>14.7</b>
Maximum peak output power at antenna input terminal (mW):	<b>29.51</b>
Prediction distance (cm):	<b>20</b>
Antenna Gain, typical (dBi):	<b>2.8</b>
Maximum Antenna Gain (numeric):	<b>1.91</b>
The worst case is power density at predication frequency at 20 cm (mW/cm <sup>2</sup> ):	<b>0.0112</b>
MPE limit for general population exposure at prediction frequency (mW/cm <sup>2</sup> ):	1.0

## For BT

Maximum peak output power at antenna input terminal (dBm):	<b>4.77</b>
Maximum peak output power at antenna input terminal (mW):	<b>3.00</b>
Prediction distance (cm):	<b>20</b>
Antenna Gain, typical (dBi):	<b>2.8</b>
Maximum Antenna Gain (numeric):	<b>1.91</b>
The worst case is power density at predication frequency at 20 cm (mW/cm <sup>2</sup> ):	<b>0.0011</b>
MPE limit for general population exposure at prediction frequency (mW/cm <sup>2</sup> ):	1.0

## For BLE

Maximum peak output power at antenna input terminal (dBm):	<b>3.09</b>
Maximum peak output power at antenna input terminal (mW):	<b>2.04</b>
Prediction distance (cm):	<b>20</b>
Antenna Gain, typical (dBi):	<b>2.8</b>
Maximum Antenna Gain (numeric):	<b>1.91</b>
The worst case is power density at predication frequency at 20 cm (mW/cm <sup>2</sup> ):	<b>0.0008</b>
MPE limit for general population exposure at prediction frequency (mW/cm <sup>2</sup> ):	1.0

For simultaneous transmission

Simultaneous transmission configuration	Power density	MPE Limit
2.4GHz Wi-Fi +BDR+EDR	0.0123	1.0
5GHz Wi-Fi +BDR+EDR	0.0123	1.0
2.4G Wi-Fi + BLE	0.0258	1.0
5G Wi-Fi + BLE	0.0258	1.0

Result: Compliant

TUV SUD China, Shenzhen Branch

Reviewed by:



John Zhi/ Project Manager  
Date: 2023-11-06



Prepared By:



Joe Gu/Project Engineer  
Date: 2023-11-06