



TEST REPORT

FCC ID: 2AIZN-X6511E

Product: Mobile Phone

Model No.: X6511E

Additional Model No.: N/A

Trade Mark: Infinix

Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

Issued Date: 10 December 2021

Issued for:

INFINIX MOBILITY LIMITED

FLAT 39 8/F BLOCK D WAH LOK INDUSTRIAL CENTRE 31-35 SHAN MEI STREET
FOTAN NT

Issued By:

WORLD STANDARDIZATION CERTIFICATION & TESTING GROUP
(SHENZHEN) CO., LTD.

Building A-B, Baoshi Road, Baoshi Science & Technology Park, Bao'an District,
Shenzhen, Guangdong, People's Republic of China

TEL: + (86) 13924678855

FAX: +86-755-86376605

Note: In recognition of the successful completion of the A2LA evaluation process, (including an assessment of the laboratory's compliance with A2LA's ENERGY STAR ® Accreditation Program requirements 1) accreditation is granted to this laboratory to perform the following tests: EMC, electromagnetic compatibility, telecommunications and Energy Star.





Table of Contents

Page

1. GENERAL INFORMATION	3
1.1. GENERAL DESCRIPTION OF EUT	4
1.2. FACILITIES AND ACCREDITATIONS	5
2. TEST DESCRIPTION	6
2.1 MEASUREMENT UNCERTAINTY	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	8
2.4 CONFIGURATION OF SYSTEM UNDER TEST	8
2.5 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)	8
3. SUMMARY OF TEST RESULTS	9
4. MEASUREMENT INSTRUMENTS	10
5. EMC EMISSION TEST	11
5.1 CONDUCTED EMISSION MEASUREMENT	11
5.2 RADIATED EMISSION MEASUREMENT	15
6. ANTENNA APPLICATION	28
7. 6DB BANDWIDTH MEASUREMENT	29
7.1 TEST SETUP	29
7.2 LIMITS OF 6DB BANDWIDTH MEASUREMENT	29
7.3 TEST PROCEDURE	29
7.4 TEST RESULT	29
8. MAXIMUM CONDUCTED OUTPUT POWER	38
9. POWER SPECTRAL DENSITY MEASUREMENT	40
9.1 TEST SETUP	40
9.2 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	40
9.3 TEST PROCEDURE	40
9.4 TEST RESULT	41
10. OUT OF BAND MEASUREMENT	48
10.1 TEST SETUP FOR BAND EDGE	48
10.2 LIMITS OF OUT OF BAND EMISSIONS MEASUREMENT	48
10.3 TEST PROCEDURE	48
10.4 TEST RESULT	48



Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

1. GENERAL INFORMATION

Product:	Mobile Phone
Model No.:	X6511E
Additional Model:	N/A
Applicant:	INFINIX MOBILITY LIMITED
Address:	FLAT 39 8/F BLOCK D WAH LOK INDUSTRIAL CENTRE 31-35 SHAN MEI STREET FOTAN NT
Manufacturer:	SHENZHEN TECNO TECHNOLOGY CO.,LTD.
Address:	101,Building 24,Waijing Industrial Park,Fumin Community,Fucheng Street,Longhua District,Shenzhen City,P.R.China
Data of receipt	19 November 2021
Date of Test:	19 November 2021 to 09 December 2021
Applicable Standards:	FCC Rules Part15 Subpart C.

The above equipment has been tested by World Standardization Certification & Testing Group Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:

Wang Xiang
(Wang Xiang)

Check By:

Pu Shixi
(Pu Shixi)

Approved By:

Wang Fengbing
(Wang Fengbing)

Date:

10 December 2021



**1.1. GENERAL DESCRIPTION OF EUT**

Equipment Type:	Mobile Phone
Test Model:	X6511E
Additional Model:	N/A
Trade Mark	Infinix
Hardware version:	V1.0
Software version:	N/A
Extreme Temp. Tolerance:	-10℃ to +65℃
Battery information:	Li-ion Battery :BL-49FX Rated Voltage: 3.85V Rated Capacity:4900mAh/18.86Wh Typical Capacity:5000mAh/19.25Wh Limited Charge Voltage: 4.40 V
Adapter Information:	Adapter:U100XSA Input: AC100-240V 50/60Hz 0.3A Output: DC 5.0V 2.0A
Operating Frequency	2412-2472MHz
Channels	11
Channel Spacing	5MHz
Modulation Type	CCK for IEEE 802.11b OFDM for IEEE 802.11g/n HT-20/n HT-40
Antenna Type:	Integral Antenna
Antenna gain:	1.2dBi
Deviation	None
Condition of Test Sample	Normal



Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

1.2. FACILITIES AND ACCREDITATIONS

All measurement facilities used to collect the measurement data are located at Building A-B, Baoshi Science & Technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China of the WORLD STANDARDIZATION CERTIFICATION & TESTING GROUP (SHENZHEN) CO., LTD.

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

1.2.1. ACCREDITATIONS

China National Accreditation Service for Conformity Assessment (CNAS)

Registration number NO: L3732

American Association for Laboratory Accreditation (A2LA)

Registration NO : 5768.01

Copies of granted accreditation certificates are available for downloading from our web site,
<http://www.wsct-cert.com>





Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

2. TEST DESCRIPTION

2.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 3.2\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(<1G)	$\pm 4.7\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.7\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$



Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	802.11b
Mode 2	802.11g
Mode 3	802.11n20
Mode 4	802.11n40

For Conducted Emission	
Final Test Mode	Description
Mode 1	802.11b

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b
Mode 2	802.11g
Mode 3	802.11n20
Mode 4	802.11n40

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The EUT use new battery.
- (3) The data rate was set in 1Mbps, 6 Mbps, 6.5 Mbps and 13.5M for radiated emission due to the highest RF output power.
- (4) Record the worst case of each test item in this report.
- (5) When we test it, the duty cycle $\geq 98\%$



Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi


2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software Version	N/A
Test program	*##9646633##*

Frequency(802.11b/g/n20)	2412 MHz	2437 MHz	2462 MHz
Frequency(802.11n40)	2422 MHz	2437 MHz	2452 MHz

2.4 CONFIGURATION OF SYSTEM UNDER TEST



(EUT: Mobile Phone)

I/O Port of EUT			
I/O Port Type	Q'TY	Cable	Tested with
USB port	1	1m USB cable, unshielded	1
Power	1	1m	1

2.5 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	Adapter	/	U100XSA	/	/
2	/	/	N/A	/	/

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.
- (4) The adapter supply by the applicant.



3. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission Test	PASS	Complies
15.247(a)(2) Limit	Spectrum bandwidth of a Orthogonal Frequency Division Multiplex System Limit: 6dB bandwidth>500kHz	PASS	Complies
15.247(b)	Maximum peak outputpower Limit: max. 30dBm	PASS	Complies
15.109,15.205 & 15.209	Transmitter Radiated Emission Limit: Table 15.209	PASS	Complies
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Complies
15.247(d)	Band edge Limit: 30dB less than Reference level Restricted band limit: Table 15.209	PASS	Complies

NOTE:

(1)" N/A" denotes test is not applicable in this test report.



4. MEASUREMENT INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Calibration Date	Calibration Due.
EMI Test Receiver	R&S	ESCI	100005	2021-11-05	2022-11-04
LISN	AFJ	LS16	16010222119	2021-11-05	2022-11-04
LISN(EUT)	Mestec	AN3016	04/10040	2021-11-05	2022-11-04
Universal Radio Communication Tester	R&S	CMU 200	1100.0008.02	2021-11-05	2022-11-04
Coaxial cable	Megalon	LMR400	N/A	2021-11-05	2022-11-04
GPIO cable	Megalon	GPIO	N/A	2021-11-05	2022-11-04
Spectrum Analyzer	R&S	FSU	100114	2021-11-05	2022-11-04
Pre Amplifier	H.P.	HP8447E	2945A02715	2021-11-05	2022-11-04
Pre-Amplifier	CDSI	PAP-1G18-38	--	2021-11-05	2022-11-04
Bi-log Antenna	SUNOL Sciences	JB3	A021907	2021-11-05	2022-11-04
9*6*6 Anechoic	--	--	--	2021-11-05	2022-11-04
Horn Antenna	COMPLIANCE ENGINEERING	CE18000	--	2021-11-05	2022-11-04
Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-631	2021-11-05	2022-11-04
Cable	TIME MICROWAVE	LMR-400	N-TYPE04	2021-11-05	2022-11-04
System-Controller	CCS	N/A	N/A	N.C.R	N.C.R
Turn Table	CCS	N/A	N/A	N.C.R	N.C.R
Antenna Tower	CCS	N/A	N/A	N.C.R	N.C.R
RF cable	Murata	MXHQ87WA3000	-	2021-11-05	2022-11-04
Loop Antenna	EMCO	6502	00042960	2021-11-05	2022-11-04
Horn Antenna	SCHWARZBECK	BBHA 9170	1123	2021-11-05	2022-11-04
Power meter	Anritsu	ML2487A	6K00003613	2021-11-05	2022-11-04
Power sensor	Anritsu	MX248XD	--	2021-11-05	2022-11-04



Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

5. EMC EMISSION TEST

5.1 CONDUCTED EMISSION MEASUREMENT

5.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz




5.1.2 TEST PROCEDURE

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

5.1.3 DEVIATION FROM TEST STANDARD

No deviation

5.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

5.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




For Question,
Please Contact with WSCT
www.wsct-cert.com

Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

5.1.6 TEST RESULTS

Temperature	26 °C	Relative Humidity	54%
Pressure	1010hPa	Phase	L
Test Mode	Mode 1		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.2180	33.14	10.41	43.55	62.89	-19.34	QP
2		0.2180	26.22	10.41	36.63	52.89	-16.26	AVG
3		0.3940	35.91	10.45	46.36	57.98	-11.62	QP
4	*	0.4820	30.21	10.47	40.68	46.30	-5.62	AVG
5		1.0100	29.32	10.51	39.83	46.00	-6.17	AVG
6		1.1380	35.68	10.53	46.21	56.00	-9.79	QP
7		2.0980	17.92	10.66	28.58	46.00	-17.42	AVG
8		2.3620	30.18	10.66	40.84	56.00	-15.16	QP
9		3.7020	15.10	10.68	25.78	46.00	-20.22	AVG
10		3.7780	27.86	10.68	38.54	56.00	-17.46	QP
11		22.5700	26.95	11.01	37.96	60.00	-22.04	QP
12		23.2580	12.63	11.00	23.63	50.00	-26.37	AVG

Remark: All the modes have been investigated, and only worst mode is presented in this report.






For Question,
Please Contact with WSCT
www.wsct-cert.com

Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

Temperature	26 °C	Relative Humidity	54%
Pressure	1010hPa	Phase	N
Test Mode	Mode 1		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1740	28.09	10.41	38.50	64.76	-26.26	QP
2		0.1740	19.81	10.41	30.22	54.76	-24.54	AVG
3		0.4380	30.32	10.46	40.78	57.10	-16.32	QP
4		0.4380	22.70	10.46	33.16	47.10	-13.94	AVG
5	*	1.2300	26.65	10.54	37.19	46.00	-8.81	AVG
6		1.3220	34.16	10.56	44.72	56.00	-11.28	QP
7		2.7700	26.92	10.67	37.59	56.00	-18.41	QP
8		2.8620	15.58	10.67	26.25	46.00	-19.75	AVG
9		4.0580	13.17	10.68	23.85	46.00	-22.15	AVG
10		7.8540	24.93	10.75	35.68	60.00	-24.32	QP
11		22.8819	23.68	11.01	34.69	60.00	-25.31	QP
12		23.8380	9.50	11.00	20.50	50.00	-29.50	AVG

Remark: All the modes have been investigated, and only worst mode is presented in this report.





Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

5.2 RADIATED EMISSION MEASUREMENT

5.2.1 Radiated Emission Limits (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

5.2.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.2.3 DEVIATION FROM TEST STANDARD

No deviation







Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

5.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz




(B) Radiated Emission Test-Up Frequency 30MHz~1GHz





(C) Radiated Emission Test-Up Frequency Above 1GHz



5.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

5.2.5.1 RESULTS (Below 30 MHz)

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Mode 1

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F
--	--	--	--	P
--	--	--	--	P

NOTE:

No result in this part for margin above 20dB.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.



Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

5.2.5.2 TEST RESULTS (Between 30M – 1000 MHz)

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Polarization :	Horizontal
Test Mode	Mode 1		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	31.1798	27.64	4.34	31.98	40.00	-8.02	QP
2		43.5057	27.79	-1.45	26.34	40.00	-13.66	QP
3		71.8320	33.90	-7.03	26.87	40.00	-13.13	QP
4		138.8735	27.99	-4.23	23.76	43.50	-19.74	QP
5		275.1570	25.94	-3.44	22.50	46.00	-23.50	QP
6		996.4996	23.05	7.25	30.30	54.00	-23.70	QP


Remark: All the modes have been investigated, and only worst mode is presented in this report.





Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Polarization :	Vertical
Test Mode	Mode 1		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		30.0000	25.51	4.79	30.30	40.00	-9.70	QP
2	*	42.4508	31.44	-1.04	30.40	40.00	-9.60	QP
3		89.9047	37.14	-5.92	31.22	43.50	-12.28	QP
4		163.7550	27.53	-6.04	21.49	43.50	-22.01	QP
5		279.0436	24.04	-3.26	20.78	46.00	-25.22	QP
6		993.0114	22.99	7.19	30.18	54.00	-23.82	QP

Remark: All the modes have been investigated, and only worst mode is presented in this report.





Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

5.2.5.3 TEST RESULTS (1GHz to 25GHz)

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Mode 1 TX
Frequency	2412MHz		

Freq. (MHz)	Ant. Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	AV	PK	AV	PK	AV
4824	V	60.38	39.61	74	54	-13.62	-14.39
7236	V	59.66	39.42	74	54	-14.34	-14.58
4824	H	59.42	40.63	74	54	-14.58	-13.37
7236	H	59.31	40.31	74	54	-14.69	-13.69

Remark:

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Mode 1 TX
Frequency	2437MHz		

Freq. (MHz)	Ant. Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	AV	PK	AV	PK	AV
4874	V	60.39	41.01	74	54	-13.61	-12.99
7311	V	59.55	39.38	74	54	-14.45	-14.62
4874	H	59.20	40.19	74	54	-14.80	-13.81
7311	H	58.59	39.59	74	54	-15.41	-14.41

Remark:

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.



Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Mode 1 TX
Frequency	2462MHz		

Freq. (MHz)	Ant. Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4924	V	58.34	41.25	74	54	-15.66	-12.75
7386	V	59.73	40.72	74	54	-14.27	-13.28
4924	H	58.66	39.01	74	54	-15.34	-14.99
7386	H	59.33	40.33	74	54	-14.67	-13.67

Remark:

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Mode2 TX
Frequency	2412MHz		

Freq. (MHz)	Ant. Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4824	V	60.93	41.43	74	54	-13.07	-12.57
7236	V	59.87	40.31	74	54	-14.13	-13.69
4824	H	59.95	40.74	74	54	-14.05	-13.26
7236	H	58.49	39.49	74	54	-15.51	-14.51

Remark:

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.



Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Mode 2 TX
Frequency	2437MHz		

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4874	V	59.33	40.03	74	54	-14.67	-13.97
7311	V	59.19	39.68	74	54	-14.81	-14.32
4874	H	59.34	39.47	74	54	-14.66	-14.53
7311	H	58.54	39.54	74	54	-15.46	-14.46

Remark:

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Mode 2 TX
Frequency	2462MHz		

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4924	V	58.13	41.95	74	54	-15.87	-12.05
7386	V	59.73	40.24	74	54	-14.27	-13.76
4924	H	58.98	40.97	74	54	-15.02	-13.03
7386	H	59.40	40.40	74	54	-14.60	-13.60

Remark:

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.



Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Mode3 TX
Frequency	2412MHz		

Freq. (MHz)	Ant. Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4824	V	60.49	41.98	74	54	-13.51	-12.02
7236	V	58.18	39.40	74	54	-15.82	-14.60
4824	H	59.18	40.64	74	54	-14.82	-13.36
7236	H	59.29	40.29	74	54	-14.71	-13.71

Remark:

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Mode 3 TX
Frequency	2437MHz		

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4874	V	58.53	39.90	74	54	-15.47	-14.10
7311	V	58.36	39.77	74	54	-15.64	-14.23
4874	H	58.38	40.04	74	54	-15.62	-13.96
7311	H	59.82	40.82	74	54	-14.18	-13.18

Remark:

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.





Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Mode 3 TX
Frequency	2462MHz		

Freq. (MHz)	Ant. Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4924	V	60.74	40.83	74	54	-13.26	-13.17
7386	V	59.59	40.92	74	54	-14.41	-13.08
4924	H	58.83	39.05	74	54	-15.17	-14.95
7386	H	59.00	40.00	74	54	-15.00	-14.00

Remark:

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Mode4 TX
Frequency	2422MHz		

Freq. (MHz)	Ant. Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4844	V	59.12	41.31	74	54	-14.88	-12.69
7266	V	59.35	40.68	74	54	-14.65	-13.32
4844	H	58.85	39.77	74	54	-15.15	-14.23
7266	H	58.26	39.26	74	54	-15.74	-14.74

Remark:

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.





Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Mode 4 TX
Frequency	2437MHz		

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4874	V	60.93	40.39	74	54	-13.07	-13.61
7311	V	59.27	40.94	74	54	-14.73	-13.06
4874	H	58.90	39.70	74	54	-15.10	-14.30
7311	H	58.08	39.08	74	54	-15.92	-14.92

Remark:

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Mode 4 TX
Frequency	2452MHz		

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4904	V	59.15	39.05	74	54	-14.85	-14.95
7356	V	58.65	40.32	74	54	-15.35	-13.68
4904	H	58.49	39.70	74	54	-15.51	-14.30
7356	H	59.10	40.10	74	54	-14.90	-13.90

Remark:

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.



Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

6. ANTENNA APPLICATION

6.1 Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247

FCC part 15C section 15.247 requirements: Systems operating in the 2402-2480MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

6.2 Result

The EUT's antenna Integral Antenna, The antenna's gain is 1.2dBi and meets the requirement.






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

7. 6DB BANDWIDTH MEASUREMENT

7.1 TEST SETUP



7.2 LIMITS OF 6DB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is >500 kHz

7.3 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 100 kHz
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.4 TEST RESULT

6dB Occupied Bandwidth

Mode		802.11b		Humidity		56% RH
Temperature		24 deg. C,				
Channel	Channel Frequency (MHz)	Data Transfer Rate (Mbps)	6 dB Bandwidth (kHz)	Minimum Limit (MHz)	Pass/ Fail	
1	2412	1	13173.1	0.5	Pass	
6	2437	1	13076.9	0.5	Pass	
11	2462	1	13269.2	0.5	Pass	

Mode		802.11g		Humidity		56% RH
Temperature		24 deg. C,				
Channel	Channel Frequency (MHz)	Data Transfer Rate (Mbps)	6 dB Bandwidth (kHz)	Minimum Limit (MHz)	Pass/ Fail	
1	2412	6	18076.9	0.5	Pass	
6	2437	6	18077.9	0.5	Pass	
11	2462	6	17980.8	0.5	Pass	





Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

Mode		802.11n20		Humidity		56% RH	
Temperature		24 deg. C,					
Channel	Channel Frequency (MHz)	Data Transfer Rate (Mbps)	6 dB Bandwidth (kHz)	Minimum Limit (MHz)	Pass/ Fail		
1	2412	6.5	18173.1	0.5	Pass		
6	2437	6.5	17980.8	0.5	Pass		
11	2462	6.5	18076.9	0.5	Pass		

Mode		802.11n40		Humidity		56% RH	
Temperature		24 deg. C,					
Channel	Channel Frequency (MHz)	Data Transfer Rate (Mbps)	6 dB Bandwidth (kHz)	Minimum Limit (MHz)	Pass/ Fail		
3	2422	13.5	36794.9	0.5	Pass		
6	2437	13.5	23717.9	0.5	Pass		
9	2452	13.5	27179.5	0.5	Pass		







Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

For Question,
Please Contact with WSCT
www.wsct-cert.com

802.11b at 1Mbps of CH1




802.11b at 1Mbps of CH6






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

802.11b at 1Mbps of CH11



Date: 7.DEC.2021 10:08:34

802.11g at 6Mbps of CH1




Date: 7.DEC.2021 10:20:11






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

802.11g at 6Mbps of CH6



Date: 7.DEC.2021 10:20:11

802.11g at 6Mbps of CH11



Date: 7.DEC.2021 10:21:56






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi


For Question,
Please Contact with WSCT
www.wsct-cert.com

802.11n at HT20 of CH1



Date: 7.DEC.2021 10:25:22

802.11n at HT20 of CH6




Date: 7.DEC.2021 10:34:04






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

802.11n at HT20 of CH11




802.11n at HT40 of CH3






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

802.11n at HT40 of CH6



802.11n at HT40 of CH9





World Standardization Certification & Testing Group (Shenzhen) Co.,Ltd.



Certificate Number 5768.01

Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

For Question,
Please Contact with WSCT
www.wsct-cert.com



World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.

世标检测认证股份

ADD: Building A-B Baoshi Science & Technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
TEL: 86-755-26996192 26992306 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com [Http://www.wsct-cert.com](http://www.wsct-cert.com)

Member of the WSCT INC.



Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

8. MAXIMUM CONDUCTED OUTPUT POWER

Test Requirement: FCC 47 CFR Part 15 Subpart C 15.247(b)


Test Method: KDB 789033 D02 v01r04 Section E.3.a (Method PM)

The Maximum Peak Output Power Measurement is 30dBm.

Test Procedure:

1. Connected the EUT's antenna port to measure device by 10dB attenuator.
2. Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of Tx on burst.

For Conducted RF test setup



(EUT: Mobile Phone)



Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

Test Data:

Mode	Channel/ Frequency (MHz)	Maximum conducted output power (dBm)	Limit(dBm)	Pass / Fail
		Meas Power		
802.11b	1(2412)	14.59	30	Pass
	6(2437)	14.87	30	Pass
	11(2462)	14.63	30	Pass
802.11g	1(2412)	13.73	30	Pass
	6(2437)	13.64	30	Pass
	11(2462)	13.59	30	Pass
802.11n(HT20)	1(2412)	13.42	30	Pass
	6(2437)	13.14	30	Pass
	11(2462)	13.49	30	Pass
802.11n (HT40)	3(2422)	12.35	30	Pass
	6(2437)	12.24	30	Pass
	9(2452)	12.21	30	Pass



9. POWER SPECTRAL DENSITY MEASUREMENT

9.1 TEST SETUP



9.2 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum Power Spectral Density Measurement is 8dBm.

9.3 TEST PROCEDURE

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW = 3 kHz.
3. Set the VBW = 10 kHz.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level must be ≤ 8 dBm.

9.4 TEST RESULT

Mode		802.11b		Humidity		56% RH	
Temperature		24 deg. C,					
Channel	Channel Frequency (MHz)	Final RF Power Level in (dBm)		Maximum Limit (dBm)		Pass/ Fail	
1Mbps							
1	2412	-8.88		8		Pass	
6	2437	-9.14		8		Pass	
11	2462	-10.23		8		Pass	

Mode	802.11g		Humidity	56% RH	
Temperature	24 deg. C,				
Channel	Channel Frequency (MHz)	Final RF Power Level in (dBm)	Maximum Limit (dBm)	Pass/ Fail	
6Mbps					
1	2412	-14.58	8	Pass	
6	2437	-13.17	8	Pass	
11	2462	-14.29	8	Pass	

Mode		802.11n HT20		Humidity		56% RH	
Temperature		24 deg. C,					
Channel	Channel Frequency (MHz)	Final RF Power Level in (dBm)		Maximum Limit (dBm)		Pass/ Fail	
6.5Mbps							
1	2412	-14.47		8		Pass	
6	2437	-13.80		8		Pass	
11	2462	-15.72		8		Pass	


Mode	802.11n HT40		Humidity	56% RH	
Temperature	24 deg. C,				
Channel	Channel Frequency (MHz)	Final RF Power Level in (dBm)	Maximum Limit (dBm)	Pass/ Fail	
13.5Mbps					
3	2422	-3.71	8	Pass	
6	2437	-2.63	8	Pass	
9	2452	-1.85	8	Pass	

Remark: All of the modes have been investigated, and only worst mode is presented in this report.




Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

802.11b at 1Mbps of CH1



802.11b at 1Mbps at CH6






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

802.11b at 1Mbps of CH11




802.11g at 6Mbps of CH1






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

802.11g at 6Mbps of CH6




802.11g at 6Mbps of CH11






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

802.11n HT20 at 6.5Mbps of CH1




802.11n HT20 at 6.5Mbps of CH6






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

802.11n HT20 at 6.5Mbps of CH11




802.11n HT40 at 13.5Mbps of CH3






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

802.11n HT40 at 13.5Mbps of CH6




802.11n HT40 at 13.5Mbps of CH9





10. OUT OF BAND MEASUREMENT

10.1 TEST SETUP FOR BAND EDGE



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

10.2 LIMITS OF OUT OF BAND EMISSIONS MEASUREMENT

1. Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

10.3 TEST PROCEDURE

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of radiated emission test. (Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector)

For bandage test, the spectrum set as follows: RBW=100 kHz, VBW=100 kHz. A conducted measurement used

10.4 TEST RESULT

Please see next pages

Note: This is a handheld device. The radiated emissions should be tested under 3-axes position (Lying, Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.



Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

Radiated measurement:

802.11b

Indicated		result (PK/AV)	Antenna Polar (H/V)	Correction Factor			FCC Part 15.247		
Frequency (MHz)	Receiver Reading (dBμV/m)			Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low Channel (2412MHz)									
2390	31.13	AV	V	30.3	4.1	33.1	32.43	54	21.57
2390	30.52	AV	H	30.3	4.1	33.1	31.82	54	22.18
2390	39.36	PK	V	30.3	4.1	33.1	40.66	74	33.34
2390	41.67	PK	H	30.3	4.1	33.1	42.97	74	31.03
High Channel (2462MHz)									
2483.5	30.77	AV	V	30.3	4.1	33.1	32.07	54	21.93
2483.5	30.76	AV	H	30.3	4.1	33.1	32.06	54	21.94
2483.5	39.92	PK	V	30.3	4.1	33.1	41.22	74	32.78
2483.5	40.62	PK	H	30.3	4.1	33.1	41.92	74	32.08

802.11g

Indicated		result (PK/AV)	Antenna Polar (H/V)	Correction Factor			FCC Part 15.247		
Frequency (MHz)	Receiver Reading (dBμV/m)			Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low Channel (2412MHz)									
2390	34.46	AV	V	30.3	4.1	33.1	35.76	54	18.24
2390	33.46	AV	H	30.3	4.1	33.1	34.76	54	19.24
2390	52.11	PK	V	30.3	4.1	33.1	53.41	74	20.59
2390	50.19	PK	H	30.3	4.1	33.1	51.49	74	22.51
High Channel (2462MHz)									
2483.5	31.20	AV	V	31	4.4	32.7	33.90	54	20.10
2483.5	30.54	AV	H	31	4.4	32.7	33.24	54	20.76
2483.5	42.01	PK	V	31	4.4	32.7	44.71	74	29.29
2483.5	40.88	PK	H	31	4.4	32.7	43.58	74	30.42

Note: The BAND EDGE RESTRICTED BANDS emission is too low at least 20dB to the Fundamental.



Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

802.11n HT20

Indicated		result (PK/AV)	Antenna Polar (H/V)	Correction Factor			FCC Part 15.247		
Frequency (MHz)	Receiver Reading (dBμV/m)			Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low Channel (2412MHz)									
2390	37.57	AV	V	30.3	4.1	33.1	38.87	54	15.13
2390	37.79	AV	H	30.3	4.1	33.1	39.09	54	14.91
2390	53.56	PK	V	30.3	4.1	33.1	54.86	74	19.14
2390	52.78	PK	H	30.3	4.1	33.1	54.08	74	19.92
High Channel (2462MHz)									
2483.5	30.61	AV	V	31	4.4	32.7	33.31	54	20.69
2483.5	32.07	AV	H	31	4.4	32.7	34.77	54	19.23
2483.5	40.77	PK	V	31	4.4	32.7	43.47	74	30.53
2483.5	40.40	PK	H	31	4.4	32.7	43.10	74	30.90

802.11n HT40

Indicated		result (PK/AV)	Antenna Polar (H/V)	Correction Factor			FCC Part 15.247		
Frequency (MHz)	Receiver Reading (dBμV/m)			Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low Channel (2422MHz)									
2390	36.80	AV	V	30.3	4.1	33.1	38.10	54	15.90
2390	36.98	AV	H	30.3	4.1	33.1	38.28	54	15.72
2390	53.94	PK	V	30.3	4.1	33.1	55.24	74	18.76
2390	54.71	PK	H	30.3	4.1	33.1	56.01	74	17.99
High Channel (2452MHz)									
2483.5	31.94	AV	V	31	4.4	32.7	34.64	54	19.36
2483.5	32.57	AV	H	31	4.4	32.7	35.27	54	18.73
2483.5	44.91	PK	V	31	4.4	32.7	47.61	74	26.39
2483.5	45.09	PK	H	31	4.4	32.7	47.79	74	26.21

Note: The BAND EDGE RESTRICTED BANDS emission is too low at least 20dB to the Fundamental.






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi


Band Edges Measurement:

802.11b:

Low channel



High channel





World Standardization Certification & Testing Group (Shenzhen) Co.,Ltd.



Certificate Number 5768.01

Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

For Question,
Please Contact with WSCT
www.wsct-cert.com



World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.

世标检测认证股份

ADD: Building A-B Baoshi Science & Technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
TEL: 86-755-26996192 26992306 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com [Http://www.wsct-cert.com](http://www.wsct-cert.com)


Member of the WSCT INC.




Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

802.11g:

Low channel



High channel






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

802.11n HT20:

Low channel




High channel





Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi




802.11n HT40:

Low channel






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi



High channel







Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

Conducted measurement:
802.11b:

Low channel




Middle channel





Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi


High channel



Date: 7.DEC.2021 11:32:32

802.11g:

Low channel




Date: 7.DEC.2021 11:37:10






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

Middle channel



Date: 7.DEC.2021 11:39:03

High channel



Date: 7.DEC.2021 11:39:59






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

802.11n HT20:


Low channel





Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi


Middle channel






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

High channel



802.11n HT40:


Low channel






Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

Middle channel



High channel



---END OF REPORT---



World Standardization Certification & Testing Group (Shenzhen) Co.,Ltd.



Certificate Number 5768.01

Report No.: WSCT-A2LA-R&E211100558A-Wi-Fi

For Question,
Please Contact with WSCT
www.wsct-cert.com



World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.

世标检测认证股份

ADD: Building A-B Baoshi Science & Technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
TEL: 86-755-26996192 26992306 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com [Http://www.wsct-cert.com](http://www.wsct-cert.com)

Member of the WSCT INC.