



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08



Certificate #6613.01

# FCC TEST REPORT

## (Part 15, Subpart C)

Applicant:	Fibocom Wireless Inc.
Address:	1101, Tower A, Building 6, Shenzhen International Innovation Valley, Dashi 1st Rd, Nanshan, Shenzhen , China

Manufacturer or Supplier:	Fibocom Wireless Inc.
Address:	1101, Tower A, Building 6, Shenzhen International Innovation Valley, Dashi 1st Rd, Nanshan, Shenzhen , China
Product:	LTE Module
Brand Name:	Fibocom
Model Name:	SC206-NA
FCC ID:	ZMOSC206NA
Date of tests:	Apr. 11, 2025 - May. 14, 2025

The tests have been carried out according to the requirements of the following standard:

- FCC Part 15, Subpart C, Section 15.247  
 ANSI C63.10-2020

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Prepared by Hanwen Xu Engineer / Mobile Department	Approved by Peibo Sun Manager / Mobile Department
Date: May. 14, 2025	Date: May. 14, 2025

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

## TABLE OF CONTENTS

<b>RELEASE CONTROL RECORD .....</b>	<b>5</b>
<b>1 SUMMARY OF TEST RESULTS.....</b>	<b>6</b>
1.1 MEASUREMENT UNCERTAINTY .....	7
<b>2 GENERAL INFORMATION .....</b>	<b>8</b>
2.1 GENERAL DESCRIPTION OF EUT.....	8
2.2 DESCRIPTION OF TEST MODES.....	9
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST .....	10
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	10
2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	12
2.4 DESCRIPTION OF SUPPORT UNITS.....	12
<b>3 TEST TYPES AND RESULTS.....</b>	<b>13</b>
3.1 CONDUCTED EMISSION MEASUREMENT.....	13
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	13
3.1.2 TEST INSTRUMENTS.....	14
3.1.3 TEST PROCEDURES .....	15
3.1.4 DEVIATION FROM TEST STANDARD .....	15
3.1.5 TEST SETUP .....	16
3.1.6 EUT OPERATING CONDITIONS .....	16
3.1.7 TEST RESULTS .....	17
3.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT .....	19
3.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT .....	19
3.2.2 TEST INSTRUMENTS.....	20
3.2.3 TEST PROCEDURES .....	22
3.2.4 DEVIATION FROM TEST STANDARD .....	22
3.2.5 TEST SETUP .....	23
3.2.6 EUT OPERATING CONDITIONS .....	24
3.2.7 TEST RESULTS .....	25
3.3 NUMBER OF HOPPING FREQUENCY USED.....	57
3.3.1 LIMIT OF HOPPING FREQUENCY USED .....	57
3.3.2 TEST SETUP .....	57
3.3.3 TEST INSTRUMENTS.....	58
3.3.4 TEST PROCEDURES .....	59
3.3.5 DEVIATION FROM TEST STANDARD .....	59
3.3.6 TEST RESULTS .....	59
3.4 DWELL TIME ON EACH CHANNEL .....	60



BUREAU  
VERITAS

## Test Report No.: PSZ-QSZ2504020109RF08

3.4.1	LIMIT OF DWELL TIME USED .....	60
3.4.2	TEST SETUP .....	60
3.4.3	TEST INSTRUMENTS.....	60
3.4.4	TEST PROCEDURES .....	60
3.4.5	DEVIATION FROM TEST STANDARD .....	61
3.4.6	TEST RESULTS .....	61
3.5	CHANNEL BANDWIDTH.....	62
3.5.1	LIMITS OF CHANNEL BANDWIDTH .....	62
3.5.2	TEST SETUP .....	62
3.5.3	TEST INSTRUMENTS.....	62
3.5.4	TEST PROCEDURE.....	62
3.5.5	DEVIATION FROM TEST STANDARD .....	62
3.5.6	EUT OPERATING CONDITION .....	63
3.5.7	TEST RESULTS .....	63
3.6	HOPPING CHANNEL SEPARATION .....	64
3.6.1	LIMIT OF HOPPING CHANNEL SEPARATION .....	64
3.6.2	TEST SETUP .....	64
3.6.3	TEST INSTRUMENTS.....	64
3.6.4	TEST PROCEDURES .....	64
3.6.1	DEVIATION FROM TEST STANDARD .....	64
3.6.2	TEST RESULTS .....	64
3.7	MAXIMUM OUTPUT POWER.....	65
3.7.1	LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT .....	65
3.7.2	TEST SETUP .....	65
3.7.3	TEST INSTRUMENTS.....	65
3.7.4	TEST PROCEDURES .....	65
3.7.5	DEVIATION FROM TEST STANDARD .....	66
3.7.6	EUT OPERATING CONDITION .....	66
3.7.7	TEST RESULTS .....	66
3.7.7.1	MAXIMUM PEAK OUTPUT POWER .....	66
3.7.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	66
3.8	OUT OF BAND MEASUREMENT .....	67
3.8.1	LIMITS OF OUT OF BAND MEASUREMENT .....	67
3.8.2	TEST INSTRUMENTS.....	67
3.8.3	TEST PROCEDURE.....	67
3.8.4	DEVIATION FROM TEST STANDARD .....	67
3.8.5	EUT OPERATING CONDITION .....	67
3.8.6	TEST RESULTS .....	67



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

<b>4</b>	<b>PHOTOGRAPHS OF THE TEST CONFIGURATION .....</b>	<b>68</b>
<b>5</b>	<b>MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB</b>	
	69	
<b>6</b>	<b>APPENDIX.....</b>	<b>70</b>
	20DB EMISSION BANDWIDTH.....	70
	TEST RESULT .....	70
	TEST GRAPHS.....	70
	OCCUPIED CHANNEL BANDWIDTH .....	74
	TEST RESULT .....	74
	TEST GRAPHS.....	74
	MAXIMUM CONDUCTED OUTPUT POWER .....	78
	TEST RESULT PEAK .....	78
	CARRIER FREQUENCY SEPARATION.....	79
	TEST RESULT .....	79
	TEST GRAPHS.....	79
	TIME OF OCCUPANCY .....	81
	TEST RESULT .....	81
	TEST GRAPHS.....	81
	NUMBER OF HOPPING CHANNELS .....	85
	TEST RESULT .....	85
	TEST GRAPHS.....	85
	BAND EDGE MEASUREMENTS.....	87
	TEST RESULT .....	87
	TEST GRAPHS.....	87
	CONDUCTED SPURIOUS EMISSION.....	93
	TEST RESULT .....	93
	TEST GRAPHS.....	94
	DUTY CYCLE.....	105
	TEST RESULT .....	105
	TEST GRAPHS.....	106



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSZ-QSZ2504020109RF08	Original release	May. 14, 2025



## 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C		
STANDARD	TEST TYPE AND LIMIT	RESULT
15.207	AC Power Conducted Emission	Compliance
15.247(a)(1) (iii)	Number of Hopping Frequency Used	Compliance
15.247(a)(1) (iii)	Dwell Time on Each Channel	Compliance
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	Compliance
15.247(b)	Maximum Peak Output Power	Compliance
15.247(d)& 15.209	Transmitter Radiated Emissions	Compliance
15.247(d)	Out of band Measurement	Compliance
15.203	Antenna Requirement	Compliance

**NOTE:**

1. If the Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.
2. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

**\*Test Lab Information Reference**

**Lab A:**

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

**Lab Address:**

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province, China

**Accredited Test Lab Cert 6613.01**

The FCC Site Registration No. is 434559; The Designation No. is CN1325.




## 1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	$\pm 2.70\text{dB}$
Radiated emissions (9KHz~30MHz)	$\pm 2.68\text{dB}$
Radiated emissions (30MHz~1GHz)	$\pm 4.98\text{dB}$
Radiated emissions (1GHz ~6GHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GHz ~18GHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GHz ~40GHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{kHz}$
Conducted Output power	$\pm 2.06\text{dB}$
Power Spectral Density	$\pm 0.85 \text{ dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.



## 2 GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

PRODUCT*	LTE Module
BRAND NAME*	Fibocom
MODEL NAME*	SC206-NA
NOMINAL VOLTAGE*	3.8Vdc
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK,π/4DQPSK,8DPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
MAX. OUTPUT POWER	27.93mW (Max. Measured)
ANTENNA GAIN*	3.36dBi
ANTENNA TYPE*	Dipole Antenna
HW VERSION*	V1.0
SW VERSION*	SC206-U6.400.002
I/O PORTS*	Refer to user's manual
CABLE SUPPLIED*	NA

**NOTE:**

1. \*Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
2. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
4. Antenna gain and EUT conducted cable loss are provided by the customer, and the laboratory will record the results based on these items that involve these two parameters.



## 2.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		



## 2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 4 photograph of the test configuration for reference.

## 2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on X axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

RE≥1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- The following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	39	FHSS	8DPSK	3DH5

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- The following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	0, 39, 78	FHSS	GFSK	1DH5
-	0 to 78	0, 39, 78	FHSS	π/4 DQPSK	2DH5
-	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

**POWER LINE CONDUCTED EMISSION TEST:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture) and packet type.
- The following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	78	FHSS	$\pi/4$ -DQPSK	2DH5

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- The following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH1/DH3/DH5
0 to 78	0, 39, 78	FHSS	$\pi/4$ DQPSK	2DH1/2DH3/2DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH1/3DH3/3DH5

TEST CONDITION			
APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	23deg. C, 70%RH	DC 3.8V By DC Source	Hanwen Xu
RE≥1G	23deg. C, 70%RH	DC 3.8V By DC Source	Hanwen Xu
PLC	25deg. C, 52%RH	DC 3.8V By DC Source	Hanwen Xu
APCM	25deg. C, 60%RH	DC 3.8V By DC Source	Hanwen Xu



BUREAU  
VERITAS Test Report No.: PSZ-QSZ2504020109RF08

## 2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

### FCC Part 15, Subpart C. Section 15.247

### ANSI C63.10-2020

#### NOTE:

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

## 2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Laptop	Lenovo	Thinkpad E14	SL10W47313	N/A
2	DC Source	HYELEC	HY3010B	551016	N/A
3	Adapter	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable, 1.0m;



### 3 TEST TYPES AND RESULTS

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
0.15 ~ 0.5 0.5 ~ 5 5 ~ 30	Quasi-peak	Average
	66 to 56	56 to 46
	56	46
	60	50

##### NOTE:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

### 3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	102749	Mar.28,24	Mar.27,26
ELEKTRA test software	Rohde&Schwarz	ELEKTRA	NA	N/A	N/A
LISN network	Rohde&Schwarz	ENV216	102640	Mar.28,24	Mar.27,26
CABLE	Rohde&Schwarz	W61.01	N/A	Apr.27,24	Apr.26,25
CABLE	Rohde&Schwarz	W61.01	N/A	Apr.26,25	Apr.25,26
CABLE	Rohde&Schwarz	W601	N/A	Apr.27,24	Apr.26,25
CABLE	Rohde&Schwarz	W601	N/A	Apr.26,25	Apr.25,26

**NOTE:**

1. The test was performed in CE shielded room.
2. The calibration interval of the above test instruments is 12 /24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



### 3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

### 3.1.4 DEVIATION FROM TEST STANDARD


No deviation.



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

### 3.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

### 3.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA										
FREQUENCY RANGE		150KHz ~ 30MHz			DETECTOR FUNCTION & RESOLUTION BANDWIDTH		Quasi-Peak (QP) / Average (AV), 9 kHz			
INPUT POWER		120Vac, 60Hz			ENVIRONMENTAL CONDITIONS		26deg. C, 51%RH			
TESTED BY		Hanwen Xu								
Rg	Frequency [MHz]	QPK Level [dB $\mu$ V]	QPK Limit [dB $\mu$ V]	QPK Margin [dB]	CAV Level [dB $\mu$ V]	CAV: AVG Limit [dB $\mu$ V]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.182	51.72	64.42	12.70	47.95	54.42	6.47	12.21	L1	9.000
1	0.420	23.94	57.45	33.51	23.32	47.45	24.13	11.76	L1	9.000
1	1.680	13.10	56.00	42.90	10.24	46.00	35.76	11.75	L1	9.000
1	5.033	16.29	60.00	43.71	13.78	50.00	36.22	11.79	L1	9.000
1	14.262	35.40	60.00	24.60	34.71	50.00	15.29	11.84	L1	9.000
1	26.840	27.33	60.00	32.67	23.02	50.00	26.98	11.90	L1	9.000


**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value - Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.

The graph displays the conducted emission spectrum. The Y-axis represents the signal level in dB $\mu$ V, ranging from -10 to 70. The X-axis represents frequency in Hz, with major ticks at 150 k, 200 k, 300 k, 400 k, 500 k, 600 k, 800 k, 1 M, 2 M, 3 M, 4 M, 5 M, 6 M, 7 M, 8 M, 10 M, 20 M, and 30 M. Several traces are shown, representing different frequency bands. Key markers include:
 

- AVG Level @Spectrum Overview (green line with circles)
- CAV Level @Final Results (red line with diamonds)
- PK+ Level @Spectrum Overview (orange line with triangles)
- QPK Level @Final Results (yellow line with diamonds)
- AVG Limit @FCC Part 15 Voltage Mains Class B (green horizontal line at ~55 dB $\mu$ V)
- QPK Limit @FCC Part 15 Voltage Mains Class B (red horizontal line at ~64 dB $\mu$ V)

 The spectrum shows several peaks, notably around 200 kHz, 400 kHz, and 1.68 MHz, which exceed the QPK limit. The CAV level is consistently lower than the PK+ level across most of the frequency range.



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

<b>FREQUENCY RANGE</b>	150KHz ~ 30MHz			<b>DETECTOR FUNCTION &amp; RESOLUTION BANDWIDTH</b>	Quasi-Peak (QP) / Average (AV), 9 kHz					
<b>INPUT POWER</b>	120Vac, 60Hz			<b>ENVIRONMENTAL CONDITIONS</b>	26deg. C, 51%RH					
<b>TESTED BY</b>	Hanwen Xu									
Rg	Frequency [MHz]	QPK Level [dB $\mu$ V]	QPK Limit [dB $\mu$ V]	QPK Margin [dB]	CAV Level [dB $\mu$ V]	CAV: AVG Limit [dB $\mu$ V]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.182	51.85	64.42	12.57	47.87	54.42	6.55	12.23	N	9.000
1	0.420	24.77	57.45	32.68	24.14	47.45	23.31	12.81	N	9.000
1	1.379	7.44	56.00	48.56	1.70	46.00	44.30	12.74	N	9.000
1	5.874	17.99	60.00	42.01	15.70	50.00	34.30	12.77	N	9.000
1	14.262	36.20	60.00	23.80	35.52	50.00	14.48	12.82	N	9.000
1	26.844	31.08	60.00	28.92	29.94	50.00	20.06	12.88	N	9.000

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value - Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.





BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

## 3.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

### 3.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

#### NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB<sub>uV</sub>/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

### 3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pre-Amplifier	R&S	SCU18F1	100815	Aug.30,23	Aug.29,25
Pre-Amplifier	R&S	SCU08F1	101028	Jan.22,24	Jan.21,26
Signal Generator	R&S	SMB100A	182185	Mar.29,24	Mar.28,26
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.25,22	Nov.24,25
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-02Chamber	Nov.25,22	Nov.24,25
EMI TEST Receiver	R&S	ESW44	101973	Mar.28,24	Mar.27,26
Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Dec.26,23	Dec.25,25
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.22,23	Aug.21,25
Horn Antenna (18GHz-40GHz)	Steatite Q-par Antennas	QMS 00880	23486	Jul.15,24	Jul.14,26
Horn Antenna	Steatite Q-par Antennas	QMS 00208	23485	Aug.22,23	Aug.21,25
Loop Antenna	SCHWARZ	HFH2-Z2/Z2E	100976	Feb.22,25	Feb.21,27
WIDEBANDRADIO COMMUNICATION TESTER	R&S	CMW500	169399	Jun.19,24	Jun.18,26
Test Software	ELEKTRA	ELEKTRA4.32	N/A	N/A	N/A
Open Switch and Control Unit	R&S	OSP220	101964	N/A	N/A
DC Source	HYELEC	HY3010B	551016	Aug.31,23	Aug.30,25
Hygrothermograph	DELI	20210528	SZ014	Sep.06,23	Sep.05,25
6DB attenuator	Tonscend Technology Co., Ltd	N/A	23062787	N/A	N/A
PC	LENOVO	E14	HRSW0024	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-7.00M	N/A	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-4.00M	N/A	N/A	N/A
CABLE	R&S	W13.02	N/A	Apr.27,24	Apr.26,25
CABLE	R&S	W13.02	N/A	Apr.26,25	Apr.25,26
CABLE	R&S	W12.14	N/A	Apr.27,24	Apr.25,25
CABLE	R&S	W12.14	N/A	Apr.26,25	Apr.25,26



**Test Report No.: PSZ-QSZ2504020109RF08**

**NOTE:**

1. The calibration interval of the above test instruments is 12/ 24/ 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Chamber.
3. The FCC Site Registration No. is 434559; The Designation No. is CN1325.



### 3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

#### NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit.
5. All modes of operation were investigated and the worst-case emissions are reported.

### 3.2.4 DEVIATION FROM TEST STANDARD

No deviation.




BUREAU  
VERITAS


Test Report No.: PSZ-QSZ2504020109RF08

### 3.2.5 TEST SETUP

<Frequency Range 9KHz~30MHz >




< Frequency Range 30MHz~1GHz >





<Frequency Range above 1GHz>



**Note:** Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 3.2.6 EUT OPERATING CONDITIONS

- a. Set the EUT under full load condition and placed them on a testing table.
- b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the EUT in full functions.



## 3.2.7 TEST RESULTS


**NOTE** : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

## BELOW 1GHz WORST-CASE DATA

BT_8DPSK															
CHANNEL		Channel 39		DETECTOR FUNCTION		Quasi-Peak (QP)									
FREQUENCY RANGE		30MHz ~ 1GHz													
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M															
Rg	Frequency [MHz]	QPK Level [dB $\mu$ V/m]	QPK Limit [dB $\mu$ V/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]						
1	58.858	25.82	40.00	14.18	-9.82	H	86.9	2.00	120.000						
1	121.714	23.09	43.50	20.41	-12.77	H	225.6	2.00	120.000						
1	229.675	22.07	46.00	23.93	-8.84	H	86.9	2.00	120.000						
1	324.492	22.87	46.00	23.13	-6.06	H	5	1.00	120.000						
1	420.037	23.08	46.00	22.92	-2.46	H	225.6	2.00	120.000						
1	626.259	22.84	46.00	23.16	-2.08	H	359	1.00	120.000						

## REMARKS:

1. Emission Level(dBuV/m) = Read Level(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission level.






BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

CHANNEL		Channel 39		DETECTOR FUNCTION		Quasi-Peak (QP)					
FREQUENCY RANGE		30MHz ~ 1GHz									
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M											
Rg	Frequency [MHz]	QPK Level [dB $\mu$ V/m]	QPK Limit [dB $\mu$ V/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]		
1	35.675	25.31	40.00	14.69	-13.16	V	359.1	1.00	120.000		
1	46.199	23.66	40.00	16.34	-9.90	V	275.4	1.00	120.000		
1	121.665	22.00	43.50	21.50	-11.86	V	355.1	2.00	120.000		
1	158.574	24.59	43.50	18.91	-13.22	V	359.1	1.00	120.000		
1	293.258	16.98	46.00	29.02	-6.62	V	5	1.00	120.000		
1	581.009	22.74	46.00	23.26	-2.78	V	85.8	2.00	120.000		

**REMARKS:**

1. Emission Level(dBuV/m) = Read Level(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission level.



◆ QPK Level @Final Results | ▲ QPK Limit @FCC LIMIT



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

### ABOVE 1GHz WORST-CASE DATA

Note: All other emissions that greater than 20dB below the limit were not recorded.

BT_GFSK											
CHANNEL		TX Channel 0		DETECTOR FUNCTION		Peak (PK) Average (AV)					
FREQUENCY RANGE		1GHz ~ 25GHz									
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M											
Rg	Frequency [MHz]	PK+ Level [dB $\mu$ V/m]	PK+ Limit [dB $\mu$ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]			
5	2,378.000	46.19	74.00	27.81	6.50	H	4.9	1.00			
5	2,390.000	44.88	74.00	29.12	6.52	H	359	2.00			
5	2,402.000	92.83			6.53	H	4.9	1.00			

The graph displays the measured spectrum levels (PK+ Level @Spectrum Overview) in dB $\mu$ V/m against frequency in Hz. A blue line with circular markers represents the measured levels, which are mostly flat at approximately 45 dB $\mu$ V/m across most of the band. A single sharp peak is visible at approximately 2.402 GHz, reaching a level of about 92 dB $\mu$ V/m. A horizontal orange line represents the PK+ Limit @BT2.0&BLE CH0(XIAO MI), set at 74 dB $\mu$ V/m. Two vertical dashed blue lines mark the critical points where the measured level reaches the limit, located at approximately 2.378 GHz and 2.390 GHz.




BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	Avg Level [dB $\mu$ V/m]	Avg Limit [dB $\mu$ V/m]	Avg Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,387.000	31.03	54.00	22.97	6.51	H	294.5	1.00
5	2,390.000	31.04	54.00	22.96	6.52	H	294.5	1.00
5	2,402.000	88.17			6.53	H	4.9	1.00





BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08



Huarui 7layers High Technology  
(Suzhou) Co., Ltd.

Tower N, Innovation Center, 88 Zuyi Road, High-tech  
District, Suzhou City, Anhui Province, China

Tel: +86 (0557) 368 1008



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
Rg	Frequency [MHz]	Avg Level [dB $\mu$ V/m]	Avg Limit [dB $\mu$ V/m]	Avg Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,385.500	30.93	54.00	23.07	6.51	V	355.8	2.00
5	2,390.000	30.92	54.00	23.08	6.52	V	0.9	2.00
5	2,402.000	83.77			6.53	V	359	2.00

The graph displays the measured spectrum levels compared to the BT2.0 & BLE CHO (XIAO MI) limit. The Y-axis represents the Level in dB $\mu$ V/m, ranging from 20 to 125. The X-axis represents Frequency in Hz, ranging from 2.31 GHz to 2.41 GHz. A horizontal green line at 54.00 dB $\mu$ V/m indicates the limit. Two blue circles mark the critical points at 2.385 GHz and 2.390 GHz, where the measured level exceeds the limit.

Frequency (GHz)	Measured Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
2.385	30.93	54.00
2.390	30.92	54.00
2.402	83.77	54.00

#### REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. Margin value = Limit value - Emission level.
3. 2402MHz: Fundamental frequency.



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

CHANNEL		TX Channel 39			DETECTOR FUNCTION			Peak (PK)					
FREQUENCY RANGE		1GHz ~ 25GHz						Average (AV)					
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M													
Rg	Frequency [MHz]	PK+ Level [dB $\mu$ V/m]	PK+ Limit [dB $\mu$ V/m]	PK+ Margin [dB]	Avg Level [dB $\mu$ V/m]	Avg Limit [dB $\mu$ V/m]	Avg Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]		
2	4,882.000	50.91	74.00	23.09	40.93	54.00	13.07	14.77	H	359	2.00		
2	7,323.000	56.15	74.00	17.85	44.59	54.00	9.41	21.12	H	3.6	2.00		

Level in dB $\mu$ V/m

Frequency in Hz

AVG Level @CriticalPoint

PK+ Level @CriticalPoint


AVG Limit @FCC\_RSE\_WLAN2.4G\_HF\_LIMIT

PK+ Limit @FCC\_RSE\_WLAN2.4G\_HF\_LIMIT



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08




#### REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. Margin value = Limit value - Emission level.
3. 2402MHz: Fundamental frequency.



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

CHANNEL		TX Channel 78		DETECTOR FUNCTION		Peak (PK) Average (AV)		
FREQUENCY RANGE		1GHz ~ 25GHz						
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
Rg	Frequency [MHz]	PK+ Level [dB $\mu$ V/m]	PK+ Limit [dB $\mu$ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,479.750	83.69			6.81	H	4.8	1.00
6	2,483.500	48.48	74.00	25.52	6.80	H	355.2	2.00
6	2,484.000	47.59	74.00	26.41	6.80	H	355.2	2.00
								




BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	Avg Level [dB $\mu$ V/m]	Avg Limit [dB $\mu$ V/m]	Avg Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,480.000	79.81			6.81	H	4.2	1.00
6	2,483.500	31.41	54.00	22.59	6.80	H	90.6	2.00
6	2,488.000	31.76	54.00	22.24	6.80	H	249	1.00





BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08





BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
Rg	Frequency [MHz]	Avg Level [dB $\mu$ V/m]	Avg Limit [dB $\mu$ V/m]	Avg Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,480.000	78.58			6.81	V	359	2.00
6	2,483.500	31.37	54.00	22.63	6.80	V	359	2.00
6	2,487.000	31.68	54.00	22.32	6.80	V	0.9	2.00

Level in dB $\mu$ V/m

Frequency in Hz

Legend: ● AVG Level @CriticalPoint, ▲ AVG Level @Spectrum Overview, ■ AVG Limit @BT2.0 CH78&BLE CH39(XAI0 MI)

#### REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value – Emission level.
3. 2480MHz: Fundamental frequency.



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

BT_π/4-DQPSK											
CHANNEL		TX Channel 0		DETECTOR FUNCTION		Peak (PK) Average (AV)					
FREQUENCY RANGE		1GHz ~ 25GHz									
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M											
Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]			
5	2,382.000	45.87	74.00	28.13	6.50	H	355	2.00			
5	2,390.000	44.94	74.00	29.06	6.52	H	358.8	1.00			
5	2,402.500	90.53			6.53	H	5.5	1.00			

Level in dBμV/m

Frequency in Hz

Legend:

- PK+ Level @CriticalPoint (Blue circle)
- PK+ Level @Spectrum Overview (Orange line)
- PK+ Limit @BT2.0&BLE CH0(XIAO MI) (Red line)




BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	Avg Level [dB $\mu$ V/m]	Avg Limit [dB $\mu$ V/m]	Avg Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,394.000	31.32	54.00	22.68	6.52	H	228.7	1.00
5	2,395.000	31.30	54.00	22.70	6.52	H	228.7	1.00
5	2,402.000	86.80			6.53	H	228.7	1.00





BUREAU  
VERITAS


Test Report No.: PSZ-QSZ2504020109RF08





BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08




#### REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. Margin value = Limit value - Emission level.
3. 2402MHz: Fundamental frequency.



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

CHANNEL		TX Channel 39			DETECTOR FUNCTION			Peak (PK) Average (AV)			
FREQUENCY RANGE		1GHz ~ 25GHz									
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M											
Rg	Frequency [MHz]	PK+ Level [dB $\mu$ V/m]	PK+ Limit [dB $\mu$ V/m]	PK+ Margin [dB]	Avg Level [dB $\mu$ V/m]	Avg Limit [dB $\mu$ V/m]	Avg Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,882.000	50.08	74.00	23.92	39.83	54.00	14.17	14.77	H	359	1.00
2	7,323.000	55.31	74.00	18.69	44.74	54.00	9.26	21.12	H	260.2	2.00
											



**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	PK+ Level [dB $\mu$ V/m]	PK+ Limit [dB $\mu$ V/m]	PK+ Margin [dB]	AVG Level [dB $\mu$ V/m]	AVG Limit [dB $\mu$ V/m]	Avg Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,882.000	49.77	74.00	24.23	39.82	54.00	14.18	14.77	V	0.9	2.00
2	7,323.000	55.34	74.00	18.66	44.93	54.00	9.07	21.12	V	359	1.00

Graph showing Level in dB $\mu$ V/m vs Frequency in Hz. The Y-axis ranges from 0 to 80 dB $\mu$ V/m. The X-axis ranges from 1 G to 25 G Hz. A green horizontal line at approximately 53 dB $\mu$ V/m represents the AVG Limit. An orange horizontal line at approximately 73 dB $\mu$ V/m represents the PK+ Limit. Blue vertical dashed lines connect the measured AVG Level (39.82 dB $\mu$ V/m) and PK+ Level (49.77 dB $\mu$ V/m) at 4.882 GHz to their respective limit lines. At 7.323 GHz, the PK+ Level (55.34 dB $\mu$ V/m) is above its limit (54.00 dB $\mu$ V/m).

---


**REMARKS:**

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
  2. Margin value = Limit value - Emission level.
  3. 2441MHz: Fundamental frequency.



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

CHANNEL		TX Channel 78		DETECTOR FUNCTION		Peak (PK) Average (AV)					
FREQUENCY RANGE		1GHz ~ 25GHz									
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M											
Rg	Frequency [MHz]	PK+ Level [dB $\mu$ V/m]	PK+ Limit [dB $\mu$ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]			
6	2,479.750	82.71			6.81	H	4.8	1.00			
6	2,483.500	46.35	74.00	27.65	6.80	H	256.2	1.00			
6	2,492.250	47.49	74.00	26.51	6.80	H	279.4	2.00			
											




BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dB $\mu$ V/m]	AVG Limit [dB $\mu$ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,480.000	76.75			6.81	H	4.2	1.00
6	2,483.500	31.45	54.00	22.55	6.80	H	355.8	2.00
6	2,487.000	31.73	54.00	22.27	6.80	H	253.8	1.00





BUREAU  
VERITAS


Test Report No.: PSZ-QSZ2504020109RF08





BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08



#### REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. Margin value = Limit value - Emission level.
3. 2480MHz: Fundamental frequency.



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

BT_8DPSK								
CHANNEL		TX Channel 0		DETECTOR FUNCTION		Peak (PK) Average (AV)		
FREQUENCY RANGE		1GHz ~ 25GHz						
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
Rg	Frequency [MHz]	PK+ Level [dB $\mu$ V/m]	PK+ Limit [dB $\mu$ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,373.500	46.76	74.00	27.24	6.49	H	15.4	2.00
5	2,390.000	45.54	74.00	28.46	6.52	H	1.3	2.00
5	2,402.000	92.01			6.53	H	4.2	1.00

Level in dB $\mu$ V/m

Frequency in Hz

Legend:

- PK+ Level @CriticalPoint (Blue circle)
- PK+ Level @Spectrum Overview (Orange triangle)
- PK+ Limit @BT2.0&BLE CHO(XIAO MI) (Red triangle)




BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	Avg Level [dB $\mu$ V/m]	Avg Limit [dB $\mu$ V/m]	Avg Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,388.000	31.02	54.00	22.98	6.51	H	355.1	2.00
5	2,390.000	31.06	54.00	22.94	6.52	H	4.2	1.00
5	2,402.500	84.65			6.53	H	4.2	1.00





BUREAU  
VERITAS


Test Report No.: PSZ-QSZ2504020109RF08





BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08




#### REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. Margin value = Limit value - Emission level.
3. 2402MHz: Fundamental frequency.



BUREAU  
VERITAS


Test Report No.: PSZ-QSZ2504020109RF08





BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08



#### REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
2. Margin value = Limit value - Emission level.
3. 2402MHz: Fundamental frequency.



BUREAU  
VERITAS

Test Report No.: PSZ-QSZ2504020109RF08

CHANNEL		TX Channel 78		DETECTOR FUNCTION		Peak (PK) Average (AV)		
FREQUENCY RANGE		1GHz ~ 25GHz						
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
Rg	Frequency [MHz]	PK+ Level [dB $\mu$ V/m]	PK+ Limit [dB $\mu$ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,479.750	82.55			6.81	H	5	1.00
6	2,483.500	46.71	74.00	27.29	6.80	H	191	2.00
6	2,489.000	47.13	74.00	26.87	6.80	H	359.1	1.00
