

FCC ID: 2AG69LV300N Contains FCC ID:QIPELS61-US

## **RF Exposure Evaluation**

### Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)					
(A) Limits for Occupational/Controlled Exposures									
0.3–3.0	614	1.63	*(100)	6					
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6					
30–300	61.4	0.163	1.0	6					
300–1500			f/300	6					
1500–100,000			5	6					
(B) Limits for General Population/Uncontrolled Exposure									
0.3–1.34	614	1.63	*(100)	30					
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30					
30–300	27.5	0.073	0.2	30					
300–1500			f/1500	30					
1500–100,000			1.0	30					

f = frequency in MHz

Friis transmission formula:  $Pd = (Pout*G)/(4*pi*r^2)$ 

#### Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, <math>Pi = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### **Test Procedure**

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.





FCC ID: 2AG69LV300N Contains FCC ID:QIPELS61-US

# **Test Result of RF Exposure Evaluation**

Mode	Antenna gain (dBi)	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm²)	Limit (mW/cm2)	Result
LTE-B2	2.15	25	316.23	0.1032	1.0	PASS
LTE-B4	2.15	25	316.23	0.1032	1.0	PASS
LTE-B5	2.15	25	316.23	0.1032	0.55	PASS
LTE-B12	2.15	25	316.23	0.1032	0.47	PASS
WCDMA-B2	2.15	25	316.23	0.1032	1.0	PASS
WCDMA-B4	2.15	25	316.23	0.1032	1.0	PASS
WCDMA-B5	2.15	25	316.23	0.1032	0.55	PASS
BLE	1.88	5.62	3.65	0.0011	1.0	PASS

BLE and cellular Simultaneous Transmission:

$$\sum_{k=1}^{c} \frac{Evaluated_k}{Exposure\ Limit_k}$$

BLE + LTE =(0.0011/1)+(0.1032/0.47)=0.0011+0.2196=0.2207<1

BLE + WCDMA=(0.0011/1)+(0.1032/0.55)=0.0011+0.1876=0.1887<1

The max power density is less than MPE exempt limit, so it is compliance.