## FCC ID: ZHW-8044149

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \*  $[\sqrt{f}(GHz)] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

Bluetooth:	
------------	--

Transmit Frequency (GHz)	Mode	Measured Power (dBm)	Tune-up power (dBm)	Max tune-up power(dBm)	Result	1g SAR
2.402		0.87	0±1	1	0.3902	3
2.441	GFSK	0.51	0±1	1	0.3934	3
2.48		-0.48	0±1	1	0.3965	3
2.402	π/4-DQPSK	-0.50	-1±1	0	0.3100	3
2.441		-1.16	-1±1	0	0.3125	3
2.48		-0.43	-1±1	0	0.3150	3
2.402		-0.29	-0.5±1	0.5	0.3478	3
2.441	8DPSK	-0.27	-0.5±1	0.5	0.3506	3
2.48		-1.21	-0.5±1	0.5	0.3534	3

**Conclusion:** 

For the max result : 0.3965≤ 3.0 for 1g SAR, No SAR is required.

Jason chen

Signature:

Date: 2016-4-29

NAME AND TITLE (Please print or type): Jason Chen /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.