

FCC Test Report

Report No.: AGC13372211102EE08

FCC ID	÷	2A300RB23
PRODUCT DESIGNATION	:	Walkie Talkie
BRAND NAME	:	RETEVIS
MODEL NAME	:	RB23
APPLICANT	:	Shenzhen Ysair Technology Co., LTD
DATE OF ISSUE	÷	Dec. 13, 2021
STANDARD(S)	: @	FCC Part 15 Rules
REPORT VERSION	:	V 1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter aphorization of AGE (ne test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day Safter the issuerce of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agc-cert.com



Report No.: AGC13372211102EE08 Page 2 of 25

REPORT REVISE RECORD

Report Version	Revise Time Issued Date		Valid Version	Notes
V1.0		Dec. 13, 2021	Valid	Initial Release

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agc-cert.com



Report No.: AGC13372211102EE08 Page 3 of 25

TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE	
2. PRODUCT INFORMATION	5
3. IDENTIFICATION OF THE RESPONSIBLE TESTING LOCATION	6
4. SUPPORT EQUIPMENT LIST	7
5. SYSTEM DESCRIPTION	7
6. MEASUREMENT UNCERTAINTY	
7. SUMMARY OF TEST RESULTS	
8. FCC RADIATED EMISSION TEST	9
8.1 PROVISIONS APPLICABLE	
8.2 TEST SETUP BLOCK DIAGRAM	
8.3 TEST PROCEDURE	11
8.4 TEST RESULT	
9. FCC CONDUCTED EMISSION TEST	
9.1 PROVISIONS APPLICABLE	16
9.2 TEST SETUP BLOCK DIAGRAM	16
9.4 TEST RESULT	
10. ANTENNA CONDUCTED POWER FOR RECEIVERS	
10.1 PROVISIONS APPLICABLE	20
10.2 TEST SETUP BLOCK DIAGRAM	
10.3 TEST PROCEDURE	
10.4 TEST RESULT	21
11. SCANNING RECEIVERS AND FREQUENCY CONVERTERS USED WITH SCANNING REC	EIVERS 23
11.1 PROVISIONS APPLICABLE	23
11.2 TEST SETUP BLOCK DIAGRAM	23
11.3 TEST PROCEDURE	23
11.4 TEST RESULT	
APPENDIX I PHOTOGRAPHS OF TEST SETUP	25
APPENDIX II: PHOTOGRAPHS OF TEST FUT	25

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written approver, or having not been stamped by the Bedicated Pesting/Inspection presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuerce of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



1. VERIFICATION OF COMPLIANCE

Applicant:	Shenzhen Ysair Technology Co., LTD					
Address:	6 / F, building 6, Yunli intelligent park, No. 3, Changfa Middle Road, Yangmei community, Bantian street, Longgang District, Shenzhen, Guangdong, China					
Manufacturer:	Shenzhen Ysair Technology Co., LTD					
Address:	6 / F, building 6, Yunli intelligent park, No. 3, Changfa Middle Road, Yangmei community, Bantian street, Longgang District, Shenzhen,Guangdong,China					
Factory:	Shenzhen Ysair Technology Co., LTD					
Address:	6 / F, building 6, Yunli intelligent park, No. 3, Changfa Middle Road, Yangmei community, Bantian street, Longgang District, Shenzhen,Guangdong,China					
Product Designation:	Walkie Talkie					
Brand Name:	RETEVIS					
Test Model:	RB23					
Measurement Procedure:	ANSI C63.4: 2014					
Deviation:	No any deviation from the test method.					
Date of Test:	Nov. 18, 2021~Dec. 13, 2021					
Condition of Test Sample:	Normal					
Test Result:	Pass					
Report Template;	AGCRT-US-PTT/EMC					

The above equipment was tested by Attestation Of Global Compliance (Shenzhen) Co., Ltd. for compliance with the requirements set forth in the FCC Rules and Regulations Part 15, the measurement procedure according to ANSI C63.4:2014. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment are within the compliance requirements. The test results of this report relate only to the tested sample identified in this report.

Prepared By

Bibo zhang

Bibo Zhang (Project Engineer)

Dec. 13, 2021

Reviewed By

Calin Lin

Calvin Liu (Reviewer)

Dec. 13, 2021

Approved By

Max Zhang

Max Zhang Authorized Officer

Dec. 13, 2021

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the stead festing/inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter exchanged by the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issue of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



2. PRODUCT INFORMATION

The EUT is a Walkie Talkie designed for voice communication. It is designed by way of utilizing the F3E

modulation achieves the system operating.

A major technical description of EUT is described as following:

Communication Type	Voice / Tone only
Modulation	FM
RX Frequency Range	462.5625MHz-462.7125MHz, 462.5500MHz-462.7250MHz, 467.5625MHz-467.7125MHz (Scanning Receiver)
Emission Type	F3E
Antenna Designation	Inseparable Antenna
Antenna Gain	2.15dBi
Hardware Version	V1.01
Software Version	V1.0
Power Supply	DC 7.4V,1800mAh by battery, charging for DC 12V with adapter.

I/O Port Information (Applicable

Not Applicable)

I/O Port of EUT					
I/O Port Type	Q'TY	Cable	Tested with		
Antenna Port	1	<u>د</u> کی	1		
Earphone Port	1				

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated for the formation of the stamp. Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



3. IDENTIFICATION OF THE RESPONSIBLE TESTING LOCATION

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd					
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China					
Designation Number	CN1259					
FCC Test Firm Registration Number	975832					
A2LA Cert. No.	5054.02					
Description	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by A2LA					

List of Test Equipment:

TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	May 11, 2021	May 10, 2022
LISN	R&S	ESH2-Z5	100086	Jun. 09, 2021	Jun. 08, 2022
TEST SOFTWARE	FARA	EZ-EMC (Ver.AGC-C ON03A1)	N/A	N/A	N/A

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	May 11, 2021	May 10, 2022
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 08, 2021	Jan. 07, 2023
ANTENNA	SCHWARZBECK	VULB9168	D69250	Apr. 28, 2021	Apr. 27, 2023
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Sep. 03, 2020	Sep. 02, 2022
POSITIONING CONTROLLER	MF	MF-7802	MF780208285	<u> </u>	G - 2
HORN ANTENNA	ETS LINDGREN	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
RF Communication Test Set	HP	8920B	US35010161	Sep. 01, 2021	Aug. 31, 2022
EXA Signal Analyzer	Agilent	N9020A	MY53300860	Jun. 09, 2021	Jun. 08, 2022
Attenuator	Schaffner	58-30-33	ML030	Oct. 24, 2021	Oct. 23, 2022
Test software	Tonscend	JS32-RE (Ver.2.5)	N/A	N/A	N/A

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Festing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter authorization of AGE. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



4. SUPPORT EQUIPMENT LIST

Device Type	Manufacturer	Model Name	Serial No.	Data Cable	Power Cable
Adapter	- C	SA23			2.G-
Battery	2	BL23	- ©	-	
Charger	0	DC 23	LGC	-6	0
Back clip	- CO-	N/A	-	0 - C	0 - 0
USB Cable		N/A	· ·	е -	-0-
Lanyard		N/A	· .	0 - 0	- 6

5. SYSTEM DESCRIPTION

EUT TEST PROCEDURE:

- 1. Connect EUT and peripheral devices.
- 2. Power on the EUT, the EUT begins to work.
- 3. Make sure the EUT normal working.

EMC TEST MODE:

No.	TEST MODES				
1	Scanning mode				
2	Scanning stopped/Receiving at low channel of 462.5625 MHz to 462.7125 MHz				
3	Scanning stopped/Receiving at middle channel of 462.5625 MHz to 462.7125 MHz				
4	Scanning stopped/Receiving at high channel of 462.5625 MHz to 462.7125 MHz				
5	Scanning stopped/Receiving at low channel of 462.5500 MHz to 462.7250 MHz				
6	Scanning stopped/Receiving at middle channel of 462.5500 MHz to 462.7250 MHz				
7	Scanning stopped/Receiving at high channel of 462.5500 MHz to 462.7250 MHz				
8	Scanning stopped/Receiving at low channel of 467.5625 MHz to 467.7125MHz				
9	Scanning stopped/Receiving at middle channel of 467.5625 MHz to 467.7125MHz				
10	Scanning stopped/Receiving at high channel of 467.5625 MHz to 467.7125MHz				

Note: Only the result of the worst case was recorded in the report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated frame/inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC in the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15da/Castra the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



6. MEASUREMENT UNCERTAINTY

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in measurement" (GUM) published by CISPR and ANSI.

- Uncertainty of Conducted Emission, Uc = ±3.1 dB
- Uncertainty of Radiated Emission below 1GHz, Uc = ±4.0 dB
- Uncertainty of Radiated Emission above 1GHz, Uc = ±4.8 Db

7. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.107	Conduction Emission	Compliant
§15.109	Radiated Emission	Compliant
§15.111	Antenna Conducted Power for receivers	Compliant
§15.121(b)	Scanning receivers and frequency converters used with scanning receivers	Compliant

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated frame/inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC in the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day affect the issue of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



8. FCC RADIATED EMISSION TEST


8.1 PROVISIONS APPLICABLE

FCC CFR Title 47 Part 15 Subpart B Section 15.109:

Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

Note: The lower limit shall apply at the transition frequency. Because the EUT RX frequency range up to 467.7125MHz, so the upper the frequency range up to 2 GHz.

8.2 TEST SETUP BLOCK DIAGRAM




RADIATED EMISSION TEST SETUP 30MHz-1000MHz

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated resting/inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Report No.: AGC13372211102EE08 Page 10 of 25



RADIATED EMISSION TEST SETUP ABOVE 1000MHz

EMI TEST RECEIVER SETUP:

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurment
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz		PK 💿
Above I GHZ	1MHz	10 Hz	/	Ave.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated for the formation of the stamp. Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



8.3 TEST PROCEDURE


- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. The EUT received power by AC 120V/60Hz.
- 5. The antenna was placed at 3 meter away from the EUT as stated in FCC Part 15. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
- The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 7. The test mode(s) were scanned during the test:
- 8. Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and Q.P./Peak reading is presented. For emissions below 1GHz, use 120KHz RBW and VBW>=3RBW for QP reading.
- 9. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 10. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 11. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 12. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 13. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.
- 14. The test data of the worst case condition (mode 1) was reported on the following Data page.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated resting/inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Report No.: AGC13372211102EE08 Page 12 of 25

8.4 TEST RESULT



RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the stand of the report is not permitted without the written authorization of AGE in the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day and the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



ode	Mod	e 1	5	8	Polarity:		Vertical	GO
72.0 d	lBu∀/m						Limit:	
							Margin:	
					J 			
32			3		- 6			
۱ ۸۸		2	M	7	MAL.		prover ability and	months
- 1	1000 march	the water they have	when when	WWW	Whit appression	martinet		
_	•	NAMP IN	a. H. M. W.					
-8								
-8	40	50 60 70	80	(MHz)	300	400 500	600 700	1000.000
30.000 			Reading	Correct	Measure-			1000.000
30.000 	0 40 0. Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
30.000 		. Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	1000.000 Detector
30.000 		. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
30.000	o. Mk	. Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
30.000 	o. Mk 1	. Freq. MHz 30.5306	Reading Level dBuV 18.20	Correct Factor dB 7.19	Measure- ment dBuV/m 25.39	Limit dBuV/m 40.00	Over dB -14.61	Detector peak
30.000	o. Mk 1 2	Freq. MHz 30.5306 61.5618	Reading Level dBuV 18.20 12.31	Correct Factor dB 7.19 11.91	Measure- ment dBuV/m 25.39 24.22	Limit dBuV/m 40.00 40.00	Over dB -14.61 -15.78	Detector peak peak
30.000	o. Mk 1 2 3	. Freq. MHz 30.5306 61.5618 109.0286	Reading Level dBuV 18.20 12.31 19.86	Correct Factor dB 7.19 11.91 10.25	Measure- ment dBuV/m 25.39 24.22 30.11	Limit dBuV/m 40.00 40.00 43.50	Over dB -14.61 -15.78 -13.39	Detector peak peak peak

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



			Radiated En	nission Above	GHz Test R	esult		
Test Mo	ode 1	Node 1	.C	©	Polarity:		Horizonta	al
Level(dBu/m)	40 30 20 10 -10 1G 	imit — AV Limit	Horizontal PK	FCC PART 15	2 2 3 3 3 6	46	5G	6G
NO.	Freq. [MHz]	Level [dBµV/m	Factor] [dB]	Limit [dBµV/m]	[dB]	Height [cm]	Angle [°]	Polarity
1	1177.01	77 38.21	-16.81	74.00	35.79	100	80	Horizontal
2	2044.60		-11.63	74.00	34.17	100	40	Horizontal
3	2605.66		-9.64	74.00	31.95	100	100	Horizontal
4	3427.74	42.51	-7.85	74.00	31.49	100	300	Horizontal
5	4252.82		-5.84	74.00	30.41		280	

74.00

28.97

100

60

Horizontal

RESULT: PASS

6

4837.8838

45.03

-4.88

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written approver, and the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



			Ra	adiated Err	nission Above1	GHz Test R	esult		
Test M	lode	Mod	le 1	5	8	Polarity:		Vertical	C.C
	130 120 110				FCC PART 15	B			
	100 90								
	80 70 70 60 50								
-	50 50 40 30	hand black and a state of the	1. ประเทศสายชาวอยู่ว่าประเทศสายสายสายเป็นชาวอย่างเป็นเป็นเป็นเป็นเป็นเป็นเป็นเป็นเป็นเป็น	an a		, A ana ka		s ar water and water from the beauty	Y
	20								
	10								
					26	3G	4G	5G	
	10 0 -10 1G	 PK Limit AV Detector 		- Vertical PK	2G Frequency[Hz		46	56	6G
NO.	10 0 -10 1G	AV Detecto		- Vertical PK Factor [dB]			4G Height [cm]	56 Angle [°]	Polarity
NO.	10 0 -10 16 Fre	eq. Hz]	Level	Factor	Frequency[Hz	Margin	Height	Angle	
	10 0 -10 1G Fre [MH	eq. Hz] 0185	Level [dBµV/m]	Factor [dB]	Frequency[Hz Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	10 0 -10 16 Fre [MH 1185.	eq. Hz] 0185 5996	Level [dBµV/m] 38.81	Factor [dB] -16.82	Frequency[Hz	Margin [dB] 35.19	Height [cm] 100	Angle [°] 250	Polarity Vertical
1 2	10 0 -10 16 Free [MF 1185.1 1995.3	AV Detect eq. 1z] 0185 5996 1669	Level [dBµV/m] 38.81 40.11	Factor [dB] -16.82 -11.87	Frequency[Hz	Margin [dB] 35.19 33.89	Height [cm] 100 100	Angle [°] 250 170	Polarity Vertical Vertical

RESULT: PASS

6

4753.3753

45.11

Note: 1. Factor=Antenna Factor + Cable loss - Amplifier gain, Margin= Limit-Measurement.

-4.96

2. The "Factor" value can be calculated automatically by software of measurement system.

74.00

28.89

100

270

Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGE. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



9. FCC CONDUCTED EMISSION TEST


9.1 PROVISIONS APPLICABLE

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the, the radio frequency voltage that is conducted back onto the AC power line on any frequencies within the band 150 KHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50uH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted Limit(dBuV)		
	Quasi-Peak	Average	
0.15 – 0.5	66 to 56 *	56 to 46 *	
0.5 – 5	56	46	
5 – 30	60	50	

* Decreases with the logarithm of the frequency.

9.2 TEST SETUP BLOCK DIAGRAM



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated frame/inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC in the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15da/Cafter the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




9.3 TEST PROCEDURE

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. The EUT received AC 120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5. All support equipments received AC power from a second LISN, if any.
- 6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test data of the worst case condition (mode 1) was reported on the following Data page.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pertor/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter adhorization of AGE. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



9.4 TEST RESULT



MEASUREMENT RESULT: "agc_fin"

2021/12/6 21:46 Frequency Level Transd Limit Margin Detector Line MHz dBµV dB dBµV dB 45.50 0.150000 6.9 66 20.5 QP ь1 38.50 5.4 17.5 0.622000 56 QP ь1 0.750000 36.40 5.4 56 19.6 QP ь1 5.4 0.998000 35.90 56 20.1 ь1 QP 37.90 5.6 56 1.122000 18.1 ь1 QP 1.494000 37.00 6.0 56 19.0 ь1 QP


MEASUREMENT RESULT: "agc fin2"

2021/12/6 21:	46					
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.622000	34.00	5.4	46	12.0	AV	L1
0.750000	32.10	5.4	46	13.9	AV	ь1
0.874000	29.90	5.4	46	16.1	AV	ь1
0.998000	30.50	5.4	46	15.5	AV	L1
1.122000	33.60	5.6	46	12.4	AV	ь1
1.246000	32.20	5.8	46	13.8	AV	L1

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Perturbution" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written aphorization of AGE The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Report No.: AGC13372211102EE08 Page 19 of 25



MEASUREMENT RESULT: "agc_fin"

2021/12/6 21:48

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.626000	34.00	5.4	56	22.0	QP	N
0.746000	40.60	5.4	56	15.4	QP	N
1.118000	40.00	5.6	56	16.0	QP	N
1.242000	39.10	5.8	56	16.9	QP	N
1.614000	37.90	6.2	56	18.1	QP	N
2.114000	34.20	6.5	56	21.8	QP	N

MEASUREMENT RESULT: "agc_fin2"

2021/12/6 21 Frequency	Level			-	Detector	Line
MHz	dBµV	dB	dBµV	dB		
0.622000	33.20	5.4	46	12.8	AV	N
0.746000	34.90	5.4	46	11.1	AV	N
0.870000	31.80	5.4	46	14.2	AV	N
1.118000	34.50	5.6	46	11.5	AV	N
1.242000	32.90	5.8	46	13.1	AV	N
1.618000	26.80	6.2	46	19.2	AV	N

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the submitted restriction of AGE. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




10. ANTENNA CONDUCTED POWER FOR RECEIVERS

10.1 PROVISIONS APPLICABLE

The antenna conducted power of the receiver as defined in §15.111 shall not exceed the values given in the following tables

Frequency Range	9 KHz to 2GHz		
Limit	2.0 nW (-57 dBm)		

10.2 TEST SETUP BLOCK DIAGRAM



10.3 TEST PROCEDURE

- 1. The receiver antenna terminal connected to a spectrum analyzer.
- 2. Receiver set as follow:

Frequency range	RBW (kHz)	VBW (kHz)
9 kHz ~ 150 kHz		3
150 kHz ~ 30 MHz	10	30
30 MHz ~ 1000 MHz	100	300
1000 MHz ~ 3000 MHz	1000	3000

The test data of the worst case condition (mode 1) was reported on the following Data page.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Particular" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGE The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




10.4 TEST RESULT




Conducted Measurement (9 KHz to 150 KHz)

Conducted Measurement (150 KHz to 30MHz)



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated festing/inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written approver, and horization of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuence of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.





Conducted Measurement (30MHz to 1GHz)

nt Spectrum Analyzer - Swept SA Agilent Spectrum V L RF |50 Ω AC | Start Freq 1.000000000 GHz PN0: Fast ↓ IFGain:Low Frequency Avg Type: Log-Pwi Avg|Hold:>100/100 Trig: Free Run Atten: 6 dB TYP DE Auto Tune 1.024 60 GHz -74.876 dBm Mkr1 Ref -37.00 dBm 10 dB/div **Center Frea** 1.500000000 GHz Start Freq 1.00000000 GHz Stop Freq 2.00000000 GHz CF Ster 100.000000 MH <u>Auto</u> Ma **Freq Offset** 0 Hz Start 1.0000 GHz #Res BW 1.0 MHz Stop 2.0000 GHz Sweep 2.000 ms (30000 pts) #VBW 3.0 MHz STATUS

Conducted Measurement (1GHz to 2GHz)

RESULT:PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Pasting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGE. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuence of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




11. SCANNING RECEIVERS AND FREQUENCY CONVERTERS USED WITH SCANNING RECEIVERS

11.1 PROVISIONS APPLICABLE

Except as provided in paragraph (c) of this section, scanning receivers shall reject any signals from the Cellular Radiotelephone Service frequency bands that are 38 dB or lower based upon a 12 dB SINAD measurement, which is considered the threshold where a signal can be clearly discerned from any interference that may be present.

11.2 TEST SETUP BLOCK DIAGRAM



11.3 TEST PROCEDURE

- 1. Connected the EUT as shown in the above block diagram.
- 2. Apply a RF signal to the receiver input port at lowest, middle and highest channel frequencies of receiver operation band.
- 3. Adjust the audio output level of the receiver to it's rated value with the distortion less than 10%.
- 4. Adjust the RF Signal Generator Output Power to produce 12 dB SINAD without the audio output power dropping by more than 3 dB.This output level of the RF SG at each channel frequency is the sensitivity of the receiver.
- 5. Select the lowest or worse-case sensitivity level for all of the bands as the reference sensitivity.
- 6. Adjust the RF Signal Generator output to a level of +60 dB above the reference sensitivity obtained in step5) and its frequency to the frequency points in the cellular band.
- 7. Set the Receiver squelch to threshold, the signal required to open the squelch must be lower than the reference sensitivity level.
- 8. Set the receiver in a scanning mode and allow it to scan through it's complete receiving range.
- 9. If the receiver unsquelched or stopped on any frequency, receiving at this frequency, then adjust the signal generator output level until 12 dB SINAD is produced, this level is the spurious value and the difference between the reference sensitivity and the spurious value is the rejection ratio and must be at least 38dB.
- 10. Repeat above procedure at the frequencies 824.5, 836.0, and 848.5 MHz for the mobile band, and 869.1, 881.5, and 893.5MHz for the cellular base band.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter approver and the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Report No.: AGC13372211102EE08 Page 24 of 25

11.4 TEST RESULT

Note: The scanning receive frequency range of this EUT is from 462.5500MHz to 462.7250MHz, 462.5625MHz to 462.7125MHz, 467.5500MHz to 467.7250MHz not in the cellular radiotelephone service frequency bands, so this item is not applicable.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the stand of the test results of the test results been at the report is not permitted without the writter aphorization of AGE in the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Report No.: AGC13372211102EE08 Page 25 of 25

APPENDIX I PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC13373211102AP03

APPENDIX II: PHOTOGRAPHS OF Test EUT

Refer to the Report No.: AGC13373211102AP02

-----END OF REPORT-----

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the stand restriction of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agc-cert.com

Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the solution of a stamp of the test results for the test results and the test of the test of the test results of the test results of the test report is not permitted without the writter apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.