



Test report issued under the responsibility of:
EMITECH MONTPELLIER laboratory
MRA US-EU Designation Number: FR0006
Canadian CAB Identifier: FR0003

RADIO TEST REPORT

FCC Part 15 :2018
ANSI C63.10 : 2013
RSS-Gen - Issue 5, April 2018
RSS-210-Issue 9, August 2016

Company: **PRASTEL FRANCE**
Address.....: 225 impasse du Serpolet
ZI Athélia II
13600 LA CIOTAT
FRANCE

Test item description: **Remote control 4 channels**
Trade Mark: PRASTEL
Manufacturer: PRASTEL FRANCE
Model/Type reference.....: SLIM+
FCC ID.....: 2AEHC-SLIMPLUS
IC: None
Ratings.....: 3 Vdc

Testing Laboratory: **EMITECH MONTPELLIER laboratory**
Address.....: 145 rue de Massacan
34740 VENDARGUES Cedex
FRANCE

Report Reference No: **R410-18-101706-12A**
Test procedure: FCC&IC Certification
Diffusion.....: Mr JAUMES
Applicant's name: PRASTEL FRANCE
Date of issue.....: 20/05/2019
Total number of pages.....: 26
Revision: 0
Modified page(s).....: Creation
Compiled by.....: Morgan PATEY
Approved by (+ signature).....: Olivier HEYER (Laboratory Manager)

*Duplication of this test report is only permitted for an integral photographic facsimile. It includes the number of pages referenced here above.
This document is the result of testing a specimen or a sample of the product submitted. It does not imply an assessment of the conformity of
the whole manufactured products of the tested sample.*



Siège Social : Emitech - 3, rue des Coudriers - CAP 78 - ZA de l'Observatoire - 78180 MONTIGNY LE BX - France
Siret : 344 545 645 00022 - Tél. : 33 (0)1 30 57 55 55 - Fax : 33 (0)1 30 43 74 48 - E-mail : contact@emitech.fr - URL : www.emitech.fr
S.A. au capital de 1 560 000 € - R.C.S. VERSAILLES 344 545 645 - APE 7112B

REPORT INDEX:

1. GENERAL INFORMATIONS	3
2. REFERENCE DOCUMENT(S)	4
3. EQUIPMENT TECHNICAL DESCRIPTION	5
3.1. TEST CONDITIONS	5
3.2. EUT MECHANICAL AND ELECTRICAL DESIGN	5
3.3. EUT INPUT/OUTPUT PORTS	6
3.4. EUT RADIO SPECIFICATIONS	7
4. RESULT SUMMARY	8
5. MEASUREMENT UNCERTAINTY	9
6. TEST CONDITIONS AND RESULTS	10
6.1. RADIATED SPURIOUS EMISSIONS <30MHZ	10
6.2. RADIATED SPURIOUS EMISSIONS >30MHZ	15
6.3. RADIATED FIELD STRENGTH OF FUNDAMENTAL	20
6.4. OCCUPIED BANDWIDTH 99% & 20 DB BANDWIDTH	22

2. REFERENCE DOCUMENT(S)

NORMATIVE REFERENCES:

The following referenced documents are necessary for the application of the present test report.

FCC Part 15 :2018

Code of Federal Regulations
Title 47 – Telecommunications
Chapter 1 – Federal Communications Commission
Part 15 – Radio frequency devices
Subpart C – Intentional Radiators

ANSI C63.10 : 2013

American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

RSS-Gen - Issue 5, April 2018

General requirements and Information for the Certification of radio Apparatus

RSS-210-Issue 9, August 2016

Licence-exempt Radio Apparatus: Category I Equipment

INFORMATIVE REFERENCES:

The following referenced documents are not necessary for the application of the present test report but they assist the user with regard to a particular subject area.

3. EQUIPMENT TECHNICAL DESCRIPTION

3.1. Test Conditions

Test item description. : SLIM+
 Model/Type reference..... : SLIM+
 Trade Mark. : PRASTEL
 Serial number (S/N)..... : Not communicated
 Part number (P/N). : Not communicated
 Software version..... : Not communicated
 Firmware version. : Not communicated
 Type of sample. : Pre-serial
 Function(s)..... : Door opening remote control
 Manufacturer name. : PRASTEL FRANCE

General product information:

N/A


3.2. EUT Mechanical and Electrical Design

Power supply. : 3 Vdc
 Power supply range..... : 3 Vdc
 Power type..... : Battery (CR2032)
 Power : 75 mW
 Nominal current : 25 mA
 Dimensions (L x W x H) (m). : 0.065x0.03x0.011
 Weight (kg). : 0.027
 Temperature range..... : -20°C to +55°C
 Ground bounding strap..... : No


Comments:

Batteries was remplaced by external power source during tests.

Photos:



3.3. EUT Input/Output ports



DC power supply (Internal Battery)

RF antenna

PORT	NAME	TYPE	LENGHT	CABLE TYPE	COMMENTS
0	Main frame	N/E	N/A	Plastic Metallic	
1	DC power supply (Internal Battery)	DC	N/A	Internal battery	Remplaced by external power source (Emitech n°8496)
2	RF antenna	RF	433.92 MHz	RF Antenna	

AC/DC : AC/DC Converter port

AC.....: Alternative current port

DC.....: Discontinuous current port

I/O.....: Input or Output port

TP.....: Telecommunication port

RF.....: Radio frequency port

N/E.....: Non Electrical port

3.4. EUT Radio Specifications

a) GENERAL INFORMATIONS

According to manufacturer's declarations :

EUT type..... : Transmitter
 Technology : SRD
 Environmental profile..... : Light Industry – Residential
 Temperature range..... : -20°C to +60°C
 Antenna type : Integral
 Antenna Gain..... : Not communicated

Comments:

N/A

b) TRANSMITTER PARAMETERS (Tx)

Frequency bands : 433.92 MHz
 RF Power..... : 10 mW
 Number of channels / Separation..... : 1
 Modulation type : OOK + GFSK
 Duty cycle : 0.002%
 Tested frequency..... : 433.92 MHz


c) RECEIVER PARAMETERS (Rx)

Frequency bands : N/A
 Category/Class : N/A
 Bandwidth : N/A

d) TRANSMISSION TIME (Tx)

To comply with §15.231 (a) (1) or (2) it was verified that the emission of the product lasted less than 5 s after a key was pressed.

It was found that the transmission lasted no less than 500 ms after each press (see below)



4. RESULT SUMMARY

TEST DESIGNATION	SEVERITY	VERDICT	BASIC STANDARDS / COMMENTS
Antenna requirement	-	PASS	Integrated antenna
Conducted voltage emission (measurement)		N/A	ANSI C63.10: 2013 //15.207 and RSS-Gen Powered by internal batteries
Radiated spurious emissions <30MHz			15.209
- RNE_TX / 0°	Tx	PASS	
- RNE_TX / 45°	Tx	PASS	
- RNE_TX / 90°	Tx	PASS	
Radiated spurious emissions >30MHz			15.209 & 15.231 and RSS-Gen & RSS-210 Annex A1
- RNE / Tx Mode / SLIM+ / OOK	Tx	PASS	
- RNE / Tx Mode / SLIM+ / GFSK	Tx	PASS	
Radiated field strength of fundamental	a)	PASS	15.231 a) and RSS-210 Annex A1
Occupied bandwidth	-	PASS	RSS-Gen §6.7

Sample subject to the test complies with the requirements of the reference document(s) listed in §2 of this test report and, where applicable, with deviation(s) specified in this document.

To declare, or not, the compliance with the specifications, it was not explicitly taken account of uncertainty associated with the results.

Opinion(s) and interpretation(s): N/A

5. MEASUREMENT UNCERTAINTY

PARAMETER	MAXIMAL EMITECH UNCERTAINTY	MINIMAL STANDARD UNCERTAINTY
Conducted emission		
(Artificial Mains Network) 3kHz – 9kHz	± 3.8 dB	/
(Artificial Mains Network) 9kHz – 150kHz	± 3.6 dB	± 3.6 dB
(Artificial Mains Network) 150kHz – 30MHz	± 3.4 dB	± 3.4 dB
(Voltage probe) 9kHz – 30MHz	± 2.9 dB	± 2.9 dB
(Asymmetric Artificial Network) 150kHz – 30MHz	± 3.5 dB	± 5.0 dB
(Current measurement) 150kHz – 30MHz	± 2.9 dB	± 2.9 dB
(Capacitive Voltage Probe) 150kHz – 30MHz	± 3.6 dB	± 3.9 dB
(Discontinuous) 150kHz – 30MHz	± 3.4 dB	± 3.4 dB
(Van Veen) 9kHz – 30MHz	± 3.3 dB	/
(Coupling Decoupling Network) 30MHz – 300MHz	± 3.5 dB	± 3.8 dB
(Splitter) 30MHz – 2.15GHz	± 3.4 dB	/
Radio frequency	± 1 x 10 ⁻⁷	± 1 x 10 ⁻⁷
Occupied bandwidth		
RF power	± 1.2 %	± 5 %
Radiated emission (magnetic field)		
9kHz – 30MHz	± 2.7 dB	± 6 dB
Supply voltages	± 3 %	± 3 %
Temperature	± 1 °C	± 1°C
Humidity	± 5 %	± 5 %
Time / Duty cycle	± 4.4 %	± 5 %
Radiated emission (electric field for FCC standard)		
9kHz – 30MHz	± 2.7 dB	/
30MHz – 1GHz	± 5.2 dB	/
1GHz – 18GHz	± 5.3 dB	/
18GHz – 26GHz	± 5.5 dB	/
26GHz – 40GHz	± 5.5 dB	/

For the calcul of expanded uncertainty, the confidence interval is 95 % (k=2).

6. TEST CONDITIONS AND RESULTS

6.1. Radiated spurious emissions <30MHz

Reference standard:	CFR 47 FCC part 15 and RSS-Gen
Test method:	15.209
Test description: : Spurious domain emission limits are limits on emissions at frequencies other than those of the carrier and sidebands associated with normal test modulation. EUT is set on an insulating support at 80cm above the ground reference plane. Preliminary (peak) measurements were performed at an antenna to EUT separation distance of 3-meter in a anechoic chamber. The EUT was rotated 360° in order to maximize radiated levels. Test antenna was oriented in 3 axes (0°, 45° and 90°). If necessary, final measurements (quasi-peak) are then performed in a 10-meter Open Area Test Site that complies to CISPR 16 in the same measurement conditions. All frequencies were investigated, where applicable.	

TESTED CONFIGURATION	PARAMETER	SEVERITY	RESULT TAB.	VERDICT
RNE_TX / 0°	9kHz-30MHz	Class Tx	EMI5797	PASS
RNE_TX / 45°	9kHz-30MHz	Class Tx	EMI5798	PASS
RNE_TX / 90°	9kHz-30MHz	Class Tx	EMI5799	PASS


LABORATORY PARAMETERS:	REQUIRED PRIOR TO THE TEST	DURING THE TEST
Ambient Temperature	15 to 35 °C	See Graph(es)
Relative Humidity	20 to 75 %	See Graph(es)
Atmospheric pressure	N/A	See Graph(es)
Test method deviation: N/A		
Supplementary information: limit indicated on the curves is calculated with 40 dB/decade extrapolation factor and 51.5 dB conversion factor.		


TEST EQUIPMENT USED					
CATEGORY	BRAND	TYPE	IDENTIFIER	CAL. DATE	CAL. DUE
Antenna	Rohde & Schwarz	HFH2-Z2	5825	20/09/2017	20/11/2019
Cable	Huber Suhner	N-10m	8472	16/02/2017	16/04/2019
Cable	SUCOFLEX	N-3m	14378	18/01/2017	18/03/2019
Cable	SUCOFLEX	N-6,5m	14380	18/01/2017	18/03/2019
Receiver	Agilent Technologies	E4440A	5824	18/04/2018	18/06/2020
Shielded enclosure	COMTEST	SAC 3m	14494	14/02/2017	14/04/2020
Software	Nexio	BAT EMC v3.16.0.64	0000		
Thermohygrometer	Testo	608-H2	12268	27/11/2017	27/01/2020
Thermohygrometer	Bioblock Scientific	Météostar	0963	27/12/2016	27/02/2019
Turntable	Maturo	NCD	14657		

Blank cells = Permanent validity

TEST SETUP PHOTO(S) – RNE_TX / 0°







RADIATED SPURIOUS EMISSIONS <30MHz - GRAPH				
RNE_TX / 90°			EMI5797	
EUT mode:	The transmitter is modulated (OOK+GFSK) in continuous mode by an internal D-M3 data signal.		T (°C):	19.7
Test Date:	03/05/2018		H (%):	41.6
Test Operator:	MPA		P (hPa):	1009
FCC/FCC Part 15 §209 - Classe:Tx - Moyenne/3.0m/ FCC/FCC Part 15 §209 - Classe:Tx - QCrête/3.0m/ Mes. Peak 80 70 60 50 40 30 20 10 0 -10 -20 -30 -40 -50 9kHz <				

All unwanted radiated spurious (<30MHz) are at least 20 dB below specified limits.

6.2. Radiated spurious emissions >30MHz

Reference standard:	CFR 47 FCC part 15 and RSS-Gen
Test method:	15.209
Test description: : Test is done in fully anechoic shielded chamber at 3m. E.U.T. is set on a styrofoam table. Measurements are done in max-hold peak detection in hopping mode maximized at 360°.	

TESTED CONFIGURATION	PARAMETER	SEVERITY	RESULT TAB.	VERDICT
RNE / Tx mode / SLIM+ / OOK	30MHz-6GHz	Class Tx	EMI5797	PASS
RNE / Tx mode / SLIM+ / GFSK	30MHz-6GHz	Class Tx	EMI5797	PASS

LABORATORY PARAMETERS:	REQUIRED PRIOR TO THE TEST	DURING THE TEST
Ambient Temperature	15 to 35 °C	See Graph(es)
Relative Humidity	20 to 75 %	See Graph(es)
Atmospheric pressure	N/A	See Graph(es)
Test method deviation: N/A		
Supplementary information: N/A		

TEST EQUIPMENT USED					
CATEGORY	BRAND	TYPE	IDENTIFIER	CAL. DATE	CAL. DUE
Antenna	ETS-Lindgren	3117	5456	16/03/2016	16/05/2019
Antenna	Electro Metrics	BIA-30HF	0824	25/04/2015	25/06/2018
Antenna	Rohde & Schwarz	HL223	3126	25/04/2015	25/06/2018
Cable	TechniWAVE	N-0.23m	14894	23/02/2018	23/04/2020
Cable	TechniWAVE	N-0.23m	14896	23/02/2018	23/04/2020
Cable	STORM MICROWAVE	N-0.2m	10265	05/10/2016	05/12/2018
Cable	Huber Suhner	N-10m	8472	16/02/2017	16/04/2019
Cable	SUCOFLEX	N-3m	14379	18/01/2017	18/03/2019
Cable	SUCOFLEX	N-6,5m	14380	18/01/2017	18/03/2019
Filter	Micro-Tronics	HPM 11630	4392	05/10/2016	05/12/2018
Preamplifier	IMPULSE	CA118-546ACN	9169	13/10/2017	13/12/2018
Receiver	Agilent Technologies	E4440A	5824	18/04/2018	18/06/2020
Shielded enclosure	COMTEST	SAC 3m	14494	14/02/2017	14/04/2020
Software	Nexio	BAT EMC v3.6.0.32	0000		
Antenna mast	Maturo	NCD	14656		
Turntable	Maturo	NCD	14657		
Thermohygrometer	Testo	608-H1	12269	27/12/2016	27/02/2019
Thermohygrometer	Bioblock Scientific	Météostar	0963	27/12/2016	27/02/2019

Blank cells = Permanent validity

TEST SETUP PHOTO(S) -





TEST SETUP PHOTO(S) -



TEST SETUP PHOTO(S) -







6.3. Radiated field strength of fundamental

Reference standard:	CFR 47 FCC part 15 and RSS-210
Test method:	15.231
Test description: : Test is done in fully anechoic shielded chamber at 3m. E.U.T. is set on a styrofoam table. Measurements are done in max-hold peak detection in hopping mode maximized at 360°.	

TESTED CONFIGURATION	PARAMETER	SEVERITY	RESULT TAB.	VERDICT
Tx / Vertical	100kHz	(b)	EMI5797	PASS
Tx / Horizontal	100kHz	(b)	EMI5798	PASS
Deactivate time	N/A	(a)(1)	EMI5799	PASS

LABORATORY PARAMETERS:	REQUIRED PRIOR TO THE TEST	DURING THE TEST
Ambient Temperature	15 to 35 °C	See Graph(es)
Relative Humidity	20 to 75 %	See Graph(es)
Atmospheric pressure	N/A	See Graph(es)
Test method deviation: N/A		
Supplementary information: N/A		

TEST EQUIPMENT USED					
CATEGORY	BRAND	TYPE	IDENTIFIER	CAL. DATE	CAL. DUE
Antenna	Rohde & Schwarz	HFH2-Z2	5825	20/09/2017	20/11/2019
Cable	Huber Suhner	N-10m	8472	16/02/2017	16/04/2019
Cable	SUCOFLEX	N-3m	14378	18/01/2017	18/03/2019
Cable	SUCOFLEX	N-6,5m	14380	18/01/2017	18/03/2019
Receiver	Agilent Technologies	E4440A	5824	18/04/2018	18/06/2020
Shielded enclosure	COMTEST	SAC 3m	14494	14/02/2017	14/04/2020
Software	Nexio	BAT EMC v3.16.0.64	0000		
Thermohygrometer	Testo	608-H2	12268	27/11/2017	27/01/2020
Thermohygrometer	Bioblock Scientific	Météostar	0963	27/12/2016	27/02/2019
Turntable	Maturo	NCD	14657		

Blank cells = Permanent validity

TEST SETUP PHOTO(S) -

RADIATED FIELD STRENGTH OF FUNDAMENTAL - GRAPH

RNE / Tx MODE / SLIM+ / OOK				EMI5797	
EUT mode:	The transmitter is modulated (OOK) in continuous mode.			T (°C):	19.7
Test Date:	03/05/2018			H (%):	41.6
Test Operator:	MPA			P (hPa):	1009
POSITION	FREQUENCIES	QUASI PEAK LEVEL	LIMIT		
Vertical	433.92 MHz	6,026 μV/m	10,997 μV/m		
Horizontal	433.92 MHz	8,710 μV/m	10,997 μV/m		
Configuration:	Measurements maximized at 360°				
Comments:	N/A				
EUT modification(s): N/A					

RADIATED FIELD STRENGTH OF FUNDAMENTAL - GRAPH

RNE / Tx MODE / SLIM+ / GFSK				EMI5797	
EUT mode:	The transmitter is modulated (GFSK) in continuous mode.			T (°C):	19.7
Test Date:	03/05/2018			H (%):	41.6
Test Operator:	MPA			P (hPa):	1009
POSITION	FREQUENCIES	QUASI PEAK LEVEL	LIMIT		
Vertical	433.92 MHz	5,957 μV/m	10,997 μV/m		
Horizontal	433.92 MHz	8,610 μV/m	10,997 μV/m		
Configuration:	Measurements maximized at 360°				
Comments:	N/A				
EUT modification(s): N/A					

6.4. Occupied Bandwidth 99% & 20 dB Bandwidth

Reference standard:	RSS-Gen § 6.7
Test method:	RSS-Gen § 6.7
General test setup: A near field probe detects field near equipment (relative measurement). The 99 % OBW function is used .	

TESTED	FREQUENCY	SEVERITY	RESULT TAB.	VERDICT
OBW 99%	433.92 MHz	NA	EMI5756	PASS
-20 dB Bandwidth	433.92 MHz	NA	EMI5797	PASS

LABORATORY PARAMETERS:	REQUIRED PRIOR TO THE TEST	DURING THE TEST
Ambient Temperature	15 to 35 °C	20.1 °C
Relative Humidity	20 to 75 %	42.5%
Atmospheric pressure	N/A	1015 hPa
Test method deviation: N/A		
Supplementary information: N/A		

TEST EQUIPMENT USED					
CATEGORY	BRAND	TYPE	IDENTIFIER	CAL. DATE	CAL. DUE
Attenuator	Radiall	R412720124	4391	01/02/2018	01/04/2020
Cable	MICRO-COAX	N-3m	10536	12/10/2017	12/12/2019
Cable	C&C	N-3m	14332	15/12/2016	15/02/2019
Cable	C&C	N-3m	14333	15/12/2016	15/02/2019
Climatic enclosure	Heraeus	UT6060	2116		
Multimeter	Agilent Technologies	U1252A	6138	24/01/2018	24/03/2020
Power supply	TTi	PL303QMD	8496		
Receiver	Agilent Technologies	E4440A	5824	18/04/2018	18/06/2020
Software	Nexio	BAT EMC v3.6.0.32	0000		
Thermohygrometer	Testo	608-H2	12268	27/11/2017	27/01/2020
Thermohygrometer	Bioblock Scientific	Météostar	0963	27/12/2016	27/02/2019


Blank cells = Permanent validity

OCCUPIED BANDWIDTH 99% - GRAPH	
OBW / SLIM+ / OOK	
EMI5756	
EUT mode:	D-M2 (OOK)
Test Date:	14/05/2018
Test Operator:	MPA


Agilent 15:17:52 May 14, 2018		R	T	Span
Ch Freq 433.919 MHz		Trig Free		Span 50.0000000 kHz
Occupied Bandwidth				Span Zoom
Mkr1 433.919 01 MHz				Full Span
Ref 0 dBm		Atten 10 dB		Zero Span
#Peak				Last Span
Log				
10 dB/				
Center 433.919 01 MHz		Span 50 kHz		
#Res BW 300 Hz		VBW 910 Hz		
Sweep 530.5 ms (601 pts)				
Occupied Bandwidth		Occ BW % Pwr 99.00 %		
18.6029 kHz		x dB -26.00 dB		
Transmit Freq Error 17.324 Hz				
x dB Bandwidth 13.796 kHz				
Copyright 2000-2012 Agilent Technologies				

EUT modification(s): N/A


PERMITTED RANGE OF OPERATING FREQUENCIES - TABULATED RESULTS			
OBW / SLIM+ / OOK			EMI5756
Center Frequency	RBW	OCCUPIED BANDWIDTH 99%	N/A
433.919 MHz	300 Hz	18.6029 kHz	N/A



PERMITTED RANGE OF OPERATING FREQUENCIES - TABULATED RESULTS			
OBW / SLIM+ / GFSK			EMI5756
Center Frequency	RBW	OCCUPIED BANDWIDTH 99%	N/A
433.92 MHz	3 kHz	95.5296 kHz	N/A



PERMITTED RANGE OF OPERATING FREQUENCIES - TABULATED RESULTS			
20dB / SLIM+ / OOK			EMI5797
Center Frequency	RBW	20DB BANDWIDTH	N/A
433.92 MHz	300 Hz	8.34 kHz	N/A



PERMITTED RANGE OF OPERATING FREQUENCIES - TABULATED RESULTS			
20dB / SLIM+ / GFSK			EMI5797
Center Frequency	RBW	20DB BANDWIDTH	N/A
433.92 MHz	3 kHz	100.5 kHz	N/A

End of test report