



**CFR 47 FCC PART 15 SUBPART C  
ISED RSS-247 ISSUE 2**

**CERTIFICATION TEST REPORT**

*For*

**Jobsite Radio with Bluetooth**

**MODEL NUMBER: GPB18V-2C**

**FCC ID: TXTGPB18V-2C**

**IC: 909H-GPB18V2C**

**REPORT NUMBER: 4789384986-2**

**ISSUE DATE: March 27, 2020**

*Prepared for*

**Robert Bosch Tool Corporation  
1800 West Central Road, Mount Prospect, IL, USA**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch  
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake  
Hi-Tech Development Zone Dongguan, People's Republic of China  
Tel: +86 769 22038881  
Fax: +86 769 33244054  
Website: [www.ul.com](http://www.ul.com)**

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification.



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V0	03/27/2020	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC/ISED Rules	Test Results
1	20dB Bandwidth and 99% Occupied Bandwidth	FCC 15.247 (a) (1) RSS-247 Clause 5.1 (a) RSS-Gen Clause 6.7	Pass
2	Conducted Output Power	FCC 15.247 (b) (1) RSS-247 Clause 5.1 (b)	Pass
3	Carrier Hopping Channel Separation	FCC 15.247 (a) (1) RSS-247 Clause 5.1 (b)	Pass
4	Number of Hopping Frequency	15.247 (a) (1) III RSS-247 Clause 5.1 (d)	Pass
5	Time of Occupancy (Dwell Time)	15.247 (a) (1) III RSS-247 Clause 5.1 (d)	Pass
6	Conducted Bandedge	FCC 15.247 (d) RSS-247 Clause 5.5	Pass
7	Radiated Bandedge and Spurious	FCC 15.247 (d) FCC 15.209 FCC 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 8.9 RSS-GEN Clause 8.10	Pass
8	Conducted Emission Test For AC Power Port	FCC 15.207 RSS-GEN Clause 8.8	Pass
9	Antenna Requirement	FCC 15.203 RSS-GEN Clause 6.8	Pass
This test report is only published to and used by the applicant, and it is not for evidence purpose in China			



## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS.....</b>	<b>6</b>
<b>2. TEST METHODOLOGY .....</b>	<b>7</b>
<b>3. FACILITIES AND ACCREDITATION.....</b>	<b>7</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>8</b>
4.1. MEASURING INSTRUMENT CALIBRATION .....	8
4.2. MEASUREMENT UNCERTAINTY .....	8
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>9</b>
5.1. DESCRIPTION OF EUT .....	9
5.2. MAXIMUM OUTPUT POWER.....	9
5.3. PACKET TYPE CONFIGURATION.....	9
5.4. CHANNEL LIST.....	10
5.5. TEST CHANNEL CONFIGURATION .....	10
5.6. THE WORSE CASE POWER SETTING PARAMETER.....	10
5.7. DESCRIPTION OF AVAILABLE ANTENNAS .....	11
5.8. WORST-CASE CONFIGURATIONS.....	11
5.9. TEST ENVIRONMENT .....	11
5.10. DESCRIPTION OF TEST SETUP.....	12
5.11. MEASURING INSTRUMENT AND SOFTWARE USED .....	13
<b>6. ANTENNA PORT TEST RESULTS .....</b>	<b>15</b>
6.1. ON TIME AND DUTY CYCLE .....	15
6.2. 20dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....	17
6.2.1. GFSK MODE .....	18
6.2.2. 8DPSK MODE .....	22
6.3. CONDUCTED OUTPUT POWER .....	26
6.3.1. GFSK MODE .....	27
6.3.2. 8DPSK MODE .....	27
6.4. CARRIER HOPPING CHANNEL SEPARATION.....	28
6.4.1. GFSK MODE .....	29
6.4.2. 8DPSK MODE .....	30
6.5. NUMBER OF HOPPING FREQUENCY .....	31
6.5.1. GFSK MODE .....	32
6.5.2. 8DPSK MODE .....	33
6.6. TIME OF OCCUPANCY (DWELL TIME).....	34
6.6.1. GFSK MODE .....	35



6.6.2.	8DPSK MODE .....	38
6.7.	CONDUCTED SPURIOUS EMISSION .....	40
6.6.3.	GFSK MODE .....	41
6.6.4.	8DPSK MODE .....	48
<b>7.</b>	<b>RADIATED TEST RESULTS .....</b>	<b>55</b>
7.1.	LIMITS AND PROCEDURE .....	55
7.2.	RESTRICTED BANDEDGE .....	60
7.2.1.	GFSK MODE .....	60
7.2.2.	8DPSK MODE .....	64
7.3.	SPURIOUS EMISSIONS (1~3GHz) .....	68
7.3.1.	GFSK MODE .....	68
7.3.2.	8DPSK MODE .....	74
7.4.	SPURIOUS EMISSIONS (3~18GHz) .....	80
7.4.1.	GFSK MODE .....	80
7.4.2.	8DPSK MODE .....	86
7.5.	SPURIOUS EMISSIONS 18G ~ 26GHz.....	92
7.5.1.	GFSK MODE .....	92
7.6.	SPURIOUS EMISSIONS 30M ~ 1 GHz.....	94
7.6.1.	GFSK MODE .....	94
7.7.	SPURIOUS EMISSIONS BELOW 30M.....	96
7.7.1.	GFSK MODE .....	96
<b>8.</b>	<b>AC POWER LINE CONDUCTED EMISSIONS .....</b>	<b>99</b>
8.1.1.	8DPSK MODE .....	100
<b>9.</b>	<b>ANTENNA REQUIREMENTS .....</b>	<b>102</b>



## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

Company Name: Robert Bosch Tool Corporation  
Address: 1800 West Central Road, Mount Prospect, IL, USA

### Manufacturer Information

Company Name: Da Chang Industries Co., Ltd  
Address: JinBei Road, Chang Ping Town, Dong Guan City, Guangdong Province Dong Guan China

### EUT Description

EUT Name: Jobsite Radio with Bluetooth  
Model: GPB18V-2C  
Brand: BOSCH  
Sample Status: Normal  
Sample ID: 2903381  
Sample Received date: Feb 24, 2020  
Date Tested: March 02, 2020~ March 06, 2020

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS
ISED RSS-247 Issue 2	PASS
ISED RSS-GEN Issue 5	PASS

Prepared By:

Kebo Zhang  
Project Engineer

Checked By:

Shawn Wen  
Laboratory Leader

Approved By:

Stephen Guo  
Laboratory Manager



## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part2, CFR 47 FCC Part 15, ANSI C63.10-2013, ISED RSS-247 Issue 2 and ISED RSS-GEN Issue 5.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>ISED(Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	---

Note:

1. All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China.
2. The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.
3. For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62dB
Radiation Emission test(include Fundamental emission) (9kHz-30MHz)	2.2dB
Radiation Emission test(include Fundamental emission) (30MHz-1GHz)	4.00dB
Radiation Emission test (1GHz to 26GHz)( include Fundamental emission)	5.78dB (1GHz-18GHz)
	5.23dB (18GHz-26GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

EUT Name	Jobsite Radio with Bluetooth				
Model	GPB18V-2C				
Product Description	Operation Frequency		2402 MHz ~ 2480 MHz		
	Modulation Type		Data Rate		
	GFSK		1Mbps		
	π/4-DQPSK		2Mbps		
	8DPSK		3Mbps		
Bluetooth version	BT5.0				
Supply Voltage	<input type="checkbox"/> AC mains State	NA			
	<input checked="" type="checkbox"/> DC State	<input type="checkbox"/> Internal Power Supply	NA		
		<input checked="" type="checkbox"/> External Power Supply or AC/DC adapter	Rate Input:	AC100-240V, 50/60Hz, 800mA	
			Rate Output:	DC 18V, 1800mA	
		<input checked="" type="checkbox"/> Battery	DC 18V		

### 5.2. MAXIMUM OUTPUT POWER

Bluetooth Mode	Frequency (MHz)	Channel Number	Max PEAK Output Power (dBm)	EIRP (dBm)
GFSK	2402-2480	0-78[79]	7.558	9.558
8DPSK	2402-2480	0-78[79]	6.063	8.063

### 5.3. PACKET TYPE CONFIGURATION

Bluetooth Mode	Packet Type	Setting (Packet Length)
GFSK	DH1	27
	DH3	183
	DH5	339
π/4-DQPSK	2-DH1	54
	2-DH3	367
	2-DH5	679
8DPSK	3-DH1	83
	3-DH3	552
	3-DH5	1021



#### 5.4. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	/	/

#### 5.5. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
GFSK-DH5	CH 0(Low Channel), CH 39(MID Channel), CH 78(High Channel)	2402MHz, 2441MHz, 2480MHz
8DPSK-3DH5	CH 0(Low Channel), CH 39(MID Channel), CH 78(High Channel)	2402MHz, 2441MHz, 2480MHz
GFSK-DH5	Hopping	2402MHz ~ 2480MHz
8DPSK-3DH5	Hopping	2402MHz ~ 2480MHz

#### 5.6. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software		Bluetooth test 3		
Modulation Type	Transmit Antenna Number	Test Channel		
		CH 00	CH 39	CH 78
GFSK	1	Default	Default	Default
8DPSK	1	Default	Default	Default



## 5.7. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2402-2480	PCB Antenna	2.0

Modulation	Transmit and Receive Mode	Description
GFSK	☒1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
π/4-DQPSK	☒1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
8DPSK	☒1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.

## 5.8. WORST-CASE CONFIGURATIONS

Bluetooth Mode	Modulation Technology	Modulation Type	Data Rate (Mbps)
BR	FHSS	GFSK	1Mbit/s
EDR	FHSS	8DPSK	3Mbit/s

Note: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates.

## 5.9. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests	
Relative Humidity	45 ~ 70%	
Atmospheric Pressure:	1025Pa	
Temperature	TN	22 ~ 28 °C
Voltage:	VL	N/A
	VN	AC 120V,60Hz
	VH	N/A

Note: VL= Lower Extreme Test Voltage  
VN= Nominal Voltage.  
VH= Upper Extreme Test Voltage  
TN= Normal Temperature



## 5.10. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	PC	Dell	Vostro 3902	8KNDDDB2
2	USB Debugger	/	/	/
3	Mobile Phone	HUAWEI	ALP-AL00	/
4	Dummy load	/	/	5 Vdc,1.2 A

### I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	/	/	1.0	/
2	AUX	/	/	1.0	/


### ACCESSORY

Item	Accessory	Brand Name	Model Name	Description
1	Switching Power Supply	BOSCH	1619pb4882	Input: AC 100-240V 50/60Hz 800mA

### TEST SETUP

The EUT can work in an engineer mode with software.

### SETUP DIAGRAM FOR TESTS





### 5.11. MEASURING INSTRUMENT AND SOFTWARE USED

Conducted Emissions						
Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	EMI Test Receiver	R&S	ESR3	101961	Dec.05,2019	Dec.05,2020
<input checked="" type="checkbox"/>	Two-Line V- Network	R&S	ENV216	101983	Dec.05,2019	Dec.05,2020
<input checked="" type="checkbox"/>	Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Dec.05,2019	Dec.05,2020
Software						
Used	Description		Manufacturer	Name		Version
<input checked="" type="checkbox"/>	Test Software for Conducted disturbance		Farad	EZ-EMC		Ver. UL-3A1
Radiated Emissions						
Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	MXE EMI Receiver	KESIGHT	N9038A	MY56400 036	Dec.06,2019	Dec.06,2020
<input checked="" type="checkbox"/>	Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Sep.17, 2018	Sep.17, 2021
<input checked="" type="checkbox"/>	Preamplifier	HP	8447D	2944A090 99	Dec.05,2019	Dec.05,2020
<input checked="" type="checkbox"/>	EMI Measurement Receiver	R&S	ESR26	101377	Dec.05,2019	Dec.05,2020
<input checked="" type="checkbox"/>	Horn Antenna	TDK	HRN-0118	130939	Sep.17, 2018	Sep.17, 2021
<input checked="" type="checkbox"/>	High Gain Horn Antenna	Schwarzbeck	BBHA-9170	691	Aug.11, 2018	Aug.11, 2021
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-0118	TRS-305- 00066	Dec.05,2019	Dec.05,2020
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-2	TRS-307- 00003	Dec.05,2019	Dec.05,2020
<input checked="" type="checkbox"/>	Loop antenna	Schwarzbeck	1519B	00008	Jan.07, 2019	Jan.07, 2022
<input checked="" type="checkbox"/>	Band Reject Filter	Wainwright	WRCJV8- 2350-2400- 2483.5- 2533.5-40SS	4	Dec.05,2019	Dec.05,2020
<input checked="" type="checkbox"/>	High Pass Filter	Wi	WHKX10- 2700-3000- 18000-40SS	23	Dec.05,2019	Dec.05,2020
Software						
Used	Description		Manufacturer	Name		Version
<input checked="" type="checkbox"/>	Test Software for Radiated disturbance		Farad	EZ-EMC		Ver. UL-3A1
Other instruments						



Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9030A	MY55410512	Dec.06,2019	Dec.06,2020
<input checked="" type="checkbox"/>	Power Meter	Keysight	N1911A	MY55416024	Dec.06,2019	Dec.06,2020
<input checked="" type="checkbox"/>	Power Sensor	Keysight	U2021XA	MY5100022	Dec.06,2019	Dec.06,2020




## 6. ANTENNA PORT TEST RESULTS

### 6.1. ON TIME AND DUTY CYCLE

#### LIMITS

None; for reporting purposes only

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	26.2°C	Relative Humidity	55%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V,60Hz

#### RESULTS

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
GFSK	1.680	2.505	0.67	67%	1.74	0.6	1
8DPSK	1.680	2.505	0.67	67%	1.74	0.6	1



Note:

Duty Cycle Correction Factor=10log (1/x).

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.





## 6.2. 20dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

### LIMITS

CFR 47FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (a) (1) RSS-247 Clause 5.1 (a)	20dB Occupied Bandwidth	/	2400-2483.5
ISED RSS-Gen Clause 6.7	99% Occupied Bandwidth	/	2400-2483.5


### TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	For 20dB:Occupied Bandwidth:1% to 5% of the 20 dB bandwidth For 99%:Occupied Bandwidth: 1% to 5% of the occupied bandwidth
VBW	approximately three times RBW
Span	For 20dB: between 2 times and 5 times the OBW. For 99dB: between 1.5 times and 5.0 times the OBW.
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB and 99% relative to the maximum level measured in the fundamental emission.

### TEST SETUP





## TEST ENVIRONMENT


Temperature	26.2°C	Relative Humidity	55%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V,60Hz



## RESULTS



### 6.2.1. GFSK MODE


Channel	Frequency (MHz)	20dB Occupied bandwidth (MHz)	99% Occupied bandwidth (MHz)	Result
Low	2402	0.9391	0.86332	PASS
Middle	2441	0.9386	0.86363	PASS
High	2480	0.9405	0.86247	PASS

## Test Graph

















### 6.2.2. 8DPSK MODE

Channel	Frequency (MHz)	20dB Occupied bandwidth (MHz)	99% Occupied bandwidth (MHz)	Result
Low	2402	1.252	1.1686	PASS
Middle	2441	1.252	1.1683	PASS
High	2480	1.251	1.1666	PASS











### 6.3. CONDUCTED OUTPUT POWER

#### LIMITS

CFR 47 FCC Part15 (15.247) , Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (b) (1) ISED RSS-247 Clause 5.4 (b)	Peak Conducted Output Power	Hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel : 1 watt or 30dBm; Hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel : 125 mW or 21dBm	2400-2483.5


#### TEST PROCEDURE

Place the EUT on the table and set it in the transmitting mode.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power sensor.

Measure peak power of each channel.

#### TEST SETUP





## **TEST ENVIRONMENT**

Temperature	26.2°C	Relative Humidity	55%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V,60Hz

## **RESULTS**

### **6.3.1. GFSK MODE**

Channel	Frequency	Maximum Conducted Output Power(PK)	EIRP	Limit	Result
	(MHz)	(dBm)	(dBm)	(dBm)	
Low	2402	6.341	8.341	30	Pass
Middle	2441	7.558	9.558	30	Pass
High	2480	6.500	8.500	30	Pass

Note: EIRP= Maximum Conducted Output Power + Antenna Gain

Note: The channel separation is 1MHz and the 20dB Bandwidth is less than 1MHz.

### **6.3.2. 8DPSK MODE**

Channel	Frequency	Maximum Conducted Output Power(PK)	EIRP	Limit	Result
	(MHz)	(dBm)	(dBm)	(dBm)	
Low	2402	4.763	6.763	21	Pass
Middle	2441	6.063	8.063	21	Pass
High	2480	4.878	6.878	21	Pass

Note: EIRP= Maximum Conducted Output Power + Antenna Gain

Note: The channel separation is 1MHz and the 20dB Bandwidth is bigger than 1MHz.



## 6.4. CARRIER HOPPING CHANNEL SEPARATION

### LIMITS

CFR 47 FCC Part15 (15.247) , Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (a) (1) ISED RSS-247 Clause 5.1 (b)	Carrier Hopping Channel Separation	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel.	2400-2483.5

### TEST PROCEDURE

Connect the UUT to the spectrum Analyzer and use the following settings:


Center Frequency	The center frequency of the channel under test
Span	wide enough to capture the peaks of two adjacent channels
Detector	Peak
RBW	Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
VBW	$\geq$ RBW
Trace	Max hold
Sweep time	Auto couple

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Compliance of an EUT with the appropriate regulatory limit shall be determined.

A plot of the data shall be included in the test report.

### TEST SETUP






## TEST ENVIRONMENT

Temperature	26.2°C	Relative Humidity	55%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V,60Hz

## RESULTS

### 6.4.1. GFSK MODE


Channel	Carrier Hopping Channel Separation (MHz)	Limit (MHz)	Result
Middle	1.005	≥ 20 dB Bandwidth Of The Hopping Channel	PASS



Note: For 20 dB Bandwidth of The Hopping Channel, please refer to clause 6.2.

### 6.4.2. 8DPSK MODE

Channel	Carrier Hopping Channel Separation (MHz)	Limit (MHz)	Result
Middle	1.005	≥ two-thirds of the 20 dB Bandwidth Of The Hopping Channel	PASS



Note: For 20 dB Bandwidth of The Hopping Channel, please refer to clause 6.2.



## 6.5. NUMBER OF HOPPING FREQUENCY

### LIMITS

CFR 47 FCC Part15 (15.247) , Subpart C ISED RSS-247 ISSUE 2		
Section	Test Item	Limit
CFR 47 15.247 (a) (1) III ISED RSS-247 Clause 5.1 (d)	Number of Hopping Frequency	at least 15 hopping channels

### TEST PROCEDURE

Connect the EUT to the spectrum Analyzer and use the following settings:

Detector	Peak
RBW	To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
VBW	≥RBW
Span	The frequency band of operation
Trace	Max hold
Sweep time	Auto couple


Set EUT to transmit maximum output power and switch on frequency hopping function. then set enough count time (larger than 5000 times) to get all the hopping frequency channel displayed on the screen of spectrum analyzer.

Count the quantity of peaks to get the number of hopping channels.

FHSS Mode: 79 Channels observed.

AFHSS Mode: 20 Channels declared.

### TEST SETUP



### TEST ENVIRONMENT


Temperature	26.2°C	Relative Humidity	55%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V,60Hz



## RESULTS

### 6.5.1. GFSK MODE

Hopping numbers	Limit	Results
79	$\geq 15$	Pass





### 6.5.2. 8DPSK MODE

Hopping numbers	Limit	Results
79	$\geq 15$	Pass



## 6.6. TIME OF OCCUPANCY (DWELL TIME)

### LIMITS

CFR 47 FCC Part15 (15.247) , Subpart C ISED RSS-247 ISSUE 2		
Section	Test Item	Limit
CFR 47 15.247 (a) (1) III ISED RSS-247 Clause 5.1 (d)	Time of Occupancy (Dwell Time)	The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed.

### TEST PROCEDURE

Connect the UUT to the spectrum Analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	1MHz
VBW	≥RBW
Span	zero span
Trace	Clear Write
Sweep time	As necessary to capture the entire dwell time per hopping channel

- The transmitter output (antenna port) was connected to the spectrum analyzer
- Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for DH5, DH3 and DH1 packet transmitting.
- Measure the maximum time duration of one single pulse.  
 $A \text{ Period Time} = (\text{channel number}) \times 0.4$

For FHSS Mode (79 Channel):


DH1 Time Slot: Reading \* (1600/2)\*31.6/(channel number)  
DH3 Time Slot: Reading \* (1600/4)\*31.6/(channel number)  
DH5 Time Slot: Reading \* (1600/6)\*31.6/(channel number)

For AFHSS Mode (20 Channel):

DH1 Time Slot: Reading \* (800/2)\*8/(channel number)  
DH3 Time Slot: Reading \* (800/4)\*8/(channel number)  
DH5 Time Slot: Reading \* (800/6)\*8/(channel number)



## TEST SETUP



## TEST ENVIRONMENT

Temperature	26.2°C	Relative Humidity	55%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V,60Hz



## RESULTS


### 6.6.1. GFSK MODE

FHSS Mode				
Packet	Channel	Burst Width [ms/hop/ch]	Dwell Time [s]	Results
DH1	MCH	0.435	0.1392	PASS
DH3	MCH	1.680	0.2688	PASS
DH5	MCH	2.925	0.3120	PASS
AFHSS Mode				
DH1	MCH	0.435	0.0696	PASS
DH3	MCH	1.680	0.1344	PASS
DH5	MCH	2.925	0.1560	PASS



## Test Graph










## 6.6.2. 8DPSK MODE

FHSS Mode				
Packet	Channel	Burst Width [ms/hop/ch]	Dwell Time [s]	Results
3DH1	MCH	0.420	0.1344	PASS
3DH3	MCH	1.680	0.2688	PASS
3DH5	MCH	2.940	0.3136	PASS
AFHSS Mode				
3DH1	MCH	0.420	0.0672	PASS
3DH3	MCH	1.680	0.1344	PASS
3DH5	MCH	2.940	0.1568	PASS

## Test Graph







## 6.7. CONDUCTED SPURIOUS EMISSION

### LIMITS

CFR 47 FCC Part15 (15.247) , Subpart C ISED RSS-247 ISSUE 2		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d) ISED RSS-247 5.5	Conducted Spurious Emission	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### TEST PROCEDURE

For Bandedge use the following settings:


Detector	Peak
RBW	100kHz
VBW	300kHz
Span	wide enough to fully capture the emission being measured
Trace	Max hold
Sweep time	Auto couple.

For Spurious Emission use the following settings:

Detector	Peak
RBW	100kHz
VBW	300kHz
Span	wide enough to fully capture the emission being measured
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum amplitude level.

### TEST SETUP



### TEST ENVIRONMENT


Temperature	26.2°C	Relative Humidity	55%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V,60Hz




## RESULTS

### 6.6.3. GFSK MODE

#### LOW CH BANDEDGE




#### LOW CH REFERENCE LEVER






### LOW CH SPURIOUS EMISSIONS 30MHz-10GHz




### LOW CH SPURIOUS EMISSIONS 10-26GHz






### MID CH REFERENCE LEVER




### MID CH SPURIOUS EMISSIONS 30MHz-10GHz






### MID CH SPURIOUS EMISSIONS 10-26GHz




### HIGH CH BANDEDGE






### HIGH CH REFERENCE LEVER




### HIGH CH SPURIOUS EMISSIONS 30MHz-10GHz






### HIGH CH SPURIOUS EMISSIONS 10-26GHz






## SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON

### LOW CH BANDEDGE WITH HOPPING ON




### HIGH CH BANDEDGE WITH HOPPING ON






## 6.6.4. 8DPSK MODE

### LOW CH BANDEDGE




### LOW CH REFERENCE LEVER






### LOW CH SPURIOUS EMISSIONS 30MHz-10GHz




### LOW CH SPURIOUS EMISSIONS 10-26GHz






### MID CH REFERENCE LEVER




### MID CH SPURIOUS EMISSIONS 30MHz-10GHz






### MID CH SPURIOUS EMISSIONS 10-26GHz




### HIGH CH BANDEDGE






### HIGH CH REFERENCE LEVER




### HIGH CH SPURIOUS EMISSIONS 30MHz-10GHz






### HIGH CH SPURIOUS EMISSIONS 10-26GHz






## SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON

### LOW CH BANDEDGE WITH HOPPING ON



### HIGH CH BANDEDGE WITH HOPPING ON





## 7. RADIATED TEST RESULTS

### 7.1. LIMITS AND PROCEDURE

#### LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209

Please refer to ISSED RSS-GEN Clause 8.9 and Clause 8.10

Radiation Disturbance Test Limit for FCC (Class B)(9kHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.


Radiation Disturbance Test Limit for FCC (Above 1G)

Frequency (MHz)	dB(uV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54

About Restricted bands of operation please refer to RSS-Gen section 8.10 and FCC §15.205 (a)

## TEST SETUP AND PROCEDURE

### Below 30MHz




The setting of the spectrum Analyzer

RBW	200Hz (From 9kHz to 0.15MHz)/ 9kHz (From 0.15MHz to 30MHz)
VBW	200Hz (From 9kHz to 0.15MHz)/ 9kHz (From 0.15MHz to 30MHz)
Sweep	Auto
Detector	Peak/QP/ Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30m OFS. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Below 1G and above 30MHz




The setting of the spectrum Analyzer

RBW	120kHz
VBW	300kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1G



RBW	1M
VBW	PEAK: 3MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 150cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector. For the Duty Cycle please refer to clause 6.1.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

### **TEST ENVIRONMENT**


Temperature	23.1°C	Relative Humidity	57%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V,60Hz



## 7.2. RESTRICTED BANDEDGE

### 7.2.1. GFSK MODE

#### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2383.715	16.53	32.92	49.45	74.00	-24.55	peak
2	2390.000	15.18	32.94	48.12	74.00	-25.88	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2380.380	16.63	32.91	49.54	74.00	-24.46	peak
2	2390.000	15.20	32.94	48.14	74.00	-25.86	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2.If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3.Peak: Peak detector.

4.Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)**

**PEAK**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	17.37	33.58	50.95	74.00	-23.05	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2.If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3.Peak: Peak detector.  
4.Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**

**PEAK**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	16.28	33.58	49.86	74.00	-24.14	peak
2	2488.025	17.18	33.62	50.80	74.00	-23.20	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2.If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3.Peak: Peak detector.  
4.Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



## 7.2.2. 8DPSK MODE

### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2361.175	15.82	32.85	48.67	74.00	-25.33	peak
2	2390.000	13.94	32.94	46.88	74.00	-27.12	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2342.200	15.90	32.79	48.69	74.00	-25.31	peak
2	2390.000	14.24	32.94	47.18	74.00	-26.82	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)**

**PEAK**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	17.03	33.58	50.61	74.00	-23.39	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**

**PEAK**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	14.69	33.58	48.27	74.00	-25.73	peak
2	2486.975	16.55	33.61	50.16	74.00	-23.84	peak


- Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



### 7.3. SPURIOUS EMISSIONS (1~3GHz)

#### 7.3.1. GFSK MODE

##### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1060.000	49.37	-13.54	35.83	74.00	-38.17	peak
2	1242.000	48.22	-12.53	35.69	74.00	-38.31	peak
3	2402.000	53.77	-7.85	45.92	/	/	fundamental
4	2506.000	50.91	-7.20	43.71	74.00	-30.29	peak
5	2558.000	51.34	-7.47	43.87	74.00	-30.13	peak
6	2610.000	47.13	-7.64	39.49	74.00	-34.51	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1064.000	49.75	-13.54	36.21	74.00	-37.79	peak
2	1326.000	49.14	-12.35	36.79	74.00	-37.21	peak
3	1598.000	50.42	-11.42	39.00	74.00	-35.00	peak
4	2402.000	52.29	-7.85	44.44	/	/	fundamental
5	2506.000	51.45	-7.20	44.25	74.00	-29.75	peak
6	2558.000	52.09	-7.47	44.62	74.00	-29.38	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1062.000	49.01	-13.55	35.46	74.00	-38.54	peak
2	1630.000	45.99	-11.25	34.74	74.00	-39.26	peak
3	2132.000	47.63	-9.00	38.63	74.00	-35.37	peak
4	2441.000	52.60	-7.57	45.03	/	/	fundamental
5	2546.000	53.81	-7.41	46.40	74.00	-27.60	peak
6	2598.000	51.82	-7.69	44.13	74.00	-29.87	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1062.000	50.06	-13.55	36.51	74.00	-37.49	peak
2	1332.000	47.27	-12.35	34.92	74.00	-39.08	peak
3	1910.000	45.80	-9.93	35.87	74.00	-38.13	peak
4	2441.000	49.23	-7.57	41.66	/	/	fundamental
5	2520.000	47.71	-7.27	40.44	74.00	-33.56	peak
6	2768.000	43.87	-6.40	37.47	74.00	-36.53	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1064.000	49.19	-13.54	35.65	74.00	-38.35	peak
2	1254.000	46.84	-12.50	34.34	74.00	-39.66	peak
3	2126.000	47.18	-9.02	38.16	74.00	-35.84	peak
4	2480.000	56.82	-7.31	49.51	/	/	fundamental
5	2584.000	53.62	-7.62	46.00	74.00	-28.00	peak
6	2720.000	44.89	-6.92	37.97	74.00	-36.03	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1064.000	48.23	-13.54	34.69	74.00	-39.31	peak
2	1326.000	47.93	-12.35	35.58	74.00	-38.42	peak
3	1746.000	45.85	-10.45	35.40	74.00	-38.60	peak
4	2092.000	44.56	-9.20	35.36	74.00	-38.64	peak
5	2480.000	59.51	-7.31	52.20	/	/	fundamental
6	2784.000	43.56	-6.23	37.33	74.00	-36.67	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### 7.3.2. 8DPSK MODE

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1360.000	56.72	-12.36	44.36	74.00	-29.64	peak
2	1556.000	56.91	-11.76	45.15	74.00	-28.85	peak
3	1848.000	56.54	-9.93	46.61	74.00	-27.39	peak
4	2206.000	52.39	-8.64	43.75	74.00	-30.25	peak
5	2402.000	54.24	-7.85	46.39	/	/	fundamental
6	2506.000	50.55	-7.20	43.35	74.00	-30.65	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1328.000	51.10	-12.36	38.74	74.00	-35.26	peak
2	1592.000	49.86	-11.47	38.39	74.00	-35.61	peak
3	2402.000	52.92	-7.85	45.07	74.00	-28.93	peak
4	2558.000	50.58	-7.47	43.11	74.00	-30.89	peak
5	2664.000	49.44	-7.34	42.10	74.00	-31.90	peak
6	2996.000	56.03	-5.30	50.73	74.00	-23.27	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1062.000	50.58	-13.55	37.03	74.00	-36.97	peak
2	1328.000	49.46	-12.36	37.10	74.00	-36.90	peak
3	1600.000	50.94	-11.40	39.54	74.00	-34.46	peak
4	2130.000	47.34	-9.01	38.33	74.00	-35.67	peak
5	2441.000	46.16	-7.57	38.59	/	/	fundamental
6	2880.000	45.47	-5.62	39.85	74.00	-34.15	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1062.000	50.34	-13.55	36.79	74.00	-37.21	peak
2	1328.000	51.56	-12.36	39.20	74.00	-34.80	peak
3	1598.000	49.63	-11.42	38.21	74.00	-35.79	peak
4	2441.000	50.98	-7.57	43.41	/	/	fundamental
5	2546.000	53.66	-7.41	46.25	74.00	-27.75	peak
6	2660.000	48.80	-7.35	41.45	74.00	-32.55	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1062.000	51.80	-13.55	38.25	74.00	-35.75	peak
2	1594.000	48.97	-11.45	37.52	74.00	-36.48	peak
3	2130.000	47.15	-9.01	38.14	74.00	-35.86	peak
4	2480.000	57.68	-7.31	50.37	/	/	fundamental
5	2584.000	55.08	-7.62	47.46	74.00	-26.54	peak
6	2720.000	45.63	-6.92	38.71	74.00	-35.29	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1062.000	47.98	-13.55	34.43	74.00	-39.57	peak
2	1328.000	47.88	-12.36	35.52	74.00	-38.48	peak
3	1814.000	45.08	-9.93	35.15	74.00	-38.85	peak
4	2192.000	43.78	-8.70	35.08	74.00	-38.92	peak
5	2480.000	57.04	-7.31	49.73	/	/	fundamental
6	2782.000	44.04	-6.25	37.79	74.00	-36.21	peak


- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



## 7.4. SPURIOUS EMISSIONS (3~18GHz)

### 7.4.1. GFSK MODE

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4260.000	48.91	-1.71	47.20	74.00	-26.80	peak
2	4800.000	49.56	0.46	50.02	74.00	-23.98	peak
3	6375.000	42.28	4.22	46.50	74.00	-27.50	peak
4	7200.000	43.94	5.82	49.76	74.00	-24.24	peak
5	10545.000	37.96	11.64	49.60	74.00	-24.40	peak
6	13920.000	33.93	16.17	50.10	74.00	-23.90	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4245.000	53.54	-1.59	51.95	74.00	-22.05	peak
2	4800.000	47.50	0.46	47.96	74.00	-26.04	peak
3	6000.000	49.58	3.29	52.87	74.00	-21.13	peak
4	6390.000	49.14	4.28	53.42	74.00	-20.58	peak
5	7200.000	46.59	5.82	52.41	74.00	-21.59	peak
6	8505.000	45.05	7.41	52.46	74.00	-21.54	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4245.000	48.50	-1.59	46.91	74.00	-27.09	peak
2	4875.000	50.36	0.76	51.12	74.00	-22.88	peak
3	6375.000	41.95	4.22	46.17	74.00	-27.83	peak
4	7323.017	48.41	6.15	54.56	74.00	-19.44	peak
5	7323.017	45.72	6.15	51.87	54.00	-2.13	AVG
6	11505.000	36.16	13.42	49.58	74.00	-24.42	peak
7	17220.000	31.08	21.08	52.16	74.00	-21.84	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3690.000	49.69	-2.81	46.88	74.00	-27.12	peak
2	4245.000	51.29	-1.59	49.70	74.00	-24.30	peak
3	4875.000	48.65	0.76	49.41	74.00	-24.59	peak
4	6384.056	50.26	4.25	54.51	74.00	-19.49	peak
5	6384.056	25.60	4.25	29.85	54.00	-24.15	AVG
6	7323.018	50.75	6.15	56.90	74.00	-17.10	peak
7	7323.018	45.56	6.15	51.71	54.00	-2.29	AVG
8	8535.000	43.26	7.39	50.65	74.00	-23.35	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4245.000	47.51	-1.59	45.92	74.00	-28.08	peak
2	4950.000	51.27	1.13	52.40	74.00	-21.60	peak
3	6375.000	45.00	4.22	49.22	74.00	-24.78	peak
4	7440.000	49.96	6.32	56.28	74.00	-17.72	peak
5	7440.080	44.28	6.32	50.60	54.00	-3.40	AVG
6	11565.000	36.39	13.26	49.65	74.00	-24.35	peak
7	17595.000	30.45	21.77	52.22	74.00	-21.78	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4260.000	49.89	-1.71	48.18	74.00	-25.82	peak
2	4950.000	49.47	1.13	50.60	74.00	-23.40	peak
3	6000.000	48.61	3.29	51.90	74.00	-22.10	peak
4	6390.000	47.57	4.28	51.85	74.00	-22.15	peak
5	7440.080	50.44	6.32	56.76	74.00	-17.24	peak
6	7440.080	44.68	6.32	51.00	54.00	-3.00	AVG
7	8490.000	45.31	7.44	52.75	74.00	-21.25	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



## 7.4.2. 8DPSK MODE

### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4245.000	49.21	-1.59	47.62	74.00	-26.38	peak
2	6390.000	44.07	4.28	48.35	74.00	-25.65	peak
3	7890.000	41.08	7.30	48.38	74.00	-25.62	peak
4	11520.000	35.94	13.38	49.32	74.00	-24.68	peak
5	13800.000	33.31	17.10	50.41	74.00	-23.59	peak
6	17295.000	29.99	21.71	51.70	74.00	-22.30	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3180.000	49.11	-4.33	44.78	74.00	-29.22	peak
2	4245.000	52.19	-1.59	50.60	74.00	-23.40	peak
3	5310.000	45.30	2.02	47.32	74.00	-26.68	peak
4	6000.000	48.74	3.29	52.03	74.00	-21.97	peak
5	7200.000	43.56	5.82	49.38	74.00	-24.62	peak
6	8505.000	41.49	7.41	48.90	74.00	-25.10	peak
7	17700.000	30.42	22.43	52.85	74.00	-21.15	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3195.000	49.08	-4.42	44.66	74.00	-29.34	peak
2	4245.000	48.05	-1.59	46.46	74.00	-27.54	peak
3	4875.000	47.37	0.76	48.13	74.00	-25.87	peak
4	6390.000	42.59	4.28	46.87	74.00	-27.13	peak
5	7320.000	45.06	6.14	51.20	74.00	-22.80	peak
6	13800.000	33.13	17.10	50.23	74.00	-23.77	peak
7	17655.000	30.72	22.15	52.87	74.00	-21.13	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4245.000	52.38	-1.59	50.79	74.00	-23.21	peak
2	6000.000	48.69	3.29	51.98	74.00	-22.02	peak
3	7320.000	46.34	6.14	52.48	74.00	-21.52	peak
4	8505.000	44.54	7.41	51.95	74.00	-22.05	peak
5	11520.000	35.66	13.38	49.04	74.00	-24.96	peak
6	16455.000	32.28	19.00	51.28	74.00	-22.72	peak
7	17910.000	29.04	23.35	52.39	74.00	-21.61	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. AVG:  $VBW=1/Ton$  where: ton is transmit duration.


5. For duty cycle, please refer to clause 6.1.

6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

7. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4260.000	47.77	-1.71	46.06	74.00	-27.94	peak
2	4950.000	48.34	1.13	49.47	74.00	-24.53	peak
3	5490.000	48.94	2.93	51.87	74.00	-22.13	peak
4	6375.000	44.32	4.22	48.54	74.00	-25.46	peak
5	7440.000	45.74	6.32	52.06	74.00	-21.94	peak
6	13875.000	34.05	16.44	50.49	74.00	-23.51	peak
7	17760.000	30.02	22.95	52.97	74.00	-21.03	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4260.000	52.55	-1.71	50.84	74.00	-23.16	peak
2	4950.000	46.71	1.13	47.84	74.00	-26.16	peak
3	6000.000	49.84	3.29	53.13	74.00	-20.87	peak
4	6390.000	46.09	4.28	50.37	74.00	-23.63	peak
5	7440.000	44.91	6.32	51.23	74.00	-22.77	peak
6	8502.413	46.81	7.41	54.22	74.00	-19.78	peak
7	8502.413	23.43	7.41	30.84	54.00	-23.16	AVG
8	17925.000	29.11	23.37	52.48	74.00	-21.52	peak


- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. AVG: VBW=1/Ton where: ton is transmit duration.  
5. For duty cycle, please refer to clause 6.1.  
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.



## 7.5. SPURIOUS EMISSIONS 18G ~ 26GHz

### 7.5.1. GFSK MODE

#### SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18576.000	50.47	-4.51	45.96	74.00	-28.04	peak
2	19880.000	49.35	-4.36	44.99	74.00	-29.01	peak
3	21032.000	51.02	-5.32	45.70	74.00	-28.30	peak
4	22584.000	51.44	-5.77	45.67	74.00	-28.33	peak
5	24328.000	50.86	-3.28	47.58	74.00	-26.42	peak
6	25304.000	48.96	-1.32	47.64	74.00	-26.36	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.



**SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18808.000	51.55	-4.85	46.70	74.00	-27.30	peak
2	19744.000	51.14	-4.35	46.79	74.00	-27.21	peak
3	21136.000	50.86	-5.41	45.45	74.00	-28.55	peak
4	22552.000	51.67	-5.78	45.89	74.00	-28.11	peak
5	23992.000	53.22	-4.03	49.19	74.00	-24.81	peak
6	25296.000	49.20	-1.30	47.90	74.00	-26.10	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.


Note: All the modes and channels have been tested, only the worst data was recorded in the report.



## 7.6. SPURIOUS EMISSIONS 30M ~ 1 GHz

### 7.6.1. GFSK MODE

#### SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	34.8500	37.65	-17.50	20.15	40.00	-19.85	QP
2	71.7100	40.70	-20.20	20.50	40.00	-19.50	QP
3	79.4700	46.36	-20.39	25.97	40.00	-14.03	QP
4	88.2000	41.84	-20.94	20.90	43.50	-22.60	QP
5	109.5400	42.93	-21.48	21.45	43.50	-22.05	QP
6	455.8300	50.31	-11.83	38.48	46.00	-7.52	QP


Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.



### SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.9700	51.39	-17.08	34.31	40.00	-5.69	QP
2	77.5300	54.21	-20.37	33.84	40.00	-6.16	QP
3	293.8400	38.62	-14.53	24.09	46.00	-21.91	QP
4	455.8300	45.94	-11.83	34.11	46.00	-11.89	QP
5	740.0400	35.31	-6.40	28.91	46.00	-17.09	QP
6	797.2700	38.55	-5.60	32.95	46.00	-13.05	QP

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.  
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto


Note: All the modes and channels have been tested, only the worst data was recorded in the report.



## 7.7. SPURIOUS EMISSIONS BELOW 30M

### 7.7.1. GFSK MODE

#### SPURIOUS EMISSIONS (MID CHANNEL, LOOP ANTENNA FACE ON TO THE EUT, WORST-CASE CONFIGURATION)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.0126	69.93	-101.38	-31.45	45.59	-82.95	-5.91	-77.04	peak
2	0.0160	67.47	-101.37	-33.90	43.52	-85.40	-7.98	-77.42	peak
3	0.0252	64.32	-101.37	-37.05	39.57	-88.55	-11.93	-76.62	peak
4	0.0417	61.08	-101.44	-40.36	35.20	-91.86	-16.3	-75.56	peak
5	0.0529	59.30	-101.49	-42.19	33.13	-93.69	-18.37	-75.32	peak
6	0.0796	56.53	-101.63	-45.10	29.58	-96.6	-21.92	-74.68	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

4.  $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}(120\pi) = \text{dBuV/m} - 51.5$ .




150kHz ~ 0.49MHz



No.	Frequency	Reading	Correct	FCC Result	FCC Limit	ISED Result	ISED Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuA/m)	(dBuA/m)	(dB)	
1	0.1720	68.19	-101.67	-33.48	22.90	-84.98	-28.6	-56.38	peak
2	0.2053	63.79	-101.73	-37.94	21.35	-89.44	-30.15	-59.29	peak
3	0.2298	62.55	-101.77	-39.22	20.37	-90.72	-31.13	-59.59	peak
4	0.2757	60.56	-101.83	-41.27	18.79	-92.77	-32.71	-60.06	peak
5	0.3084	59.95	-101.86	-41.91	17.82	-93.41	-33.68	-59.73	peak
6	0.3714	56.28	-101.93	-45.65	16.20	-97.15	-35.3	-61.85	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.  
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.  
4.  $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}(120\pi) = \text{dBuV/m} - 51.5$ .



No.	Frequency	Reading	Correct	FCC Result	FCC Limit	ISED Result	ISED Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuA/m)	(dBuA/m)	(dB)	
1	0.6532	58.98	-62.10	-3.12	31.30	-54.62	-20.2	-34.42	peak
2	1.3044	55.16	-62.14	-6.98	25.30	-58.48	-26.2	-32.28	peak
3	2.5261	50.91	-61.69	-10.78	29.54	-62.28	-21.96	-40.32	peak
4	6.1287	48.83	-61.33	-12.50	29.54	-64.00	-21.96	-42.04	peak
5	13.8871	47.60	-60.97	-13.37	29.54	-64.87	-21.96	-42.91	peak
6	23.4783	48.74	-60.56	-11.82	29.54	-63.32	-21.96	-41.36	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.  
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.  
4.  $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}(120\pi) = \text{dBuV/m} - 51.5$ .

Note: All the modes and channels have been tested, only the worst data was recorded in the report.


## 8. AC POWER LINE CONDUCTED EMISSIONS

### LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8.

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

### TEST SETUP AND PROCEDURE



The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9kHz.


The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.



### 8.1.1. 8DPSK MODE

#### TEST RESULTS (HIGH CHANNEL, WORST-CASE CONFIGURATION)

##### LINE N RESULTS



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1553	22.84	9.60	32.44	65.71	-33.27	QP
2	0.1553	0.66	9.60	10.26	55.71	-45.45	AVG
3	0.3425	15.18	9.60	24.78	59.14	-34.36	QP
4	0.3425	-3.38	9.60	6.22	49.14	-42.92	AVG
5	1.4213	2.74	9.61	12.35	56.00	-43.65	QP
6	1.4213	1.44	9.61	11.05	46.00	-34.95	AVG
7	2.5584	4.72	9.64	14.36	56.00	-41.64	QP
8	2.5584	3.67	9.64	13.31	46.00	-32.69	AVG
9	8.0543	5.34	9.72	15.06	60.00	-44.94	QP
10	8.0543	-0.16	9.72	9.56	50.00	-40.44	AVG
11	28.8105	-0.79	9.93	9.14	60.00	-50.86	QP
12	28.8105	-4.09	9.93	5.84	50.00	-44.16	AVG

Note: 1. Result = Reading +Correct Factor.


2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.



## LINE L RESULTS



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1640	21.62	9.61	31.23	65.26	-34.03	QP
2	0.1640	0.05	9.61	9.66	55.26	-45.60	AVG
3	0.2614	13.21	9.60	22.81	61.39	-38.58	QP
4	0.2614	-2.10	9.60	7.50	51.39	-43.89	AVG
5	0.3389	16.62	9.60	26.22	59.23	-33.01	QP
6	0.3389	-3.16	9.60	6.44	49.23	-42.79	AVG
7	0.8533	2.28	9.60	11.88	56.00	-44.12	QP
8	0.8533	0.19	9.60	9.79	46.00	-36.21	AVG
9	8.4332	4.74	9.72	14.46	60.00	-45.54	QP
10	8.4332	-1.65	9.72	8.07	50.00	-41.93	AVG
11	26.6814	-2.16	9.90	7.74	60.00	-52.26	QP
12	26.6814	-4.79	9.90	5.11	50.00	-44.89	AVG

Note: 1. Result = Reading +Correct Factor.  
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).  
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

Note: All the modes and channels have been tested, only the worst data was recorded in the report.



## 9. ANTENNA REQUIREMENTS

### APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### RESULTS

Complies

**END OF REPORT**