



8. Radio Frequency Exposure

8.1. Applicable Standards

The measurements shown in this test report were made in accordance with the procedures given in FCC Part 2 (Section 2.1091)

8.2. EUT Specification

Frequency band (Operating)	13.553MHz ~ 13.567MHz
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation)
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure <input checked="" type="checkbox"/> General Population/Uncontrolled exposure
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A
Remark: 1. The maximum Fundamental Emission is <u>66.33dBuV/m</u> at <u>13.56MHz</u> (with <u>0dBi antenna gain</u> .) 2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance. 3. For mobile or fixed location transmitters, no SAR consideration applied.	

8.3. Test Results

No non-compliance noted.



8.4. Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

**8.5. Test Results**

Channel Frequency (MHz)	Fundamental Emission (dBm)	Max. Tune up power (dBm)	Antenna Gain(dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW)
13.56	-28.90	-28.40	0.00	20	0.0000003	0.979

Antenna Gain (dBi)	Antenna Gain (linear)	Distance (m)	Fundamental Emission (dBuV/m)	Fundamental Emission (V/m)	Fundamental Emission (W)	Fundamental Emission (dBm)
0	1	3	66.33	0.00207	0.0000013	-28.90

Maximum Permissible Exposure (Co-location)**NFC + BT +2.4G Wifi**

Channel Frequency (MHz)	Max. Conducted output power (dBm)	Max. Tune up power (dBm)	Antenna Gain(dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	MPE Ratio
13.56	-28.90	-28.40	0	20	0.0000003	0.979	0.000
2402-2480	12.84	13.34	0	20	0.004	1.000	0.004
2412-2462	22.76	23.26	2	20	0.067	1.000	0.067
Co-location Total							0.071
Σ MPE ratios Limit							1

NFC + BT +5G Wifi

Channel Frequency (MHz)	Max. Conducted output power (dBm)	Max. Tune up power (dBm)	Antenna Gain(dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	MPE Ratio
13.56	-28.90	-28.40	0	20	0.0000003	0.979	0.000
2402-2480	12.84	13.34	0	20	0.004	1.000	0.004
5725-5850	17.43	17.93	4.5	20	0.035	1.000	0.035
Co-location Total							0.039
Σ MPE ratios Limit							1

-----THE END OF REPORT-----