

Letter of acceptance

Customer name: _____

Customer PN : _____

Our model: _____YZ-G25(2.6-6.8UH-3000GS-10MM)_____

Sample delivery date: _____Apr. 13, 2024_____

Supplier: _____

Draw	Check	Approval
Feng Boqun	Su Yanping	


Customer recognition:

Appositional	Incongruent case	Acknowledge
Remark		

Shenzhen Shenchuang Hi-Tech Electronics Co.,Ltd
F/6 Building A, JingFaZhiZao Park, Gushu Community, Baoan District, Shenzhen
518126, China

Customer name	Customer PN	Our model	Edition	Date
	18-XQ-00019	YZ-G25-2.6-6.8UH-3000GS-10MM	A0	Apr. 13, 2024

一、Plane structure: unit:MM



二、Product parameter:

Foot position	Wire diameter	Number of turns	remark
1 - 2	0.08*24	12	Hot air stranding wire

三、Technical requirements: (Magnetic force of 2900~3100 Gauss)

- Secure the cable end to prevent loose cables
- According to customer requirements, the long thread is cut and tinned, and the tinning depth is 2±1MM
- Spot the appropriate white glue on the magnetic disc, attach the coil, and ensure that the product surface is clean and tidy during the process.
- The magnetic disc used is with round hole, without damage

5. Additional process (according to customer requirements) : Install 7.6x2.0mm magnet in the middle round hole of the finished product and attach a double-sided adhesive with a diameter of 14mm after the finished product, and then pack

四、Electrical parameter:

1. Inductance value, Q value:

PIN 1 — 2 = $6.8\mu\text{H} \pm 0.3\mu\text{H}$

Q value ≥ 25

The above inductance values are based on Quanhua 1062B instrument, 10KHZ/0.3Vrms as the standard or equivalent instrument.

Q value is based on Quanhua 1062B instrument, 100KHZ/0.3Vrms as the standard or equivalent instrument

五、 Bill of materials:

Serial number	name	material	supplier	remark
1	Hot air stranding wire	0.08X24	Weiham or equivalent	
2	Magnetic sheet	G25 Die cast substrate	Tiantong or equivalent	
3	tin	High temperature environmental protection	Thousand Islands or equivalent	
4	White glue	BY882	Moon or equivalent	
5	Strong magnetic	7.6*2 (intensity 3000GS±100GS)	United win or equivalent	Additional processes, according to customer requirements
6	Double-sided tape	513-14mm	Honghui or equivalent	