

Test Report

Report No.: MTi230518003-10E1

Date of issue: 2023-05-31

Applicant: Shenzhen Yifeng Intelligent Technology Co., Ltd.

Product: 3-in-1 Magnetic Wireless Charging Stand

Model(s): M7

FCC ID: 2AXY5-M7

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

Instructions

1. This test report shall not be partially reproduced without the written consent of the laboratory.
2. The test results in this test report are only responsible for the samples submitted
3. This test report is invalid without the seal and signature of the laboratory.
4. This test report is invalid if transferred, altered, or tampered with in any form without authorization.
5. Any objection to this test report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

Table of contents

1. General Description	5
1.1 Description of the EUT	5
1.2 Description of test modes	6
1.3 Description of support units	7
1.4 Environmental conditions	7
2. Measurement uncertainty	8
3. Test laboratory	8
4. Summary of Test Result	9
5. List of test equipment	10
6. Test Results	11
6.1 Antenna requirement	11
6.2 AC power line conducted emissions	12
6.3 Radiated emissions	15
6.4 Occupied bandwidth test	22
Photographs of the test setup	24
Photographs of the EUT	24


Test Result Certification	
Applicant:	Shenzhen Yifeng Intelligent Technology Co., Ltd.
Address:	10th Floor, Building 2, Chaxi, Zone B, Huafeng First Science Park, Hangcheng Street, Gushu, Baoan District, Shenzhen, China.
Manufacturer:	Shenzhen Yifeng Intelligent Technology Co., Ltd.
Address:	10th Floor, Building 2, Chaxi, Zone B, Huafeng First Science Park, Hangcheng Street, Gushu, Baoan District, Shenzhen, China.
Factory:	Shenzhen Yifeng Intelligent Technology Co., Ltd.
Address:	10th Floor, Building 2, Chaxi, Zone B, Huafeng First Science Park, Hangcheng Street, Gushu, Baoan District, Shenzhen, China.
Product description	
Product name:	3-in-1 Magnetic Wireless Charging Stand
Trademark:	YFZN
Model name:	M7
Series Model:	N/A
Standards:	FCC 47 CFR Part 15 Subpart C
Test method:	ANSI C63.10-2013
Date of Test	
Date of test:	2023-05-24 ~ 2023-05-31
Test result:	Pass

Test Engineer :



(Maleah Deng)

Reviewed By :



(Leon Chen)

Approved By :



(Tom Xue)

1. General Description

1.1 Description of the EUT

Product name:	3-in-1 Magnetic Wireless Charging Stand
Model name:	M7
Series Model:	N/A
Model difference:	N/A
Electrical rating:	Input: DC 9V/2A Output: Coil 1(Phone): 5W/7.5W/10W/15W Max, Coil 2(Earphone):5W Max, Coil 3(Watch): 3W Max
Accessories:	N/A
Hardware version:	V1.3
Software version:	V0x75
Test sample(s) number:	MTi230518003-10S1001
RF specification:	
Operation frequency:	Transmitter 1 (Phone): 115 kHz – 205 kHz Transmitter 2 (Earphone): 115 kHz – 205 kHz Transmitter 3 (Watch): 300 kHz – 350 kHz
Modulation type:	ASK
Antenna type:	Coil Antenna

1.2 Description of test modes

All the test modes were carried out with the EUT in normal operation, the final test mode of the EUT was the worst test mode for emission test, which was shown in this report and defined as:

No.	Emission test modes
Mode 1	Wireless Output(5W)
Mode 2	Wireless Output(7.5W)
Mode 3	Wireless Output(10W)
Mode 4	Wireless Output(15W)
Mode 5	Earphone(5W)
Mode 6	Watch(3W)
Mode 7	Wireless Output(5W)+Earphone(5W)
Mode 8	Wireless Output(7.5W)+Earphone(5W)
Mode 9	Wireless Output(10W)+Earphone(5W)
Mode 10	Wireless(5W)+Watch(3W)
Mode 11	Wireless(7.5W)+Watch(3W)
Mode 12	Wireless(10W)+Watch(3W)
Mode 13	Wireless(15W)+Watch(3W)
Mode 14	Wireless(5W)+Watch(3W)+Earphone(5W)
Mode 15	Wireless(7.5W)+Watch(3W)+Earphone(5W)
Mode 16	Wireless(10W)+Watch(3W)+Earphone(5W)
Mode 17	Watch(3W)+ Earphone(5W)
Mode 18	Stand-by

The worst test mode of conducted emissions: Mode 15

The worst test mode of radiated emissions (Below 30MHz): Mode 16

The worst test mode of radiated emissions (Below 1GHz): Mode 13

1.3 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support equipment list			
Description	Model	Serial No.	Manufacturer
Load	YBZ1.1	/	YBZ
Air Pods	A2190	H6LDLEZ70C6L	Apple
iWatch	iWatch S8	M0JVGQG1VP	Apple
Adapter	191106C	/	ifory
Support cable list			
Description	Length (m)	From	To
/	/	/	/

1.4 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C~35°C
Humidity:	20 % RH ~ 75 % RH
Atmospheric pressure:	98 kPa~101 kPa

2. Measurement uncertainty

Measurement	Uncertainty
Conducted emission (9 kHz~30 MHz)	± 2.5 dB
Radiated emission (9 kHz ~ 30 MHz)	± 4.0 dB
Radiated emission (30 MHz~1 GHz)	± 4.2 dB
Radiated emission (above 1 GHz)	± 4.3 dB
Occupied bandwidth	± 3 %
Temperature	± 1 degree
Humidity	± 5 %

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

3. Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No.7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573

4. Summary of Test Result

No.	FCC reference	Description of test	Result
Emission			
1	FCC Part 15.203	Antenna requirement	Pass
2	FCC Part 15.207	AC power line Conducted emissions	Pass
3	FCC Part 15.209	Radiated emissions	Pass
4	FCC Part 15.215	Occupied bandwidth	Pass

5. List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
MTi-E043	EMI test receiver	R&S	ESCI7	101166	2023/04/26	2024/04/25
MTi-E044	Broadband antenna	Schwarzbeck	VULB9163	9163-1338	2021/05/30	2024/05/29
MTi-E045	Horn antenna	Schwarzbeck	BBHA9120D	9120D-2278	2021/05/30	2024/05/29
MTi-E046	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00066	2021/05/30	2024/05/29
MTi-E047	Pre-amplifier	Hewlett-Packard	8447F	3113A06184	2023/04/26	2024/04/25
MTi-E048	Pre-amplifier	Agilent	8449B	3008A01120	2023/05/04	2024/05/03
MTi-E005	EMI test receiver	R&S	ESPI7	100314	2023/04/26	2024/04/25
MTi-E120	Broadband antenna	Schwarzbeck	VULB9163	9163-1419	2021/05/30	2024/05/29
MTi-E121	Pre-amplifier	Hewlett-Packard	8447D	2944A09365	2023/05/04	2024/05/03
MTi-E123	Pre-amplifier	Agilent	8449B	3008A04723	2023/05/04	2024/05/03
MTi-E001	Artificial Mains Network	R&S	ESH2-Z5	100263	/	/
MTi-E002	EMI Test Receiver	R&S	ESCI3	101368	2023/04/26	2024/04/25
MTi-E023	Artificial power network	Schwarzbeck	NSLK8127	NSLK8127#841	2023/05/04	2024/05/03
MTi-E025	Artificial power network	Schwarzbeck	NSLK8127	8127183	2023/04/26	2024/04/25
MTi-E026	8-wire Impedance Stabilization Network	Schwarzbeck	NTFM 8158	NTFM 8158 #199	2023/04/26	2024/04/25
MTi-E043	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2023/04/26	2024/04/25
MTi-E024	Artificial power network	Schwarzbeck	NSLK8127	01001	2023/05/06	2024/05/05

Note: the calibration interval of the test equipment is 12 or 24 months and the calibrations are traceable to international system unit(SI)

6. Test Results

6.1 Antenna requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Description of the EUT antenna

The antenna of EUT is coil antenna, which is integrated on the main PCB of the EUT and no consideration of replacement.

6.2 AC power line conducted emissions

6.2.1 Limits


Frequency (MHz)	Detector type / Bandwidth	Limit-Quasi-peak dB μ V	Limit-Average dB μ V
0.15 -0.5	Average / 9 kHz	66 to 56	56 to 46
0.5 -5		56	46
5 -30		60	50

Note 1: the limit decreases with the logarithm of the frequency in the range of 0.15 MHz to 0.5 MHz.

6.2.2 Test Procedures

- The test setup is refer to the standard ANSI C63.10-2013.
- The EUT is connected to the main power through a line impedance stabilization network (LISN). All support equipment is powered from additional LISN(s).
- Emissions were measured on each current carrying line of the EUT using an EMI test receiver connected to the LISN powering the EUT.
- The test receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes described in Item 1.2.
- The test data of the worst-case condition(s) was recorded.

6.2.3 Test setup



For the actual test configuration, please refer to the related item – Photographs of the test setup.


6.2.4 Test Result

Calculation formula:

Measurement (dB μ V) = Reading Level (dB μ V) + Correct Factor (dB)


Over (dB) = Measurement (dB μ V) – Limit (dB μ V)

Test mode:	Mode 15	Phase:	L
Power supply:	Powered by AC/DC adapter (AC 120V/60Hz)	Test site:	CE chamber 1



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1620	40.89	10.18	51.07	65.36	-14.29	QP
2		0.1620	26.00	10.18	36.18	55.36	-19.18	AVG
3		0.4460	23.02	10.21	33.23	56.95	-23.72	QP
4		0.4460	19.86	10.21	30.07	46.95	-16.88	AVG
5		2.8140	24.07	10.39	34.46	56.00	-21.54	QP
6		3.0700	21.09	10.42	31.51	46.00	-14.49	AVG
7		6.2700	24.18	10.74	34.92	60.00	-25.08	QP
8		6.7820	21.67	10.78	32.45	50.00	-17.55	AVG
9		11.7700	28.87	10.70	39.57	60.00	-20.43	QP
10		13.5620	27.78	10.66	38.44	50.00	-11.56	AVG
11	*	17.4020	28.37	10.60	38.97	50.00	-11.03	AVG
12		17.9100	30.01	10.60	40.61	60.00	-19.39	QP

Test mode:	Mode 15	Phase:	N
Power supply:	Powered by AC/DC adapter (AC 120V/60Hz)	Test site:	CE chamber 1



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1620	38.95	10.13	49.08	65.36	-16.28	QP
2		0.1620	25.69	10.13	35.82	55.36	-19.54	AVG
3		0.4460	27.25	10.05	37.30	56.95	-19.65	QP
4		0.4460	24.04	10.05	34.09	46.95	-12.86	AVG
5		1.8980	22.09	10.34	32.43	56.00	-23.57	QP
6		1.9180	15.18	10.34	25.52	46.00	-20.48	AVG
7		6.6500	26.63	10.64	37.27	60.00	-22.73	QP
8		7.2900	22.38	10.66	33.04	50.00	-16.96	AVG
9		12.1500	30.43	10.68	41.11	60.00	-18.89	QP
10		12.7900	27.31	10.67	37.98	50.00	-12.02	AVG
11		17.1420	29.87	10.60	40.47	60.00	-19.53	QP
12	*	17.1420	29.05	10.60	39.65	50.00	-10.35	AVG

6.3 Radiated emissions

6.3.1 Limits

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Note 1: the tighter limit applies at the band edges.

Note 2: the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector

§ 15.35 (b) requirements:

When average radiated emission measurements are specified in this part, including average emission measurements below 1000 MHz, there also is a limit on the peak level of the radio frequency emissions. Unless otherwise specified, e.g., see §§ 15.250, 15.252, 15.253(d), 15.255, 15.256, and 15.509 through 15.519, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

According to ANSI C63.10, the tests shall be performed in the frequency range shown in the following table:

Frequency range of measurements for unlicensed wireless device

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz, whichever is lower
At or above 10 GHz to below 30 GHz	5th harmonic of highest fundamental frequency or to 100 GHz, whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz, whichever is lower, unless otherwise specified

Frequency range of measurements for unlicensed wireless device with digital device

Highest frequency generated or used in the device or on which the device operates or tunes	Upper frequency range of measurement
Below 1.705 MHz	30 MHz
1.705 MHz to 108 MHz	1000 MHz
108 MHz to 500 MHz	2000 MHz
500 MHz to 1000 MHz	5000 MHz
Above 1000 MHz	5th harmonic of the highest frequency or 40 GHz, whichever is lower

Test instrument setup

Frequency	Test receiver / Spectrum analyzer setting
9 kHz ~ 150 kHz	Quasi Peak / 200 Hz
150 kHz ~ 30 MHz	Quasi Peak / 9 kHz
30 MHz ~ 1 GHz	Quasi Peak / 120 kHz

6.3.2 Test Procedures

The EUT is placed on a non-conducting table 80cm above the ground plane for measurement below 1 GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10-2013.

For measurement below 1 GHz, the resolution bandwidth is set as item 5.4.2.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4m meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and horizontal positions.

Special requirements for 9 kHz to 30 MHz:


The lowest height of the magnetic antenna shall be 1 m above the ground

When the EUT contains a loop antenna that can only be placed in a vertical axis, normal measurements shall be made aligning the measurement antenna along the site axis, and then orthogonal to the axis. For each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable.


When the EUT contains a loop antenna that can be placed in a horizontal or vertical axis, normal measurements shall be made aligning the measurement antenna along the site axis, orthogonal to the axis, and then with the measurement antenna horizontal. For each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable.

6.3.3 Test Setup

Below 30 MHz:



Below 1 GHz:



For the actual test configuration, please refer to the related item – Photographs of the test setup.

6.3.4 Test result

Calculation formula:


Measurement (dB μ V/m) = Reading Level (dB μ V) + Correct Factor (dB/m)

Over (dB) = Measurement (dB μ V/m) – Limit (dB μ V/m)

Note: For 9 kHz - 30 MHz testing, all the required orthogonal orientations of the measurement loop antenna were performed for pre-scan, the maximum radiated transmissions (Site axis) were recorded.

Frequency 9 kHz ~ 150 kHz


Test mode:	Mode 16	Polarization:	Site axis
Power supply:	Powered by AC/DC adapter (AC 120V/60Hz)	Test site:	RE chamber 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.1340	60.63	21.22	81.85	125.08	-43.23	peak
2	0.1340	60.63	21.22	81.85	105.08	-23.23	AVG
3	0.1454	62.79	21.28	84.07	124.37	-40.30	peak
4 *	0.1454	62.79	21.28	84.07	104.37	-20.30	AVG

Frequency 150 kHz ~ 30 MHz

Test mode:	Mode 16	Polarization:	Site axis
Power supply:	Powered by AC/DC adapter (AC 120V/60Hz)	Test site:	RE chamber 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.3100	60.71	21.33	82.04	117.78	-35.74	peak
2 *	0.3100	60.71	21.33	82.04	97.78	-15.74	AVG
3	0.4282	33.89	21.32	55.21	114.97	-59.76	peak
4	0.4282	33.89	21.32	55.21	94.97	-39.76	AVG
5	0.4661	42.58	21.32	63.90	114.23	-50.33	peak
6	0.4661	42.58	21.32	63.90	94.23	-30.33	AVG
7	0.7751	30.82	21.62	52.44	69.83	-17.39	QP
8	1.0881	24.20	21.87	46.07	66.89	-20.82	QP
9	1.3956	15.46	24.67	40.13	64.73	-24.60	QP

Frequency 30 MHz ~ 1 GHz

Test mode:	Mode 13	Polarization:	Horizontal
Power supply:	Powered by AC/DC adapter (AC 120V/60Hz)	Test site:	RE chamber 1



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		94.0979	40.12	-8.13	31.99	43.50	-11.51	QP
2	*	175.6516	49.18	-8.96	40.22	43.50	-3.28	QP
3		191.7450	44.38	-7.40	36.98	43.50	-6.52	QP
4		233.3487	41.88	-5.68	36.20	46.00	-9.80	QP
5		289.0021	37.19	-4.48	32.71	46.00	-13.29	QP
6		359.1860	32.63	-3.18	29.45	46.00	-16.55	QP

Frequency 30 MHz ~ 1 GHz

Test mode:	Mode 13	Polarization:	Vertical
Power supply:	Powered by AC/DC adapter (AC 120V/60Hz)	Test site:	RE chamber 1



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	94.0979	44.07	-7.98	36.09	43.50	-7.41	QP
2		189.7385	41.76	-7.58	34.18	43.50	-9.32	QP
3		231.7179	34.09	-5.40	28.69	46.00	-17.31	QP
4		269.4284	32.45	-4.62	27.83	46.00	-18.17	QP
5		443.2943	29.97	-0.91	29.06	46.00	-16.94	QP
6		541.3725	30.21	1.33	31.54	46.00	-14.46	QP

6.4 Occupied bandwidth test


6.4.1 Test Procedures

- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW.
- Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation.
- The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement
- Set detection mode to peak and trace mode to max hold.
- Determine the “-xx dB down amplitude” using [(reference value) - xx]. Alternatively, this calculation may be made by using the marker-delta function of the instrument.

6.4.2 Test Result


Note: Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300 Hz to perform the occupied bandwidth test.

Transmitter 1:




Transmitter 2:

Frequency kHz	20 dB occupied bandwidth Hz	99% occupied bandwidth Hz
145.700	752	640


Transmitter 3:

Frequency kHz	20 dB occupied bandwidth Hz	99% occupied bandwidth Hz
325.550	755	652



Photographs of the test setup

See the Appendix – Test Setup Photos.

Photographs of the EUT

See the Appendix - EUT Photos.

----End of Report----