



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.247

TEST REPORT

For

Waylens Inc.

2711 Centerville Road - Suite 400, Wilmington, Delaware 19808, United States

FCC ID: 2AKAF-TW06C2

Report Type: Original Report	Product Type: Secure 4K
Project Engineer:	Chao Gao <i>Chao Gao</i>
Report Number:	RSHF200730001-00A
Report Date:	2020-12-10
Reviewed By:	Oscar Ye <i>Oscar Ye</i> EMC Manager
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
EUT EXERCISE SOFTWARE	6
SUPPORT EQUIPMENT LIST AND DETAILS	9
EXTERNAL I/O CABLE.....	9
BLOCK DIAGRAM OF TEST SETUP	10
SUMMARY OF TEST RESULTS	11
TEST EQUIPMENT LIST	12
FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)	13
FCC §15.203 - ANTENNA REQUIREMENT.....	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER SETUP.....	17
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST RESULTS SUMMARY	17
TEST DATA	18
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	51
APPLICABLE STANDARD	51
TEST PROCEDURE	51
TEST DATA	51
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	61
APPLICABLE STANDARD	61
TEST PROCEDURE	61
TEST DATA	62
FCC §15.247(d) – BAND EDGE.....	65
APPLICABLE STANDARD	65
TEST PROCEDURE	65
TEST DATA	65
FCC §15.247(e) - POWER SPECTRAL DENSITY	71
APPLICABLE STANDARD	71
TEST PROCEDURE	71
TEST DATA	71

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	Waylens Inc.
Tested Model	TW06
Product Type	Secure 4K
Power Supply	DC 12.0V from External power supply
RF Function	2.4G Wi-Fi, BLE(1Mbps)
Operating Band/Frequency	2.4G Wi-Fi: 2412~2462 MHz (802.11b/g/n20), 2422~2452 MHz (802.11n40) BLE(1Mbps): 2402-2480MHz
Channel Number	2.4G Wi-Fi: 11 (802.11b/g/n20), 7 (802.11n40) BLE(1Mbps): 40
Channel Separation	2.4G Wi-Fi: 5MHz, BLE(1Mbps): 2MHz
Modulation Type	2.4G Wi-Fi: OFDM,DSSS; BLE(1Mbps): GFSK
Antenna Type	2.4G Wi-Fi/BLE: PCB Antenna
*Maximum Antenna Gain	2.4G Wi-Fi/BLE: 1.5dBi

Note: The Maximum Antenna Gain was declared by the manufacturer.

**All measurement and test data in this report was gathered from production sample serial number: 20200730001
(Assigned by the BACL. The EUT supplied by the applicant was received on 2020-07-30)*

Objective

This report is prepared on behalf of *Waylens Inc.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS Submittal with FCC ID: 2AKAF-TW06C2

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Test channel list is as below:

For 802.11b, 802.11g and 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11.

For 802.11n-HT40 mode, EUT was tested with Channel 3, 6 and 9.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For BLE mode, EUT was tested with channel 0, 19 and 39.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
18	2438	38	2478
19	2440	39	2480

Equipment Modifications

No modification was made to the EUT tested.


EUT Exercise Software

RF test tool: CRT


Pre-scan with all the data rates, and the worst case was performed as below:

Mode	Data Rate	Channel	*Power Level
802.11b	1Mbps	Low	Default
		Middle	Default
		High	Default
802.11g	6Mbps	Low	Default
		Middle	Default
		High	Default
802.11n-HT20	MCS0	Low	Default
		Middle	Default
		High	Default
802.11n-HT40	MCS0	Low	Default
		Middle	Default
		High	Default
BLE	1Mbps	Low	Default
		Middle	Default
		High	Default


Note: The power level setting was declared by the applicant.

Duty Cycle:


802.11g Mode Middle Channel




802.11n-HT20 Mode Middle Channel



802.11n-HT40 Mode Middle Channel



BLE Mode Middle Channel



Mode	Duty Cycle (%)	T(ms)	1/T(kHz)	10log(1/x)
802.11b	100	/	/	0
802.11g	100	/	/	0
802.11n-HT20	100	/	/	0
802.11n-HT40	100	/	/	0
BLE	65.41%	0.409	2.45	1.84

Note: “x” means the Duty Cycle.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
MCH	DC Source	MCH-303D-II	14070562


External I/O Cable

Cable Description	Length (m)	From	To
Power Cable	3.0	EUT	DC Source
Power Cable	1.0	DC Source	AC Source

Block Diagram of Test Setup


For Radiated Emissions (Below 1GHz):

Turntable
2m Diameter



For Radiated Emissions (Above 1GHz):

Turntable
2m Diameter



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (I), §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Not Applicable (See Note)
§15.247(d)	Spurious Emissions at Antenna Port	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

Note: The EUT is a vehicle device.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2019-12-14	2020-12-13
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2017-12-26	2020-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2020-08-14	2021-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-8	008	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2020-08-15	2021-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2020-04-01	2021-03-31
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2020-07-15	2023-07-14
ETS-LINDGREN	Horn Antenna	3116	00084159	2019-12-12	2022-12-11
A.H.Systems,inc	Amplifier	PAM-0118P	512	2020-02-20	2021-02-19
EM Electronics Corporation	Amplifier	EM18G40G	060726	2020-03-22	2021-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2020-08-05	2021-08-04
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-12-12	2020-12-11
MICRO-COAX	Coaxial Cable	Cable-11	011	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2020-08-15	2021-08-14
RF Conducted Test					
Rohde & Schwarz	EMI Test Receiver	ESIB26	100146	2019-12-14	2020-12-13
Agilent	Power Meter	N1912A	MY5000492	2019-11-18	2020-11-17
Agilent	Power Sensor	N1921A	MY54210024	2019-11-18	2020-11-17
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
Waylens Inc.	RF Cable	Waylens Inc. C01	C01	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Output Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
BT	2402-2480	1.5	1.41	7.50	5.62	20	0.0016	1.0
BLE	2402-2480	1.5	1.41	2.00	1.58	20	0.0004	1.0
802.11b	2412-2462	1.5	1.41	20.50	112.20	20	0.0315	1.0
802.11g		1.5	1.41	17.50	56.23	20	0.0158	1.0
802.11n-HT20		1.5	1.41	17.50	56.23	20	0.0158	1.0
802.11n-HT40	2422-2452	1.5	1.41	17.00	50.12	20	0.0141	1.0
WCDMA Band 2	1850~1910	4.8	3.02	23.00	199.53	20	0.1199	1.0
WCDMA Band 5	824-849	3.5	2.24	23.50	223.87	20	0.0997	0.55
LTE Band 2	1850~1910	4.8	3.02	22.50	177.83	20	0.1068	1.0
LTE Band 4	1710~1755	4.8	3.02	22.00	158.49	20	0.0952	1.0
LTE Band 5	824-849	3.5	2.24	23.50	223.87	20	0.0997	0.55
LTE Band 12	699~716	3.5	2.24	23.50	223.87	20	0.0997	0.47
LTE Band 17	704-716	3.5	2.24	23.00	199.53	20	0.0889	0.47

Note:

- (1) The all tune-up output powers are declared by the Manufacturer.
- (2) The LTE module FCC ID: SRQ-ME3630, Date of Grant: 08/28/2017.
- (3) Wi-Fi /BLE /BT and LTE can transmit simultaneously; the worst condition is 802.11b of Wi-Fi and LTE Band 12 as below:

$$\sum_i \frac{S_i}{S_{Limit,i}} = 0.0315/1.0 + 0.0997/0.47 = 0.0315 + 0.2121 = 0.2436 < 1.0$$

Result: The device meet FCC MPE at 20 cm distance.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine Compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.
- And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has a PCB antenna for 2.4G Wi-Fi and Bluetooth, and the antenna gain is 1.5dBi. The antenna is permanently attached to the unit, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

According to ANSI C63.10-2013 clause 6.5, 6.6 and 6.7.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dB μ V/m) = Meter Reading (dB μ V) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data**Environmental Conditions**

Temperature:	23.4~25.6 °C
Relative Humidity:	50~64 %
ATM Pressure:	100.7~101.6 kPa

The testing was performed by Chao Gao from 2020-08-14 to 2020-12-09


Test Result: Compliant.

EUT operation mode: Transmitting

For Wi-Fi Mode:

Spurious Emission Test:**30MHz-1GHz:**

Pre-scan with 802.11b, 802.11g, 802.11n-HT20 and 802.11n-HT40 modes of operation in the X,Y and Z axes of orientation, the worst case **middle channel of 802.11b mode in Y-axis of orientation** was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
185.616250	29.17	100.0	V	0.0	-13.7	43.50	14.33
282.638150	31.42	100.0	H	14.0	-11.6	46.00	14.58
334.135200	33.54	200.0	V	189.0	-10.2	46.00	12.46
519.747050	37.93	100.0	V	336.0	-6.0	46.00	8.07
594.008500	36.20	200.0	H	262.0	-5.5	46.00	9.80
890.984900	39.30	100.0	H	252.0	0.0	46.00	6.70

1GHz-18GHz:**802.11b Mode:**


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Y-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1260.100000	35.68	---	150.0	H	149.0	-17.7	74.00	38.32
1260.100000	---	26.35	150.0	H	149.0	-17.7	54.00	27.65
1793.900000	37.12	---	150.0	V	190.0	-15.2	74.00	36.88
1793.900000	---	32.18	150.0	V	190.0	-15.2	54.00	21.82
4824.000000	41.04	---	150.0	V	279.0	-5.5	74.00	32.96
4824.000000	---	37.82	150.0	V	279.0	-5.5	54.00	16.18
7836.000000	---	37.33	200.0	H	161.0	1.5	54.00	16.67
7836.000000	46.48	---	200.0	H	161.0	1.5	74.00	27.52
13061.500000	---	42.59	200.0	V	330.0	5.3	54.00	11.41
13061.500000	50.03	---	200.0	V	330.0	5.3	74.00	23.97
17653.200000	52.95	---	200.0	H	136.0	8.9	74.00	21.05
17653.200000	---	47.71	200.0	H	136.0	8.9	54.00	6.29

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1260.100000	34.07	---	150.0	H	127.0	-17.7	74.00	39.93
1260.100000	---	25.56	150.0	H	127.0	-17.7	54.00	28.44
1793.900000	38.79	---	200.0	V	296.0	-15.2	74.00	35.21
1793.900000	---	31.73	200.0	V	296.0	-15.2	54.00	22.27
4874.000000	---	32.87	150.0	H	346.0	-5.4	54.00	21.13
4874.000000	40.84	---	150.0	H	346.0	-5.4	74.00	33.16
7210.100000	---	36.70	200.0	H	90.0	0.4	54.00	17.30
7210.100000	46.02	---	200.0	H	90.0	0.4	74.00	27.98
13087.000000	---	41.94	150.0	H	64.0	5.3	54.00	12.06
13087.000000	50.44	---	150.0	H	64.0	5.3	74.00	23.56
17712.700000	---	45.33	150.0	V	359.0	8.9	54.00	8.67
17712.700000	54.68	---	150.0	V	359.0	8.9	74.00	19.32

High Channel: 2462MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1270.300000	36.65	---	150.0	V	249.0	-17.6	74.00	37.35
1270.300000	---	28.62	150.0	V	249.0	-17.6	54.00	25.38
1795.600000	---	28.34	200.0	V	185.0	-15.2	54.00	25.66
1795.600000	37.16	---	200.0	V	185.0	-15.2	74.00	36.84
4924.000000	41.10	---	150.0	V	274.0	-5.3	74.00	32.90
4924.000000	---	35.06	150.0	V	274.0	-5.3	54.00	18.94
7726.900000	---	36.82	150.0	V	198.0	1.4	54.00	17.18
7726.900000	46.14	---	150.0	V	198.0	1.4	74.00	27.86
13962.500000	---	41.44	150.0	H	352.0	6.1	54.00	12.56
13962.500000	51.25	---	150.0	H	352.0	6.1	74.00	22.75
17656.600000	55.63	---	150.0	V	339.0	8.9	74.00	18.37
17656.600000	---	46.03	150.0	V	339.0	8.9	54.00	7.97

802.11g Mode:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Y-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1112.200000	32.29	---	150.0	H	256.0	-18.5	74.00	41.71
1112.200000	---	27.24	150.0	H	256.0	-18.5	54.00	26.76
1792.200000	37.02	---	150.0	H	269.0	-15.3	74.00	36.98
1792.200000	---	29.52	150.0	H	269.0	-15.3	54.00	24.48
4824.000000	---	33.68	200.0	V	118.0	-5.5	54.00	20.32
4824.000000	40.23	---	200.0	V	118.0	-5.5	74.00	33.77
7983.600000	---	36.23	200.0	V	325.0	1.8	54.00	17.77
7983.600000	46.47	---	200.0	V	325.0	1.8	74.00	27.53
12993.500000	---	40.68	150.0	V	212.0	5.2	54.00	13.32
12993.500000	50.26	---	150.0	V	212.0	5.2	74.00	23.74
17756.900000	---	45.86	200.0	V	337.0	8.8	54.00	8.14
17756.900000	54.37	---	200.0	V	337.0	8.8	74.00	19.63

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1112.200000	33.47	---	150.0	V	237.0	-18.5	74.00	40.53
1112.200000	---	27.04	150.0	V	237.0	-18.5	54.00	26.96
1792.200000	36.47	---	150.0	H	131.0	-15.3	74.00	37.53
1792.200000	---	30.94	150.0	H	131.0	-15.3	54.00	23.06
3718.300000	---	29.66	200.0	V	350.0	-8.0	54.00	24.34
3718.300000	38.76	---	200.0	V	350.0	-8.0	74.00	35.24
4874.000000	---	32.11	150.0	V	186.0	-5.4	54.00	21.89
4874.000000	40.04	---	150.0	V	186.0	-5.4	74.00	33.96
8301.500000	---	38.28	150.0	V	249.0	1.5	54.00	15.72
8301.500000	47.57	---	150.0	V	249.0	1.5	74.00	26.43
17558.000000	---	44.65	200.0	H	29.0	8.9	54.00	9.35
17558.000000	54.36	---	200.0	H	29.0	8.9	74.00	19.64

High Channel: 2462MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1112.200000	---	26.72	150.0	V	143.0	-18.5	54.00	27.28
1112.200000	32.36	---	150.0	V	143.0	-18.5	74.00	41.64
1793.900000	---	30.19	200.0	V	168.0	-15.2	54.00	23.81
1793.900000	36.95	---	200.0	V	168.0	-15.2	74.00	37.05
4924.000000	---	33.04	150.0	V	168.0	-5.3	54.00	20.96
4924.000000	39.05	---	150.0	V	168.0	-5.3	74.00	34.95
8719.700000	---	38.58	150.0	H	178.0	1.6	54.00	15.42
8719.700000	47.00	---	150.0	H	178.0	1.6	74.00	27.00
13882.600000	---	42.00	200.0	H	84.0	6.0	54.00	12.00
13882.600000	50.50	---	200.0	H	84.0	6.0	74.00	23.50
17695.700000	52.68	---	200.0	V	191.0	8.9	74.00	21.32
17695.700000	---	47.66	200.0	V	191.0	8.9	54.00	6.34

802.11n-HT20 Mode:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Y-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Low Channel: 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1260.100000	35.60	---	150.0	V	244.0	-17.7	74.00	38.40
1260.100000	---	26.27	150.0	V	244.0	-17.7	54.00	27.73
1795.600000	37.42	---	150.0	V	270.0	-15.2	74.00	36.58
1795.600000	---	28.68	150.0	V	270.0	-15.2	54.00	25.32
4824.000000	41.20	---	200.0	H	161.0	-5.5	74.00	32.80
4824.000000	---	33.66	200.0	H	161.0	-5.5	54.00	20.34
7198.200000	45.97	---	150.0	V	21.0	0.4	74.00	28.03
7198.200000	---	37.30	150.0	V	21.0	0.4	54.00	16.70
11582.500000	---	38.67	150.0	V	340.0	3.0	54.00	15.33
11582.500000	48.47	---	150.0	V	340.0	3.0	74.00	25.53
17702.500000	54.29	---	150.0	V	21.0	8.9	74.00	19.71
17702.500000	---	47.75	150.0	V	21.0	8.9	54.00	6.25

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1260.100000	---	25.98	150.0	V	291.0	-17.7	54.00	28.02
1260.100000	33.93	---	150.0	V	291.0	-17.7	74.00	40.07
1790.500000	37.96	---	150.0	V	191.0	-15.3	74.00	36.04
1790.500000	---	29.77	150.0	V	191.0	-15.3	54.00	24.23
3499.000000	---	30.78	150.0	V	204.0	-8.8	54.00	23.22
3499.000000	39.31	---	150.0	V	204.0	-8.8	74.00	34.69
4976.300000	---	32.62	150.0	H	107.0	-5.2	54.00	21.38
4976.300000	39.71	---	150.0	H	107.0	-5.2	74.00	34.29
10514.900000	---	36.53	200.0	V	0.0	2.3	54.00	17.47
10514.900000	47.04	---	200.0	V	0.0	2.3	74.00	26.96
17716.100000	---	45.89	150.0	H	202.0	8.9	54.00	8.11
17716.100000	54.64	---	150.0	H	202.0	8.9	74.00	19.36

High Channel: 2462MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1261.800000	---	26.30	150.0	H	135.0	-17.7	54.00	27.70
1261.800000	34.12	---	150.0	H	135.0	-17.7	74.00	39.88
1793.900000	---	30.21	150.0	V	230.0	-15.2	54.00	23.79
1793.900000	37.54	---	150.0	V	230.0	-15.2	74.00	36.46
4924.000000	---	32.32	150.0	V	34.0	-5.3	54.00	21.68
4924.000000	40.64	---	150.0	V	34.0	-5.3	74.00	33.36
7239.000000	---	37.37	150.0	H	8.0	0.5	54.00	16.63
7239.000000	46.44	---	150.0	H	8.0	0.5	74.00	27.56
12976.500000	50.76	---	200.0	H	356.0	5.1	74.00	23.24
12976.500000	---	40.67	200.0	H	356.0	5.1	54.00	13.33
17733.100000	53.29	---	150.0	V	323.0	8.8	74.00	20.71
17733.100000	---	48.44	150.0	V	323.0	8.8	54.00	5.56

802.11n-HT40 Mode:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Y-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2422MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1260.100000	34.95	---	200.0	H	143.0	-17.7	74.00	39.05
1260.100000	---	26.19	200.0	H	143.0	-17.7	54.00	27.81
1793.900000	36.61	---	150.0	H	258.0	-15.2	74.00	37.39
1793.900000	---	31.29	150.0	H	258.0	-15.2	54.00	22.71
4844.000000	40.51	---	150.0	H	324.0	-5.5	74.00	33.49
4844.000000	---	33.04	150.0	H	324.0	-5.5	54.00	20.96
6256.400000	---	36.45	200.0	H	90.0	-2.1	54.00	17.55
6256.400000	44.17	---	200.0	H	90.0	-2.1	74.00	29.83
10635.600000	---	37.62	150.0	V	311.0	2.5	54.00	16.38
10635.600000	47.21	---	150.0	V	311.0	2.5	74.00	26.79
17704.200000	52.55	---	200.0	H	283.0	8.9	74.00	21.45
17704.200000	---	47.71	200.0	H	283.0	8.9	54.00	6.29

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1494.700000	35.61	---	150.0	V	33.0	-16.4	74.00	38.39
1494.700000	---	27.43	150.0	V	33.0	-16.4	54.00	26.57
1792.200000	37.03	---	150.0	V	270.0	-15.3	74.00	36.97
1792.200000	---	27.77	150.0	V	270.0	-15.3	54.00	26.23
4874.000000	41.01	---	200.0	H	288.0	-5.4	74.00	32.99
4874.000000	---	32.17	200.0	H	288.0	-5.4	54.00	21.83
7781.300000	---	37.86	200.0	V	217.0	1.5	54.00	16.14
7781.300000	46.67	---	200.0	V	217.0	1.5	74.00	27.33
13831.600000	52.05	---	200.0	V	179.0	6.0	74.00	21.95
13831.600000	---	41.24	200.0	V	179.0	6.0	54.00	12.76
17658.300000	---	47.16	200.0	V	217.0	8.9	54.00	6.84
17658.300000	55.31	---	200.0	V	217.0	8.9	74.00	18.69

High Channel: 2452MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1112.200000	33.81	---	150.0	H	218.0	-18.5	74.00	40.19
1112.200000	---	27.51	150.0	H	218.0	-18.5	54.00	26.49
1793.900000	38.72	---	200.0	V	231.0	-15.2	74.00	35.28
1793.900000	---	32.17	200.0	V	231.0	-15.2	54.00	21.83
4904.000000	---	32.89	150.0	V	166.0	-5.4	54.00	21.11
4904.000000	39.70	---	150.0	V	166.0	-5.4	74.00	34.30
6717.100000	---	35.23	150.0	V	179.0	-0.7	54.00	18.77
6717.100000	44.75	---	150.0	V	179.0	-0.7	74.00	29.25
10707.000000	---	38.37	150.0	H	348.0	2.6	54.00	15.63
10707.000000	47.74	---	150.0	H	348.0	2.6	74.00	26.26
17709.300000	53.05	---	200.0	V	103.0	8.9	74.00	20.95
17709.300000	---	47.81	200.0	V	103.0	8.9	54.00	6.19

18GHz-25GHz:

Pre-scan with 802.11b, 802.11g, 802.11n-HT20 and 802.11n-HT40 modes of operation in the X,Y and Z axes of orientation, the worst case **middle channel of 802.11b mode in Y-axis of orientation** was recorded

Horizontal

Date: 26.NOV.2020 13:36:46

Vertical

Date: 26.NOV.2020 13:39:55

Restricted Bands Emissions Test:

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)

Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)**802.11b Mode:** (Pre-scan in the X,Y and Z axes of orientation, the worst case Y-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.000000	---	40.39	200.0	V	349.0	-2.9	54.00	13.61
2390.000000	43.30	---	200.0	V	349.0	-2.9	74.00	30.70
High Channel: 2462MHz								
2483.500000	44.53	---	200.0	V	22.0	-2.5	74.00	29.47
2483.500000	---	40.43	200.0	V	22.0	-2.5	54.00	13.57

802.11g Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case Y-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.000000	43.81	---	200.0	H	23.0	-2.9	74.00	30.19
2390.000000	---	39.67	200.0	H	23.0	-2.9	54.00	14.33
High Channel: 2462MHz								
2483.500000	45.16	---	150.0	H	358.0	-2.5	74.00	28.84
2483.500000	---	41.40	150.0	H	358.0	-2.5	54.00	12.60

802.11n-HT20 Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case Y-axis of orientation was recorded)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.000000	43.87	---	150.0	H	14.0	-2.9	74.00	30.13
2390.000000	---	41.16	150.0	H	14.0	-2.9	54.00	12.84
High Channel: 2462MHz								
2483.500000	---	42.38	200.0	H	0.0	-2.5	54.00	11.62
2483.500000	46.13	---	200.0	H	0.0	-2.5	74.00	27.87

802.11n-HT40 Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case Y-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2422MHz								
2390.000000	46.20	---	150.0	H	358.0	-2.9	74.00	27.80
2390.000000	---	42.00	150.0	H	358.0	-2.9	54.00	12.00
High Channel: 2452MHz								
2483.500000	46.13	---	150.0	H	30.0	-2.5	74.00	27.87
2483.500000	---	41.29	150.0	H	30.0	-2.5	54.00	12.71

For BLE Mode:**Spurious Emission Test:****30MHz-1GHz**

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **low channel of operation in the Y axis of orientation** was recorded)



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
185.624050	28.92	100.0	V	260.0	-13.7	43.50	14.58
282.642950	31.06	100.0	H	30.0	-11.6	46.00	14.94
334.112400	33.40	200.0	V	220.0	-10.2	46.00	12.60
519.754550	38.77	100.0	V	103.0	-6.0	46.00	7.23
799.339000	28.55	100.0	V	2.0	-1.4	46.00	17.45
890.947100	37.43	100.0	H	35.0	0.0	46.00	8.57

1GHz-18GHz


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Y-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1112.200000	33.52	---	150.0	H	104.0	-18.5	74.00	40.48
1112.200000	---	27.64	150.0	H	104.0	-18.5	54.00	26.36
1793.900000	---	27.54	200.0	V	273.0	-15.2	54.00	26.46
1793.900000	37.16	---	200.0	V	273.0	-15.2	74.00	36.84
4804.000000	---	32.61	150.0	V	235.0	-5.6	54.00	21.39
4804.000000	39.44	---	150.0	V	235.0	-5.6	74.00	34.56
7968.300000	---	37.35	200.0	V	157.0	1.8	54.00	16.65
7968.300000	46.67	---	200.0	V	157.0	1.8	74.00	27.33
11565.500000	---	38.52	150.0	H	92.0	2.9	54.00	15.48
11565.500000	48.58	---	150.0	H	92.0	2.9	74.00	25.42
17714.400000	---	46.52	150.0	H	281.0	8.9	54.00	7.48
17714.400000	54.96	---	150.0	H	281.0	8.9	74.00	19.04

Middle Channel: 2440MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1260.100000	---	25.41	150.0	H	141.0	-17.7	54.00	28.59
1260.100000	34.12	---	150.0	H	141.0	-17.7	74.00	39.88
1793.900000	---	32.28	200.0	V	296.0	-15.2	54.00	21.72
1793.900000	37.73	---	200.0	V	296.0	-15.2	74.00	36.27
3988.600000	---	31.64	150.0	H	60.0	-7.0	54.00	22.36
3988.600000	40.03	---	150.0	H	60.0	-7.0	74.00	33.97
4880.000000	---	31.49	200.0	V	90.0	-5.4	54.00	22.51
4880.000000	40.17	---	200.0	V	90.0	-5.4	74.00	33.83
13253.600000	---	41.36	150.0	V	130.0	5.5	54.00	12.64
13255.300000	50.76	---	150.0	V	130.0	5.5	74.00	23.24
17728.000000	---	46.05	200.0	V	296.0	8.8	54.00	7.95
17728.000000	55.04	---	200.0	V	296.0	8.8	74.00	18.96

High Channel: 2480MHz

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1112.200000	---	27.35	150.0	H	322.0	-18.5	54.00	26.65
1112.200000	33.05	---	150.0	H	322.0	-18.5	74.00	40.95
1790.500000	---	28.53	150.0	V	238.0	-15.3	54.00	25.47
1790.500000	36.84	---	150.0	V	238.0	-15.3	74.00	37.16
4960.000000	---	33.65	200.0	V	225.0	-5.3	54.00	20.35
4960.000000	41.86	---	200.0	V	225.0	-5.3	74.00	32.14
7801.700000	---	36.96	150.0	V	104.0	1.5	54.00	17.04
7801.700000	47.97	---	150.0	V	104.0	1.5	74.00	26.03
13899.600000	---	41.21	150.0	V	200.0	6.0	54.00	12.79
13899.600000	50.77	---	150.0	V	200.0	6.0	74.00	23.23
17764.800000	---	47.20	200.0	H	225.0	8.8	54.00	6.80
17765.400000	54.82	---	200.0	H	225.0	8.8	74.00	19.18

18GHz-25GHz


(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **low** channel of operation in the **Y** axis of orientation was recorded)

Horizontal



Date: 25.AUG.2020 14:32:35

Vertical



Date: 25.AUG.2020 14:44:10

Restricted Bands Emissions Test:

(Pre-scan in the X,Y and Z axes of orientation, the worst case **Y-axis of orientation** was recorded)

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)


Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)

Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.000000	42.48	---	150.0	V	10.0	-2.9	74.00	31.52
2390.000000	---	38.37	200.0	V	10.0	-2.9	54.00	15.63
High Channel: 2480MHz								
2483.500000	43.35	---	200.0	V	274.0	-2.5	74.00	30.65
2483.500000	---	39.67	150.0	V	274.0	-2.5	54.00	14.33

Transmitting simultaneously test:**30MHz-1GHz**


(The worst case Band 12 of LTE, 802.11b low Channel of 2.4G Wi-Fi mode transmitting simultaneously in Y-axis of orientation was recorded)



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	QuasiPeak (dB μ V/m)	Height (cm)	Polar (H/V)				
186.847500	29.75	200.0	V	120.0	-12.5	43.50	13.75
283.116400	31.26	100.0	V	25.0	-11.7	46.00	14.74
334.207550	34.77	200.0	V	162.0	-10.2	46.00	11.23
519.812350	38.89	200.0	V	186.0	-5.9	46.00	7.11
593.458300	36.35	200.0	H	286.0	-5.6	46.00	9.65
890.700350	39.90	200.0	V	150.0	0.1	46.00	6.10

1GHz-18GHz


(The worst case Band 12 of LTE, 802.11b low Channel of 2.4G Wi-Fi mode transmitting simultaneously in Y-axis of orientation was recorded))




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1433.500000	---	20.93	150.0	V	0.0	-17.5	54.00	33.07
1433.500000	31.42	---	200.0	V	14.0	-17.5	74.00	42.58
3774.400000	---	27.59	150.0	H	31.0	-8.2	54.00	26.41
3774.400000	37.33	---	150.0	H	31.0	-8.2	74.00	36.67
4823.300000	---	30.43	150.0	H	215.0	-4.3	54.00	23.57
4823.300000	38.32	---	150.0	V	259.0	-4.3	74.00	35.68
6917.700000	---	33.49	200.0	V	272.0	1.3	54.00	20.51
6917.700000	43.72	---	200.0	V	272.0	1.3	74.00	30.28
10756.300000	---	37.37	150.0	V	305.0	4.9	54.00	16.63
10756.300000	45.70	---	200.0	V	345.0	4.9	74.00	28.30
17454.300000	---	43.79	150.0	V	305.0	8.9	54.00	10.21
17454.300000	52.97	---	150.0	V	305.0	8.9	74.00	21.03

18GHz-25GHz:

((The worst case Band 12 of LTE, 802.11b low Channel of 2.4G Wi-Fi mode transmitting simultaneously in Y-axis of orientation was recorded))

Vertical


Date: 9.DEC.2020 08:20:37

Horizontal


Date: 9.DEC.2020 08:24:51

Conducted Spurious Emissions at Antenna Port


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




802.11n-HT40 Mode Low Channel




802.11n-HT40 Mode Middle Channel




802.11n-HT40 Mode High Channel




BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

Temperature:	25.4 °C
Relative Humidity:	52 %
ATM Pressure:	101.3 kPa

The testing was performed by Chao Gao on 2020-08-17.

Test Result: Compliant.

EUT operation mode: Transmitting

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
802.11b Mode			
Low	2412	10.100	≥ 0.5
Middle	2437	10.110	≥ 0.5
High	2462	10.120	≥ 0.5
802.11g Mode			
Low	2412	16.593	≥ 0.5
Middle	2437	16.603	≥ 0.5
High	2462	16.613	≥ 0.5
802.11n-HT20 Mode			
Low	2412	17.796	≥ 0.5
Middle	2437	17.806	≥ 0.5
High	2462	17.816	≥ 0.5
802.11n-HT40 Mode			
Low	2422	36.553	≥ 0.5
Middle	2437	36.553	≥ 0.5
High	2452	36.553	≥ 0.5
BLE Mode			
Low	2402	0.764	≥ 0.5
Middle	2440	0.764	≥ 0.5
High	2480	0.764	≥ 0.5

Delta 1 [T1] 0.16 dB

Ref Lvl 20 dBm

RBW 100 kHz

SWT 10 ms

RF Att 30 dB

Unit dBm

10.5 dB Offset

D1 4.91 dBm

D2 -1.09 dBm

1MAX

IN1 1MA

Center 2.412 GHz

Span 40 MHz

4 MHz/

Date: 17. AUG. 2020 10:23:31

Delta 1 [T1] 0.09 dB
 RBW 100 kHz RF Att 30 dB
 VBW 300 kHz
 Ref Lvl 20 dBm 10.11022044 MHz SWT 10 ms Unit dBm

10.5 dB Offset
 -D1 5.28 dBm
 -D2 -0.72 dBm
 1MAX
 IN1 IMA

Center 2.437 GHz 4 MHz/ Span 40 MHz

Date: 17.AUG.2020 10:26:06

Delta 1 [T1] 0.00 dB

RBW 100 kHz RF Att 30 dB

Ref Lvl 20 dBm 10.12024048 MHz

SWT 10 ms Unit dBm

10.5 dB Offset

D1 5.54 dBm

D2 0.46 dBm

1MAX

▼1 [T1] -0.06 dBm

▲1 [T1] 0.00 dB

10.12024048 MHz

IN1 1MA

Center 2.462 GHz 4 MHz/ Span 40 MHz

Date: 17. AUG. 2020 10:27:46

Delta 1 [T1]

RBW 100 kHz RF Att 30 dB

Ref Lvl 0.25 dB

20 dBm 16.59318637 MHz

SWT 10 ms Unit dBm

10.5 dB Offset

▼1 [T1] -12.25 dBm

▲1 [T1] 0.25 dBm

2.40370341 GHz

16.59318637 MHz

-D1 -5.72 dBm

-D2 -11.72 dBm

1MAX

IN1 1MAX


Center 2.412 GHz

4 MHz/


Span 40 MHz

Date: 17. AUG. 2020 10:18:43


802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




802.11n-HT40 Mode Low Channel




802.11n-HT40 Mode Middle Channel




802.11n-HT40 Mode High Channel




BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, Compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

For Wi-Fi:

According to ANSI C63.10-2013 sub-clause 11.9.1.3


The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.



For BLE:

According to ANSI C63.10-2013 sub-clause 11.9.1.1

1. Set the RBW $\geq$ DTS bandwidth.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 3 \times$ RBW
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.



Test Data**Environmental Conditions**

Temperature:	25.4 °C
Relative Humidity:	52 %
ATM Pressure:	101.3 kPa

The testing was performed by Chao Gao on 2020-08-17.

Test Result: Compliant.

EUT operation mode: Transmitting

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
802.11b Mode				
Low	2412	19.76	30	Pass
Middle	2437	20.12	30	Pass
High	2462	20.03	30	Pass
802.11g Mode				
Low	2412	16.90	30	Pass
Middle	2437	17.18	30	Pass
High	2462	17.41	30	Pass
802.11n-HT20 Mode				
Low	2412	16.57	30	Pass
Middle	2437	17.01	30	Pass
High	2462	17.34	30	Pass
802.11n-HT40 Mode				
Low	2422	16.52	30	Pass
Middle	2437	16.81	30	Pass
High	2452	16.95	30	Pass
BLE Mode				
Low	2402	1.59	30	Pass
Middle	2440	1.27	30	Pass
High	2480	1.06	30	Pass

Marker 1 [T1]

Ref Lvl 30 dBm

1.59 dBm

RBW 1 MHz

RF Att 30 dB

VSW 3 MHz

SWT 5 ms

Unit dBm

10.5 dB Offset

▼1 [T1]

1.59 dBm

2.40205711 GHz

1MAX

IN1 1MA

Center 2.402 GHz

300 kHz/

Span 3 MHz

Date: 17.AUG.2020 13:12:05

Marker 1 [T1]

Ref Lvl 30 dBm

Att 30 dB

RBW 1 MHz

VBW 3 MHz

SWT 5 ms

Unit dBm

10.5 dB Offset

▼1 [T1]

1.27 dBm

2.44008116 GHz

1MAX

IN1 1MA


Center 2.4 GHz

300 kHz/

Span 3 MHz

Date: 17.AUG.2020 13:13:17

BLE Mode High Channel



FCC §15.247(d) – BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	25.4 °C
Relative Humidity:	52 %
ATM Pressure:	101.3 kPa


The testing was performed by Chao Gao on 2020-08-17

Test Result: Compliant.


802.11b Mode Left Side




802.11g Mode Left Side




802.11g Mode Right Side




802.11n-HT20 Mode Left Side




802.11n-HT20 Mode Right Side




802.11n-HT40 Mode Left Side




802.11n-HT40 Mode Right Side



BLE Mode Left Side



BLE Mode Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

1. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
2. Set the VBW $\geq 3 \times \text{RBW}$.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions

Temperature:	25.4 °C
Relative Humidity:	52 %
ATM Pressure:	101.3 kPa


The testing was performed by Chao Gao on 2020-08-17

Test Result: Compliant.


EUT operation mode: Transmitting

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b Mode			
Low	2412	-14.66	≤ 8
Middle	2437	-14.11	≤ 8
High	2462	-14.02	≤ 8
802.11g Mode			
Low	2412	-20.68	≤ 8
Middle	2437	-20.11	≤ 8
High	2462	-19.61	≤ 8
802.11n-HT20 mode			
Low	2412	-20.43	≤ 8
Middle	2437	-20.09	≤ 8
High	2462	-19.54	≤ 8
802.11n-HT40 mode			
Low	2422	-22.26	≤ 8
Middle	2437	-20.06	≤ 8
High	2452	-19.81	≤ 8
BLE Mode			
Low	2402	-13.57	≤ 8
Middle	2440	-13.89	≤ 8
High	2480	-14.04	≤ 8


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




802.11n-HT40 Mode Low Channel




802.11n-HT40 Mode Middle Channel




802.11n-HT40 Mode High Channel




BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



Declarations

1: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

2: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

3: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

4: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

5: This report cannot be reproduced except in full, without prior written approval of the Company.

6: This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

******* END OF REPORT *******