



M. Flom Associates, Inc. - Global Compliance Center

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

Date: July 12, 2002

Federal Communications Commission
Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: Kenwood Communications Corporation
Equipment: TKR-840-2
FCC ID: ALH30643120
FCC Rules: 90, CLASS II PERMISSIVE CHANGE

Gentlemen:

On behalf of the Applicant, enclosed please find Application Form 731, Engineering Test Report and all pertinent documentation, the whole for approval of the referenced equipment as shown i.e.:

- a) Application Form
- b) Test Report
- c) Filing Fees
- d) Copy of Original Grant
- e) Expository Statement

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

A handwritten signature in black ink, reading 'M. Flom P. Eng.' with a stylized, cursive script.

Morton Flom, P. Eng.

enclosure(s)
cc: Applicant
MF/cvr



M. Flom Associates, Inc. - Global Compliance Center

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

C L A S S I I P E R M I S S I V E C H A N G E

of

FCC ID: ALH30643120

MODEL: TKR-840-2

to

FEDERAL COMMUNICATIONS COMMISSION

Rule Part(s) 90

DATE OF REPORT: July 12, 2002

ON THE BEHALF OF THE APPLICANT:

Kenwood Communications Corporation

AT THE REQUEST OF:

P.O. JBF-001

Kenwood Communications Corporation
Technology Park at Johns Creek
3975 Johns Creek Court #300
Suwanee, GA 30024

Attention of:

Joel E. Berger, Research & Development
JBerger@kenwoodusa.com
(678) 474-4722; FAX: -4731

SUPERVISED BY:

A handwritten signature in black ink that reads 'M. Flom P. Eng.' The signature is written in a cursive, flowing style.

Morton Flom, P. Eng.

THE APPLICANT HAS BEEN CAUTIONED AS TO THE FOLLOWING:

15.21 INFORMATION TO USER.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) SPECIAL ACCESSORIES.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

TABLE OF CONTENTS

<u>RULE</u>	<u>DESCRIPTION</u>	<u>PAGE</u>
	Test Report	1
	Expository Statement for Permissive Changes	2
2.1033(c)	General Information Required	3
2.1033(c)(14)	Rule Summary	6
	Standard Test Conditions and Engineering Practices	7
2.1046(a)	Carrier Output Power (Conducted)	8
2.1046(a)	ERP Carrier Power (Radiated)	10
2.1053(a)	Field Strength of Spurious Radiation	14
2.1049(c)(1)	Emission Masks (Occupied Bandwidth)	18
90.214	Transient Frequency Behavior	25
2.202(g)	Necessary Bandwidth and Emission Bandwidth	31

PAGE NO.

1 of 31.

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a)

TEST REPORT

b) Laboratory: M. Flom Associates, Inc.
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107
(Canada: IC 2044) Chandler, AZ 85225

c) Report Number: d0270008

d) Client: Kenwood Communications Corporation
Technology Park at Johns Creek
3975 Johns Creek Court #300
Suwanee, GA 30024

e) Identification: TKR-840-2
FCC ID: ALH30643120
EUT Description: UHF FM Repeater

f) EUT Condition: Not required unless specified in individual tests.

g) Report Date: July 12, 2002
EUT Received: July 2, 2002

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Uncertainty: In accordance with MFA internal quality manual.

m) Supervised by:



Morton Flom, P. Eng.

n) Results: The results presented in this report relate only to the item tested.

o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

PAGE NO. 2 of 31.

EXPOSITORY STATEMENT
PERMISSIVE CHANGE

APPLICANT: Kenwood Communications Corporation

FCC ID: ALH30643120

The applicant has made design changes/improvements to the originally FCC approved equipment.

Data contained herein confirms that a Permissive Change to the unit has been effected and that the performance of the unit is at or better than the levels originally reported to the commission.

The following changes/improvements have been made as per attached letter of Explanation:

No circuit changes were involved. Only the addition of data transmission.

PAGE NO. 3 of 31.

LIST OF GENERAL INFORMATION REQUIRED FOR CERTIFICATIONIN ACCORDANCE WITH FCC RULES AND REGULATIONS,
VOLUME II, PART 2 AND TO

90, 90.210

Sub-part 2.1033

(c)(1): NAME AND ADDRESS OF APPLICANT:Kenwood Communications Corporation
Technology Park at Johns Creek
3975 Johns Creek Court #300
Suwanee, GA 30024MANUFACTURER:Kenwood Corporation
14-6, Dogenzaka 1-Chome
Shibuya-ku, Tokyo 150, Japan(c)(2): FCC ID: ALH30643120MODEL NO: TKR-840-2(c)(3): INSTRUCTION MANUAL(S):


PLEASE SEE ATTACHED EXHIBITS

(c)(4): TYPE OF EMISSION: 16K0F3E, 11K0F3E, 16K0F1D,
11K0F1D(c)(5): FREQUENCY RANGE, MHz: 480 to 512(c)(6): POWER RATING, Watts: 0.1 to 5
Switchable x Variable N/AFCC GRANT NOTE: BB - Power output
continuously variable from
value listed to less than
0.5 watts.(c)(7): MAXIMUM POWER RATING, Watts: 300DUT RESULTS: Passes x Fails

PAGE NO.

4 of 31.

M. Flom Associates, Inc. is accredited by the American Association for Laboratory Accreditation (A2LA) as shown in the scope below.



"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, or which have been undertaken by a subcontractor that is not A2LA accredited, such data would not covered by this laboratory's A2LA accreditation.

PAGE NO. 5 of 31.

Subpart 2.1033 (continued)

(c)(8): VOLTAGES & CURRENTS IN ALL ELEMENTS IN FINAL R. F. STAGE,
INCLUDING FINAL TRANSISTOR OR SOLID STATE DEVICE:

COLLECTOR CURRENT, A = per manual
COLLECTOR VOLTAGE, Vdc = per manual
SUPPLY VOLTAGE, Vdc = 13.8

(c)(9): TUNE-UP PROCEDURE:

PLEASE SEE ATTACHED EXHIBITS

(c)(10): CIRCUIT DIAGRAM/CIRCUIT DESCRIPTION:

Including description of circuitry & devices provided for
determining and stabilizing frequency, for suppression of
spurious radiation, for limiting modulation and limiting
power.

PLEASE SEE ATTACHED EXHIBITS

(c)(11): LABEL INFORMATION:

PLEASE SEE ATTACHED EXHIBITS

(c)(12): PHOTOGRAPHS:

PLEASE SEE ATTACHED EXHIBITS

(c)(13): DIGITAL MODULATION DESCRIPTION:

 ATTACHED EXHIBITS
 X N/A

(c)(14): TEST AND MEASUREMENT DATA:

FOLLOWS

PAGE NO.

6 of 31.

Sub-part
2.1033(c)(14):TEST AND MEASUREMENT DATA

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- _____ 21 - Domestic Public Fixed Radio Services
- _____ 22 - Public Mobile Services
- _____ 22 Subpart H - Cellular Radiotelephone Service
- _____ 22.901(d) - Alternative technologies and auxiliary services
- _____ 23 - International Fixed Public Radiocommunication services
- _____ 24 - Personal Communications Services
- _____ 74 Subpart H - Low Power Auxiliary Stations
- _____ 80 - Stations in the Maritime Services
- _____ 80 Subpart E - General Technical Standards
- _____ 80 Subpart F - Equipment Authorization for Compulsory Ships
- _____ 80 Subpart K - Private Coast Stations and Marine Utility Stations
- _____ 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- _____ 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- _____ 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- _____ 80 Subpart V - Emergency Position Indicating Radiobeacons (EPIRB'S)
- _____ 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- _____ 80 Subpart X - Voluntary Radio Installations
- _____ 87 - Aviation Services
- x 90 - Private Land Mobile Radio Services
- _____ 94 - Private Operational-Fixed Microwave Service
- _____ 95 Subpart A - General Mobile Radio Service (GMRS)
- _____ 95 Subpart C - Radio Control (R/C) Radio Service
- _____ 95 Subpart D - Citizens Band (CB) Radio Service
- _____ 95 Subpart E - Family Radio Service
- _____ 95 Subpart F - Interactive Video and Data Service (IVDS)
- _____ 97 - Amateur Radio Service
- _____ 101 - Fixed Microwave Services

PAGE NO.

7 of 31.

STANDARD TEST CONDITIONS
and
ENGINEERING PRACTICES

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2000 Draft, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

PAGE NO. 8 of 31.
NAME OF TEST: Carrier Output Power (Conducted)
SPECIFICATION: 47 CFR 2.1046(a)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.1
TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE


1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an R. F. Power Meter.
2. Measurement accuracy is $\pm 3\%$.

MEASUREMENT RESULTS
(worst case)

FREQUENCY OF CARRIER, MHz = 496, 480, 512


POWER SETTING	R. F. POWER, WATTS
Low	0.1
High	5

PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

TRANSMITTER POWER CONDUCTED MEASUREMENTS

TEST 1: R. F. POWER OUTPUT
 TEST 2: FREQUENCY STABILITY



Asset	Description (as applicable)	s/n
(1)	<u>COAXIAL ATTENUATOR</u>	
i00122	Narda 766-10	7802
i00123	Narda 766-10	7802A
i00069	Bird 8329 (30 dB)	1006
i00113	Sierra 661A-3D	1059
(2)	<u>POWER METERS</u>	
i00014	HP 435A	1733A05836
i00039	HP 436A	2709A26776
i00020	HP 8901A POWER MODE	2105A01087
(3)	<u>FREQUENCY COUNTER</u>	
i00042	HP 5383A	1628A00959
i00019	HP 5334B	2704A00347
i00020	HP 8901A FREQUENCY MODE	2105A01087

PAGE NO. 10 of 31.


NAME OF TEST: ERP Carrier Power (Radiated)

SPECIFICATION: TIA/EIA 603A (Substitution Method)

2.2.17.1 Definition: The average radiated power of a licensed device is the equivalent power required, when delivered to a half-wave dipole or horn antenna, to produce at a distant point the same average received power as produced by the licensed device.

2.2.17.2 Method of Measurement:

a) Connect the equipment as illustrated. Place the transmitter to be tested on the turntable in the standard test site.



b) Raise and lower the test antenna from 1m to 6 m with the transmitter facing the antenna and record the highest received signal in dB as LVL.

c) Repeat step b) for seven additional readings at 45° interval positions of the turntable.

d) Replace the transmitter under test with a half-wave or horn vertically polarized antenna. The center of the antenna should be at the same location as the transmitter under test. Connect the antenna to a signal generator with a known output power and record the path loss in dB or LOSS.

e) Calculate the average radiated output power from the readings in step c) and d) by the following:

$$\text{average radiated power} = 10 \log_{10} \Sigma 10(\text{LVL} - \text{LOSS})/10 \text{ (dBm)}$$

	480 MHz		496 MHz		512 MHz	
	LVL, dbm	Path Loss, db	LVL, dbm	Path Loss, db	LVL, dbm	Path Loss, db
0°	33.4	1.1	33.5	1.0	33.8	0.8
45°	34.0	1.1	34.7	1.0	36.5	0.8
90°	35.4	1.1	35.3	1.0	33.3	0.8
135°	33.1	1.1	32.8	1.0	31.4	0.8
180°	33.8	1.1	32.6	1.0	31.8	0.8
225°	34.5	1.1	32.1	1.0	31.0	0.8
270°	32.0	1.1	35.5	1.0	30.2	0.8
315°	36.1	1.1	35.1	1.0	30.9	0.8


	480 MHz	496 MHz	512 MHz
Av. Radiated Power:	35.14 dbm	34.95 dbm	33.16 dbm

PAGE NO.

11 of 31.

TRANSMITTER SPURIOUS EMISSION

TEST A. OCCUPIED BANDWIDTH (IN-BAND SPURIOUS)
 TEST B. OUT-OF-BAND SPURIOUS



Asset Description (as applicable)	s/n
(1) <u>AUDIO OSCILLATOR/GENERATOR</u>	
i00010 HP 204D	1105A04683
i00017 HP 8903A	2216A01753
i00012 HP 3312A	1432A11250
(2) <u>COAXIAL ATTENUATOR</u>	
i00122 Narda 766-10	7802
i00123 Narda 766-10	7802A
i00069 Bird 8329 (30 dB)	1006
i00113 Sierra 661A-3D	1059
(3) <u>FILTERS; NOTCH, HP, LP, BP</u>	
i00126 Eagle TNF-1	100-250
i00125 Eagle TNF-1	50-60
i00124 Eagle TNF-1	250-850
(4) <u>SPECTRUM ANALYZER</u>	
i00048 HP 8566B	2511A01467
i00029 HP 8563E	3213A00104


PAGE NO. 12 of 31.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)

LIMIT(S), dBc $-(50+10 \times \text{LOG } P) = -40$ (0.1 Watts) $-(50+10 \times \text{LOG } P) = -57$ (5 Watts)

STATE: 1:Low Power g0270070: 2002-Jul-10 Wed 11:01:00

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	MARGIN, dB
480.000000	960.005500	-51.9	-71.9	-31.9
496.000000	992.007000	-58.1	-78.1	-38.1
512.000000	1024.002500	-58.6	-78.6	-38.6
480.000000	1440.007500	-43.6	-63.6	-23.6
496.000000	1488.001000	-48.8	-68.8	-28.8
512.000000	1536.003500	-51.2	-71.2	-31.2
480.000000	1920.008000	-53.8	-73.8	-33.8
496.000000	1984.004500	-54.3	-74.3	-34.3
512.000000	2048.003500	-58.8	-78.8	-38.8
480.000000	2400.011500	-60.5	-80.5	-40.5
496.000000	2479.997000	-61.1	-81.1	-41.1
512.000000	2560.227800	-62.7	-82.7	-42.7
480.000000	2879.807800	-62.9	-82.9	-42.9
496.000000	2976.195700	-63.4	-83.4	-43.4
512.000000	3071.796300	-63.8	-83.8	-43.8
480.000000	3360.244300	-64.2	-84.2	-44.2
496.000000	3471.909400	-63.2	-83.2	-43.2
512.000000	3583.794800	-63.5	-83.5	-43.5
480.000000	3839.828800	-63.6	-83.6	-43.6
496.000000	3968.014500	-63.2	-83.2	-43.2
512.000000	4095.816300	-63.8	-83.8	-43.8
480.000000	4319.784700	-64	-84	-44
496.000000	4463.810800	-64.2	-84.2	-44.2
512.000000	4608.087100	-64	-84	-44
480.000000	4799.947400	-63.5	-83.5	-43.5
496.000000	4959.904400	-64.3	-84.3	-44.3
512.000000	5120.033500	-63.8	-83.8	-43.8
480.000000	5279.777200	-63.7	-83.7	-43.7
496.000000	5455.763700	-62.9	-82.9	-42.9
512.000000	5632.054100	-62.7	-82.7	-42.7
480.000000	5760.221300	-63.5	-83.5	-43.5
496.000000	5952.197400	-58.4	-78.4	-38.4
512.000000	6143.870900	-57.3	-77.3	-37.3
480.000000	6240.103200	-58	-78	-38
496.000000	6448.050900	-57.5	-77.5	-37.5
512.000000	6656.190500	-56.8	-76.8	-36.8
480.000000	6719.858900	-58.1	-78.1	-38.1
496.000000	6944.046400	-57.7	-77.7	-37.7
512.000000	7167.958100	-58	-78	-38
480.000000	7200.104700	-58.2	-78.2	-38.2
496.000000	7439.914700	-58.3	-78.3	-38.3
512.000000	7679.853900	-58.6	-78.6	-38.6



PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

PAGE NO. 13 of 31.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)

LIMIT(S), dBc $-(50+10 \times \text{LOG } P) = -40$ (0.1 Watts) $-(50+10 \times \text{LOG } P) = -57$ (5 Watts)

STATE: 2:High Power g0270069: 2002-Jul-10 Wed 10:51:00

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	MARGIN, dB
480.000000	960.019000	-41.7	-78.6	-21.7
496.000000	992.116100	-42.7	-79.6	-22.7
512.000000	1023.879900	-43.2	-80.1	-23.2
480.000000	1439.994000	-39.1	-76	-19.1
496.000000	1488.004500	-41.3	-78.2	-21.3
512.000000	1536.141200	-41.8	-78.7	-21.8
480.000000	1919.833800	-41.7	-78.6	-21.7
496.000000	1984.008000	-42.6	-79.5	-22.6
512.000000	2048.178700	-41.5	-78.4	-21.5
480.000000	2400.057600	-41.3	-78.2	-21.3
496.000000	2480.201700	-41.3	-78.2	-21.3
512.000000	2559.865300	-41.8	-78.7	-21.8
480.000000	2879.872300	-43.9	-80.8	-23.9
496.000000	2976.180700	-44.3	-81.2	-24.3
512.000000	3071.840800	-45	-81.9	-25
480.000000	3359.795300	-44.3	-81.2	-24.3
496.000000	3472.173200	-43.6	-80.5	-23.6
512.000000	3583.832300	-44.4	-81.3	-24.4
480.000000	3840.050100	-45.4	-82.3	-25.4
496.000000	3967.788700	-44.2	-81.1	-24.2
512.000000	4095.785700	-44.2	-81.1	-24.2
480.000000	4320.193200	-44.6	-81.5	-24.6
496.000000	4463.880900	-44.4	-81.3	-24.4
512.000000	4608.007500	-45	-81.9	-25
480.000000	4799.765200	-44.4	-81.3	-24.4
496.000000	4959.872800	-44.2	-81.1	-24.2
512.000000	5120.097100	-43.7	-80.6	-23.7
480.000000	5280.199200	-43.7	-80.6	-23.7
496.000000	5455.801800	-44.1	-81	-24.1
512.000000	5632.076600	-44.1	-81	-24.1
480.000000	5759.975000	-44.1	-81	-24.1
496.000000	5952.062800	-37.3	-74.2	-17.3
512.000000	6144.235800	-38	-74.9	-18
480.000000	6239.883800	-38.7	-75.6	-18.7
496.000000	6447.845400	-38.2	-75.1	-18.2
512.000000	6656.051900	-39.1	-76	-19.1
480.000000	6719.772600	-37.6	-74.5	-17.6
496.000000	6943.828000	-37.6	-74.5	-17.6
512.000000	7168.137100	-36.9	-73.8	-16.9
480.000000	7199.963600	-38.4	-75.3	-18.4
496.000000	7440.003000	-37.2	-74.1	-17.2
512.000000	7680.032400	-38.8	-75.7	-18.8

PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

PAGE NO. 14 of 31.

NAME OF TEST: Field Strength of Spurious Radiation

SPECIFICATION: 47 CFR 2.1053(a)


GUIDE: ANSI/TIA/EIA-603-1992/2001, Paragraph 1.2.12 and Table 16, 47 CFR 22.917

MEASUREMENT PROCEDURE

1.2.12.1 Definition: Radiated spurious emissions are emissions from the equipment when transmitting into a non-radiating load on a frequency or frequencies which are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communications desired.

1.2.12.2 Method of Measurement


- A) Connect the equipment as illustrated
- B) Adjust the spectrum analyzer for the following settings:
 - 1) Resolution Bandwidth 100 kHz (<1 GHz), 1 MHz (> 1GHz).
 - 2) Video Bandwidth ≥ 3 times Resolution Bandwidth, or 30 kHz (22.917)
 - 3) Sweep Speed ≤ 2000 Hz/second
 - 4) Detector Mode = Mean or Average Power
- C) Place the transmitter to be tested on the turntable in the standard test site. The transmitter is transmitting into a non-radiating load which is placed on the turntable. The RF cable to this load should be of minimum length.



PAGE NO. 15 of 31.

NAME OF TEST: Field Strength of Spurious Radiation (Cont.)

- D) For each spurious measurement the test antenna should be adjusted to the correct length for the frequency involved. This length may be determined from a calibration ruler supplied with the equipment. Measurements shall be made from the lowest radio frequency generated in the equipment to the tenth harmonic of the carrier, except for the region close to the carrier equal to $\pm$ the test bandwidth (see section 1.3.4.4).
- E) For each spurious frequency, raise and lower the test antenna from 1 m to 4 m to obtain a maximum reading on the spectrum analyzer with the test antenna at horizontal polarity. Repeat this procedure to obtain the highest possible reading. Record this maximum reading.
- F) Repeat step E) for each spurious frequency with the test antenna polarized vertically.



- G) Reconnect the equipment as illustrated.
- H) Keep the spectrum analyzer adjusted as in step B).
- I) Remove the transmitter and replace it with a substitution antenna (the antenna should be half-wavelength for each frequency involved). The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground.

PAGE NO. 16 of 31.

NAME OF TEST: Field Strength of Spurious Radiation (Cont.)

- J) Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a non-radiating cable. With the antennas at both ends horizontally polarized and with the signal generator tuned to a particular spurious frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output.
- K) Repeat step J) with both antennas vertically polarized for each spurious frequency.
- L) Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps J) and K) by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna.
- M) The levels recorded in step L) are absolute levels of radiated spurious emissions in dBm. The radiated spurious emissions in dB can be calculated by the following:

Radiated spurious emissions dB =
 $10\log_{10}(\text{TX power in watts}/0.001) - \text{the levels in step l})$

NOTE: It is permissible that other antennas provided can be referenced to a dipole.

Test Equipment:


Asset Description (as applicable)	s/n	Cycle	Last Cal
Per ANSI C63.4-1992/2000 Draft, 10.1.4			
TRANSDUCER			
i00088 EMC0 3109-B 25MHz-300MHz	2336	12 mo.	Sep-01
i00065 EMC0 3301-B Active Monopole	2635	12 mo.	Sep-01
i00089 Aprel 2001 200MHz-1GHz	001500	12 mo.	Sep-01
i00103 EMC0 3115 1GHz-18GHz	9208-3925	12 mo.	Sep-01
AMPLIFIER			
i00028 HP 8449A	2749A00121	12 mo.	Mar-02
SPECTRUM ANALYZER			
i00029 HP 8563E	3213A00104	12 mo.	Jan-02
i00033 HP 85462A	3625A00357	12 mo.	Jan-02
i00048 HP 8566B	2511AD1467	6 mo.	Jan-02
MICROPHONE, ANTENNA PORT, AND CABELING			
Microphone	Yes/No <u>Y</u>	Cable Length <u>1.0</u> Meters	
Antenna Port Terminated	Yes/No <u>Y</u>	Load <u>N</u> Antenna Gain <u>0dBd</u>	
All Ports Terminated by	Load <u>Y</u>	Peripheral <u>N</u>	

PAGE NO. 17 of 31.

NAME OF TEST: Field Strength of Spurious Radiation
 g0270062: 2002-Jul-08 Mon 10:43:00
 STATE: 2:High Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	ERP, dBm	ERP, dbc
496.000000	992.007500	-31.1	≤ -66.4
496.000000	1488.007500	-29.4	≤ -66.4
496.000000	1984.006400	-43.2	≤ -66.4
496.000000	2480.018400	-44.1	≤ -66.4
496.000000	2976.012500	-48.4	≤ -66.4
496.000000	3472.010833	-48.2	≤ -66.4
496.000000	3968.001667	-52.7	≤ -66.4
496.000000	4464.008333	-55.3	≤ -66.4
496.000000	4960.011667	-52.8	≤ -66.4

SUPERVISED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO. 18 of 31.
NAME OF TEST: Emission Masks (Occupied Bandwidth)
SPECIFICATION: 47 CFR 2.1049(c)(1)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.11
TEST EQUIPMENT: As per previous page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.
2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for $\pm 2.5/\pm 1.25$ kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

19 of 31.


NAME OF TEST: Emission Masks (Occupied Bandwidth)
g0270064: 2002-Jul-10 Wed 10:14:00
STATE: 1:Low Power



POWER:
MODULATION:

LOW
NONE


PERFORMED BY:


Doug Noble, B.A.S. E.E.T.

PAGE NO.

20 of 31.


NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0270065: 2002-Jul-10 Wed 10:16:00
 STATE: 1:Low Power



POWER:
 MODULATION:

LOW
 RANDOM DATA @ 19.2 K/BITS
 PER SECOND
 MASK: B, VHF/UHF 25kHz,
 w/LPF


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

21 of 31.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g0270068: 2002-Jul-10 Wed 10:24:00
STATE: 1:Low Power



POWER:
MODULATION:

LOW
RANDOM DATA @ 19.2 K/BITS
PER SECOND
MASK: D, VHF/UHF 12.5kHz BW


PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

PAGE NO.

22 of 31.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g0270063: 2002-Jul-10 Wed 10:12:00
STATE: 2:High Power



POWER:
MODULATION:

HIGH
NONE


PERFORMED BY:


Doug Noble, B.A.S. E.E.T.

PAGE NO.

23 of 31.


NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0270066: 2002-Jul-10 Wed 10:18:00
 STATE: 2:High Power



POWER:
 MODULATION:

HIGH
 RANDOM DATA @ 19.2 K/BITS
 PER SECOND
 MASK: B, VHF/UHF 25kHz,
 w/LPF


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

24 of 31.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0270067: 2002-Jul-10 Wed 10:22:00
 STATE: 2:High Power



POWER:
 MODULATION:

HIGH
 RANDOM DATA @ 19.2 K/BITS
 PER SECOND
 MASK: D, VHF/UHF 12.5kHz BW

PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO. 25 of 31.

NAME OF TEST: Transient Frequency Behavior

SPECIFICATION: 47 CFR 90.214

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.19

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was setup as shown on the attached page, following TIA/EIA-603 steps a, b, and c as a *guide*.
2. The transmitter was turned on.
3. Sufficient attenuation was provided so that the transmitter carrier level measured at the output of the combiner was 40 dB below the maximum input level of the test receiver. This level was recorded as step f.
4. The transmitter was turned off.
5. An RF signal generator (1) modulated with a 1 kHz tone at either 25, 12.5, or 6.25 kHz deviation, and set to the same frequency as the assigned transmitter frequency, (2) was adjusted to a level -20 dB below the level recorded for step f, as measured at the output of the combiner. This level was then fixed for the remainder of the test and is recorded at step h.
6. The oscilloscope was setup using TIA/EIA-603 steps j and k as a guide, and to either 10 ms/div (UHF) or 5 ms/div (VHF).
7. The 30 dB attenuator was removed, the transmitter was turned on, and the level of the carrier at the output of the combiner was recorded as step l.
8. The carrier on-time as referenced in TIA/EIA-603 steps m, n, and o was captured and plotted. The carrier off-time as referenced in TIA/EIA-603 steps p, q, r, and s was captured and plotted.

LEVELS MEASURED:

<u>step f</u> , dBm	=	-3.4
<u>step h</u> , dBm	=	-45.1
<u>step l</u> , dBm	=	5.2




PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

PAGE NO.

26 of 31.


TRANSIENT FREQUENCY BEHAVIOR

Asset	Description (as applicable)	s/n
(1)	<u>ATTENUATOR</u> (Removed after 1st step)	
	i00112 Philco 30 dB	989
(2)	<u>ATTENUATOR</u>	
	i00112 Philco 30 dB	989
	i00172 Bird 30 dB	989
	i00122 Narda 10 dB	7802
	i00123 Narda 10 dB	7802A
	i00110 Kay Variable	145-387
(3)	<u>COMBINER</u>	
	i00154 4 x 25 Ω COMBINER	154
(4)	<u>CRYSTAL DETECTOR</u>	
	i00159 HP 8470B	1822A10054
(5)	<u>RF SIGNAL GENERATOR</u>	
	i00018 HP 8656A	2228A03472
	i00031 HP 8656A	2402A06180
	i00067 HP 8920A	3345U01242
(6)	<u>MODULATION ANALYZER</u>	
	i00020 HP 8901A	2105A01087
(7)	<u>SCOPE</u>	
	i00030 HP 54502A	2927A00209

PAGE NO.

27 of 31.

NAME OF TEST: Transient Frequency Behavior
 g0270071: 2002-Jul-10 Wed 11:57:00
 STATE: 2:High Power




Timebase Delay/Pos
 Main 10.0 ms/div 40.0000 ms Center
 Sensitivity Offset Probe
 Channel 1 275 mV/div 0.00000 V 1.000 :1
 Trigger mode :
 0A Negative Edge Of
 Trigger
 Chan2 = -24.000 mV (noise)
 Holdoff = 40.000

POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=12.5 kHz Deviation
 CARRIER ON TIME


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

28 of 31.

NAME OF TEST: Transient Frequency Behavior
 g0270072: 2002-Jul-10 Wed 11:58:00
 STATE: 2:High Power




Timebase Delay/Pos
 Main 10.0 ms/div -30.0000 ms Center
 Sensitivity Offset Probe
 Channel 1 275 mV/div 0.00000 V 1.000 :1
 Trigger mode :
 0A Positive Edge Of
 Trigger
 Chan2 = -175.000 mV (noise)
 Holdoff = 40.000

POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=12.5 kHz Deviation
 CARRIER OFF TIME


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

29 of 31.

NAME OF TEST: Transient Frequency Behavior
 g0270073: 2002-Jul-10 Wed 12:23:00
 STATE: 2:High Power



Timebase Delay/Pos
 Main 10.0 ms/div 40.0000 ms Center
 Sensitivity Offset Probe
 Channel 1 500 mV/div 0.00000 V 1.000 :1
 Trigger mode :
 0A Negative Edge Of
 Trigger
 Chan2 = -1.500 mV (noise)
 Holdoff = 40.000

POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=25 kHz Deviation
 CARRIER ON TIME


PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO.

30 of 31.

NAME OF TEST: Transient Frequency Behavior
 g0270074: 2002-Jul-10 Wed 12:24:00
 STATE: 2:High Power




Main Timebase Delay/Pos Center
 10.0 ms/div -30.0000 ms
 Channel 1 Sensitivity Offset Probe
 500 mV/div 0.00000 V 1.000 :1
 Trigger mode :
 00 Positive Edge Of
 Trigger
 Chan2 = -175.000 mV (noise)
 Holdoff = 40.000

POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=25 kHz Deviation
 CARRIER OFF TIME

PERFORMED BY:


 Doug Noble, B.A.S. E.E.T.

PAGE NO. 31 of 31.

NAME OF TEST: Necessary Bandwidth and Emission Bandwidth

SPECIFICATION: 47 CFR 2.202(g)

MODULATION = 16K0F3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	= 3
MAXIMUM DEVIATION (D), kHz	= 5
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B _N), kHz	= (2xM)+(2xDxK)
	= 16.0

MODULATION = 11K0F3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	= 3
MAXIMUM DEVIATION (D), kHz	= 2.5
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B _N), kHz	= (2xM)+(2xDxK)
	= 11.0

MODULATION = 16K0F1D

NECESSARY BANDWIDTH CALCULATION:


MAXIMUM MODULATION (M), kHz	= 3
MAXIMUM DEVIATION (D), kHz	= 5
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B _N), kHz	= (2xM)+(2xDxK)
	= 16.0

MODULATION = 11K0F1D

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	= 4
MAXIMUM DEVIATION (D), kHz	= 1
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B _N), kHz	= (2xM)+(2xDxK)

PERFORMED BY:


Doug Noble, B.A.S. E.E.T.

END OF TEST REPORT

TESTIMONIAL
AND
STATEMENT OF CERTIFICATION

THIS IS TO CERTIFY THAT:

1. THAT the application was prepared either by, or under the direct supervision of, the undersigned.
2. THAT the technical data supplied with the application was taken under my direction and supervision.
3. THAT the data was obtained on representative units, randomly selected.
4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

CERTIFYING ENGINEER:


Morton Flom, P. Eng.