



Highest Channel 99% Occupied Bandwidth



Highest Channel 26dBc Bandwidth kHz





TEST A.5: SPURIOUS EMISSIONS AT ANTENNA TERMINALS

I IMITO.	Product standard:	FCC Part 27 / IC RSS-199
LIMITS:	Test standard:	FCC §2.1051 and § 27.53 / RSS-199 Clause 4.5

LIMITS

According to specification, the power of emissions shall be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. P in watts.

At Po transmitting power of 2 watts (33 dBm), the specified minimum attenuation becomes 43+10log (Po). and the level in dBm relative to Po becomes:


Po (dBm) - [43 + 10 log (Po in watts)] = -13 dBm

TEST SETUP

The EUT RF output connector was connected to a spectrum analyzer and to the Universal Radio Communication Tester R&S CMW500 (selecting maximum transmission power of the EUT and different modes of modulation) using a 50-ohm attenuator and a power splitter.

The reading of the spectrum analyzer is corrected with the attenuation loss of connection between output terminal of EUT and input of the spectrum analyzer.

For LTE mode the configuration of Resource Blocks and modulation which is the worst case for conducted power was used.





TESTED SAMPLES:	S/01	
TESTED CONDITIONS MODES:	TC#01	
TEST RESULTS:	PASS	

Frequency range 30 MHz - 26 GHz

LTE QPSK MODULATION. BW = 5 MHz

Lowest Channel

The spurious signals were detected more than 10 dB below the limit in the frequency range.

Middle Channel

The spurious signals were detected more than 10 dB below the limit in the frequency range.

Highest Channel

The spurious signals were detected more than 10 dB below the limit in the frequency range.

LTE QPSK MODULATION. BW = 10 MHz

Lowest Channel

The spurious signals were detected more than 10 dB below the limit in the frequency range.

Middle Channel

The spurious signals were detected more than 10 dB below the limit in the frequency range.

Highest Channel

The spurious signals were detected more than 10 dB below the limit in the frequency range.

LTE QPSK MODULATION. BW = 15 MHz

Lowest Channel

The spurious signals were detected more than 10 dB below the limit in the frequency range.

Middle Channel

The spurious signals were detected more than 10 dB below the limit in the frequency range.

Highest Channel

The spurious signals were detected more than 10 dB below the limit in the frequency range.

LTE QPSK MODULATION. BW = 20 MHz

Lowest Channel

The spurious signals were detected more than 10 dB below the limit in the frequency range.

Middle Channel

The spurious signals were detected more than 10 dB below the limit in the frequency range.


Highest Channel

The spurious signals were detected more than 10 dB below the limit in the frequency range.




LTE QPSK MODULATION. BW = 5MHz

Lowest Channel




Middle Channel






Highest Channel




LTE QPSK MODULATION. BW = 10 MHz


Lowest Channel





Middle Channel









LTE QPSK MODULATION. BW = 15 MHz

Lowest Channel




Middle Channel






Highest Channel




LTE QPSK MODULATION. BW = 20 MHz


Lowest Channel





Middle Channel







TEST A.6: SPURIOUS EMISSIONS AT ANTENNA TERMINALS AT BLOCK EDGES

LIMITO	Product standard:	FCC Part 27 / IC RSS-199
LIMITS:	Test standard:	FCC § 27.53 / RSS- Clause 4.5

LIMITS

According to specification, the power of emissions shall be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. P in watts.

At Po transmitting power of 2 watts (33 dBm), the specified minimum attenuation becomes 43+10log (Po). and the level in dBm relative to Po becomes:

Po (dBm) - [43 + 10 log (Po in watts)] = -13 dBm


TEST SETUP

The EUT RF output connector was connected to a spectrum analyzer and to the Universal Radio Communication tester R&S CMW500 (selecting maximum transmission power of the EUT and different modes of modulation) using a 50 ohm attenuator and a power splitter.

The reading of the spectrum analyzer is corrected with the attenuation loss of connection between output terminal of EUT and input of the spectrum analyzer.

For LTE mode the configuration of modulation which is the worst case for conducted power was used.

As indicated in FCC part 27.53 (h) (3), in the 1 MHz bands immediately outside and adjacent to the licensee's frequency block or band, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.





TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	TC#01
TEST RESULTS:	PASS

RESULTS

.TS				
LTE QPSK MODULATION	RB=1 Offset =0 BW = 5 MHz	RB=1 Offset =0 BW = 10 MHz	RB=. Offset =0 BW = 15 MHz	RB=1 Offset =0 BW = 20 MHz
Maximum measured level at lowest Block Edge at antenna port (dBm)	-20.94	-32.65	-23.07	-21.32
LTE QPSK MODULATION	RB=25 Offset =0 BW = 5 MHz	RB=50 Offset =0 BW = 10 MHz	RB=75 Offset =0 BW = 15 MHz	RB=100 Offset =0 BW = 20 MHz
Maximum measured level at lowest Block Edge at antenna port (dBm)	-26.19	-31.71	-23.91	-22.7
LTE QPSK MODULATION	RB=1 Offset =0 BW = 5 MHz	RB=1 Offset =0 BW = 10 MHz	RB=1 Offset =0 BW = 15 MHz	RB=1 Offset =0 BW = 20 MHz
Maximum measured level at Highest Block Edge at antenna port (dBm)	-29.15	-33.12	-29.73	-33.09
LTE QPSK MODULATION	RB=25 Offset =0 BW = 5 MHz	RB=50 Offset =0 BW = 10 MHz	RB=75 Offset =0 BW = 15 MHz	RB=100 Offset =0 BW = 20 MHz
Maximum measured level at Highest Block Edge at antenna port (dBm)	-28.95	-31.45	-30.32	-31.93




LTE QPSK MODULATION. RB = 1. Offset = 0. BW = 5 MHz

Lowest Channel




LTE QPSK MODULATION. RB = 1. Offset = Max. BW = 5 MHz






LTE QPSK MODULATION. RB = 25. Offset = 0. BW = 5 MHz

Lowest Channel









LTE QPSK MODULATION. RB = 1. Offset = 0. BW = 10 MHz

Lowest Channel




LTE QPSK MODULATION. RB = 1. Offset = Max. BW = 10 MHz






LTE QPSK MODULATION. RB = 50. Offset = 0. BW = 10 MHz

Lowest Channel









LTE QPSK MODULATION. RB = 1. Offset = 0. BW = 15 MHz

Lowest Channel




LTE QPSK MODULATION. RB = 1. Offset = Max. BW = 15 MHz





LTE QPSK MODULATION. RB = 75. Offset = 0. BW = 15 MHz

Lowest Channel








LTE QPSK MODULATION. RB = 1. Offset = 0. BW = 20 MHz

Lowest Channel




LTE QPSK MODULATION. RB = 1. Offset = Max. BW = 20 MHz






LTE QPSK MODULATION. RB = 100. Offset = 0. BW = 20 MHz

Lowest Channel







TEST A.7: RADIATED EMISSIONS

_	Product standard:	FCC Part 27 / IC RSS-199
LIMITS:	Test standard:	FCC §2.1053 and §27.53 / RSS-199 Clause 4.5

LIMITS

According to specification, the power of emissions shall be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. P in watts.

At Po transmitting power of 2 watts (33 dBm), the specified minimum attenuation becomes 43+10log (Po). and the level in dBm relative to Po becomes:

Po (dBm) - [43 + 10 log (Po in watts)] = -13 dBm


TEST SETUP

The measurement was performed with the EUT inside an anechoic chamber. The spectrum was scanned from 30 MHz to at least the 10th harmonic of the highest frequency generated within the equipment.


The EUT was placed on a non-conductive stand at a 3-meter distance from the measuring antenna for measurements below 1 GHz and at 1-meter distance for measurements above 1 GHz.

Detected emissions were maximized at each frequency by rotating the EUT and adjusting the measuring antenna height and polarization. The maximum reading was recorded.

Radiated measurements < 1GHz



Radiated measurements > 1GHz





TESTED SAMPLES:	S/01	
TESTED CONDITIONS MODES:	TC#01	
TEST RESULTS:	PASS	

RESULTS

A preliminary scan determined the QPSK 20 MHz bandwidth as the worst case. The configuration of Resource Blocks which is the worst case for conducted power was used.

The following plots show the results for this configuration.


No spurious signal was found at less than 20dB respect to the limit in all the frequency ranges.

LTE QPSK MODULATION.

Lowest Channel. RB = 1. Offset = 0. BW = 15 MHz

FREQUENCY RANGE: 30-1000 MHz

Frequency	PK+_CLRWR	PK+_MAXH
(MHz)	(dBm)	(dBm)
30.097000	-63.23	-58.36
991.302333	-53.07	-48.45







TEST RESULTS (Cont): Lowest Channel

FREQUENCY RANGE: 1-18 GHz

Frequency	PK+_CLRWR	PK+_MAXH	Comment
(MHz)	(dBm)	(dBm)	
2500.866667	18.79	24.51	Fundamental
6969.000000	-40.19	-36.46	
12310.500000	-49.21	-42.96	
13369.000000	-46.05	-40.71	
17776.000000	-44.89	-38.14	










Middle Channel

Middle Channel RB = 1. Offset = 0. BW = 15 MHz

FREQUENCY RANGE: 30-1000 MHz

Frequency (MHz)	PK+_CLRWR (dBm)	PK+_MAXH (dBm)
30.291000	-63.50	-58.57
968.669000	-54.18	-47.80







TEST RESULTS (Cont): Middle Channel

FREQUENCY RANGE: 1-18 GHz

Frequency (MHz)	PK+_CLRWR (dBm)	PK+_MAXH (dBm)	Comment
1711.400000	-42.1	-36.3	
2536.133333	22.2	23.1	Fundamental










Highest Channel

Highest Channel RB = 1. Offset = 0. BW = 15 MHz

FREQUENCY RANGE: 30MHz-1 GHz

Frequency (MHz)	PK+_CLRWR (dBm)	PK+_MAXH (dBm)
30.032333	-64.74	-59.21
916.418333	-54.29	-48.39





TEST RESULTS (Cont):	High Channel
----------------------	--------------

FREQUENCY RANGE: 1-18 GHz

Frequency (MHz)	PK+_CLRWR (dBm)	PK+_MAXH (dBm)	Comment
2565.866667	18.47	24.78	Fundamental
6854.500000	-41.28	-36.03	
11715.000000	-49.34	-43.27	
14244.500000	-45.84	-40.67	
17694.000000	-43.50	-37.57	

