

FCC §15.247 (i), §2.1091 - RF Exposure

FCC ID: Y40-ENVOIS

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ², H ²or S (minutes)	
0.3-3.0	614	1.63	(100)*	6	
3.0-30	1842 / f	4.89 / f	(900 / f)*	6	
30-300	61.4	0.163	1.0	6	
300-1500			F/300	6	
1500-100,000			5	6	

Note: f is frequency in MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

TEST RESULTS

^{* =} Power density limit is applicable at frequencies greater than 100 MHz

^{* =} Plane-wave equivalent power density



ВТ

/ I					
		1Mbps			
Test Channel	Frequency	Peak Output Power	Peak Output Power		
	(MHz)	(dBm)	(mW)		
CH00	2402	-1.599	0.692		
CH39	2441	-1.319	0.738		
CH78	2480	-1.022	0.790		
		2Mbps			
CH00	2402	-1.585	0.694		
CH39	2441	-1.479	0.711		
CH78	2480	-0.713	0.849		
		3Mbps			
CH00	2402	-1.232	0.753		
CH39	2441	2441 -0.998 0.795			
CH78	2480	-0.853	0.822		

Mode	Range	Maximum peak output power (dBm)	Output power (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm²)	Limit of Power Density (S) (mW/ cm ²)	Result
BT	-2~0	0	1.0	1(1.26)	0.0003	1	Pass