

Channel	TX Channel 100	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	64.9 PK	74.0	-9.1	3.12 H	6	61.1	3.8
2	5460.00	53.9 AV	54.0	-0.1	3.12 H	6	50.1	3.8
3	#5469.14	67.5 PK	68.2	-0.7	3.12 H	6	63.6	3.9
4	*5500.00	116.4 PK			3.12 H	6	112.5	3.9
5	*5500.00	106.3 AV			3.12 H	6	102.4	3.9
6	11000.00	55.7 PK	74.0	-18.3	1.73 H	126	42.7	13.0
7	11000.00	43.8 AV	54.0	-10.2	1.73 H	126	30.8	13.0
8	#16500.00	46.5 PK	68.2	-21.7	1.51 H	157	31.9	14.6

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	58.4 PK	74.0	-15.6	1.11 V	45	54.6	3.8
2	5460.00	48.5 AV	54.0	-5.5	1.11 V	45	44.7	3.8
3	#5465.35	59.2 PK	68.2	-9.0	1.11 V	45	55.3	3.9
4	*5500.00	108.6 PK			1.11 V	45	104.7	3.9
5	*5500.00	102.0 AV			1.11 V	45	98.1	3.9
6	11000.00	51.8 PK	74.0	-22.2	1.49 V	162	38.8	13.0
7	11000.00	41.2 AV	54.0	-12.8	1.49 V	162	28.2	13.0
8	#16500.00	50.8 PK	68.2	-17.4	2.61 V	55	36.2	14.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 116	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	117.5 PK			2.07 H	357	113.7	3.8
2	*5580.00	109.8 AV			2.07 H	357	106.0	3.8
3	11160.00	59.0 PK	74.0	-15.0	1.65 H	83	45.9	13.1
4	11160.00	47.6 AV	54.0	-6.4	1.65 H	83	34.5	13.1
5	#16740.00	51.3 PK	68.2	-16.9	1.42 H	160	35.1	16.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	114.9 PK			1.10 V	41	111.1	3.8
2	*5580.00	106.0 AV			1.10 V	41	102.2	3.8
3	11160.00	56.1 PK	74.0	-17.9	1.53 V	126	43.0	13.1
4	11160.00	46.5 AV	54.0	-7.5	1.53 V	126	33.4	13.1
5	#16740.00	55.6 PK	68.2	-12.6	2.53 V	68	39.4	16.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 140	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	114.8 PK			3.01 H	3	110.8	4.0
2	*5700.00	107.1 AV			3.01 H	3	103.1	4.0
3	#5725.00	67.5 PK	68.2	-0.7	3.01 H	3	63.5	4.0
4	11400.00	59.0 PK	74.0	-15.0	1.65 H	102	45.8	13.2
5	11400.00	47.7 AV	54.0	-6.3	1.65 H	102	34.5	13.2
6	#17100.00	51.0 PK	68.2	-17.2	1.49 H	170	33.8	17.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	111.4 PK			1.04 V	36	107.4	4.0
2	*5700.00	103.3 AV			1.04 V	36	99.3	4.0
3	#5725.00	61.7 PK	68.2	-6.5	1.04 V	36	57.7	4.0
4	11400.00	56.6 PK	74.0	-17.4	1.50 V	148	43.4	13.2
5	11400.00	46.2 AV	54.0	-7.8	1.50 V	148	33.0	13.2
6	#17100.00	54.4 PK	68.2	-13.8	2.60 V	94	37.2	17.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 144	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	53.4 PK	74.0	-20.6	1.50 H	7	49.6	3.8
2	5460.00	42.9 AV	54.0	-11.1	1.50 H	7	39.1	3.8
3	#5470.00	54.3 PK	68.2	-13.9	1.50 H	7	50.4	3.9
4	*5720.00	116.2 PK			1.50 H	7	112.3	3.9
5	*5720.00	109.3 AV			1.50 H	7	105.4	3.9
6	#5850.00	63.9 PK	68.2	-4.3	1.50 H	7	59.5	4.4
7	11440.00	58.5 PK	74.0	-15.5	1.59 H	91	45.2	13.3
8	11440.00	47.3 AV	54.0	-6.7	1.59 H	91	34.0	13.3
9	#17160.00	51.3 PK	68.2	-16.9	1.41 H	172	33.9	17.4

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	47.6 PK	74.0	-26.4	1.13 V	45	43.8	3.8
2	5460.00	38.7 AV	54.0	-15.3	1.13 V	45	34.9	3.8
3	#5470.00	50.4 PK	68.2	-17.8	1.13 V	45	46.5	3.9
4	*5720.00	114.8 PK			1.13 V	45	110.9	3.9
5	*5720.00	105.7 AV			1.13 V	45	101.8	3.9
6	#5850.00	54.6 PK	68.2	-13.6	1.13 V	45	50.2	4.4
7	11440.00	55.6 PK	74.0	-18.4	1.52 V	150	42.3	13.3
8	11440.00	46.4 AV	54.0	-7.6	1.52 V	150	33.1	13.3
9	#17160.00	55.5 PK	68.2	-12.7	2.59 V	79	38.1	17.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 149	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5651.34	61.0 PK	69.2	-8.2	2.13 H	7	56.6	4.4
2	*5745.00	115.4 PK			2.13 H	7	111.4	4.0
3	*5745.00	107.2 AV			2.13 H	7	103.2	4.0
4	#5944.65	56.5 PK	68.2	-11.7	2.13 H	7	51.6	4.9
5	11490.00	52.4 PK	74.0	-21.6	1.59 H	99	39.1	13.3
6	11490.00	42.5 AV	54.0	-11.5	1.59 H	99	29.2	13.3
7	#17235.00	53.7 PK	68.2	-14.5	1.37 H	161	36.1	17.6

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5649.54	60.0 PK	68.2	-8.2	1.06 V	45	55.6	4.4
2	*5745.00	111.7 PK			1.06 V	45	107.7	4.0
3	*5745.00	103.5 AV			1.06 V	45	99.5	4.0
4	#5927.24	54.5 PK	68.2	-13.7	1.06 V	45	49.6	4.9
5	11490.00	52.1 PK	74.0	-21.9	1.42 V	137	38.8	13.3
6	11490.00	42.1 AV	54.0	-11.9	1.42 V	137	28.8	13.3
7	#17235.00	59.6 PK	68.2	-8.6	2.59 V	101	42.0	17.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 157	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5651.22	58.1 PK	69.1	-11.0	2.16 H	3	53.7	4.4
2	*5785.00	114.5 PK			2.16 H	3	110.4	4.1
3	*5785.00	107.1 AV			2.16 H	3	103.0	4.1
4	#5925.84	57.9 PK	68.2	-10.3	2.16 H	3	53.0	4.9
5	11570.00	52.1 PK	74.0	-21.9	1.56 H	105	38.9	13.2
6	11570.00	42.0 AV	54.0	-12.0	1.56 H	105	28.8	13.2
7	#17355.00	53.6 PK	68.2	-14.6	1.32 H	147	36.0	17.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5645.55	56.6 PK	68.2	-11.6	1.03 V	47	52.3	4.3
2	*5785.00	110.9 PK			1.03 V	47	106.8	4.1
3	*5785.00	103.7 AV			1.03 V	47	99.6	4.1
4	#5938.21	55.9 PK	68.2	-12.3	1.03 V	47	50.9	5.0
5	11570.00	52.2 PK	74.0	-21.8	1.46 V	141	39.0	13.2
6	11570.00	42.5 AV	54.0	-11.5	1.46 V	141	29.3	13.2
7	#17355.00	59.5 PK	68.2	-8.7	2.53 V	103	41.9	17.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 165	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5626.65	55.1 PK	68.2	-13.1	2.17 H	8	50.8	4.3
2	*5825.00	114.3 PK			2.17 H	8	110.0	4.3
3	*5825.00	107.3 AV			2.17 H	8	103.0	4.3
4	#5930.49	59.0 PK	68.2	-9.2	2.17 H	8	54.1	4.9
5	11650.00	52.4 PK	74.0	-21.6	1.61 H	83	39.1	13.3
6	11650.00	42.6 AV	54.0	-11.4	1.61 H	83	29.3	13.3
7	#17475.00	54.0 PK	68.2	-14.2	1.42 H	171	36.1	17.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5636.37	53.6 PK	68.2	-14.6	1.07 V	41	49.3	4.3
2	*5825.00	111.2 PK			1.07 V	41	106.9	4.3
3	*5825.00	103.6 AV			1.07 V	41	99.3	4.3
4	#5925.23	55.9 PK	68.2	-12.3	1.07 V	41	51.0	4.9
5	11650.00	52.2 PK	74.0	-21.8	1.47 V	130	38.9	13.3
6	11650.00	42.7 AV	54.0	-11.3	1.47 V	130	29.4	13.3
7	#17475.00	60.0 PK	68.2	-8.2	2.59 V	104	42.1	17.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

802.11ax (HE20)

Channel	TX Channel 36	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	63.0 PK	74.0	-11.0	1.97 H	1	59.3	3.7
2	5150.00	53.5 AV	54.0	-0.5	1.97 H	1	49.8	3.7
3	*5180.00	114.5 PK			1.97 H	1	110.9	3.6
4	*5180.00	104.3 AV			1.97 H	1	100.7	3.6
5	#10360.00	55.3 PK	68.2	-12.9	1.71 H	113	42.6	12.7
6	15540.00	51.3 PK	74.0	-22.7	1.61 H	122	38.1	13.2
7	15540.00	37.4 AV	54.0	-16.6	1.61 H	122	24.2	13.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	59.6 PK	74.0	-14.4	1.07 V	49	55.9	3.7
2	5150.00	50.2 AV	54.0	-3.8	1.07 V	49	46.5	3.7
3	*5180.00	109.7 PK			1.07 V	49	106.1	3.6
4	*5180.00	100.9 AV			1.07 V	49	97.3	3.6
5	#10360.00	55.0 PK	68.2	-13.2	1.67 V	119	42.3	12.7
6	15540.00	54.3 PK	74.0	-19.7	2.46 V	54	41.1	13.2
7	15540.00	42.4 AV	54.0	-11.6	2.46 V	54	29.2	13.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 40	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	63.9 PK	74.0	-10.1	1.72 H	1	60.2	3.7
2	5150.00	53.9 AV	54.0	-0.1	1.72 H	1	50.2	3.7
3	*5200.00	115.4 PK			1.72 H	1	111.9	3.5
4	*5200.00	105.9 AV			1.72 H	1	102.4	3.5
5	5439.90	55.8 PK	74.0	-18.2	1.72 H	1	52.1	3.7
6	5439.90	45.8 AV	54.0	-8.2	1.72 H	1	42.1	3.7
7	#10400.00	57.6 PK	68.2	-10.6	1.72 H	109	44.8	12.8
8	15600.00	51.7 PK	74.0	-22.3	1.56 H	135	38.2	13.5
9	15600.00	38.1 AV	54.0	-15.9	1.56 H	135	24.6	13.5

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	60.3 PK	74.0	-13.7	1.08 V	52	56.6	3.7
2	5150.00	50.8 AV	54.0	-3.2	1.08 V	52	47.1	3.7
3	*5200.00	110.4 PK			1.08 V	52	106.9	3.5
4	*5200.00	101.5 AV			1.08 V	52	98.0	3.5
5	5350.00	53.2 PK	74.0	-20.8	1.08 V	52	49.8	3.4
6	5350.00	41.9 AV	54.0	-12.1	1.08 V	52	38.5	3.4
7	#10400.00	55.6 PK	68.2	-12.6	1.64 V	116	42.8	12.8
8	15600.00	54.5 PK	74.0	-19.5	2.49 V	69	41.0	13.5
9	15600.00	43.7 AV	54.0	-10.3	2.49 V	69	30.2	13.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 48	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	64.7 PK	74.0	-9.3	1.83 H	360	61.0	3.7
2	5150.00	53.9 AV	54.0	-0.1	1.83 H	360	50.2	3.7
3	*5240.00	116.0 PK			1.83 H	360	112.5	3.5
4	*5240.00	106.7 AV			1.83 H	360	103.2	3.5
5	5350.00	60.1 PK	74.0	-13.9	1.83 H	360	56.7	3.4
6	5350.00	47.5 AV	54.0	-6.5	1.83 H	360	44.1	3.4
7	#10480.00	58.9 PK	68.2	-9.3	1.75 H	116	45.8	13.1
8	15720.00	50.9 PK	74.0	-23.1	1.53 H	145	37.1	13.8
9	15720.00	39.3 AV	54.0	-14.7	1.53 H	145	25.5	13.8

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	60.6 PK	74.0	-13.4	1.12 V	64	56.9	3.7
2	5150.00	50.1 AV	54.0	-3.9	1.12 V	64	46.4	3.7
3	*5240.00	111.4 PK			1.12 V	64	107.9	3.5
4	*5240.00	102.7 AV			1.12 V	64	99.2	3.5
5	5350.00	56.6 PK	74.0	-17.4	1.12 V	64	53.2	3.4
6	5350.00	44.6 AV	54.0	-9.4	1.12 V	64	41.2	3.4
7	#10480.00	56.0 PK	68.2	-12.2	1.61 V	129	42.9	13.1
8	15720.00	55.8 PK	74.0	-18.2	2.58 V	73	42.0	13.8
9	15720.00	45.9 AV	54.0	-8.1	2.58 V	73	32.1	13.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 52	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	58.8 PK	74.0	-15.2	1.91 H	0	55.1	3.7
2	5150.00	49.3 AV	54.0	-4.7	1.91 H	0	45.6	3.7
3	*5260.00	117.0 PK			1.91 H	0	113.6	3.4
4	*5260.00	106.5 AV			1.91 H	0	103.1	3.4
5	5350.00	61.3 PK	74.0	-12.7	1.91 H	0	57.9	3.4
6	5350.00	50.2 AV	54.0	-3.8	1.91 H	0	46.8	3.4
7	#10520.00	59.0 PK	68.2	-9.2	1.73 H	128	45.9	13.1
8	15780.00	50.8 PK	74.0	-23.2	1.56 H	143	37.3	13.5
9	15780.00	39.5 AV	54.0	-14.5	1.56 H	143	26.0	13.5

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	57.6 PK	74.0	-16.4	1.15 V	75	53.9	3.7
2	5150.00	46.7 AV	54.0	-7.3	1.15 V	75	43.0	3.7
3	*5260.00	110.8 PK			1.15 V	75	107.4	3.4
4	*5260.00	102.3 AV			1.15 V	75	98.9	3.4
5	5350.00	58.9 PK	74.0	-15.1	1.15 V	75	55.5	3.4
6	5350.00	47.4 AV	54.0	-6.6	1.15 V	75	44.0	3.4
7	#10520.00	56.6 PK	68.2	-11.6	1.57 V	124	43.5	13.1
8	15780.00	55.2 PK	74.0	-18.8	2.51 V	76	41.7	13.5
9	15780.00	45.4 AV	54.0	-8.6	2.51 V	76	31.9	13.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 60	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	116.1 PK			1.86 H	9	112.8	3.3
2	*5300.00	106.8 AV			1.86 H	9	103.5	3.3
3	10600.00	58.7 PK	74.0	-15.3	1.71 H	102	45.8	12.9
4	10600.00	47.0 AV	54.0	-7.0	1.71 H	102	34.1	12.9
5	15900.00	51.2 PK	74.0	-22.8	1.59 H	134	38.4	12.8
6	15900.00	39.6 AV	54.0	-14.4	1.59 H	134	26.8	12.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	111.3 PK			1.18 V	65	108.0	3.3
2	*5300.00	102.6 AV			1.18 V	65	99.3	3.3
3	10600.00	56.3 PK	74.0	-17.7	1.64 V	113	43.4	12.9
4	10600.00	46.6 AV	54.0	-7.4	1.64 V	113	33.7	12.9
5	15900.00	56.0 PK	74.0	-18.0	2.55 V	83	43.2	12.8
6	15900.00	45.8 AV	54.0	-8.2	2.55 V	83	33.0	12.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 64	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	114.7 PK			2.04 H	352	111.3	3.4
2	*5320.00	104.7 AV			2.04 H	352	101.3	3.4
3	5350.00	62.8 PK	74.0	-11.2	2.04 H	352	59.4	3.4
4	5350.00	53.9 AV	54.0	-0.1	2.04 H	352	50.5	3.4
5	10640.00	55.9 PK	74.0	-18.1	1.69 H	115	43.0	12.9
6	10640.00	44.6 AV	54.0	-9.4	1.69 H	115	31.7	12.9
7	15960.00	51.6 PK	74.0	-22.4	1.66 H	127	38.8	12.8
8	15960.00	37.8 AV	54.0	-16.2	1.66 H	127	25.0	12.8

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	109.7 PK			1.05 V	48	106.3	3.4
2	*5320.00	100.2 AV			1.05 V	48	96.8	3.4
3	5350.00	59.6 PK	74.0	-14.4	1.05 V	48	56.2	3.4
4	5350.00	49.1 AV	54.0	-4.9	1.05 V	48	45.7	3.4
5	10640.00	54.7 PK	74.0	-19.3	1.64 V	118	41.8	12.9
6	10640.00	43.9 AV	54.0	-10.1	1.64 V	118	31.0	12.9
7	15960.00	54.2 PK	74.0	-19.8	2.41 V	68	41.4	12.8
8	15960.00	42.2 AV	54.0	-11.8	2.41 V	68	29.4	12.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 100	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	64.2 PK	74.0	-9.8	1.96 H	358	60.4	3.8
2	5460.00	53.0 AV	54.0	-1.0	1.96 H	358	49.2	3.8
3	#5468.18	67.5 PK	68.2	-0.7	1.96 H	358	63.6	3.9
4	*5500.00	115.8 PK			1.96 H	358	111.9	3.9
5	*5500.00	105.1 AV			1.96 H	358	101.2	3.9
6	11000.00	59.1 PK	74.0	-14.9	1.79 H	101	46.1	13.0
7	11000.00	47.7 AV	54.0	-6.3	1.79 H	101	34.7	13.0
8	#16500.00	51.0 PK	68.2	-17.2	1.49 H	137	36.4	14.6

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	57.8 PK	74.0	-16.2	1.21 V	47	54.0	3.8
2	5460.00	49.0 AV	54.0	-5.0	1.21 V	47	45.2	3.8
3	#5468.24	61.1 PK	68.2	-7.1	1.21 V	47	57.2	3.9
4	*5500.00	111.6 PK			1.21 V	47	107.7	3.9
5	*5500.00	101.1 AV			1.21 V	47	97.2	3.9
6	11000.00	56.3 PK	74.0	-17.7	1.67 V	107	43.3	13.0
7	11000.00	46.3 AV	54.0	-7.7	1.67 V	107	33.3	13.0
8	#16500.00	55.5 PK	68.2	-12.7	2.60 V	95	40.9	14.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 116	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	117.0 PK			1.92 H	357	113.2	3.8
2	*5580.00	106.8 AV			1.92 H	357	103.0	3.8
3	11160.00	59.1 PK	74.0	-14.9	1.80 H	131	46.0	13.1
4	11160.00	46.7 AV	54.0	-7.3	1.80 H	131	33.6	13.1
5	#16740.00	50.5 PK	68.2	-17.7	1.56 H	149	34.3	16.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	111.6 PK			1.15 V	66	107.8	3.8
2	*5580.00	102.8 AV			1.15 V	66	99.0	3.8
3	11160.00	56.4 PK	74.0	-17.6	1.64 V	108	43.3	13.1
4	11160.00	47.0 AV	54.0	-7.0	1.64 V	108	33.9	13.1
5	#16740.00	55.5 PK	68.2	-12.7	2.49 V	93	39.3	16.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 140	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	115.8 PK			1.83 H	358	111.8	4.0
2	*5700.00	105.0 AV			1.83 H	358	101.0	4.0
3	#5725.00	67.9 PK	68.2	-0.3	1.83 H	358	63.9	4.0
4	11400.00	58.4 PK	74.0	-15.6	1.74 H	105	45.2	13.2
5	11400.00	47.0 AV	54.0	-7.0	1.74 H	105	33.8	13.2
6	#17100.00	51.5 PK	68.2	-16.7	1.49 H	129	34.3	17.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	111.1 PK			1.21 V	81	107.1	4.0
2	*5700.00	102.6 AV			1.21 V	81	98.6	4.0
3	#5725.00	60.4 PK	68.2	-7.8	1.21 V	81	56.4	4.0
4	11400.00	56.7 PK	74.0	-17.3	1.68 V	110	43.5	13.2
5	11400.00	47.1 AV	54.0	-6.9	1.68 V	110	33.9	13.2
6	#17100.00	56.5 PK	68.2	-11.7	2.59 V	96	39.3	17.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 144	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	50.4 PK	74.0	-23.6	1.77 H	358	46.6	3.8
2	5460.00	40.6 AV	54.0	-13.4	1.77 H	358	36.8	3.8
3	#5470.00	51.3 PK	68.2	-16.9	1.77 H	358	47.4	3.9
4	*5720.00	116.3 PK			1.77 H	358	112.4	3.9
5	*5720.00	105.3 AV			1.77 H	358	101.4	3.9
6	#5850.00	60.3 PK	68.2	-7.9	1.77 H	358	55.9	4.4
7	11440.00	58.1 PK	74.0	-15.9	1.74 H	106	44.8	13.3
8	11440.00	46.6 AV	54.0	-7.4	1.74 H	106	33.3	13.3
9	#17160.00	51.3 PK	68.2	-16.9	1.48 H	126	33.9	17.4

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	47.5 PK	74.0	-26.5	1.24 V	65	43.7	3.8
2	5460.00	38.9 AV	54.0	-15.1	1.24 V	65	35.1	3.8
3	#5470.00	50.3 PK	68.2	-17.9	1.24 V	65	46.4	3.9
4	*5720.00	111.7 PK			1.24 V	65	107.8	3.9
5	*5720.00	103.0 AV			1.24 V	65	99.1	3.9
6	#5850.00	55.0 PK	68.2	-13.2	1.24 V	65	50.6	4.4
7	11440.00	57.0 PK	74.0	-17.0	1.68 V	118	43.7	13.3
8	11440.00	47.1 AV	54.0	-6.9	1.68 V	118	33.8	13.3
9	#17160.00	56.1 PK	68.2	-12.1	2.52 V	95	38.7	17.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 149	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5647.55	60.4 PK	68.2	-7.8	1.94 H	5	56.0	4.4
2	*5745.00	113.8 PK			1.94 H	5	109.8	4.0
3	*5745.00	104.7 AV			1.94 H	5	100.7	4.0
4	#5927.85	54.3 PK	68.2	-13.9	1.94 H	5	49.4	4.9
5	11490.00	52.9 PK	74.0	-21.1	1.65 H	79	39.6	13.3
6	11490.00	42.7 AV	54.0	-11.3	1.65 H	79	29.4	13.3
7	#17235.00	53.6 PK	68.2	-14.6	1.41 H	182	36.0	17.6

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5638.54	56.3 PK	68.2	-11.9	1.08 V	40	52.0	4.3
2	*5745.00	110.5 PK			1.08 V	40	106.5	4.0
3	*5745.00	99.9 AV			1.08 V	40	95.9	4.0
4	#5944.53	52.6 PK	68.2	-15.6	1.08 V	40	47.7	4.9
5	11490.00	51.3 PK	74.0	-22.7	1.45 V	118	38.0	13.3
6	11490.00	41.8 AV	54.0	-12.2	1.45 V	118	28.5	13.3
7	#17235.00	59.6 PK	68.2	-8.6	2.54 V	115	42.0	17.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 157	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5642.21	56.5 PK	68.2	-11.7	2.02 H	9	52.2	4.3
2	*5785.00	113.8 PK			2.02 H	9	109.7	4.1
3	*5785.00	104.3 AV			2.02 H	9	100.2	4.1
4	#5932.78	57.6 PK	68.2	-10.6	2.02 H	9	52.7	4.9
5	11570.00	52.3 PK	74.0	-21.7	1.63 H	94	39.1	13.2
6	11570.00	42.3 AV	54.0	-11.7	1.63 H	94	29.1	13.2
7	#17355.00	53.6 PK	68.2	-14.6	1.40 H	175	36.0	17.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5647.86	53.8 PK	68.2	-14.4	1.06 V	43	49.4	4.4
2	*5785.00	110.0 PK			1.06 V	43	105.9	4.1
3	*5785.00	100.2 AV			1.06 V	43	96.1	4.1
4	#5940.02	53.4 PK	68.2	-14.8	1.06 V	43	48.4	5.0
5	11570.00	52.2 PK	74.0	-21.8	1.49 V	147	39.0	13.2
6	11570.00	42.6 AV	54.0	-11.4	1.49 V	147	29.4	13.2
7	#17355.00	58.9 PK	68.2	-9.3	2.56 V	92	41.3	17.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 165	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5649.09	54.4 PK	68.2	-13.8	2.20 H	5	50.0	4.4
2	*5825.00	115.2 PK			2.20 H	5	110.9	4.3
3	*5825.00	105.4 AV			2.20 H	5	101.1	4.3
4	#5925.64	57.7 PK	68.2	-10.5	2.20 H	5	52.8	4.9
5	11650.00	52.5 PK	74.0	-21.5	1.55 H	81	39.2	13.3
6	11650.00	42.9 AV	54.0	-11.1	1.55 H	81	29.6	13.3
7	#17475.00	53.6 PK	68.2	-14.6	1.40 H	168	35.7	17.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5649.14	51.6 PK	68.2	-16.6	1.04 V	42	47.2	4.4
2	*5825.00	109.7 PK			1.04 V	42	105.4	4.3
3	*5825.00	99.9 AV			1.04 V	42	95.6	4.3
4	#5933.15	54.4 PK	68.2	-13.8	1.04 V	42	49.5	4.9
5	11650.00	52.0 PK	74.0	-22.0	1.52 V	132	38.7	13.3
6	11650.00	42.4 AV	54.0	-11.6	1.52 V	132	29.1	13.3
7	#17475.00	59.9 PK	68.2	-8.3	2.52 V	92	42.0	17.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

802.11ax (HE40)

Channel	TX Channel 38	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	63.7 PK	74.0	-10.3	1.91 H	359	60.0	3.7
2	5150.00	53.7 AV	54.0	-0.3	1.91 H	359	50.0	3.7
3	*5190.00	111.2 PK			1.91 H	359	107.6	3.6
4	*5190.00	101.3 AV			1.91 H	359	97.7	3.6
5	#10380.00	53.5 PK	68.2	-14.7	1.73 H	101	40.8	12.7
6	15570.00	49.9 PK	74.0	-24.1	1.76 H	149	36.5	13.4
7	15570.00	37.7 AV	54.0	-16.3	1.76 H	149	24.3	13.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	58.2 PK	74.0	-15.8	1.13 V	48	54.5	3.7
2	5150.00	49.3 AV	54.0	-4.7	1.13 V	48	45.6	3.7
3	*5190.00	107.4 PK			1.13 V	48	103.8	3.6
4	*5190.00	97.6 AV			1.13 V	48	94.0	3.6
5	#10380.00	51.8 PK	68.2	-16.4	1.46 V	143	39.1	12.7
6	15570.00	50.7 PK	74.0	-23.3	2.54 V	71	37.3	13.4
7	15570.00	40.9 AV	54.0	-13.1	2.54 V	71	27.5	13.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 46	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	62.8 PK	74.0	-11.2	1.92 H	353	59.1	3.7
2	5150.00	52.1 AV	54.0	-1.9	1.92 H	353	48.4	3.7
3	*5230.00	112.1 PK			1.92 H	353	108.6	3.5
4	*5230.00	102.6 AV			1.92 H	353	99.1	3.5
5	5350.00	56.7 PK	74.0	-17.3	1.92 H	353	53.3	3.4
6	5350.00	47.2 AV	54.0	-6.8	1.92 H	353	43.8	3.4
7	#10460.00	55.2 PK	68.2	-13.0	1.67 H	89	42.2	13.0
8	15690.00	51.2 PK	74.0	-22.8	1.73 H	146	37.3	13.9
9	15690.00	38.1 AV	54.0	-15.9	1.73 H	146	24.2	13.9

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	57.6 PK	74.0	-16.4	1.11 V	38	53.9	3.7
2	5150.00	48.4 AV	54.0	-5.6	1.11 V	38	44.7	3.7
3	*5230.00	108.7 PK			1.11 V	38	105.2	3.5
4	*5230.00	98.5 AV			1.11 V	38	95.0	3.5
5	5350.00	53.5 PK	74.0	-20.5	1.11 V	38	50.1	3.4
6	5350.00	43.2 AV	54.0	-10.8	1.11 V	38	39.8	3.4
7	#10460.00	53.6 PK	68.2	-14.6	1.43 V	156	40.6	13.0
8	15690.00	52.4 PK	74.0	-21.6	2.61 V	91	38.5	13.9
9	15690.00	42.8 AV	54.0	-11.2	2.61 V	91	28.9	13.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 54	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	58.5 PK	74.0	-15.5	1.81 H	1	54.8	3.7
2	5150.00	47.1 AV	54.0	-6.9	1.81 H	1	43.4	3.7
3	*5270.00	110.3 PK			1.81 H	1	106.9	3.4
4	*5270.00	102.7 AV			1.81 H	1	99.3	3.4
5	5350.00	60.3 PK	74.0	-13.7	1.81 H	1	56.9	3.4
6	5350.00	49.5 AV	54.0	-4.5	1.81 H	1	46.1	3.4
7	#10540.00	55.1 PK	68.2	-13.1	1.70 H	91	42.1	13.0
8	15810.00	51.1 PK	74.0	-22.9	1.72 H	131	37.9	13.2
9	15810.00	37.8 AV	54.0	-16.2	1.72 H	131	24.6	13.2

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	53.2 PK	74.0	-20.8	1.15 V	53	49.5	3.7
2	5150.00	43.1 AV	54.0	-10.9	1.15 V	53	39.4	3.7
3	*5270.00	108.7 PK			1.15 V	53	105.3	3.4
4	*5270.00	98.7 AV			1.15 V	53	95.3	3.4
5	5350.00	55.7 PK	74.0	-18.3	1.15 V	53	52.3	3.4
6	5350.00	46.6 AV	54.0	-7.4	1.15 V	53	43.2	3.4
7	#10540.00	53.7 PK	68.2	-14.5	1.49 V	147	40.7	13.0
8	15810.00	52.9 PK	74.0	-21.1	2.61 V	94	39.7	13.2
9	15810.00	43.0 AV	54.0	-11.0	2.61 V	94	29.8	13.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 62	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5310.00	111.7 PK			1.77 H	360	108.4	3.3
2	*5310.00	101.6 AV			1.77 H	360	98.3	3.3
3	5350.00	61.3 PK	74.0	-12.7	1.77 H	360	57.9	3.4
4	5350.00	53.6 AV	54.0	-0.4	1.77 H	360	50.2	3.4
5	10620.00	53.4 PK	74.0	-20.6	1.71 H	104	40.5	12.9
6	10620.00	41.7 AV	54.0	-12.3	1.71 H	104	28.8	12.9
7	15930.00	49.6 PK	74.0	-24.4	1.71 H	137	36.8	12.8
8	15930.00	37.6 AV	54.0	-16.4	1.71 H	137	24.8	12.8

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5310.00	106.8 PK			1.00 V	45	103.5	3.3
2	*5310.00	97.6 AV			1.00 V	45	94.3	3.3
3	5350.00	57.9 PK	74.0	-16.1	1.00 V	45	54.5	3.4
4	5350.00	49.2 AV	54.0	-4.8	1.00 V	45	45.8	3.4
5	10620.00	52.1 PK	74.0	-21.9	1.46 V	146	39.2	12.9
6	10620.00	41.9 AV	54.0	-12.1	1.46 V	146	29.0	12.9
7	15930.00	50.7 PK	74.0	-23.3	2.55 V	82	37.9	12.8
8	15930.00	40.9 AV	54.0	-13.1	2.55 V	82	28.1	12.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Channel	TX Channel 102	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	61.8 PK	74.0	-12.2	1.89 H	358	58.0	3.8
2	5460.00	53.5 AV	54.0	-0.5	1.89 H	358	49.7	3.8
3	#5469.95	67.5 PK	68.2	-0.7	1.89 H	358	63.6	3.9
4	*5510.00	111.5 PK			1.89 H	358	107.6	3.9
5	*5510.00	101.6 AV			1.89 H	358	97.7	3.9
6	11020.00	55.6 PK	74.0	-18.4	1.66 H	127	42.6	13.0
7	11020.00	44.2 AV	54.0	-9.8	1.66 H	127	31.2	13.0
8	#16530.00	51.9 PK	68.2	-16.3	1.62 H	133	37.2	14.7

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	60.1 PK	74.0	-13.9	1.11 V	46	56.3	3.8
2	5460.00	49.5 AV	54.0	-4.5	1.11 V	46	45.7	3.8
3	#5468.74	61.6 PK	68.2	-6.6	1.11 V	46	57.7	3.9
4	*5510.00	108.1 PK			1.11 V	46	104.2	3.9
5	*5510.00	98.5 AV			1.11 V	46	94.6	3.9
6	11020.00	53.5 PK	74.0	-20.5	1.45 V	171	40.5	13.0
7	11020.00	43.2 AV	54.0	-10.8	1.45 V	171	30.2	13.0
8	#16530.00	52.6 PK	68.2	-15.6	2.65 V	97	37.9	14.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 110	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5550.00	112.2 PK			1.90 H	358	108.4	3.8
2	*5550.00	102.3 AV			1.90 H	358	98.5	3.8
3	11100.00	55.8 PK	74.0	-18.2	1.73 H	106	42.8	13.0
4	11100.00	43.9 AV	54.0	-10.1	1.73 H	106	30.9	13.0
5	#16650.00	51.3 PK	68.2	-16.9	1.72 H	117	35.6	15.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5550.00	108.3 PK			1.08 V	58	104.5	3.8
2	*5550.00	98.8 AV			1.08 V	58	95.0	3.8
3	11100.00	53.3 PK	74.0	-20.7	1.45 V	156	40.3	13.0
4	11100.00	43.1 AV	54.0	-10.9	1.45 V	156	30.1	13.0
5	#16650.00	52.5 PK	68.2	-15.7	2.65 V	88	36.8	15.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 134	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5670.00	109.6 PK			1.79 H	358	105.6	4.0
2	*5670.00	99.8 AV			1.79 H	358	95.8	4.0
3	#5725.00	59.6 PK	68.2	-8.6	1.79 H	358	55.6	4.0
4	11340.00	55.7 PK	74.0	-18.3	1.62 H	116	42.5	13.2
5	11340.00	44.3 AV	54.0	-9.7	1.62 H	116	31.1	13.2
6	#17010.00	51.6 PK	68.2	-16.6	1.58 H	128	34.6	17.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5670.00	108.1 PK			1.05 V	49	104.1	4.0
2	*5670.00	98.6 AV			1.05 V	49	94.6	4.0
3	#5725.00	53.7 PK	68.2	-14.5	1.05 V	49	49.7	4.0
4	11340.00	53.9 PK	74.0	-20.1	1.47 V	166	40.7	13.2
5	11340.00	43.7 AV	54.0	-10.3	1.47 V	166	30.5	13.2
6	#17010.00	52.6 PK	68.2	-15.6	2.63 V	96	35.6	17.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 142	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	51.5 PK	74.0	-22.5	1.77 H	359	47.7	3.8
2	5460.00	41.1 AV	54.0	-12.9	1.77 H	359	37.3	3.8
3	#5470.00	54.1 PK	68.2	-14.1	1.77 H	359	50.2	3.9
4	*5710.00	114.8 PK			1.77 H	359	110.8	4.0
5	*5710.00	101.4 AV			1.77 H	359	97.4	4.0
6	#5850.00	55.7 PK	68.2	-12.5	1.77 H	359	51.3	4.4
7	11420.00	55.6 PK	74.0	-18.4	1.72 H	104	42.4	13.2
8	11420.00	43.8 AV	54.0	-10.2	1.72 H	104	30.6	13.2
9	#17130.00	51.2 PK	68.2	-17.0	1.75 H	114	34.0	17.2

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	47.0 PK	74.0	-27.0	1.10 V	53	43.2	3.8
2	5460.00	38.6 AV	54.0	-15.4	1.10 V	53	34.8	3.8
3	#5470.00	50.5 PK	68.2	-17.7	1.10 V	53	46.6	3.9
4	*5710.00	108.1 PK			1.10 V	53	104.1	4.0
5	*5710.00	98.7 AV			1.10 V	53	94.7	4.0
6	#5850.00	54.9 PK	68.2	-13.3	1.10 V	53	50.5	4.4
7	11420.00	53.7 PK	74.0	-20.3	1.49 V	171	40.5	13.2
8	11420.00	43.6 AV	54.0	-10.4	1.49 V	171	30.4	13.2
9	#17130.00	52.1 PK	68.2	-16.1	2.60 V	100	34.9	17.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 151	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5646.40	59.0 PK	68.2	-9.2	2.02 H	7	54.7	4.3
2	*5755.00	112.2 PK			2.02 H	7	108.2	4.0
3	*5755.00	101.6 AV			2.02 H	7	97.6	4.0
4	#5932.98	55.5 PK	68.2	-12.7	2.02 H	7	50.6	4.9
5	11510.00	52.2 PK	74.0	-21.8	1.62 H	95	38.9	13.3
6	11510.00	42.3 AV	54.0	-11.7	1.62 H	95	29.0	13.3
7	#17265.00	53.2 PK	68.2	-15.0	1.35 H	200	35.7	17.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5642.22	56.2 PK	68.2	-12.0	1.05 V	47	51.9	4.3
2	*5755.00	106.4 PK			1.05 V	47	102.4	4.0
3	*5755.00	97.5 AV			1.05 V	47	93.5	4.0
4	#5927.24	52.2 PK	68.2	-16.0	1.05 V	47	47.3	4.9
5	11510.00	50.8 PK	74.0	-23.2	1.49 V	112	37.5	13.3
6	11510.00	41.4 AV	54.0	-12.6	1.49 V	112	28.1	13.3
7	#17265.00	57.7 PK	68.2	-10.5	2.59 V	102	40.2	17.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Channel	TX Channel 159	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 40GHz		Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5618.87	56.4 PK	68.2	-11.8	2.11 H	9	52.1	4.3
2	*5795.00	112.2 PK			2.11 H	9	108.0	4.2
3	*5795.00	102.1 AV			2.11 H	9	97.9	4.2
4	#5941.26	56.1 PK	68.2	-12.1	2.11 H	9	51.1	5.0
5	11590.00	51.7 PK	74.0	-22.3	1.58 H	98	38.4	13.3
6	11590.00	42.0 AV	54.0	-12.0	1.58 H	98	28.7	13.3
7	#17385.00	53.5 PK	68.2	-14.7	1.31 H	196	35.8	17.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5639.12	54.3 PK	68.2	-13.9	1.07 V	45	50.0	4.3
2	*5795.00	106.1 PK			1.07 V	45	101.9	4.2
3	*5795.00	97.2 AV			1.07 V	45	93.0	4.2
4	#5935.55	54.3 PK	68.2	-13.9	1.07 V	45	49.4	4.9
5	11590.00	51.0 PK	74.0	-23.0	1.51 V	124	37.7	13.3
6	11590.00	41.7 AV	54.0	-12.3	1.51 V	124	28.4	13.3
7	#17385.00	57.4 PK	68.2	-10.8	2.54 V	117	39.7	17.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.