



FCC AND ISCED CERTIFICATION TEST REPORT

Applicant	:	Globe Electric Company Inc.
Address of Applicant	:	150 Oneida, Montreal, Quebec, Canada, H9R 1A8
Manufacturer	:	ZHONGSHAN FANER LIGHTING TECHNOLOGY CO.,LTD
Address of Manufacturer	:	No. 1, South 3rd Road, Dong an West Road, Haizhou, Guzhen Town, Zhongshan City, Guangdong Province, China
Equipment under Test	:	Ceiling Fan With Light
Model No.	:	37000110, 37000098, 37000119, 37000001
FCC ID	:	2AQUQGE37110
IC	:	8290A-GE37110
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, RSS-247 Issue 3 August 2023, ANSI C63.10:2013, RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021)
Report No.	:	DDT-RE24092407-1E02
Issue Date	:	2024/12/16
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	Summary of Test Results	7
2.	General Test Information	8
2.1.	Description of EUT	8
2.2.	Accessories of EUT	9
2.3.	Block diagram of EUT configuration for test	9
2.4.	Decision of final test mode	9
2.5.	Deviations of test standard	10
2.6.	Test environment conditions	10
2.7.	Test laboratory	10
2.8.	Measurement uncertainty	11
3.	Equipment Used During Conductive Test	12
4.	6dB Bandwidth	13
4.1.	Block diagram of test setup	13
4.2.	Limits	13
4.3.	Test procedure	13
4.4.	Test result	14
4.5.	Test graphs	15
5.	99% Bandwidth	19
5.1.	Block diagram of test setup	19
5.2.	Limits	19
5.3.	Test procedure	19
5.4.	Test result	20
5.5.	Test graphs	21
6.	Conducted Output Power	25
6.1.	Block diagram of test setup	25
6.2.	Limits	25
6.3.	Test procedure	25
6.4.	Test result average	26
7.	Power Spectral Density	27
7.1.	Block diagram of test setup	27
7.2.	Limits	27
7.3.	Test procedure	27
7.4.	Test result	28
7.5.	Test graphs	29
8.	Band Edge Compliance (Conducted Method)	33
8.1.	Block diagram of test setup	33

8.2.	Limits.....	33
8.3.	Test procedure.....	33
8.4.	Test result	34
8.5.	Test graphs.....	35
9.	RF Conducted Spurious Emissions.....	38
9.1.	Block diagram of test setup	38
9.2.	Limits.....	38
9.3.	Test procedure.....	38
9.4.	Test result	39
9.5.	Test graphs.....	40
10.	Duty Cycle.....	52
10.1.	Block diagram of test setup	52
10.2.	Limit.....	52
10.3.	Test procedure.....	52
10.4.	Test result	53
10.5.	Test graphs.....	54
11.	Antenna Requirements	58
11.1.	Limit.....	58
11.2.	Result.....	58
12.	Radiated Emission.....	59
12.1.	Test equipment	59
12.2.	Block diagram of test setup	60
12.3.	Limits.....	61
12.4.	Assistant equipment used for test	63
12.5.	Test procedure.....	63
12.6.	Test result	64
12.7.	Test data	65
13.	Band Edge Compliance	97
13.1.	Test equipment	97
13.2.	Block diagram of test setup	98
13.3.	Limits.....	98
13.4.	Assistant equipment used for test	98
13.5.	Test procedure.....	98
13.6.	Test result	98
13.7.	Test data	99
14.	Power Line Conducted Emissions.....	107
14.1.	Test equipment	107
14.2.	Block diagram of test setup	107

14.3.	Limits.....	107
14.4.	Assistant equipment used for test	107
14.5.	Test procedure.....	108
14.6.	Test result	108
14.7.	Test data	109
15.	Test Setup Photograph.....	117
16.	Photos of the EUT	122

Test Report Declare

Applicant	:	Globe Electric Company Inc.
Address of Applicant	:	150 Oneida, Montreal, Quebec, Canada, H9R 1A8
Equipment under Test	:	Ceiling Fan With Light
Model No.	:	37000110, 37000098, 37000119, 37000001
Manufacturer	:	ZHONGSHAN FANER LIGHTING TECHNOLOGY CO.,LTD
Address of Manufacturer	:	No. 1, South 3rd Road, Dong an West Road, Haizhou, Guzhen Town, Zhongshan City, Guangdong Province, China

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C,
RSS-247 Issue 3 August 2023,
ANSI C63.10:2013,
RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021)

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE24092407-1E02		
Date of Receipt:	2024/09/25	Date of Test:	2024/09/25 - 2024/12/16

Prepared By:

Tiger Mo

Tiger Mo/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/12/16	

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	6 dB Bandwidth and 99% Bandwidth	FCC Part 15: 15.247(a)(2), RSS-247 Issue 3 clause 5.2(a), RSS-Gen Issue 5 clause 6.7	/	Pass
2	Peak Output Power	FCC Part 15: 15.247(b)(3), RSS-247 Issue 3 clause 5.4(d)	/	Pass
3	Power Spectral Density	FCC Part 15:15.247(e), RSS-247 Issue 3 clause 5.2(b)	/	Pass
4	RF Conducted Spurious Emissions	FCC Part 15: 15.247(d), RSS-247 Issue 3 clause 5.5	/	Pass
5	Radiated Emission	FCC Part 15: 15.205, FCC Part 15: 15.209, FCC Part 15: 15.247(d), RSS-247 Issue 3 clause 5.5, RSS-Gen Issue 5 clause 8.9, RSS-Gen Issue 5 clause 8.10	/	Pass
6	Band Edge Compliance	FCC Part 15: 15.205, FCC Part 15: 15.209, FCC Part 15: 15.247(d), RSS-247 Issue 3 clause 5.5, RSS-Gen Issue 5 clause 8.9, RSS-Gen Issue 5 clause 8.10	/	Pass
7	Power Line Conducted Emissions	FCC Part 15: 15.207(a), RSS-Gen Issue 5 clause 8.8	/	Pass
8	Antenna Requirement	FCC Part 15: 15.203, RSS-Gen Issue 5 clause 6.8	/	Pass
Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.				

2. General Test Information

2.1. Description of EUT

EUT Name	: Ceiling Fan With Light
Model Number	: 37000110, 37000098, 37000119, 37000001
Difference of model number	: All the models are electrical identical including the same hardware design (i.e., circuit design, PCB Layout, RF module/circuit, antenna type(s) and antenna location, components on PCB, etc.), only the Model Number, appearance are different for all the models, therefore the test performed on the model 37000110.
EUT Function Description	: Please reference user manual of this device
Power Supply	: AC 120V/60Hz
Antenna Type	: Copper tube antenna
Max Antenna Gain(dBi)	: 1.08

Note: This EUT support Bluetooth LE, 2.4 GHz WLAN, this report only for 2.4 GHz WLAN.

Radio Technology	: IEEE 802.11b/g/n
Operation frequency	: IEEE 802.11b: 2412MHz-2462MHz IEEE 802.11g: 2412MHz-2462MHz IEEE 802.11n HT20: 2412MHz-2462MHz IEEE 802.11n HT40: 2422MHz-2452MHz
Modulation	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)

Channel information					
CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	/	/


Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☒” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

2.3. Block diagram of EUT configuration for test



2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

Test software: Wifi Test Tool v1.6.0 release

The test software was used to control EUT work in Continuous Tx mode and select test channel, wireless mode as below table.

The pathloss of external cable: 0.5dB (According to the manufacturer's claims)

Tested mode, channel, and data rate information				
Mode	Setting Tx Power	Data rate (Mbps) (see Note)	Channel	Frequency (MHz)
	ANT1			
IEEE 802.11b	Default	1	LCH: CH1	2412
	Default	1	MCH: CH6	2437
	Default	1	HCH: CH11	2462
IEEE 802.11g	Default	6	LCH: CH1	2412
	Default	6	MCH: CH6	2437
	Default	6	HCH: CH11	2462
IEEE 802.11n HT20	Default	MCS 0	LCH: CH1	2412
	Default	MCS 0	MCH: CH6	2437
	Default	MCS 0	HCH: CH11	2462
IEEE 802.11n HT40	20	MCS 0	LCH: CH3	2422
	20	MCS 0	MCH: CH6	2437
	20	MCS 0	HCH: CH9	2452
Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.				

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to 106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Frequencies Stability	6.7×10^{-8} (Antenna couple method) 5.5×10^{-8} (Conducted method)
Conducted spurious emissions	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.40 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$) 1.66 dB ($8 \text{ GHz} \leq f < 26.5 \text{ GHz}$)
Uncertainty for radio frequency (RBW < 20 kHz)	3×10^{-8}
Temperature	0.4 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.70 dB (Antenna Polarize: V) 4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.10 dB (1 - 6 GHz) 4.40 dB (6 GHz - 18 GHz) 3.54 dB (18 GHz - 26 GHz) 4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.34dB (150KHz-30MHz) 3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date
☑RF Connected Test (RF Measurement System 3#)				
SIGNAL ANALYZER	R&S	FSV40	101407	2025/07/08
Wideband Radio Communication Tester	R&S	CMW500	117491	2025/03/31
EXG Analog Signal Generator	KEYSIGHT	N5173B	MY62153058	2025/07/08
MXG Vector Signal Generator	Agilent	N5182A	MY48180912	2025/03/31
RF Control Unit	Tonscend	JS0806-2	20C8060230	2025/03/31
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2025/04/22
Test Software	Tonscend	JS1120-3	Ver.3.2.22	N/A

4. 6dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz

4.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 11.8.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for 6 dB Bandwidth:

RBW:	100 kHz
VBW:	$\geq [3 \times \text{RBW}]$
Detector Mode:	peak
Sweep time:	auto
Trace mode	max hold


Allow the trace to stabilize, measure the 6 dB bandwidth of signal, and record the results in the report


4.4. Test result

Test Engineer:	Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	25.5℃,39.8%RH	Test Date:	2024.10.16
Test Power Supply:	AC 120V/60HZ	Sample Number:	S24092407-001


Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
11B	Ant1	2412	11.08	2406.12	2417.20	0.5	PASS
		2437	11.08	2431.12	2442.20	0.5	PASS
		2462	12.56	2455.60	2468.16	0.5	PASS
11G	Ant1	2412	15.16	2404.56	2419.72	0.5	PASS
		2437	15.12	2429.56	2444.68	0.5	PASS
		2462	15.16	2454.56	2469.72	0.5	PASS
11N20SISO	Ant1	2412	13.80	2404.60	2418.40	0.5	PASS
		2437	12.52	2429.64	2442.16	0.5	PASS
		2462	15.04	2454.60	2469.64	0.5	PASS
11N40SISO	Ant1	2422	32.56	2404.64	2437.20	0.5	PASS
		2437	32.56	2419.64	2452.20	0.5	PASS
		2452	32.56	2434.64	2467.20	0.5	PASS

4.5. Test graphs







11G Ant1_2437




11G Ant1_2462




11N20SISO Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462




11N40SISO_Ant1_2422



11N40SISO_Ant1_2437




11N40SISO_Ant1_2452



5. 99% Bandwidth

5.1. Block diagram of test setup



5.2. Limits

Just for Report.

5.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 6.9.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 99% Bandwidth:

RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 1.5 times and 5.0 times the OBW
Detector Mode:	peak
Sweep time:	auto
Trace mode	max hold


Allow the trace to stabilize, measure the 99% bandwidth of signal, and record the results in the report.


5.4. Test result

Test Engineer:	Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	25.5℃,39.8%RH	Test Date:	2024.10.16
Test Power Supply:	AC 120V/60HZ	Sample Number:	S24092407-001


TestMode	Antenna	Channel Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	15.265	2404.4875	2419.7522	---	---
		2437	15.265	2429.4476	2444.7123	---	---
		2462	15.225	2454.4875	2469.7123	---	---
11G	Ant1	2412	17.502	2403.3686	2420.8711	---	---
		2437	17.502	2428.3686	2445.8711	---	---
		2462	17.502	2453.3686	2470.8711	---	---
11N20SISO	Ant1	2412	18.422	2402.8891	2421.3107	---	---
		2437	18.422	2427.8891	2446.3107	---	---
		2462	18.422	2452.8891	2471.3107	---	---
11N40SISO	Ant1	2422	35.564	2404.2577	2439.8222	---	---
		2437	35.564	2419.2577	2454.8222	---	---
		2452	35.564	2434.2577	2469.8222	---	---

5.5. Test graphs







11G Ant1_2437




11G Ant1_2462




11N20SISO Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462




11N40SISO_Ant1_2422



11N40SISO_Ant1_2437




11N40SISO_Ant1_2452



6. Conducted Output Power

6.1. Block diagram of test setup



6.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 11.9.2.3.
- (2) Connect EUT's antenna output to RF power meter by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously, If the transmitter does not transmit continuously, measure the duty cycle, D, of the transmitter output signal.
- (4) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
- (5) Adjust the measurement in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.
- (6) Record the RF average power of each antenna port.

6.4. Test result average


Test Engineer:	Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	25.5℃,39.8%RH	Test Date:	2024.10.16
Test Power Supply:	AC 120V/60HZ	Sample Number:	S24092407-001

Test Mode	Antenna	Frequency [MHz]	Average power [dBm]	Duty Cycle [%]	DC Factor [dB]	Result [dBm]	Limit [dBm]	EIRP [dBm]	EIRP Limit [dBm]	Verdict
11B	Ant1	2412	11.08	98.94	0.05	11.13	≤30.00	12.21	≤36.00	PASS
		2437	10.35	98.94	0.05	10.40	≤30.00	11.48	≤36.00	PASS
		2462	9.73	98.82	0.05	9.78	≤30.00	10.86	≤36.00	PASS
11G	Ant1	2412	8.30	98.58	0.06	8.36	≤30.00	9.44	≤36.00	PASS
		2437	7.73	98.58	0.06	7.79	≤30.00	8.87	≤36.00	PASS
		2462	6.80	98.58	0.06	6.86	≤30.00	7.94	≤36.00	PASS
11N20SISO	Ant1	2412	7.19	98.48	0.07	7.26	≤30.00	8.34	≤36.00	PASS
		2437	6.61	98.48	0.07	6.68	≤30.00	7.76	≤36.00	PASS
		2462	5.71	98.48	0.07	5.78	≤30.00	6.86	≤36.00	PASS
11N40SISO	Ant1	2422	-0.69	100.00	0.00	-0.69	≤30.00	0.39	≤36.00	PASS
		2437	-0.79	100.00	0.00	-0.79	≤30.00	0.29	≤36.00	PASS
		2452	-1.53	100.00	0.00	-1.53	≤30.00	-0.45	≤36.00	PASS

Note: EIRP (dBm)=Conducted Output Power (dBm)+ Antenna Gain (dBi)

7. Power Spectral Density

7.1. Block diagram of test setup



7.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 11.10.5.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for Power Spectral Density measurement:

Center frequency	DTS Channel center frequency
RBW:	$3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5 times the DTS bandwidth
Detector Mode:	RMS
Sweep time:	auto
Trace mode	max hold
	Employ trace averaging (rms)
Trace	mode over a minimum of 100 traces.
- (5) Add $[10 \log (1 / D)]$, where D is the duty cycle measured in step a), to the measured PSD to compute the average PSD during the actual transmission time.
If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


7.4. Test result


Test Engineer:	Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	25.5℃,39.8%RH	Test Date:	2024.10.16
Test Power Supply:	AC 120V/60HZ	Sample Number:	S24092407-001

Test Mode	Antenna	Frequency [MHz]	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-26.14	≤8.00	PASS
		2437	-20.42	≤8.00	PASS
		2462	-19.56	≤8.00	PASS
11G	Ant1	2412	-15.18	≤8.00	PASS
		2437	-15.63	≤8.00	PASS
		2462	-16.36	≤8.00	PASS
11N20SISO	Ant1	2412	-14.07	≤8.00	PASS
		2437	-14.31	≤8.00	PASS
		2462	-15.12	≤8.00	PASS
11N40SISO	Ant1	2422	-15.94	≤8.00	PASS
		2437	-17.55	≤8.00	PASS
		2452	-17.07	≤8.00	PASS


Note: The Duty Cycle Factor is compensated in the graph.

7.5. Test graphs







11G Ant1_2437




11G Ant1_2462




11N20SISO Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462




11N40SISO_Ant1_2422



11N40SISO_Ant1_2437




11N40SISO_Ant1_2452



8. Band Edge Compliance (Conducted Method)

8.1. Block diagram of test setup



8.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

8.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.


Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.


8.4. Test result

Test Engineer:	Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	25.5℃,39.8%RH	Test Date:	2024.10.16
Test Power Supply:	AC 120V/60HZ	Sample Number:	S24092407-001


EUT Set Mode	CH or Frequency	Result(dBm)	EUT Set Mode	CH or Frequency	Result (dBm)
11b	CH1	Pass	11g	CH1	Pass
	CH11	Pass		CH11	Pass
11n HT 20	CH1	Pass	11n HT 40	CH3	Pass
	CH11	Pass		CH9	Pass

8.5. Test graphs







11N20SISO_Ant1_Low_2412




11N20SISO_Ant1_High_2462



11N40SISO_Ant1_Low_2422




11N40SISO_Ant1_High_2452



9. RF Conducted Spurious Emissions

9.1. Block diagram of test setup



9.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

9.3. Test procedure

- Connect EUT's antenna output to spectrum analyzer by RF cable.
- Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold
- Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{Span/RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold


(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band


9.4. Test result


Test Engineer:	Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	25.5℃,39.8%RH	Test Date:	2024.10.16
Test Power Supply:	AC 120V/60HZ	Sample Number:	S24092407-001

EUT Set Mode	CH or Frequency	Result(dBm)	EUT Set Mode	CH or Frequency	Result (dBm)
11b	CH1	Pass	11g	CH1	Pass
	CH11	Pass		CH11	Pass
11n HT 20	CH1	Pass	11n HT 40	CH3	Pass
	CH11	Pass		CH9	Pass


9.5. Test graphs









11B_Ant1_2462_30~1000




11B_Ant1_2462_1000~26500




11G_Ant1_2412_0~Reference







11G_Ant1_2437_30~1000





11G_Ant1_2437_1000~26500





11G_Ant1_2462_0~Reference



















11N40SISO_Ant1_2452_30~1000




11N40SISO_Ant1_2452_1000~26500



10. Duty Cycle

10.1. Block diagram of test setup



10.2. Limit

Just for Report.

10.3. Test procedure

- (1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, The cable loss and attenuator loss have been put into spectrum analyzer as amplitude offset.
set the Spectrum Analyzer as below:
 - Centre Frequency: The centre frequency of the middle hopping channel.
 - Resolution BW: 10 MHz.
 - Video BW: 10 MHz.
 - Span: Zero span.
 - Detector: Peak.
 - Trace Mode: Clear Write.
 - Sweep: Video Trigger
- (2) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.
- (3) Calculate dwell time follow below formula:
Duty cycle= Pulse's on time / Burst cycle


10.4. Test result


Test Engineer:	Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	25.5℃,39.8%RH	Test Date:	2024.10.16
Test Power Supply:	AC 120V/60HZ	Sample Number:	S24092407-001

Test Mode	Antenna	Frequency [MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	Ant1	2412	8.39	8.48	98.94
		2437	8.40	8.49	98.94
		2462	8.38	8.48	98.82
11G	Ant1	2412	1.39	1.41	98.58
		2437	1.39	1.41	98.58
		2462	1.39	1.41	98.58
11N20SISO	Ant1	2412	1.30	1.32	98.48
		2437	1.30	1.32	98.48
		2462	1.30	1.32	98.48
11N40SISO	Ant1	2422	30.00	30.00	100.00
		2437	30.00	30.00	100.00
		2452	30.00	30.00	100.00


10.5. Test graphs








11N20SISO_Ant1_2437



11N20SISO_Ant1_2462



11N40SISO_Ant1_2422