

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
CERTIFICATION TO FCC PART 15 REQUIREMENTS**

for

INTENTIONAL RADIATOR

434 MHz CAR ALARM TRANSMITTER

MODEL NO: PRO-OE2C4S

FCC ID NO: ELVAT1G

REPORT NO: 01E9813

ISSUE DATE: SEPTEMBER 27, 2001

Prepared for

NUTEK CORPORATION

**5F, NO. 3, ALLEY 6, LANE 45, PAO-HSING RD.,
HSING-TIEN CITY, TAIPEI, TAIWAN, R. O. C.**

Prepared by

COMPLIANCE ENGINEERING SERVICES, INC.

**NO. 199, CHUNG SHENG ROAD,
HSIN TIEN CITY, TAIPEI,
TAIWAN, R. O. C.**

d.b.a.

COMPLIANCE CERTIFICATION SERVICES



**FCC, VCCI, CISPR, CE
UL, CSA, TÜV, VDE**

**U.S.A. : P.O.BOX 612650, SAN JOSE, CA 95161-2650
TAIPEI : P.O.BOX 17-82, HSIN TIEN, TAIWAN, R.O.C.**

TABLE OF CONTENTS	PAGE
1. VERIFICATION OF COMPLIANCE.....	1
2. Product Description.....	2
3. Test Facility.....	2
4. Measurement Standards	2
5. Test Methodology	2
6. Measurement Equipment Used	3
7. POWERLINE RFI LIMIT	3
8. RADIATED EMISSION LIMITS	3
9. SYSTEM TEST CONFIGURATION.....	4
10. Test Procedure.....	5
11. Equipment Modifications.....	6
12. TEST RESULT	7
12.1 Maximum Modulation Percentage (M%)	7
12.2 The Emissions Bandwidth.....	7

TEST DATA

- Maximum Modulation Percentage Plot
- Emission Bandwidth Plot
- Radiated Emission Worksheet for Average Measurement

1. VERIFICATION OF COMPLIANCE

COMPANY NAME: NUTEK CORPORATION
5F, NO. 3, ALLEY 6, LANE 45, PAO-HSING RD.,
HSING-TIEN CITY, TAIPEI, TAIWAN, R. O. C.

CONTACT PERSON: RUBY HSIEH / MARKETING DEPT.

TELEPHONE NO.: (02) 2918-9478 # 120

EUT DESCRIPTION: 434 MHz CAR ALARM TRANSMITTER

MODEL NAME/NUMBER: PRO-OE2C4S

FCC ID: ELVAT1G

DATE TESTED: SEPTEMBER 13 ~ 20, 2001

REPORT NUMBER: 01E9813

TYPE OF EQUIPMENT	SECURITY EQUIPMENT (INTENTIONAL RADIATOR)
EQUIPMENT TYPE	434 MHz CAR ALARM TRANSMITTER
MEASUREMENT PROCEDURE	ANSI C63.4 / 1992
LIMIT TYPE	CERTIFICATION
FCC RULE	CFR 47, PART 15

The above equipment was tested by Compliance Engineering Services, Inc. for compliance with the requirements set forth in the FCC CFR 47, PART 15. The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties. **Warning** : This document reports conditions under which testing was conducted and results of tests performed. This document may not be altered or revised in any way unless done so by Compliance Engineering Services, Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Engineering Services, Inc. will constitute fraud and shall nullify the document.


RICK YEO / EMC MANAGER
COMPLIANCE ENGINEERING SERVICES, INC.

2. Product Description

Fundamental Frequency	434 MHz
Power Source	12V Battery
Transmitting Time	Periodic $\leq$ 5 seconds
Associated Receiver	FCC ID: ELVAR8B

3. Test Facility

The open area test sites and conducted measurement facilities used to collect the radiated data are located at No. 199, Chung Sheng Road, Hsin Tien City, Taipei, Taiwan R.O.C. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

4. Measurement Standards

The site is constructed and calibrated in conformance with the requirements of ANSI C63.4/1992.

5. Test Methodology

For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 KHz, up to at least the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower. (CFR 47 Section 15.33)

6. Measurement Equipment Used

Manufacturer	Model Number	Description	Cal Due Date
ROHDE & SCHWARZ	DSAI- D 804.8932.52	EMI Test Display	11/2001
ROHDE & SCHWARZ	ESBI- RF/1005.4300.52	EMI Test RF Unit	11/2001
H.P.	8595EM	Spectrum Analyzer (9KHz – 6.5GHz)	01/2002
EMCO	3115	Antenna (1-18GHz)	02/2002
SCHWARZBECK	VULB 9160	Antenna (30-2000 MHz)	05/2002
H.P.	8447D	Amplifier	05/2002
MITEQ	NSP2600-44	Amplifier(1-26GHz)	02/2002

7. POWERLINE RFI LIMIT


CONNECTED TO AC POWER LINE	SECTION 15.207
CARRIER CURRENT SYSTEM IN THE FREQUENCY RANGE OF 450 KHZ TO 30 MHz	SECTION 15.205 AND SECTION 15.209, 15.221, 15.223, 15.225 OR 15.227, AS APPROPRIATE.
BATTERY POWER	NO REQUIRED.

8. RADIATED EMISSION LIMITS

GENERAL REQUIREMENTS	SECTION 15.209
RESTRICTED BANDS OF OPERATION	SECTION 15.205
PERIODIC OPERATION IN THE BAND 40.66 -40.70 MHz AND ABOVE 70 MHz.	SECTION 15.231


9. SYSTEM TEST CONFIGURATION

Use a block of foam and combined it with EUT wrapping rubber band around it. This way it can test X.Y, and Z axis. To activate continuous transmission, place a small plastic block between rubber band and EUT push button.



10. Test Procedure


Radiated Emissions, 15.231(4)(b)



preamplifier/spectrum analyzer

Fig. 1

1. The EUT was placed on a wooden table on the outdoor ground plane. The search antenna was placed 3-meters from the EUT.
2. The turntable was slowly rotated to locate the direction of maximum emission at each emission falling in the restricted bands of 15.205. The EUT was moved throughout the XY, XZ, and YZ planes to maximize emissions received by the search antenna.
3. Once maximum direction was determined, the search antenna was raised and lowered in both vertical and horizontal polarizations. The maximum readings so obtained are recorded in the data listed below.



1. The EUT was placed on a wooden table on the outdoor ground plane. The search antenna was placed 1-meters from the EUT. The EUT antenna was mounted vertically as per normal installation.
2. The turntable was slowly rotated to locate the direction of maximum emission at each emission falling in the restricted bands of 15.205. The EUT was moved throughout the XY, XZ, and YZ planes to maximize emissions received by the search antenna.
3. Once maximum direction was determined, the search antenna was raised and lowered in both vertical and horizontal polarizations. The maximum readings so obtained are recorded in the data listed below.

11. Equipment Modifications

To achieve compliance to FCC Section 15.231 technical limits, the following change(s) were made during compliance testing:

NONE

12. TEST RESULT

Powerline RFI Class B	Eut	Radiated Emission Limits	Eut
SECTION 15.207		SECTION 15.209	X
SECTION 15.205, 15.209, 15.221, 15.223, x 15.225 OR 15.227		SECTION 15.205	
BATTERY POWER	X	SECTION 15.231 (b)	X
		SECTION 15.231 (e)	

12.1 Maximum Modulation Percentage (M%)

CALCULATION:

Average Reading = Peak Reading (dBuV/m)+ 20log (Duty Cycle)

In order to determine possible Maximum Modulation percentage, alternations are made to the EUT. We measured:

WHERE 1 Period = 71.25 mS
 Long pulse = 0.8625 mS
 Short pulse = 0.375 mS
 No of Long pulse = 14
 No of Short pulse = 11

Duty Cycle = (N1L1+N2L2+...+Nn-1Ln-1+NnLn)/100 or T

Duty Cycle = ((14x0.8625)+(11x0.375))/71.25=0.2274=22.74% or -12.8642dB

12.2 The Emissions Bandwidth

The bandwidth of the emissions were investigated per 15.231(c)

Center Frequency	Measured	Limits
434 MHz	366.6 kHz < (refer to plot)	434MHzX0.25%=1085 kHz

[illegible]



FCC, VCCI, CISPR, CE, AUSTEL, NZ
UL, CSA, TUV, BSMI, DHHS, NVLAP

No. 199 Chung Sheng Road
Hsin Tien City, Taipei, Taiwan, R.O.C.
PHONE: 02-2217-0894 FAX: 02-2217-1254

Project #: 01E9813
Report #: 9813D2
Date & Time: 2001/09/20
Test Engr: Vince Chiang

Company: NUTEK CORPORATION
EUT Description: PRO-OE2C4S (Alarm Tx / 434MHz)
Test Configuration : EUT ONLY
Type of Test: FCC 15.231(b)/FCC 15.209
Mode of Operation: NORMAL MODE

☒ D Site ☐ E Site

Freq. (MHz)	Pk Rdg (dBuV)	Av Rdg (dBuV)	AF (dB)	Closs (dB)	Pre-amp (dB)	Level (dBuV/m)	Limit FCC_B	Margin (dB)	Pol (H/V)	Az (Deg)	Height (Meter)	Mark (P/Q/A)
1303	47.48	34.62	24.9	2.8	38.00	24.34	54.0	-29.66	1mV	180	1.0	A
1733	47.44	34.58	26.3	3.3	37.95	26.24	60.8	-34.58	1mV	90	1.2	A
1303	47.48	34.62	24.9	2.8	38.00	24.34	54.0	-29.66	1mH	180	1.0	A
1733	46.64	33.78	26.3	3.3	37.95	25.44	60.8	-35.38	1mH	90	1.2	A

* No other emission were found within 20dB under the limits upto 4.5 GHz.

Total data #:4
V.2d

P(Peak): RBW=VBW=1MHz
A(Average): Pk Reading - 12.864 dB

20:54:18 SEP 13, 2001

MKR Δ 71.250002 msec

REF 87.0 dB μ V ATTEN 10 dB

.00 dB

PEAK

LOG

10

dB/

CENTER
433.863 MHz

SA SB

WC FS

CORR


CENTER 433.863 MHz

#RES BW 120 KHz

SPAN 0 Hz

#SWP 150 msec

VBW 300 KHz



22:16:47 SEP 13, 2001

MKR 44.374999 msec

REF 87.0 dB μ V ATTN 10 dB

22.27 dB μ V

PEAK

LOG

10

dB/

CENTER
433.869 MHz

SA SB

VC FC

CORR


CENTER 433.869 MHz

#RES BW 120 KHz

VBW 300 KHz

SPAN 0 Hz

#SWP 50 msec



22: 10: 27 SEP 13. 2001

70 MKR Δ 862.500 μ sec
-- .05 dB

REF 87.0 dB μ W ATTEN 10 dB

PEAK

LOG

10

dB/

CENTER
433.869 MHz

SA SB

VC FC

CORR


CENTER 433.869 MHz

#RES BW 120 KHz

VBW 300 KHz

SPAN 0 Hz

#SWP 15 msec



21:08:32 SEP 13, 2001

MKR Δ 375.000 μ sec

REF 87.0 dB μ V ATTEN 10 dB

- .03 dB

PEAK


LOG

10

dB/

CENTER
433.869 MHz

SA SB
WC FS
CORR



CENTER 433.869 MHz

#RES BW 120 KHz

VBW 300 KHz

SPAN 0 Hz

#SWP 15 msec



Date 14.Sep.'01 Time 23:19:29

Ref.Lvl Delta

80.00 dBuV

-0.17 dB

366.6 kHz

Res.Bw

TG.Lvl

CF.Stp

120 kHz [imp]

Off

200.000 kHz

Vid.Bw


RF.Att

Unit

300 kHz

10 dB

[dBuV]



N dB down Level 20.0 dB
DELTA MARK 366.6 KHz