



## SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053

Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com

Report No.: SZEM180400250602

Page: 1 of 100

# FCC REPORT

**Application No:** SZEM1804002506RG  
**Applicant:** Hisense International Co., Ltd.  
**Manufacturer:** Hisense Communications Co., Ltd.  
**Factory:** Hisense Communications Co., Ltd.  
**Product Name:** Mobile Phone  
**Model No.(EUT):** Hisense T17  
**Trade Mark:** Hisense  
**FCC ID:** 2ADOBT17  
**Standards:** 47 CFR Part 15, Subpart C  
**Test Method:** KDB 558074 D01 DTS Meas Guidance v04  
ANSI C63.10 (2013)  
**Date of Receipt:** 2018-03-19  
**Date of Test:** 2018-03-19 to 2018-03-26  
**Date of Issue:** 2018-04-09

<b>Test Result:</b>	<b>PASS *</b>
---------------------	---------------

. \* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Derek Yang  
Wireless Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



## 2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2018-04-09		Original

Authorized for issue by:				
Tested By				2018-03-36
				Date
Checked By				2018-04-09
				Date
		(Mike Hu) /Project Engineer		
		(Jim Huang) /Reviewer		



### 3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS



Model No.: Hisense T17

This test report (Ref. No.: SZEM180400250602) is only valid with the original test report (Ref. No.: SZEM180100087902).

According to the declaration from the applicant, the model in this report and model in original report was identical, with only difference on the supplier of TP/LCD/Camera is as bellowing:

**Main Supply**

Part Name	Model Name	supplier	Remark
TP	Y138067F2-D-X	YUYE	
Front-facing Camera	C10910	CXTCCM	
LCD	Y87397	DIGITAL	
Rear Camera	C10911	CXTCCM	

**Secondary Supply**

Part Name	Model Name	supplier	Remark
TP	CCG10117-5.5	HOLITHECH	
Front-facing Camera	HEPS7543-A	HOLITHECH	
LCD	HTT055H517	HOLITHECH	
Rear Camera	HFBS7545-A	HOLITHECH	

Considering to the difference, pre-scan was performed on the sample in this report to find the items which can be influential to the result in the original test report for fully retest.

Therefore, in this report worse case mode of Field strength of spurious radiation on Model Hisense T17 are retested and shown the data in this report.



## 4 Contents

	Page
.....	1
2 VERSION .....	2
3 TEST SUMMARY .....	3
4 CONTENTS .....	5
5 GENERAL INFORMATION.....	6
5.1 CLIENT INFORMATION .....	6
5.2 GENERAL DESCRIPTION OF EUT .....	6
5.3 TEST ENVIRONMENT AND MODE .....	8
5.4 DESCRIPTION OF SUPPORT UNITS .....	8
5.5 TEST LOCATION .....	8
5.6 TEST FACILITY .....	8
5.7 DEVIATION FROM STANDARDS .....	9
5.8 ABNORMALITIES FROM STANDARD CONDITIONS .....	9
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	9
5.10 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2) .....	9
5.11 EQUIPMENT LIST .....	10
6 TEST RESULTS AND MEASUREMENT DATA.....	13
6.1 ANTENNA REQUIREMENT.....	13
6.2 CONDUCTED EMISSIONS .....	14
6.3 CONDUCTED PEAK OUTPUT POWER .....	18
6.4 6dB OCCUPY BANDWIDTH .....	20
6.5 POWER SPECTRAL DENSITY .....	27
6.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS .....	34
6.7 RF CONDUCTED SPURIOUS EMISSIONS .....	38
6.8 RADIATED SPURIOUS EMISSIONS.....	44
6.8.1 Radiated emission below 1GHz.....	47
6.8.2 Transmitter emission above 1GHz.....	50
6.9 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY .....	72
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS .....	100



## 5 General Information

### 5.1 Client Information

Applicant:	Hisense International Co., Ltd.
Address of Applicant:	Floor 22, Hisense Tower, 17 Donghai Xi Road, Qingdao, 266071, China
Manufacturer:	Hisense Communications Co., Ltd.
Address of Manufacturer:	218 Qianwangang Road, Economic & Technological Development Zone, Qingdao, Shandong Province, P.R. China
Factory:	Hisense Communications Co., Ltd.
Address of Factory:	218 Qianwangang Road, Economic & Technological Development Zone, Qingdao, Shandong Province, P.R. China

### 5.2 General Description of EUT

Product Name:	Mobile Phone
Model No.:	Hisense T17
Trade Mark:	Hisense
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20) : OFDM (64QAM,16QAM,QPSK,BPSK)
Sample Type:	Portable Device
Antenna Type:	PIFA
Antenna Gain:	-0.3dBi
Power Supply	DC3.8V (1 x 3.8V Rechargeable battery) 2450mAh Battery: Charge by DC 5V
AC adaptor:	Model:TPA-97050100UU Input: AC100-240V 50/60Hz 0.15A Output:DC5.0V 1A



Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11b/g/n (HT20):

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz

### 5.3 Test Environment and Mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	50 % RH
Atmospheric Pressure:	1010 mbar
Test mode:	
Transmitting mode:	Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.

### 5.4 Description of Support Units

The EUT has been tested independent unit.

### 5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.  
 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

### 5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

• **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

• **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.





## **5.7 Deviation from Standards**

None.

## **5.8 Abnormalities from Standard Conditions**

None.

## **5.9 Other Information Requested by the Customer**

None.

## **5.10 Measurement Uncertainty (95% confidence levels, k=2)**

No.	Item	Measurement Uncertainty
1	Total RF power, conducted	0.75dB
2	RF power density, conducted	2.84dB
3	Spurious emissions, conducted	0.75dB
4	Radiated Spurious emission test	4.5dB (30MHz-1GHz)
		4.8dB (1GHz-25GHz)
5	Conduct emission test	3.12 dB(9KHz- 30MHz)
6	Temperature test	1 °C
7	Humidity test	3%
8	DC and low frequency voltages	0.5%



## 5.11 Equipment List

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Duedate (yyyy-mm-dd)
1	Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2017/5/10	2018/5/10
2	LISN	Rohde & Schwarz	ENV216	SEM007-01	2017/10/9	2018/10/9
3	LISN	ETS-LINDGREN	3816/2	SEM007-02	2017/4/14	2018/4/14
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	EMC0120	2017/9/28	2018/9/28
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	EMC0121	2017/9/28	2018/9/28
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	EMC0122	2017/9/28	2018/9/28
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2017/4/14	2018/4/14
8	DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2017/10/9	2018/10/9

RF connected test						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Duedate (yyyy-mm-dd)
1	DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017/10/9	2018/10/9
2	Signal Analyzer	Rohde &Schwarz	FSV	W005-02	2018/3/13	2019/3/12
3	Signal Generator	Rohde &Schwarz	SML03	SEM006-02	2017/4/14	2018/4/14
4	Power Meter	Rohde &Schwarz	NRVS	SEM014-02	2017/10/9	2018/10/9
5	Power Sensor	Agilent Technologies	U2021XA	SEM009-01	2017/10/9	2018/10/9



RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2017/5/10	2018/5/10
2	EMI Test Receiver	Agilent Technologies	N9038A	SEM004-05	2017/10/9	2018/10/9
3	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-01	2017/11/1	2020/11/1
4	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEM003-11	2015/10/17	2018/10/17
5	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEM003-12	2017/11/24	2020/11/24
6	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEM005-01	2017/4/14	2018/4/14
7	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A
8	DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2017/10/9	2018/10/9
9	Loop Antenna	Beijing Daze	ZN30401	SEM003-09	2015/5/13	2018/5/13

RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
1	10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2017/5/10	2018/5/10
2	EMI Test Receiver (9k-7GHz)	Rohde & Schwarz	ESR	SEM004-03	2017/4/14	2018/4/14
3	Trilog-Broadband Antenna(30M-1GHz)	Schwarzbeck	VULB9168	SEM003-18	2016/6/29	2019/6/29
4	Pre-amplifier	Sonoma Instrument Co	310N	SEM005-03	2017/7/6	2018/7/6
5	.Loop Antenna	ETS-Lindgren	6502	SEM003-08	2015/8/14	2018/8/14



RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2017/5/10	2018/5/10
2	EXA Spectrum Analyzer	Agilent Technologies Inc	N9010A	SEM004-09	2017/7/19	2018/7/19
3	BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-02	2017/11/15	2020/11/15
4	Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2017/10/9	2018/10/9
5	Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015/6/14	2018/6/14
6	Horn Antenna (18-26GHz)	ETS-Lindgren	3160	SEM003-12	2017/11/24	2020/11/24
7	HornAntenna (26GHz-40GHz)	A.H.Systems, inc.	SAS-573	SEM003-13	2017/10/17	2020/10/16
8	Low Noise Amplifier	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2017/10/9	2018/10/9
9	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A



## 6 Test results and Measurement Data

### 6.1 Antenna Requirement

<b>Standard requirement:</b>	47 CFR Part 15C Section 15.203 /247(c)
<p>15.203 requirement:</p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement:</p> <p>The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p> <p>The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -0.3dBi.</p>	

## 6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	<div>1) The mains terminal disturbance voltage test was conducted in a shielded room.</div> <div>2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</div> <div>3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,</div> <div>4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.</div> <div>5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</div>		
Test Setup:	<div><div>Shielding Room</div><div><div><div>AC Mains</div><div>LISN1</div></div><div><div>80cm</div><div>EUT</div><div>AE</div></div><div><div>80cm</div><div>LISN2</div><div>AC Mains</div></div><div><div>Test Receiver</div></div></div><div>Ground Reference Plane</div></div>		




Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel. Charge + Transmitting mode.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate of 802.11b at lowest channel is the worst case. Charge + Transmitting mode. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

## Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live Line:



Site : Shielding Room

Condition: Line

Job No. : 00879RG


Test mode: c

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.19	0.02	9.51	14.63	24.16	54.20	-30.04	Average
2	0.19	0.02	9.51	31.42	40.95	64.20	-23.25	QP
3	0.25	0.01	9.51	15.57	25.09	51.82	-26.73	Average
4	0.25	0.01	9.51	30.75	40.27	61.82	-21.55	QP
5	0.31	0.01	9.51	14.81	24.33	49.97	-25.64	Average
6	0.31	0.01	9.51	29.31	38.83	59.97	-21.14	QP
7	0.44	0.01	9.49	20.76	30.26	47.11	-16.85	Average
8	0.44	0.01	9.49	31.55	41.05	57.11	-16.06	QP
9	0.56	0.01	9.51	16.86	26.38	46.00	-19.62	Average
10	0.56	0.01	9.51	28.35	37.87	56.00	-18.13	QP
11	4.62	0.01	9.55	15.01	24.57	46.00	-21.43	Average
12	4.62	0.01	9.55	31.20	40.76	56.00	-15.24	QP





Neutral Line:



Site : Shielding Room

Condition: Neutral

Job No. : 00879RG


Test mode: c

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.18	0.02	9.58	14.94	24.54	54.50	-29.96	Average
2	0.18	0.02	9.58	30.33	39.93	64.50	-24.57	QP
3	0.25	0.01	9.58	18.96	28.55	51.78	-23.23	Average
4	0.25	0.01	9.58	31.71	41.30	61.78	-20.48	QP
5	0.37	0.01	9.58	18.06	27.65	48.47	-20.82	Average
6	0.37	0.01	9.58	28.37	37.96	58.47	-20.51	QP
7	0.49	0.01	9.60	24.28	33.89	46.10	-12.21	Average
8	0.49	0.01	9.60	31.59	41.20	56.10	-14.90	QP
9	0.69	0.02	9.62	19.14	28.78	46.00	-17.22	Average
10	0.69	0.02	9.62	29.16	38.80	56.00	-17.20	QP
11	4.41	0.01	9.68	20.48	30.17	46.00	-15.83	Average
12	4.41	0.01	9.68	31.89	41.58	56.00	-14.42	QP

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.

### 6.3 Conducted Peak Output Power


Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10 :2013 Section 11.9.1.3
Test Setup:	
Test Instruments:	Refer to section 5.10 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20).
Limit:	30dBm
Test Results:	Pass



**Measurement Data**

802.11b mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	16.24	30.00	Pass
Middle	16.75	30.00	Pass
Highest	15.82	30.00	Pass
802.11g mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	16.62	30.00	Pass
Middle	17.15	30.00	Pass
Highest	17.21	30.00	Pass
802.11n(HT20) mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	15.69	30.00	Pass
Middle	15.88	30.00	Pass
Highest	16.28	30.00	Pass

## 6.4 6dB Occupy Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10: 2013 Section 11.8.1 Option 1
Test Setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two vertical legs. Below the table is a Ground Reference Plane.</p>
Instruments Used:	Refer to section 5.10 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20).
Limit:	$\geq 500$ kHz
Test Results:	Pass




**Measurement Data**

802.11b mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	10.07	≥500	Pass
Middle	10.07	≥500	Pass
Highest	10.07	≥500	Pass
802.11g mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	16.42	≥500	Pass
Middle	16.39	≥500	Pass
Highest	16.39	≥500	Pass
802.11n(HT20) mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	17.44	≥500	Pass
Middle	17.41	≥500	Pass
Highest	17.41	≥500	Pass




Test plot as follows:

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------




Date: 8.FEB.2018 07:26:25

Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------




Date: 8.FEB.2018 07:36:53

Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------



Date: 8.FEB.2018 07:37:50


Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------



Date: 8.FEB.2018 07:29:01




Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------



Date: 8.FEB.2018 07:35:30

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------




Date: 8.FEB.2018 07:38:50






Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------



Date: 8.FEB.2018 07:34:17


Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------



Date: 8.FEB.2018 07:32:52




Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------



Date: 8.FEB.2018 07:40:54

## 6.5 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10 :2013 Section 11.10.2
Test Setup:	 <p>The diagram illustrates the test setup. A 'Spectrum Analyzer' is connected to an 'E.U.T' (Equipment Under Test) by a red cable. Both the analyzer and the E.U.T are placed on a 'Non-Conducted Table'. Below the table is a 'Ground Reference Plane'.</p>
Test Instruments:	Refer to section 5.10 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20).
Limit:	≤8.00dBm/3kHz
Test Results:	Pass




**Measurement Data**

802.11b mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-11.26	≤8.00	Pass
Middle	-10.23	≤8.00	Pass
Highest	-9.62	≤8.00	Pass
802.11g mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-14.00	≤8.00	Pass
Middle	-13.29	≤8.00	Pass
Highest	-14.40	≤8.00	Pass
802.11n(HT20) mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-15.02	≤8.00	Pass
Middle	-15.12	≤8.00	Pass
Highest	-14.79	≤8.00	Pass




Test plot as follows:

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------



Date: 8.FEB.2018 07:45:31


Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------



Date: 8.FEB.2018 07:46:37




Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------



Date: 8.FEB.2018 07:48:48


Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------



Date: 8.FEB.2018 07:43:35




Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------



Date: 8.FEB.2018 07:44:17


Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------



Date: 8.FEB.2018 07:44:47




Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------



Date: 8.FEB.2018 07:43:09

Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------




Date: 8.FEB.2018 07:42:45






Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------



Date: 8.FEB.2018 07:42:11


## 6.6 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013 Section 11.13
Test Setup:	 <p>The diagram illustrates the test setup for RF conducted emissions. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table, which is supported by two vertical legs. Below the table is a Ground Reference Plane.</p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20).
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass




Test plot as follows:

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------



Date: 8.FEB.2018 07:57:07


Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------



Date: 8.FEB.2018 08:23:06




Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------



Date: 8.FEB.2018 07:58:36


Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------



Date: 8.FEB.2018 08:20:37




Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------




Date: 8.FEB.2018 08:17:17

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------



Date: 8.FEB.2018 08:19:27


## 6.7 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013 Section 11.11
Test Setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two vertical legs. Below the table is a Ground Reference Plane.</p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20).
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass




Test plot as follows:

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------



Date: 8.FEB.2018 08:27:14


Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------



Date: 8.FEB.2018 08:26:18




Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------



Date: 8.FEB.2018 08:25:19

Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------




Date: 8.FEB.2018 08:28:19






Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------



Date: 8.FEB.2018 08:29:11


Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------



Date: 8.FEB.2018 08:30:27




Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------



Date: 8.FEB.2018 08:31:55


Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------



Date: 8.FEB.2018 08:32:44



Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------



Date: 8.FEB.2018 08:33:56

Remark:

Scan from 9kHz to 25GHz, the disturbance below 30MHz was very low, and the above harmonics were the highest point could be found when testing, the amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.



## 6.8 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 :2013 Section 11.12				
Test Site:	Measurement Distance: 3m or 10m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				

**Test Setup:**




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

**Test Procedure:**

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the



	<p>limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>h. Test the EUT in the lowest channel, the middle channel, the Highest channel</p> <p>i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case.</p> <p>j. Repeat above procedures until all frequencies measured was complete.</p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Charge + Transmitting mode.
Final Test Mode:	Pretest the EUT at Charge + Transmitting mode. Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); For below 1GHz, through Pre-scan, find the 1Mbps of rate of 802.11b at lowest channel is the worst case. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass



### 6.8.1 Radiated emission below 1GHz \_ Main Supply

The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L<sub>3</sub>: Level @ 3m distance. Unit: uV/m;

L<sub>10</sub>: Level @ 10m distance. Unit: uV/m;

D<sub>3</sub>: 3m distance. Unit: m


D<sub>10</sub>: 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 3m (uV/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Over Limit (dB)	Ant. Polarization
30.32	18.17	8.10	27.00	28.63	40.00	-11.37	V
54.07	18.23	8.16	27.19	28.69	40.00	-11.31	V
90.54	16.68	6.82	22.74	27.14	43.50	-16.36	V
146.37	16.61	6.77	22.56	27.07	43.50	-16.43	V
232.53	18.21	8.14	27.13	28.67	46.00	-17.33	V
618.54	25.43	18.69	62.28	35.89	46.00	-10.11	V
40.56	13.02	4.48	14.92	23.48	40.00	-16.52	H
56.79	13.50	4.73	15.77	23.96	40.00	-16.04	H
160.91	15.86	6.21	20.70	26.32	43.50	-17.18	H
549.02	21.79	12.29	40.96	32.25	46.00	-13.75	H
647.39	23.93	15.72	52.41	34.39	46.00	-11.61	H
887.61	26.50	21.13	70.45	36.96	46.00	-9.04	H



30MHz~1GHz (QP)		
Test mode:	Charge + Transmitting	Vertical



Condition: 10m VERTICAL

Job No. : 00879RG


Test Mode: WIFI

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.32	6.70	12.48	32.97	31.96	18.17	29.50	-11.33
2	54.07	6.98	12.45	32.98	31.78	18.23	29.50	-11.27
3	90.54	7.20	8.73	32.83	33.58	16.68	33.10	-16.42
4	146.37	7.43	13.18	32.75	28.75	16.61	33.10	-16.49
5	232.53	7.76	10.85	32.66	32.26	18.21	35.60	-17.39
6 pp	618.54	8.95	19.09	32.60	29.99	25.43	35.60	-10.17





Test mode:	Charge + Transmitting	Horizontal
------------	-----------------------	------------



Condition: 10m HORIZONTAL

Job No. : 00879RG


Test Mode: WIFI

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	40.56	6.80	13.27	32.99	25.94	13.02	29.50	-16.48
2	56.79	7.00	12.24	32.96	27.22	13.50	29.50	-16.00
3	160.91	7.50	13.30	32.73	27.79	15.86	33.10	-17.24
4	549.02	8.77	17.71	32.60	27.91	21.79	35.60	-13.81
5	647.39	9.02	19.50	32.60	28.01	23.93	35.60	-11.67
6 pp	887.61	9.50	22.06	32.51	27.45	26.50	35.60	-9.10



## 6.8.2 Transmitter emission above 1GHz \_ Main Supply

Test mode:	802.11b	Test channel:	Lowest	Remark:	Peak	Vertical
------------	---------	---------------	--------	---------	------	----------



Condition: 3m HORIZONTAL

Job No : 00879RG


Mode : 2412 TX RSE

Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1366.374	5.04	25.25	41.31	46.84	35.82	74.00	-38.18	peak
2	4304.400	7.34	33.60	42.38	46.54	45.10	74.00	-28.90	peak
3	4824.000	7.91	34.19	42.47	45.00	44.63	74.00	-29.37	peak
4	6507.536	11.52	35.12	41.21	46.63	52.06	74.00	-21.94	peak
5	7236.000	10.07	36.40	40.69	44.42	50.20	74.00	-23.80	peak
6 pp	9648.000	10.77	37.53	37.68	41.79	52.41	74.00	-21.59	peak



Test mode:	802.11b	Test channel:	Lowest	Remark:	Peak	Horizontal
------------	---------	---------------	--------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 00879RG


Mode : 2412 TX RSE

Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1644.019	5.30	26.44	41.50	45.00	35.24	74.00	-38.76	peak
2	4456.315	7.51	33.60	42.41	47.35	46.05	74.00	-27.95	peak
3	4824.000	7.91	34.19	42.47	46.13	45.76	74.00	-28.24	peak
4 pp	6698.373	10.97	35.67	41.07	47.62	53.19	74.00	-20.81	peak
5	7236.000	10.07	36.40	40.69	45.24	51.02	74.00	-22.98	peak
6	9648.000	10.77	37.53	37.68	40.70	51.32	74.00	-22.68	peak



Test mode:	802.11b	Test channel:	Middle	Remark:	Peak	Vertical
------------	---------	---------------	--------	---------	------	----------



Condition: 3m HORIZONTAL

Job No : 00879RG


Mode : 2437 TX RSE

Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1323.614	4.88	25.06	41.28	49.71	38.37	74.00	-35.63 peak
2	4430.628	7.48	33.60	42.41	45.92	44.59	74.00	-29.41 peak
3	4874.000	7.96	34.28	42.48	45.05	44.81	74.00	-29.19 peak
4 pp	6874.906	10.47	36.16	40.94	46.08	51.77	74.00	-22.23 peak
5	7311.000	10.05	36.37	40.64	44.24	50.02	74.00	-23.98 peak
6	9748.000	10.82	37.55	37.54	39.91	50.74	74.00	-23.26 peak



Test mode:	802.11b	Test channel:	Middle	Remark:	Peak	Horizontal
------------	---------	---------------	--------	---------	------	------------



Condition: 3m VERTICAL

Job No : 00879RG


Mode : 2437 TX RSE

Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1323.614	4.88	25.06	41.28	48.30	36.96	74.00	-37.04 peak
2	4417.841	7.47	33.60	42.40	46.48	45.15	74.00	-28.85 peak
3	4874.000	7.96	34.28	42.48	44.31	44.07	74.00	-29.93 peak
4 pp	6914.763	10.36	36.27	40.91	46.16	51.88	74.00	-22.12 peak
5	7311.000	10.05	36.37	40.64	45.43	51.21	74.00	-22.79 peak
6	9748.000	10.82	37.55	37.54	39.77	50.60	74.00	-23.40 peak



Test mode:	802.11b	Test channel:	Highest	Remark:	Peak	Vertical
------------	---------	---------------	---------	---------	------	----------



Condition: 3m HORIZONTAL

Job No : 00879RG


Mode : 2462 TX RSE

Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1663.137	5.27	26.52	41.51	57.88	48.16	74.00	-25.84 peak
2	4430.628	7.48	33.60	42.41	46.33	45.00	74.00	-29.00 peak
3	4924.000	8.01	34.37	42.49	44.57	44.46	74.00	-29.54 peak
4	6795.879	10.69	35.94	41.00	45.87	51.50	74.00	-22.50 peak
5	7386.000	10.03	36.34	40.59	43.50	49.28	74.00	-24.72 peak
6 pp	9848.000	10.87	37.57	37.41	41.31	52.34	74.00	-21.66 peak



Test mode:	802.11b	Test channel:	Highest	Remark:	Peak	Horizontal
------------	---------	---------------	---------	---------	------	------------



Condition: 3m VERTICAL

Job No : 00879RG


Mode : 2462 TX RSE

Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1366.374	5.04	25.25	41.31	46.39	35.37	74.00	-38.63	peak
2	4430.628	7.48	33.60	42.41	45.57	44.24	74.00	-29.76	peak
3	4924.000	8.01	34.37	42.49	44.48	44.37	74.00	-29.63	peak
4 pp	6717.762	10.91	35.72	41.05	46.16	51.74	74.00	-22.26	peak
5	7386.000	10.03	36.34	40.59	44.10	49.88	74.00	-24.12	peak
6	9848.000	10.87	37.57	37.41	39.93	50.96	74.00	-23.04	peak



Test mode:	802.11g	Test channel:	Lowest	Remark:	Peak	Vertical
------------	---------	---------------	--------	---------	------	----------



Condition: 3m HORIZONTAL

Job No : 00879RG

Mode : 2412 TX RSE


Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1323.614	4.88	25.06	41.28	49.78	38.44	74.00	-35.56	peak
2	4316.859	7.36	33.60	42.38	45.98	44.56	74.00	-29.44	peak
3	4824.000	7.91	34.19	42.47	45.10	44.73	74.00	-29.27	peak
4 pp	6756.708	10.80	35.83	41.03	46.13	51.73	74.00	-22.27	peak
5	7236.000	10.07	36.40	40.69	44.36	50.14	74.00	-23.86	peak
6	9648.000	10.77	37.53	37.68	40.49	51.11	74.00	-22.89	peak





Test mode:	802.11g	Test channel:	Lowest	Remark:	Peak	Horizontal
------------	---------	---------------	--------	---------	------	------------



Condition: 3m VERTICAL

Job No : 00879RG


Mode : 2412 TX RSE

Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1323.614	4.88	25.06	41.28	47.12	35.78	74.00	-38.22	peak
2	4379.699	7.43	33.60	42.40	46.48	45.11	74.00	-28.89	peak
3	4824.000	7.91	34.19	42.47	45.13	44.76	74.00	-29.24	peak
4	6602.265	11.24	35.39	41.14	46.49	51.98	74.00	-22.02	peak
5	7236.000	10.07	36.40	40.69	44.11	49.89	74.00	-24.11	peak
6 pp	9648.000	10.77	37.53	37.68	41.54	52.16	74.00	-21.84	peak



Test mode:	802.11g	Test channel:	Middle	Remark:	Peak	Vertical
------------	---------	---------------	--------	---------	------	----------



Condition: 3m HORIZONTAL

Job No : 00879RG


Mode : 2437 TX RSE

Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1319.794	4.87	25.04	41.28	47.20	35.83	74.00	-38.17	peak
2	4291.977	7.33	33.60	42.38	46.91	45.46	74.00	-28.54	peak
3	4874.000	7.96	34.28	42.48	44.98	44.74	74.00	-29.26	peak
4	6377.195	11.31	35.00	41.31	46.27	51.27	74.00	-22.73	peak
5	7311.000	10.05	36.37	40.64	44.39	50.17	74.00	-23.83	peak
6 pp	9748.000	10.82	37.55	37.54	40.96	51.79	74.00	-22.21	peak



Test mode:	802.11g	Test channel:	Middle	Remark:	Peak	Horizontal
------------	---------	---------------	--------	---------	------	------------



Condition: 3m VERTICAL

Job No : 00879RG


Mode : 2437 TX RSE

Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1323.614	4.88	25.06	41.28	48.02	36.68	74.00	-37.32 peak
2	4291.977	7.33	33.60	42.38	46.27	44.82	74.00	-29.18 peak
3	4874.000	7.96	34.28	42.48	44.96	44.72	74.00	-29.28 peak
4 pp	6071.417	10.71	34.76	41.55	47.89	51.81	74.00	-22.19 peak
5	7311.000	10.05	36.37	40.64	44.65	50.43	74.00	-23.57 peak
6	9748.000	10.82	37.55	37.54	39.56	50.39	74.00	-23.61 peak



Test mode:	802.11g	Test channel:	Highest	Remark:	Peak	Vertical
------------	---------	---------------	---------	---------	------	----------




Condition: 3m HORIZONTAL  
 Job No : 00879RG  
 Mode : 2462 TX RSE  
 Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1323.614	4.88	25.06	41.28	49.79	38.45	74.00	-35.55	peak
2	4417.841	7.47	33.60	42.40	47.27	45.94	74.00	-28.06	peak
3	4924.000	8.01	34.37	42.49	45.00	44.89	74.00	-29.11	peak
4 pp	6874.906	10.47	36.16	40.94	46.38	52.07	74.00	-21.93	peak
5	7386.000	10.03	36.34	40.59	44.19	49.97	74.00	-24.03	peak
6	9848.000	10.87	37.57	37.41	39.69	50.72	74.00	-23.28	peak



Test mode:	802.11g	Test channel:	Highest	Remark:	Peak	Horizontal
------------	---------	---------------	---------	---------	------	------------



Condition: 3m VERTICAL

Job No : 00879RG


Mode : 2462 TX RSE

Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1362.430	5.02	25.23	41.31	48.39	37.33	74.00	-36.67 peak
2	4379.699	7.43	33.60	42.40	46.75	45.38	74.00	-28.62 peak
3	4924.000	8.01	34.37	42.49	46.67	46.56	74.00	-27.44 peak
4	6358.789	11.27	34.99	41.32	46.97	51.91	74.00	-22.09 peak
5	7386.000	10.03	36.34	40.59	43.40	49.18	74.00	-24.82 peak
6 pp	9848.000	10.87	37.57	37.41	40.88	51.91	74.00	-22.09 peak



Test mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Peak	Vertical
------------	---------------	---------------	--------	---------	------	----------



Condition: 3m HORIZONTAL

Job No : 00879RG


Mode : 2412 TX RSE

Note : 2.4G WIFI 11N 20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1319.794	4.87	25.04	41.28	48.93	37.56	74.00	-36.44	peak
2	4443.453	7.50	33.60	42.41	47.18	45.87	74.00	-28.13	peak
3	4824.000	7.91	34.19	42.47	45.12	44.75	74.00	-29.25	peak
4 pp	6602.265	11.24	35.39	41.14	46.79	52.28	74.00	-21.72	peak
5	7236.000	10.07	36.40	40.69	43.94	49.72	74.00	-24.28	peak
6	9648.000	10.77	37.53	37.68	40.16	50.78	74.00	-23.22	peak



Test mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Peak	Horizontal
------------	---------------	---------------	--------	---------	------	------------



Condition: 3m VERTICAL

Job No : 00879RG


Mode : 2412 TX RSE

Note : 2.4G WIFI 11N 20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1319.794	4.87	25.04	41.28	47.06	35.69	74.00	-38.31	peak
2	4456.315	7.51	33.60	42.41	46.93	45.63	74.00	-28.37	peak
3	4824.000	7.91	34.19	42.47	46.22	45.85	74.00	-28.15	peak
4 pp	6602.265	11.24	35.39	41.14	46.40	51.89	74.00	-22.11	peak
5	7236.000	10.07	36.40	40.69	45.73	51.51	74.00	-22.49	peak
6	9648.000	10.77	37.53	37.68	40.18	50.80	74.00	-23.20	peak



Test mode:	802.11n(HT20)	Test channel:	Middle	Remark:	Peak	Vertical
------------	---------------	---------------	--------	---------	------	----------



Condition: 3m HORIZONTAL

Job No : 00879RG

Mode : 2437 TX RSE


Note : 2.4G WIFI 11N 20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1323.614	4.88	25.06	41.28	46.61	35.27	74.00	-38.73	peak
2	4062.629	7.06	33.60	42.34	46.72	45.04	74.00	-28.96	peak
3	4874.000	7.96	34.28	42.48	44.95	44.71	74.00	-29.29	peak
4 pp	6640.542	11.13	35.50	41.11	46.43	51.95	74.00	-22.05	peak
5	7311.000	10.05	36.37	40.64	43.95	49.73	74.00	-24.27	peak
6	9748.000	10.82	37.55	37.54	39.65	50.48	74.00	-23.52	peak





Test mode:	802.11n(HT20)	Test channel:	Middle	Remark:	Peak	Horizontal
------------	---------------	---------------	--------	---------	------	------------



Condition: 3m VERTICAL

Job No : 00879RG


Mode : 2437 TX RSE

Note : 2.4G WIFI 11N 20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1319.794	4.87	25.04	41.28	48.19	36.82	74.00	-37.18	peak
2	4495.125	7.55	33.60	42.42	47.72	46.45	74.00	-27.55	peak
3	4874.000	7.96	34.28	42.48	45.39	45.15	74.00	-28.85	peak
4 pp	6855.063	10.53	36.10	40.96	46.08	51.75	74.00	-22.25	peak
5	7311.000	10.05	36.37	40.64	44.36	50.14	74.00	-23.86	peak
6	9748.000	10.82	37.55	37.54	39.63	50.46	74.00	-23.54	peak



Test mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Peak	Vertical
------------	---------------	---------------	---------	---------	------	----------



Condition: 3m HORIZONTAL

Job No : 00879RG


Mode : 2462 TX RSE

Note : 2.4G WIFI 11N 20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1370.328	5.05	25.26	41.32	46.94	35.93	74.00	-38.07	peak
2	4443.453	7.50	33.60	42.41	46.40	45.09	74.00	-28.91	peak
3	4924.000	8.01	34.37	42.49	44.71	44.60	74.00	-29.40	peak
4 pp	6488.754	11.52	35.09	41.22	46.93	52.32	74.00	-21.68	peak
5	7386.000	10.03	36.34	40.59	43.89	49.67	74.00	-24.33	peak
6	9848.000	10.87	37.57	37.41	40.64	51.67	74.00	-22.33	peak



Test mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Peak	Horizontal
------------	---------------	---------------	---------	---------	------	------------



Condition: 3m VERTICAL

Job No : 00879RG

Mode : 2462 TX RSE

Note : 2.4G WIFI 11N 20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1319.794	4.87	25.04	41.28	47.84	36.47	74.00	-37.53	peak
2	4430.628	7.48	33.60	42.41	46.25	44.92	74.00	-29.08	peak
3	4924.000	8.01	34.37	42.49	44.80	44.69	74.00	-29.31	peak
4	6602.265	11.24	35.39	41.14	45.78	51.27	74.00	-22.73	peak
5	7386.000	10.03	36.34	40.59	43.53	49.31	74.00	-24.69	peak
6 pp	9848.000	10.87	37.57	37.41	40.97	52.00	74.00	-22.00	peak




### **6.8.3 Radiated emission below 1GHz \_ Secondary Supply**



Transmitter emission above 1GHz \_ Secondary Supply

Test mode:	802.11g	Test channel:	Highest	Remark:	Peak	Vertical
------------	---------	---------------	---------	---------	------	----------



Condition: 3m VERTICAL

Job No : 00879RG


Mode : 2462 TX SE

Note : 2.4G WiFi 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1315.985	4.86	25.03	41.27	50.21	38.83	74.00	-35.17	peak
2	4062.629	7.06	33.60	42.34	47.04	45.36	74.00	-28.64	peak
3	4924.000	8.01	34.37	42.49	45.53	45.42	74.00	-28.58	peak
4 pp	6679.040	11.02	35.61	41.08	46.41	51.96	74.00	-22.04	peak
5	7386.000	10.03	36.34	40.59	44.39	50.17	74.00	-23.83	peak
6	9848.000	10.87	37.57	37.41	40.17	51.20	74.00	-22.80	peak



Test mode:	802.11g	Test channel:	Highest	Remark:	Peak	Horizontal
------------	---------	---------------	---------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 00879RG

Mode : 2462 TX SE

Note : 2.4G WiFi 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1315.985	4.86	25.03	41.27	53.58	42.20	74.00	-31.80	peak
2	4443.453	7.50	33.60	42.41	47.42	46.11	74.00	-27.89	peak
3	4924.000	8.01	34.37	42.49	43.02	42.91	74.00	-31.09	peak
4 pp	6756.708	10.80	35.83	41.03	47.03	52.63	74.00	-21.37	peak
5	7386.000	10.03	36.34	40.59	44.13	49.91	74.00	-24.09	peak
6	9848.000	10.87	37.57	37.41	40.18	51.21	74.00	-22.79	peak



Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report..
- 4) Only the worstest case Radiated Spurious Emissions test data of Secondary supply showed .

## 6.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10: 2013 Section 11.12		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz






Test Procedure:	<ul style="list-style-type: none"><li>a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li><li>b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li><li>c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li><li>d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li><li>e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li><li>f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li><li>g. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel</li><li>h. Test the EUT in the lowest channel, the Highest channel</li><li>i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode. And found the X axis positioning which it is worse case.</li><li>j. Repeat above procedures until all frequencies measured was complete.</li></ul>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Charge + Transmitting mode.
Final Test Mode:	Pretest the EUT at Charge +Transmitting mode. Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20);. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass



Test plot of Main supply as follows:

Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	---------	---------------	--------	---------	------	----------




Condition: 3m VERTICAL  
Job No : 00879RG  
Mode : 2412 Band edge  
: 2.4G WIFI 11B  
: 14.5

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2383.803	5.47	29.06	41.87	49.04	41.70	74.00	-32.30 Peak
2	2390.000	5.47	29.08	41.87	47.60	40.28	74.00	-33.72 Peak
3 pp	2412.000	5.50	29.14	41.88	101.98	94.74	74.00	20.74 Peak



Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Average	Vertical
------------------	---------	---------------	--------	---------	---------	----------




Condition: 3m VERTICAL  
 Job No : 00879RG  
 Mode : 2412 Band edge  
       : 2.4G WIFI 11B  
       : 14.5

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2384.890	5.47	29.06	41.87	39.56	32.22	54.00	-21.78	Average
2	2390.000	5.47	29.08	41.87	39.21	31.89	54.00	-22.11	Average
3 pp	2412.000	5.50	29.14	41.88	100.07	92.83	54.00	38.83	Average



Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	---------	---------------	--------	---------	------	------------




Condition: 3m HORIZONTAL  
Job No : 00879RG  
Mode : 2412 Band edge  
: 2.4G WIFI 11B  
: 14.5

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2381.752	5.46	29.05	41.87	48.98	41.62	74.00	-32.38	peak
2	2390.000	5.47	29.08	41.87	47.24	39.92	74.00	-34.08	peak
3 pp	2412.000	5.50	29.14	41.88	99.53	92.29	74.00	18.29	peak



Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	---------	---------------	--------	---------	---------	------------




Condition: 3m HORIZONTAL  
 Job No : 00879RG  
 Mode : 2412 Band edge  
       : 2.4G WIFI 11B  
       : 14.5

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2382.596	5.46	29.06	41.87	40.89	33.54	54.00	-20.46 Average
2	2390.000	5.47	29.08	41.87	38.63	31.31	54.00	-22.69 Average
3 pp	2412.000	5.50	29.14	41.88	97.39	90.15	54.00	36.15 Average



Worse case mode:	802.11b	Test channel:	Highest	Remark:	Peak	Vertical
------------------	---------	---------------	---------	---------	------	----------




Condition: 3m VERTICAL  
Job No : 00879RG  
Mode : 2412 Band edge  
: 2.4G WIFI 11B  
: 14.5

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2383.803	5.47	29.06	41.87	49.04	41.70	74.00	-32.30	Peak
2	2390.000	5.47	29.08	41.87	47.60	40.28	74.00	-33.72	Peak
3 pp	2412.000	5.50	29.14	41.88	101.98	94.74	74.00	20.74	Peak



Worse case mode:	802.11b	Test channel:	Highest	Remark:	Average	Vertical
------------------	---------	---------------	---------	---------	---------	----------




Condition: 3m VERTICAL  
Job No : 00879RG  
Mode : 2412 Band edge  
: 2.4G WIFI 11B  
: 14.5

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2384.890	5.47	29.06	41.87	39.56	32.22	54.00	-21.78	Average
2	2390.000	5.47	29.08	41.87	39.21	31.89	54.00	-22.11	Average
3 pp	2412.000	5.50	29.14	41.88	100.07	92.83	54.00	38.83	Average



Worse case mode:	802.11b	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	---------	---------------	---------	---------	------	------------




Condition: 3m HORIZONTAL  
Job No : 00879RG  
Mode : 2462 Band edge  
: 2.4G WIFI 11B  
: 14.5

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2462.000	5.57	29.29	41.90	98.35	91.31	74.00	17.31	peak
2	2483.500	5.60	29.35	41.91	45.71	38.75	74.00	-35.25	peak
3	2488.813	5.61	29.37	41.91	47.85	40.92	74.00	-33.08	peak





Worse case mode:	802.11b	Test channel:	Highest	Remark:	Average	Horizontal
------------------	---------	---------------	---------	---------	---------	------------




Condition: 3m HORIZONTAL  
Job No : 00879RG  
Mode : 2462 Band edge  
: 2.4G WIFI 11B  
: 14.5

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2462.000	5.57	29.29	41.90	96.83	89.79	54.00	35.79	Average
2	2483.500	5.60	29.35	41.91	37.45	30.49	54.00	-23.51	Average
3	2499.495	5.62	29.40	41.92	37.70	30.80	54.00	-23.20	Average



Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	---------	---------------	--------	---------	------	----------



Condition: 3m VERTICAL

Job No : 00879RG

Mode : 2412 Band edge


: 2.4G WIFI 11G

: 11.5

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.968	5.47	29.08	41.87	57.04	49.72	74.00	-24.28 Peak
2	2390.000	5.47	29.08	41.87	57.04	49.72	74.00	-24.28 Peak
3 pp	2412.000	5.50	29.14	41.88	101.43	94.19	74.00	20.19 Peak



Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Average	Vertical
------------------	---------	---------------	--------	---------	---------	----------




Condition: 3m VERTICAL  
Job No : 00879RG  
Mode : 2412 Band edge  
: 2.4G WIFI 11G  
: 11.5

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	5.47	29.08	41.87	44.23	36.91	54.00	-17.09	Average
2	2390.000	5.47	29.08	41.87	44.23	36.91	54.00	-17.09	Average
3 pp	2412.000	5.50	29.14	41.88	93.96	86.72	54.00	32.72	Average



Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	---------	---------------	--------	---------	------	------------




Condition: 3m HORIZONTAL  
Job No : 00879RG  
Mode : 2412 Band edge  
: 2.4G WIFI 11G  
: 11.5

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.847	5.47	29.08	41.87	56.37	49.05	74.00	-24.95	peak
2	2390.000	5.47	29.08	41.87	54.05	46.73	74.00	-27.27	peak
3 pp	2412.000	5.50	29.14	41.88	97.84	90.60	74.00	16.60	peak



Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	---------	---------------	--------	---------	---------	------------




Condition: 3m HORIZONTAL  
Job No : 00879RG  
Mode : 2412 Band edge  
: 2.4G WIFI 11G  
: 11.5

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	5.47	29.08	41.87	42.06	34.74	54.00	-19.26	Average
2	2390.000	5.47	29.08	41.87	42.06	34.74	54.00	-19.26	Average
3 pp	2412.000	5.50	29.14	41.88	90.81	83.57	54.00	29.57	Average



Worse case mode:	802.11g	Test channel:	Highest	Remark:	Peak	Vertical
------------------	---------	---------------	---------	---------	------	----------




Condition: 3m VERTICAL  
Job No : 00879RG  
Mode : 2462 Band edge  
: 2.4G WIFI 11G  
: 11.5

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2462.000	5.57	29.29	41.90	99.51	92.47	74.00	18.47 Peak
2	2483.500	5.60	29.35	41.91	56.54	49.58	74.00	-24.42 Peak
3	2484.191	5.60	29.35	41.91	60.57	53.61	74.00	-20.39 Peak



Worse case mode:	802.11g	Test channel:	Highest	Remark:	Average	Vertical
------------------	---------	---------------	---------	---------	---------	----------




Condition: 3m VERTICAL  
Job No : 00879RG  
Mode : 2462 Band edge  
: 2.4G WIFI 11G  
: 11.5

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2462.000	5.57	29.29	41.90	92.90	85.86	54.00	31.86	Average
2	2483.500	5.60	29.35	41.91	44.42	37.46	54.00	-16.54	Average
3	2483.790	5.60	29.35	41.91	44.57	37.61	54.00	-16.39	Average



Worse case mode:	802.11g	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	---------	---------------	---------	---------	------	------------




Condition: 3m HORIZONTAL  
 Job No : 00879RG  
 Mode : 2462 Band edge  
       : 2.4G WIFI 11G  
       : 11.5

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2462.000	5.57	29.29	41.90	97.68	90.64	74.00	16.64 peak
2	2483.500	5.60	29.35	41.91	53.97	47.01	74.00	-26.99 peak
3	2484.292	5.60	29.35	41.91	54.15	47.19	74.00	-26.81 peak





Worse case mode:	802.11g	Test channel:	Highest	Remark:	Average	Horizontal
------------------	---------	---------------	---------	---------	---------	------------



Condition: 3m HORIZONTAL

Job No : 00879RG

Mode : 2462 Band edge


: 2.4G WIFI 11G

: 11.5

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2462.000	5.57	29.29	41.90	90.80	83.76	54.00	29.76	Average
2	2483.500	5.60	29.35	41.91	42.12	35.16	54.00	-18.84	Average
3	2483.940	5.60	29.35	41.91	41.84	34.88	54.00	-19.12	Average



Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	---------------	---------------	--------	---------	------	----------



Condition: 3m VERTICAL

Job No : 00879RG

Mode : 2412 Band edge


: 2.4G WIFI 11N 20

: 10.5

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.605	5.47	29.08	41.87	61.20	53.88	74.00	-20.12 Peak
2	2390.000	5.47	29.08	41.87	57.09	49.77	74.00	-24.23 Peak
3 pp	2412.000	5.50	29.14	41.88	101.00	93.76	74.00	19.76 Peak



Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Average	Vertical
------------------	---------------	---------------	--------	---------	---------	----------



Condition: 3m VERTICAL

Job No : 00879RG

Mode : 2412 Band edge


: 2.4G WIFI 11N 20

: 10.5

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	5.47	29.08	41.87	43.98	36.66	54.00	-17.34	Average
2	2390.000	5.47	29.08	41.87	43.98	36.66	54.00	-17.34	Average
3 pp	2412.000	5.50	29.14	41.88	92.65	85.41	54.00	31.41	Average



Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	---------------	---------------	--------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 00879RG

Mode : 2412 Band edge


: 2.4G WIFI 11N 20

: 10.5

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.726	5.47	29.08	41.87	54.37	47.05	74.00	-26.95	peak
2	2390.000	5.47	29.08	41.87	51.91	44.59	74.00	-29.41	peak
3 pp	2412.000	5.50	29.14	41.88	97.08	89.84	74.00	15.84	peak



Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	---------------	---------------	--------	---------	---------	------------



Condition: 3m HORIZONTAL

Job No : 00879RG

Mode : 2412 Band edge


: 2.4G WIFI 11N 20

: 10.5

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	5.47	29.08	41.87	41.81	34.49	54.00	-19.51	Average
2	2390.000	5.47	29.08	41.87	41.81	34.49	54.00	-19.51	Average
3 pp	2412.000	5.50	29.14	41.88	89.02	81.78	54.00	27.78	Average



Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Peak	Vertical
------------------	---------------	---------------	---------	---------	------	----------




Condition: 3m VERTICAL  
Job No : 00879RG  
Mode : 2462 Band edge  
: 2.4G WIFI 11G  
: 11.5

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2462.000	5.57	29.29	41.90	99.51	92.47	74.00	18.47	Peak
2	2483.500	5.60	29.35	41.91	56.54	49.58	74.00	-24.42	Peak
3	2484.191	5.60	29.35	41.91	60.57	53.61	74.00	-20.39	Peak



Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Average	Vertical
------------------	---------------	---------------	---------	---------	---------	----------




Condition: 3m VERTICAL  
Job No : 00879RG  
Mode : 2462 Band edge  
: 2.4G WIFI 11G  
: 11.5

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2462.000	5.57	29.29	41.90	92.90	85.86	54.00	31.86	Average
2	2483.500	5.60	29.35	41.91	44.42	37.46	54.00	-16.54	Average
3	2483.790	5.60	29.35	41.91	44.57	37.61	54.00	-16.39	Average



Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	---------------	---------------	---------	---------	------	------------



Condition: 3m HORIZONTAL

Job No : 00879RG

Mode : 2462 Band edge

: 2.4G WIFI 11N 20


: 10.5

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2462.000	5.57	29.29	41.90	96.59	89.55	74.00	15.55 peak
2	2483.500	5.60	29.35	41.91	51.90	44.94	74.00	-29.06 peak
3	2484.743	5.60	29.36	41.91	54.82	47.87	74.00	-26.13 peak





Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Average	Horizontal
------------------	---------------	---------------	---------	---------	---------	------------



Condition: 3m HORIZONTAL

Job No : 00879RG

Mode : 2462 Band edge

: 2.4G WIFI 11N 20


: 10.5

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2462.000	5.57	29.29	41.90	89.15	82.11	54.00	28.11	Average
2	2483.500	5.60	29.35	41.91	40.29	33.33	54.00	-20.67	Average
3	2483.790	5.60	29.35	41.91	40.34	33.38	54.00	-20.62	Average



Test plot of Secondary supply as follows:

Worse case mode:	802.11G	Test channel:	Highest	Remark:	Average	Horizontal
------------------	---------	---------------	---------	---------	---------	------------



Condition: 3m HORIZONTAL

Job No : 00879RG

Mode : 2462 Band edge


: 2.4G WiFi 11G

: 11.5

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2462.000	5.57	29.29	41.90	101.37	94.33	74.00	20.33 peak
2	2483.500	5.60	29.35	41.91	58.65	51.69	74.00	-22.31 peak
3	2483.790	5.60	29.35	41.91	59.90	52.94	74.00	-21.06 Peak



Worse case mode:	802.11G	Test channel:	Highest	Remark:	Average	Vertical
------------------	---------	---------------	---------	---------	---------	----------



Condition: 3m VERTICAL

Job No : 00879RG

Mode : 2462 Band edge

: 2.4G WiFi 11G

: 11.5

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2462.000	5.57	29.29	41.90	100.27	93.23	74.00	19.23 peak
2	2483.500	5.60	29.35	41.91	59.24	52.28	74.00	-21.72 peak
3	2484.693	5.60	29.36	41.91	59.40	52.45	74.00	-21.55 Peak



*Note:*

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

*Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor*

- 2) Only the worstest case Restricted bands around fundamental frequency test data of Secondary supply showed .

## **7 Photographs - EUT Constructional Details**

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM18040025RG.

---

The End