

# INTERTEK TESTING SERVICES

---

## Analysis Report

The equipment under test (EUT) is a transmitter for an Angry Birds R/C Slingshot Racers operating at 27.145 MHz which is controlled by a crystal. The EUT is powered by two 1.5V AA batteries. For more detail information pls. refer to the user manual.

Antenna Type: integral antenna

Antenna Gain: 0dBi

Modulation Type: Pulse modulation

The nominal conducted output power specified: -16.0dBm (+/- 3dB)

The nominal radiated output power (e.r.p) specified: -18.15dBm (+/- 3dB)

According to the KDB 447498:

The worst-case peak radiated emission for the EUT is 78.60dBuV/m at 3m in the frequency 27.145MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -16.63dBm

The ERP = EIRP - 2.15 = -18.78 dBm

which is within the production variation.

The maximum conducted output power specified is -13.0dBm = 0.05mW

The source-based time-averaging conducted output power

=  $0.05 \cdot \text{Duty Cycle}$  mW < 0.05mW (Duty Cycle < 100%)

The SAR Exclusion Threshold Level for 27.145MHz when the minimum test separation distance is < 50mm:

=  $474 \cdot [1 + \log(100/f(\text{MHz}))]/2$

= 371.2 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

### Transmitter Duty Cycle Calculation

The duration of one cycle = 89.565ms

Effective period of the cycle =  $187.6\mu\text{s} \times 13 + 762.9\mu\text{s} = 3201.7\mu\text{s} = 3.2017\text{ms}$

DC =  $3.2017\text{ms} / 89.565\text{ms} = 0.0357$  or 3.57%