



Valued Quality. Delivered.

TEST REPORT

Report No.: 14110896HKG-001

Dongguan Siliten Electronics CO.,LTD

Application
For
Certification
(Original Grant)
(FCC ID: XW3DA-8350BK)

Transceiver

Prepared and Checked by:

Approved by:

Signed On File
Leung Sung Tak, Andy
Assistant Engineer

Wong Kwok Yeung, Kenneth
Lead Engineer
Date: January 26, 2015

- Intertek's standard Terms and Conditions can be obtained at our website <http://www.intertek.com/terms/>.
- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Hong Kong Ltd.

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.

Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-ettsemko.com

INTERTEK TESTING SERVICES

GENERAL INFORMATION

Grantee:	Dongguan Siliten Electronics CO.,LTD
Grantee Address:	Sijia Yewu Industrial Estate, Shijie Town, Dongguan, China.
Contact Person:	Natural Zhou
Tel:	0769-86338696
Fax:	0769-86337646
e-mail:	er_zhou@siliten.com
Manufacturer:	siliten
Manufacturer Address:	SiJia YeWu village Industrial Park, Shijie Town, Dongguan City, Guangdong Provine, China.
Brand Name:	N/A / radioshack
Model:	DA-8350BK / 1201669
Type of EUT:	Transceiver
Description of EUT:	Portable Bluetooth Transmitter
Serial Number:	N/A
FCC ID:	XW3DA-8350BK
Date of Sample Submitted:	November 21, 2014
Date of Test:	November 21, 2014 to January 22, 2015
Report No.:	14110896HKG-001
Report Date:	January 26, 2015
Environmental Conditions:	Temperature: +10 to 40°C Humidity: 10 to 90%

INTERTEK TESTING SERVICES

SUMMARY OF TEST RESULT

TEST SPECIFICATION	REFERENCE	RESULTS
Transmitter Power Line Conducted Emissions	15.207	Pass
Radiated Emission Radiated Emission on the Bandedge	15.249	Pass
Radiated Emission in Restricted Bands	15.205	Pass

The equipment under test is found to be complying with the following standards:
FCC Part 15, October 1, 2013 Edition

- Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

INTERTEK TESTING SERVICES

Table of Contents

1.0	<u>General Description</u>	1
1.1	Product Description	1
1.2	Related Submittal(s) Grants.....	1
1.3	Test Methodology	1
1.4	Test Facility	1
2.0	<u>System Test Configuration</u>	2
2.1	Justification	2
2.2	EUT Exercising Software.....	3
2.3	Special Accessories	3
2.4	Measurement Uncertainty.....	3
2.5	Support Equipment List and Description.....	3
3.0	<u>Emission Results</u>	4
3.1	Field Strength Calculation.....	4
3.2	Radiated Emission Configuration Photograph	5
3.3	Radiated Emission Data	5
3.4	Conducted Emission Configuration Photograph	5
3.5	Conducted Emission Data	5
4.0	<u>Equipment Photographs</u>	11
5.0	<u>Product Labelling</u>	11
6.0	<u>Technical Specifications</u>	11
7.0	<u>Instruction Manual</u>	11
8.0	<u>Miscellaneous Information</u>	12
8.1	Measured Bandwidth.....	12
8.2	Discussion of Pulse Desensitization	15
8.3	Calculation of Average Factor.....	15
8.4	Emissions Test Procedures	16
9.0	<u>Equipment List</u>	18

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The Equipment Under Test (EUT) is a 2.4GHz Bluetooth 2.1 + EDR transceiver. The EUT is powered by a 3.7V rechargeable battery which can be charged with a USB cable. The Bluetooth module in the EUT is operating in the frequency range from 2402MHz to 2480MHz (79 channels with 1MHz channel spacing). Plug the EUT's build-in cable into an audio device's 3.5mm headphone jack and pair with a Bluetooth device (ie Bluetooth speaker), the audio signal can be fed to the speaker through the EUT.

The Model: 1201669 is the same as the Model: DA-8350BK in hardware aspect. The difference in model number serves as marketing strategy.

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

This is a single application for certification of a transceiver.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009). All radiated measurements were performed in an 3m Chamber. Preliminary scans were performed in the 3m Chamber only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

1.4 Test Facility

The 3m Chamber and conducted measurement facility used to collect the radiated data is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

INTERTEK TESTING SERVICES

2.0 **System Test Configuration**

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The device was powered by 3.7V rechargeable battery.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

INTERTEK TESTING SERVICES

2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

2.5 Support Equipment List and Description

1. HP Probook 430
2. iPhone 5C
(Provided by Intertek)
3. 1 x USB charging cable with length of 1.13 meter long
(Provided by Applicant)

INTERTEK TESTING SERVICES

3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where FS = Field Strength in dB μ V/m
 RA = Receiver Amplitude (including preamplifier) in dB μ V
 CF = Cable Attenuation Factor in dB
 AF = Antenna Factor in dB
 AG = Amplifier Gain in dB
 AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where FS = Field Strength in dB μ V/m
 RR = RA - AG - AV in dB μ V
 LF = CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA = 52.0 dB μ V/m	
AF = 7.4 dB	RR = 18.0 dB μ V
CF = 1.6 dB	LF = 9.0 dB
AG = 29.0 dB	
AV = 5.0 dB	
FS = RR + LF	
FS = 18 + 9 = 27 dB μ V/m	

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V/m})/20] = 22.4 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 237.475 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 3.1 dB

3.4 Conducted Emission Configuration Photograph

The worst case in line-conducted emission was found at 0.537 MHz

For electronic filing, the worst case line-conducted configuration photographs are saved with filename: conducted photo.pdf.


3.5 Conducted Emission Data

For electronic filing, the graph and data table of conducted emission is saved with filename: conducted.pdf.

Judgment: Pass by 10.7 dB

INTERTEK TESTING SERVICES

Worst-Case Operating Mode: Bluetooth Sound Playing



EDIT PEAK LIST (Final Measurement Results)				
Trace1:	CF15MQP			
Trace2:	CF15MAV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dBµV	DELTA LIMIT dB	
2 CISPR Average	159 kHz	36.38 N gnd	-19.13	
1 Quasi Peak	163.5 kHz	46.94 N gnd	-18.33	
1 Quasi Peak	537 kHz	43.25 N gnd	-12.74	
2 CISPR Average	537 kHz	35.28 N gnd	-10.71	
1 Quasi Peak	573 kHz	33.65 N gnd	-22.34	

INTERTEK TESTING SERVICES

Applicant: Dongguan Siliten Electronics CO.,LTD
 Model: DA-8350BK
 Worst-Case Operating Mode: Transmitting

Date of Test: January 22, 2015

Table 1

Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Lowest Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Average Factor (dB)	Calculated at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
H	2402.000	107.4	33	29.4	103.8	24	79.8	94.0	-14.2
H	1602.039	55.8	33	27.2	50.0	24	26.0	54.0	-28.0
V	4804.000	58.9	33	34.9	60.8	24	36.8	54.0	-17.2
V	7206.000	54.0	33	37.9	58.9	24	34.9	54.0	-19.1
V	9608.000	54.3	33	40.4	61.7	24	37.7	54.0	-16.3
V	12010.000	58.0	33	40.5	65.5	24	41.5	54.0	-12.5
V	14412.000	61.0	33	40.0	68.0	24	44.0	54.0	-10.0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
H	2402.000	107.4	33	29.4	103.8	114.0	-10.2
H	1602.039	55.8	33	27.2	50.0	74.0	-24.0
V	4804.000	58.9	33	34.9	60.8	74.0	-13.2
V	7206.000	54.0	33	37.9	58.9	74.0	-15.1
V	9608.000	54.3	33	40.4	61.7	74.0	-12.3
V	12010.000	58.0	33	40.5	65.5	74.0	-8.5
V	14412.000	61.0	33	40.0	68.0	74.0	-6.0

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.

INTERTEK TESTING SERVICES

Applicant: Dongguan Siliten Electronics CO.,LTD
 Model: DA-8350BK
 Worst-Case Operating Mode: Transmitting

Date of Test: January 22, 2015

Table 2

Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Middle Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Average Factor (dB)	Calculated at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
H	2441.000	106.4	33	29.4	102.8	24	78.8	94.0	-15.2
H	1626.018	55.6	33	27.2	49.8	24	25.8	54.0	-28.2
V	4882.000	58.8	33	34.9	60.7	24	36.7	54.0	-17.3
V	7323.000	53.4	33	37.9	58.3	24	34.3	54.0	-19.7
V	9764.000	54.0	33	40.4	61.4	24	37.4	54.0	-16.6
V	12205.000	58.4	33	40.5	65.9	24	41.9	54.0	-12.1
V	14646.000	62.9	33	38.4	68.3	24	44.3	54.0	-9.7

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
H	2441.000	106.4	33	29.4	102.8	114.0	-11.2
H	1626.018	55.6	33	27.2	49.8	74.0	-24.2
V	4882.000	58.8	33	34.9	60.7	74.0	-13.3
V	7323.000	53.4	33	37.9	58.3	74.0	-15.7
V	9764.000	54.0	33	40.4	61.4	74.0	-12.6
V	12205.000	58.4	33	40.5	65.9	74.0	-8.1
V	14646.000	62.9	33	38.4	68.3	74.0	-5.7

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.

INTERTEK TESTING SERVICES

Applicant: Dongguan Siliten Electronics CO.,LTD
Model: DA-8350BK
Worst-Case Operating Mode: Transmitting

Date of Test: January 22, 2015

Table 3

Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Highest Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Average Factor (dB)	Calculated at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
H	2480.000	105.3	33	29.4	101.7	24	77.7	94.0	-16.3
H	1652.674	55.1	33	27.2	49.3	24	25.3	54.0	-28.7
V	4960.000	57.4	33	34.9	59.3	24	35.3	54.0	-18.7
V	7440.000	53.4	33	37.9	58.3	24	34.3	54.0	-19.7
V	9920.000	54.4	33	40.4	61.8	24	37.8	54.0	-16.2
V	12400.000	57.6	33	40.5	65.1	24	41.1	54.0	-12.9
V	14880.000	39.2	33	38.4	68.6	24	44.6	54.0	-9.4

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
H	2480.000	105.3	33	29.4	101.7	114.0	-12.3
H	1652.674	55.1	33	27.2	49.3	74.0	-24.7
V	4960.000	57.4	33	34.9	59.3	74.0	-14.7
V	7440.000	53.4	33	37.9	58.3	74.0	-15.7
V	9920.000	54.4	33	40.4	61.8	74.0	-12.2
V	12400.000	57.6	33	40.5	65.1	74.0	-8.9
V	14880.000	63.2	33	38.4	68.6	74.0	-5.4

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.

INTERTEK TESTING SERVICES

Applicant: Dongguan Siliten Electronics CO.,LTD

Date of Test: January 22, 2015

Model: DA-8350BK

Worst-Case Operating Mode: Bluetooth Sound Playing

Table 4

Radiated Emissions Pursuant to FCC Part 15 Section 15.209 Requirement

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
V	31.289	39.5	16	10.0	33.5	40.0	-6.5
V	63.982	33.8	16	9.0	26.8	40.0	-13.2
V	160.345	40.2	16	16.0	40.2	43.5	-3.3
V	240.830	32.5	16	19.0	35.5	46.0	-10.5
V	399.030	25.1	16	25.0	34.1	46.0	-11.9
V	893.851	24.0	16	32.0	40.0	46.0	-6.0
H	63.982	35.0	16	9.0	28.0	40.0	-12.0
H	160.345	37.5	16	16.0	37.5	43.5	-6.0
H	168.413	32.1	16	18.0	34.1	43.5	-9.4
H	207.850	32.4	16	17.0	33.4	43.5	-10.1
H	224.519	39.2	16	18.0	41.2	46.0	-4.8
H	237.475	39.9	16	19.0	42.9	46.0	-3.1
H	240.010	39.5	16	19.0	42.5	46.0	-3.5
H	247.625	38.5	16	20.0	42.5	46.0	-3.5
H	261.975	30.6	16	21.0	35.6	46.0	-10.4
H	399.030	26.6	16	25.0	35.6	46.0	-10.4

NOTES: 1. Quasi Peak detector is used for final measurement.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.

INTERTEK TESTING SERVICES

4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

5.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

6.0 **Technical Specifications**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

INTERTEK TESTING SERVICES

8.0 **Miscellaneous Information**



The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation).

8.1 Radiated Emission on the Bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz to 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.4 (2009) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

INTERTEK TESTING SERVICES



INTERTEK TESTING SERVICES

Peak Measurement

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

$$=103.8 \text{ dB}\mu\text{V/m} - 39.3 \text{ dB}$$

$$=64.5 \text{ dB}\mu\text{V/m}$$

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

$$=79.8 \text{ dB}\mu\text{V/m} - 39.3 \text{ dB}$$

$$=45.0 \text{ dB}\mu\text{V/m}$$

Upper bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

$$=101.7 \text{ dB}\mu\text{V/m} - 46.8 \text{ dB}$$

$$=54.9 \text{ dB}\mu\text{V/m}$$

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

$$=77.7 \text{ dB}\mu\text{V/m} - 46.8 \text{ dB}$$

$$=30.9 \text{ dB}\mu\text{V/m}$$

The resultant field strength meets the general radiated emission limit in Section 15.209, which does not exceed 74 dB μ V/m (Peak Limit) and 54 dB μ V/m (Average Limit).

INTERTEK TESTING SERVICES

8.2 Discussion of Pulse Desensitization

Pulse desensitization is not applicable for this device. The effective period (T_{eff}) is approximately $625\mu s$ for a digital "1" bit which is illustrated on technical specification, with a resolution bandwidth (3dB) of 1MHz, so the pulse desensitization factor is 0dB.

8.3 Calculation of Average Factor

Based on the Bluetooth Specification Version 3.0 + EDR, the transmitter ON time for each timeslot of Bluetooth is $625\mu s$. DH5 has the maximum duty cycle, which consists of 5 continuous Tx slots and 1 Rx slot. Therefore one hopset takes $(5+1) \times 625\mu s = 3.75ms$. For one period for a pseudo-random hopping through at least 20 RF channels in adaptive mode (worst case), it takes: $20 \times 3.75ms = 75ms$.

The dwell time for DH5 is $5 \times 625\mu s = 3.125ms$.

For the worst case calculation, there are two transmissions that might occur in 100ms. Therefore,

$$\begin{aligned}\text{Duty Cycle (DC)} &= \text{Maximum On time in } 100ms/100ms \\ &= 3.125ms \times 2/100ms \\ &= 0.0625\end{aligned}$$

$$\begin{aligned}\text{Average Factor (AF) of Bluetooth in dB} &= 20 \log_{10} (0.0625) \\ &= -24 \text{ dB}\end{aligned}$$

INTERTEK TESTING SERVICES

8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz.

INTERTEK TESTING SERVICES

8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 (2009).

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.

INTERTEK TESTING SERVICES

9.0 Equipment List

1) Radiated Emissions Test

Equipment	EMI Test Receiver	BiConiLog Antenna
Registration No.	EW-2251	EW-3061
Manufacturer	R&S	EMCO
Model No.	ESCI	3412E
Calibration Date	Dec. 04, 2014	Jul. 17, 2014
Calibration Due Date	Dec. 04, 2015	Jul. 17, 2015

Equipment	Spectrum Analyzer	Pyramidal Horn Antenna	Double Ridged Guide Antenna
Registration No.	EW-2253	EW-0905	EW-1133
Manufacturer	R&S	EMCO	EMCO
Model No.	FSP40	3160-09	3115
Calibration Date	May 08, 2014	Jan. 28, 2014	Apr. 30, 2014
Calibration Due Date	May 08, 2015	Jul. 28, 2015	Oct. 30, 2015

2) Conducted Emissions Test

Equipment	EMI Test Receiver	LISN	Pulse Limiter
Registration No.	EW-2500	EW-0192	EW-0698
Manufacturer	R&S	R&S	R&S
Model No.	ESCI	ESH3-Z5	ESH3-Z2
Calibration Date	Nov. 06, 2014	Jul. 24, 2014	Jul. 07, 2014
Calibration Due Date	Nov. 06, 2015	Apr. 15, 2015	Jul. 07, 2015

3) Bandedge Measurement

Equipment	Spectrum Analyzer
Registration No.	EW-2329
Manufacturer	R&S
Model No.	FSP3
Calibration Date	Jun. 19, 2014
Calibration Due Date	Jun. 19, 2015

END OF TEST REPORT