

1. RF Exposure Requirements

1.1 General Information

Client Information

Applicant: Guangdong Transtek Medical Electronics Co., Ltd.
Address of applicant: Zone A. No. 105, Dongli Road, Torch Development District, 528437
Zhongshan, Guangdong, China

Manufacturer: Guangdong Transtek Medical Electronics Co., Ltd.
Address of manufacturer: Zone A. No. 105, Dongli Road, Torch Development District, 528437
Zhongshan, Guangdong, China

General Description of EUT:

Product Name: LINNER CONNECT
Trade Name: /
Model No.: CONN
Adding Model(s): /
Rated Voltage: Battery DC 3.7V
Battery Capacity: 600mAh
FCC ID: OU9-CONN
Equipment Type: Mobile device

Technical Characteristics of EUT:

Frequency Range: 2402-2480MHz
RF Output Power: 3.58dBm (Conducted)
Modulation: GFSK
Quantity of Channels: 79
Channel Separation: 1MHz
Type of Antenna: PIFA Antenna
Antenna Gain: 1.68dBi

1.2 RF Exposure Exemption

According to §1.1307(b)(3) and 447498 D04 Interim General RF Exposure Guidance v01, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

Option A: FCC Rule Part 1.1307 (b)(3)(i)(A): The available maximum time-averaged power is no more than 1mW, regardless of separation distance.

Option B: FCC Rule Part 1.1307 (b)(3)(i)(B): The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option C: FCC Rule Part 1.1307 (b)(3)(i)(C): The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.

| Single RF Sources Subject to Routine Environmental Evaluation | |
|---|-----------------------|
| RF Source frequency (MHz) | Threshold ERP (watts) |
| 0.3-1.34 | $1,920 R^2$ |
| 1.34-30 | $3,450 R^2/f^2$ |
| 30-300 | $3.83 R^2$ |
| 300-1,500 | $0.0128 R^2 f$ |
| 1,500-100,000 | $19.2 R^2$ |

For Multiple RF sources: FCC Rule Part 1.1307(b)(3)(ii):

- (A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required).
- (B) In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

1.3 Calculated Result

| Radio Access Technology | Min. Frequency | Max. Output Power | Max. Tune-Up Output Power | Antenna Gain | Duty Cycle | Tune-Up EIRP |
|-------------------------|----------------|-------------------|---------------------------|--------------|------------|--------------|
| | (MHz) | (dBm) | (dBm) | (dBi) | (%) | (dBm) |
| SRD 2.4GHz | 2402 | 3.58 | 4.0 | 1.68 | 100 | 5.68 |

| Frequency (MHz) | Option | Min. Distance | Tune-Up ERP | | Exposure Limit | Ratio | Result |
|-----------------|--------|---------------|-------------|------|----------------|-------|-----------|
| | | (cm) | (dBm) | (mW) | (mW) | | Pass/Fail |
| 2402 | C | 20.00 | 3.53 | 2.25 | 768.00 | 0.01 | Pass |

Note: 1. $ERP = EIRP - 2.15 \text{ dB}$; $EIRP = \text{Output Power} + \text{Antenna gain}$

2. Option A, B and C refers as clause 1.2.

3. For option B, $P_{th}(\text{mW})$ convert to Exposure Limit(mW); For option C, $ERP(\text{W})$ convert to Exposure Limit(mW).

4. $\text{Ratio} = \text{Tune-Up ERP}(\text{mW}) / \text{Exposure Limit}(\text{mW})$

Mode for Simultaneous Multi-band Transmission:

| Radio Access Technology | Ratio 1 | Ratio 2 | Simultaneous Ratio | Limit | Result |
|-------------------------|---------|---------|--------------------|-------|-----------|
| | | | | | Pass/Fail |
| -- | -- | -- | -- | -- | -- |

Result: Pass