

MAXIMUM PERMISSIBLE EXPOSURE

KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

EUT Specification

FCC ID	2A86W-N1
EUT	8 CH Wi-Fi Network Video Recorder
Frequency band (Operating)	☐ BT: 2.402GHz ~ 2.480GH ☒ WLAN: 2.412GHz ~ 2.462GHz ☒ RLAN: 5.180GHz ~ 5.240GHz ☒ RLAN: 5.260GHz ~ 5.320GHz ☒ RLAN: 5.500GHz ~ 5.700GHz ☒ RLAN: 5.745GHz ~ 5.825GHz ☐ Others:
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others:
Exposure classification	☐ Occupational/Controlled exposure ☒ General Population/Uncontrolled exposure
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	module MT7628DAN: WiFi 2.4G ANT1: 14.89 dBm (0.0247W) WiFi 2.4G ANT2: 15.01 dBm (0.0249W) WiFi 2.4G MIMO: 16.97 dBm (0.0497W) module RTL8731BU: WiFi 2.4G: 14.64 dBm (0.0246W) WiFi 5.2G: 15.16 dBm (0.0246W) WiFi 5.3G: 15.54 dBm (0.0545W) WiFi 5.6G: 16.24 dBm (0.0501W) WiFi 5.8G: 16.53dBm (0.0607W)
Antenna gain (Max)	module MT7628DAN: WiFi 2.4G ANT1: 2.69dBi WiFi 2.4G ANT2: 2.69dBi

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
 Tel: (86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotek.com



Hotline
 400-003-0500
 www.anbotek.com.cn



	module RTL8731BU: WiFi 2.4G: 2.10 dBi WiFi 5.2G: 4.45dBi WiFi 5.3G: 4.45dBi WiFi 5.6G: 4.90dBi WiFi 5.8G: 4.26dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	30
1500-100000	--	--	1	30

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotek.com



Hotline
400-003-0500
www.anbotek.com.cn



Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Max Measurement Result

Operating Mode	Measured Power	Tune up tolerance	Max. Tune up Power	Antenna Gain	Power density at 20cm	Power density Limits (mW/cm ²)
	(dBm)	(dBm)	(dBm)	(dBi)	(mW/cm ²)	
module MT7628DAN WiFi 2.4G ANT1	14.89	14.89 ±1	15.89	2.69	0.0144	1
module MT7628DAN WiFi 2.4G ANT2	15.01	15.01 ±1	16.01	2.69	0.0148	1
module RTL8731BU WiFi 2.4G	14.64	14.64 ±1	15.64	2.10	0.0118	1
module RTL8731BU WiFi 5.2G	15.16	15.16 ±1	16.16	4.45	0.0229	1
module RTL8731BU WiFi 5.3G	15.54	15.54 ±1	16.54	4.45	0.0250	1
module RTL8731BU WiFi 5.6G	16.24	16.24 ±1	17.24	4.90	0.0326	1
module RTL8731BU WiFi 5.8G	16.53	16.53 ±1	17.53	4.26	0.0301	1

No. Applicable Simultaneous Transmission

1. module MT7628DAN WiFi 2.4G ANT1+module MT7628DAN WiFi 2.4G ANT2
2. module MT7628DAN WiFi 2.4G ANT1+module RTL8731BU WiFi 2.4G
3. module MT7628DAN WiFi 2.4G ANT1+module RTL8731BU WiFi 5.2G
4. module MT7628DAN WiFi 2.4G ANT1+module RTL8731BU WiFi 5.3G
5. module MT7628DAN WiFi 2.4G ANT1+module RTL8731BU WiFi 5.6G
6. module MT7628DAN WiFi 2.4G ANT1+module RTL8731BU WiFi 5.8G



7. module MT7628DAN WiFi 2.4G ANT2+module RTL873IBU WiFi 2.4G
8. module MT7628DAN WiFi 2.4G ANT2+module RTL873IBU WiFi 5.2G
9. module MT7628DAN WiFi 2.4G ANT2+module RTL873IBU WiFi 5.3G
10. module MT7628DAN WiFi 2.4G ANT2+module RTL873IBU WiFi 5.6G
11. module MT7628DAN WiFi 2.4G ANT2+module RTL873IBU WiFi 5.8G

**The Maximum simultaneous transmission for module MT7628DAN WiFi 2.4G
ANT2+module RTL873IBU WiFi 5.8G:**

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$= S_{WiFi\ 2.4G\ ANT2} / S_{limit-2.4G} + S_{WiFi\ 5.8G} / S_{limit-5.8G}$$

$$= 0.0148 / 1 + 0.0301 / 1$$

$$= 0.0449$$

$$< 1.0$$

Result: No Standalone SAR test is required.

