

# TEST REPORT

## Client Information:

Applicant: Shenzhen Chunhong Technology Co., Ltd  
Applicant add.: 1209U8, International Chamber of Commerce Center, 168 Fuhua 3rd Road,  
Futian District, Shenzhen, China  
Manufacturer: Shenzhen Chunhong Technology Co., Ltd  
Manufacturer add.: 1209U8, International Chamber of Commerce Center, 168 Fuhua 3rd Road,  
Futian District, Shenzhen, China

## Product Information:

Product Name: Mini PC  
Model No: H20  
Brand Name: Huidun  
FCC ID : 2BMHA-H20

Applicable standards: FCC CFR Title 47 Part 15 Subpart E Section 15.407

## Prepared By:

### Dongguan Yaxu (AiT) Technology Limited

No.22, Jinqianling 3rd Street, Jitigang, Huangjiang, Dongguan,  
Guangdong, China

Tel.: +86-769-8202 0499 Fax.: +86-769-8202 0495

Date of Receipt: Nov. 29, 2024

Date of Test: Nov. 29, 2024~Jan. 09, 2025

Date of Issue: Jan. 10, 2025

Test Result: Pass

This device described above has been tested by Dongguan Yaxu (AiT) Technology Limited and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Note: This report shall not be reproduced except in full, without the written approval of Dongguan Yaxu (AiT) Technology Limited, this document may be altered or revised by Dongguan Yaxu (AiT) Technology Limited, personal only, and shall be noted in the revision of the document. This test report must not be used by the client to claim product endorsement.

Reviewed by: Emiya Lin  
Emiya Lin

Approved by: Simba Huang  
Simba Huang

# 1 Contents

	Page
<b>COVER PAGE</b>	
<b>1 CONTENTS</b>	<b>2</b>
<b>2 TEST SUMMARY</b>	<b>5</b>
2.1 Statement of the Measurement Uncertainty	5
2.2 Measurement Uncertainty	5
<b>3 TEST FACILITY</b>	<b>6</b>
3.1 Deviation from standard	6
3.2 Abnormalities from standard conditions	6
3.3 Test Location	6
<b>4 GENERAL INFORMATION</b>	<b>7</b>
4.1 Test Frequencies	9
4.2 EUT Peripheral List	9
4.3 Test Peripheral List	9
4.4 TEST METHODOLOGY	10
4.5 Description of Test Modes	11
<b>5 EQUIPMENT USED DURING TEST</b>	<b>13</b>
<b>6 TEST RESULTS AND MEASUREMENT DATA</b>	<b>15</b>
6.1 Antenna requirement	15
6.1.1 Standard requirement	15
6.1.2 EUT Antenna	15
6.2 On Time and Duty Cycle	16
6.2.1 Standard requirement	16
6.2.2 Measuring Instruments and Setting:	16
6.2.3 Test Procedures	16
6.2.4 Test Setup Layout	16
6.2.5 EUT Operation During Test	16
6.2.6 Test Result	16
6.3 Maximum Conducted Output Power Measurement	17
6.3.1 Standard requirement	17
6.3.2 Measuring Instruments	18
6.3.3 Test Procedures	18
6.3.4 Test Setup Layout	18
6.3.5 EUT Operation During Test	18
6.3.6 Test Result	18
6.4 26dB Bandwidth Measurement	19
6.4.1 Standard requirement	19
6.4.2 Measuring Instruments	19
6.4.3 Test Procedures	19
6.4.4 Test Setup Layout	19

6.4.5	EUT Operation During Test .....	19
6.4.6	Test Result .....	19
6.5	6dB Bandwidth Measurement .....	20
6.5.1	Standard requirement .....	20
6.5.2	Measuring Instruments .....	20
6.5.3	Test Procedures .....	20
6.5.4	Test Setup Layout .....	20
6.5.5	EUT Operation During Test .....	20
6.5.6	Test Result .....	20
6.6	99% Occupied Bandwidth Measurement .....	21
6.6.1	Standard requirement .....	21
6.6.2	Measuring Instruments .....	21
6.6.3	Test Procedures .....	21
6.6.4	Test Setup Layout .....	21
6.6.5	EUT Operation During Test .....	21
6.6.6	Test Result .....	21
6.7	Power Spectral Density .....	23
6.7.1	Standard requirement .....	23
6.7.2	Measuring Instruments and Setting .....	23
6.7.3	Test Procedures .....	23
6.7.4	Test Setup Layout .....	24
6.7.5	EUT Operation during Test .....	24
6.7.6	Test result .....	24
6.8	Radiated Emissions and Radiation Restricted band Measurement .....	25
6.8.1	Standard requirement .....	25
6.8.2	Measuring Instruments and Setting: .....	26
6.8.3	Test Procedures .....	26
6.8.4	Test Setup Layout .....	29
6.8.5	EUT Operation During Test .....	30
6.8.6	Test Result .....	30
6.9	Power Line Conducted Emissions .....	46
6.9.1	Standard requirement .....	46
6.9.2	Test Setup Layout .....	46
6.9.3	Test Procedures .....	46
6.9.4	EUT Operation during Test .....	46
6.9.5	Test result .....	46
6.10	Frequency Stability .....	55
6.10.1	Standard requirement .....	55
6.10.2	Measuring Instruments and Setting: .....	55
6.10.3	Test Procedures .....	55
6.10.4	Test Setup Layout .....	55
6.10.5	EUT Operation during Test .....	55
6.10.6	Test result .....	55
<b>7</b>	<b>TEST SETUP PHOTOGRAPHS OF EUT .....</b>	<b>56</b>
<b>8</b>	<b>EXTERNAL PHOTOGRAPHS OF EUT .....</b>	<b>56</b>
<b>9</b>	<b>INTERNAL PHOTOGRAPHS OF EUT .....</b>	<b>56</b>

**REPORT REVISE RECORD**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jan. 10, 2025	Valid	Initial release

## 2 Test Summary

Test Item	Section in CFR 47	Result
/	On Time and Duty Cycle	/
§15.407(a)	Maximum Conducted Output Power	Pass
§15.407(a)	Power Spectral Density	Pass
§15.407(a)	26dB Bandwidth	Pass
§15.407(a)	6dB Bandwidth	Pass
§15.209 §15.407(b)	Radiated Emissions	Pass
§15.205	Emissions at Restricted Band	Pass
§15.407(g)	Frequency Stability	Pass
§15.207(a)	Power Line Conducted Emissions	Pass
§15.203	Antenna Requirements	Pass
§2.1091	RF Exposure	Pass*

### Note

1. Test according to ANSI C63.10:2013.
2. The measurement uncertainty is not included in the test result.
3. “\*” Test results in other test report (RF Exposure Evaluation Report)

### 2.1 Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the AiT quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

### 2.2 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	0.009MHz-30MHz	3.10dB	(1)
Radiated Emission	30MHz-1GHz	3.75dB	(1)
Radiated Emission	1GHz-18GHz	3.88dB	(1)
Radiated Emission	18GHz-40GHz	3.88dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	1.20dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

### 3 Test Facility

**The test facility is recognized, certified or accredited by the following organizations:**

**.CNAS- Registration No: L6177**

Dongguan Yaxu (AiT) technology Limited is accredited to ISO/IEC 17025:2017 general Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the competence of testing and calibration laboratories) on April 18, 2022

**FCC-Registration No.: 703111 Designation Number: CN1313**

Dongguan Yaxu (AiT) technology Limited has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

**IC —Registration No.: 6819A CAB identifier: CN0122**

The 3m Semi-anechoic chamber of Dongguan Yaxu (AiT) technology Limited has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 6819A

**A2LA-Lab Cert. No.: 6317.01**

Dongguan Yaxu (AiT) technology Limited has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### 3.1 Deviation from standard

None

#### 3.2 Abnormalities from standard conditions

None

#### 3.3 Test Location

**Dongguan Yaxu (AiT) Technology Limited**

Address: No.22, Jinqianling 3rd Street, Jitigang, Huangjiang, Dongguan, Guangdong, China

Tel.: +86-769-8202 0499

Fax.: +86-769-8202 0495

## 4 General Information

EUT Name:	Mini PC			
Model No:	H20			
Serial Model:	N/A			
Test sample(s) ID:	AiTDG-241129002-1			
Sample(s) Status:	Engineer sample			
Operation frequency:	Band	Mode	Frequency Range(MHz)	Number of channels
	U-NII Band I	IEEE 802.11a	5180-5240	4
		IEEE 802.11n/ac/ax 20MHz	5180-5240	4
		IEEE 802.11n/ac/ax 40MHz	5190-5230	2
		IEEE 802.11ac/ax 80MHz	5210	1
	U-NII Band III	IEEE 802.11a	5745-5825	5
		IEEE 802.11n/ac/ax 20MHz	5745-5825	5
		IEEE 802.11n/ac/ax 40MHz	5755-5795	2
		IEEE 802.11ac/ax 80MHz	5775	1
Modulation Technology:	OFDM			
Modulation Type	IEEE 802.11a/n/ac/ax: OFDM(64QAM, 16QAM, QPSK, BPSK)			
Antenna Type:	FPC Antenna			
Antenna gain:	ANT1: 3.87dBi for 5150-5250MHz 3.55dBi for 5725-5875MHz ANT2: 3.10dBi for 5150-5250MHz 2.12dBi for 5725-5875MHz			
Hardware version.:	T8PLUS_V12			
Software version.:	23H2			
Power Supply:	DC12V from adapter			
Adapter:	Adapter1: MODEL: AD0301-1202500UB INPUT:100-240V~ 50-60Hz 0.8A Max OUTPUT:12.0V2.5A 30.0W Adapter2: MODEL: KA3601A-1202500US INPUT:100-240V~ 50/60Hz 1.0A Max OUTPUT:12.0V2.5A			
Configuration:	Configuration1:CPU(Intel Alder Lake N97) Configuration2:CPU(Intel Alder Lake N95)			
Battery	N/A			

Model different:	N/A
------------------	-----

Note:

For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



## 4.1 Test Frequencies

EUT channels and frequencies list:

Channel list for 802.11a/n(HT20)/ac(HT20)/ax(HE20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180MHz	40	5200MHz	44	5220MHz	48	5240MHz
149	5745MHz	157	5785MHz	165	5825MHz		

Channel list for 802.11n(HT40)/ac(HT40)/ax(HE40)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
38	5190MHz	46	5230MHz				
151	5755MHz	159	5795MHz				

Channel list for 802.11ac(HT80)/ax(HE80)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
42	5210MHz					--	--
155	5775MHz						

## 4.2 EUT Peripheral List

No.	Equipment	Manufacturer	Model No.	Serial No.	Power cord	Remark
1	Adapter	Shenzhen ABP Technology Co.,Ltd.	AD0301-120250 0UB	N/A	N/A	N/A
2	Adapter	Shenzhen Keyu Power Supply Technology Co., Ltd.	KA3601A-120 2500US	N/A	N/A	N/A

## 4.3 Test Peripheral List

No.	Equipment	Manufacturer	Model No.	Serial No.	Power cord	Remark
1	N/A	N/A	N/A	N/A	N/A	N/A

## 4.4 TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Dongguan Yaxu (AiT) Technology Limited

### 4.4.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 4.4.2 EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to FCC's request, Test Procedure 789033 D02 General UNII Test Procedures New Rules v01r03 and KDB 662911 D01 Multiple Transmitter Output v02r01 is required to be used for this kind of FCC 15.407 UII device.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.407 under the FCC Rules Part 15 Subpart E

### 4.4.3 General Test Procedures

#### Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

#### Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013.

## 4.5 Description of Test Modes

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position.

AC main conducted emission pre-test voltage at both AC 120V/60Hz and AC 240V/50Hz, recorded worst case;

AC main conducted emission pre-test at charge from power adapter modes, recorded worst case;

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be IEEE 802.11ac VHT20 mode (HCH).

Worst-Case data rates were utilized from preliminary testing of the Chipset, worst-case data rates used during the testing are as follows:

IEEE 802.11a Mode: 6 Mbps, OFDM.

IEEE 802.11ac VHT20 Mode: MCS0

IEEE 802.11n HT20 Mode: MCS0, OFDM.

IEEE 802.11ac VHT40 Mode: MCS0, OFDM.

IEEE 802.11n HT40 Mode: MCS0, OFDM.

IEEE 802.11ac VHT80 Mode: MCS0, OFDM.

IEEE 802.11ax HE20 Mode: MCS0, OFDM.

IEEE 802.11ax HE40 Mode: MCS0, OFDM.

IEEE 802.11ax HE80 Mode: MCS0, OFDM.

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Transmitting mode	Keep the EUT in continuously transmitting mode.					
Test software:	AX Series MP Toolkit					
Frequency	5180 MHz	5200 MHz	5240 MHz	5745 MHz	5785 MHz	5825 MHz
Parameters(802.11a)	12	12	12	8.5	8.5	8.5
Parameters(802.11n20)	8	8	8	5	5	5
Parameters(802.11ac20)	8	8	8	5	5	5
Parameters(802.11ax20)	7	7	7	4	4	4
Frequency	5190 MHz	5230 MHz	5755 MHz	5795 MHz	--	--
Parameters(802.11n40)	8	8	6	6	--	--
Parameters(802.11ac40)	8	8	6	6	--	--
Parameters(802.11ax40)	7	7	5	5	--	--
Frequency	5210 MHz	5775 MHz	--	--	--	--
Parameters(802.11ac80)	7	5	--	--	--	--
Parameters(802.11ax80)	7	5	--	--	--	--

### Antenna & Bandwidth

Antenna	Chain 1 (ANT1)			Chain 2 (ANT2)			Simultaneously
Bandwidth Mode	20MHz	40MHz	80MHz	20MHz	40MHz	80MHz	/
IEEE 802.11a	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
IEEE 802.11n	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
IEEE 802.11ac	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
IEEE 802.11ax	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

## 5 Equipment Used during Test

No	Test Equipment	Manufacturer	Model No	Serial No	Cal. Date	Cal. Due Date
1	Spectrum Analyzer	R&S	FSV40	101470	2024.09.23	2025.09.22
2	EMI Measuring Receiver	R&S	ESR	101660	2024.09.23	2025.09.22
3	Low Noise Pre Amplifier	HP	HP8447E	1937A01855	2024.09.23	2025.09.22
4	Low Noise Pre Amplifier	Tsj	MLA-0120-A02-34	2648A04738	2024.09.23	2025.09.22
5	Passive Loop	ETS	6512	00165355	2024.09.04	2026.09.03
6	TRILOG Super Broadband test Antenna	SCHWARZBECK	VULB9160	9160-3206	2024.08.29	2026.08.28
7	Broadband Horn Antenna	SCHWARZBECK	BBHA9120D	452	2024.08.29	2026.08.28
8	SHF-EHF Horn Antenna 15-40GHz	SCHWARZBECK	BBHA9170	BBHA9170367d	2023.09.12	2026.09.11
9	EMI Test Receiver	R&S	ESCI	100124	2024.09.23	2025.09.22
10	LISN	Kyoritsu	KNW-242	8-837-4	2024.09.23	2025.09.22
11	LISN	R&S	ESH3-Z5	892785/016	2024.09.23	2025.09.22
12	Pro.Temp&Humi.chamber	MENTEK	MHP-150-1C	MAA08112501	2024.09.23	2025.09.22
13	RF Automatic Test system	MW	MW100-RFCB	21033016	2024.09.23	2025.09.22
14	Signal Generator	Agilent	N5182A	MY50143009	2024.09.23	2025.09.22
15	Wideband Radio communication tester	R&S	CMW500	1201.0002K50	2024.09.23	2025.09.22
16	RF Automatic Test system	MW	MW100-RFCB	21033016	2024.09.23	2025.09.22
17	Pulse Limiter	R&S	ESH3-Z2	03578810.54	2024.09.23	2025.09.22
18	Switch	MFJ Rhinos	MFJ-2702	CZ3457	2024.09.23	2025.09.22
19	DC power supply	ZHAOXIN	RXN-305D-2	28070002559	N/A	N/A
20	RE Software	EZ	EZ-EMC_RE	Ver.AIT-03A	N/A	N/A
21	CE Software	EZ	EZ-EMC_CE	Ver.AIT-03A	N/A	N/A
22	RF Software	MW	MTS 8310	2.0.0.0	N/A	N/A
23	temporary antenna connector(Note)	NTS	R001	N/A	N/A	N/A

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

## 6 Test results and Measurement Data

### 6.1 Antenna requirement

#### 6.1.1 Standard requirement

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

And according to FCC 47 CFR Section 15.407 (a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### 6.1.2 EUT Antenna

*Refer to Section 4(General Information), reference to the Internal photos for details*

## 6.2 On Time and Duty Cycle

### 6.2.1 Standard requirement

None; for reporting purpose only


### 6.2.2 Measuring Instruments and Setting:

Please refer to equipments list in this report. The following table is the setting of the spectrum analyser.

### 6.2.3 Test Procedures

- 1). Set the Centre frequency of the spectrum analyzer to the transmitting frequency;
- 2). Set the span=0MHz, RBW=1MHz, VBW=3MHz, Sweep time=100ms;
- 3). Detector = peak;
- 4). Trace mode = Single hold.

### 6.2.4 Test Setup Layout



### 6.2.5 EUT Operation During Test

The EUT was programmed to be in continuously transmitting mode.

### 6.2.6 Test Result

*For reporting purpose only.*

*Please refer to Appendix D.1 (5150-5250MHz) and Appendix E.1(5725-5850MHz)*



## 6.3 Maximum Conducted Output Power Measurement

### 6.3.1 Standard requirement

#### (1) For the band 5.15~5.25GHz

- (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
- (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1dB reduction in maximum conducted output power is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple colocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
- (iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### (2) For the band 5.25-5.35 GHz and 5.47-5.725 GHz

The maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### (3) For 5725~5850MHz

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple colocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

### 6.3.2 Measuring Instruments

Please refer to equipment's list in this report.


### 6.3.3 Test Procedures

The transmitter output (antenna port) was connected to the power meter.

According to KDB 789033 D02 v02r01 Section 3 (a) Method PM (Measurement using an RF average power meter):

- (i) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.
  - The EUT is configured to transmit continuously or to transmit with a constant duty cycle.
  - At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
  - The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- (ii) If the transmitter does not transmit continuously, measure the duty cycle,  $x$ , of the transmitter output signal as described in section II.B.
- (iii) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- (iv) Adjust the measurement in dBm by adding  $10 \log (1/x)$  where  $x$  is the duty cycle (e.g.,  $10 \log (1/0.25)$  if the duty cycle is 25%).

### 6.3.4 Test Setup Layout



### 6.3.5 EUT Operation During Test

The EUT was programmed to be in continuously transmitting mode.

### 6.3.6 Test Result

PASS

Please refer to Appendix D.2 (5150-5250MHz) and Appendix E.2(5725-5850MHz)

Remark:

1. Measured output power at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11ac VHT20, IEEE 802.11ac VHT40, IEEE 802.11ac VHT80, IEEE 802.11ax HE20, IEEE 802.11ax HE40, IEEE 802.11ax HE80;
4. Report conducted power = Measured conducted average power + Duty Cycle factor;
5. For power measurements on IEEE 802.11 devices;
  - Array Gain = 0 dB (i.e., no array gain) for NANT  $\leq 4$ ;
  - Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any NANT;
  - Array Gain =  $5 \log (NANT/NSS)$  dB or 3 dB, whichever is less, for 20-MHz channel widths with NANT  $\geq 5$

## 6.4 26dB Bandwidth Measurement

### 6.4.1 Standard requirement

No restriction limits. But resolution bandwidth within band edge measurement is 1% of the 99% occupied bandwidth.

### 6.4.2 Measuring Instruments


Please refer to equipment list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span	> 26dB Bandwidth
Detector	Peak
Trace	Max Hold
Sweep Time	100ms

### 6.4.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The RBW = 1% - 3% of occupied bandwidth, VBW = 3\*RBW;
3. Measured the spectrum width with power higher than 26dB below carrier.

### 6.4.4 Test Setup Layout



### 6.4.5 EUT Operation During Test

The EUT was programmed to be in continuously transmitting mode.

### 6.4.6 Test Result

PASS

Please refer to Appendix D.3 (5150-5250MHz)

Remark:

1. Measured 26dB bandwidth at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11ac VHT20, IEEE 802.11ac VHT40, IEEE 802.11ac VHT80, IEEE 802.11ax HE20, IEEE 802.11ax HE40, IEEE 802.11ax HE80;

## 6.5 6dB Bandwidth Measurement

### 6.5.1 Standard requirement

No restriction limits. But resolution bandwidth within band edge measurement is 1% of the 99% occupied bandwidth.

### 6.5.2 Measuring Instruments


Please refer to equipment list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span	> 6dB Bandwidth
Detector	Peak
Trace	Max Hold
Sweep Time	100ms

### 6.5.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The RBW = 1% - 3% of occupied bandwidth, VBW = 3\*RBW;
3. Measured the spectrum width with power higher than 6dB below carrier.

### 6.5.4 Test Setup Layout



### 6.5.5 EUT Operation During Test

The EUT was programmed to be in continuously transmitting mode.

### 6.5.6 Test Result

PASS

Please refer to Appendix E.3(5725-5850MHz)

Remark:

4. Measured 6dB bandwidth at difference data rate for each mode and recorded worst case for each mode.
5. Test results including cable loss;
6. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11ac VHT20, IEEE 802.11ac VHT40, IEEE 802.11ac VHT80, IEEE 802.11ax HE20, IEEE 802.11ax HE40, IEEE 802.11ax HE80;

## 6.6 99% Occupied Bandwidth Measurement

### 6.6.1 Standard requirement

According to §2.1049: The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured under the following conditions as applicable.

### 6.6.2 Measuring Instruments


Please refer to equipment list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
RBW	> RBW
VBW	Peak
Span Frequency	Max Hold
Detector	100ms

### 6.6.3 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. Set RBW = 1%~5% OBW; VBW $\geq$ 3\*RBW;
3. Measured the 99% occupied bandwidth by related function of the spectrum analyzer.

### 6.6.4 Test Setup Layout



### 6.6.5 EUT Operation During Test

The EUT was programmed to be in continuously transmitting mode.

### 6.6.6 Test Result

PASS

Please refer to Appendix D.4 (5150-5250MHz) and Appendix E.4(5725-5850MHz)

## Remark:

1. Measured 99% bandwidth at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11ac VHT20, IEEE 802.11ac VHT40, IEEE 802.11ac VHT80, IEEE 802.11ax HE20, IEEE 802.11ax HE40, IEEE 802.11ax HE80;.

## 6.7 Power Spectral Density

### 6.7.1 Standard requirement

#### For 5.15~5.25GHz

- (i) For an outdoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band.note1
- (ii) For an indoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band.note1
- (iii) For fixed point-to-point access points operating in the band 5.15 - 5.25 GHz, transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi.
- (iv) For mobile and portable client devices in the 5.15 - 5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 MHz band. note1

Note1: If transmitting antennas of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### For the band 5.25-5.35 GHz and 5.47-5.725 GHz

The maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### For 5725~5850MHz

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

### 6.7.2 Measuring Instruments and Setting


Please refer to equipment list in this report. The following table is the setting of Spectrum Analyzer.

### 6.7.3 Test Procedures

1. Use this procedure when the maximum peak conducted output power in the fundamental 1). The transmitter was connected directly to a Spectrum Analyzer through a directional couple.
- 2). The power was monitored at the coupler port with a Spectrum Analyzer. The power level was set to the maximum level.
- 3). Set the RBW = 1MHz.
- 4). Set the VBW  $\geq$  3MHz
- 5). Span=Encompass the entire emissions bandwidth (EBW) of the signal (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- 6). Number of points in sweep  $\geq 2 \times \text{span} / \text{RBW}$ . (This ensures that bin-to-bin spacing is  $\leq \text{RBW}/2$ , so that narrowband signals are not lost between frequency bins.)
- 7). Manually set sweep time  $\geq 10 \times (\text{number of points in sweep}) \times (\text{total on/off period of the transmitted signal})$ .
- 8). Set detector = power averaging (rms).

- 9). Sweep time = auto couple.
- 10). Trace mode = max hold.
- 11). Allow trace to fully stabilize.
- 12). Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively).
- 13). Add  $10 \log(1/x)$ , where  $x$  is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission). For example, add  $10 \log(1/0.25) = 6$  dB if the duty cycle is 25%.
- 14). Use the peak marker function to determine the maximum power level in any 1MHz band segment within the fundamental EBW.

#### 6.7.4 Test Setup Layout



#### 6.7.5 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 6.7.6 Test result

PASS

Please refer to Appendix D.5 (5150-5250MHz) and Appendix E.5(5725-5850MHz)

Remark:

1. Measured power spectrum density at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11ac VHT20, IEEE 802.11ac VHT40, IEEE 802.11ac VHT80, IEEE 802.11ax HE20, IEEE 802.11ax HE40, IEEE 802.11ax HE80;.

Report conducted PSD = Measured conducted average power + Duty Cycle factor;



## 6.8 Radiated Emissions and Radiation Restricted band Measurement

### 6.8.1 Standard requirement

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
\1\ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293.	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(\2\)
13.36-13.41			

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

According to §15.247 (d): 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

I

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 6.8.2 Measuring Instruments and Setting:

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10 <sup>th</sup> carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB/VB 120kHz/1MHz for QP

### 6.8.3 Test Procedures

#### 1) Sequence of testing 9 kHz to 30 MHz

##### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

##### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.5 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

##### Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

## 2) Sequence of testing 30 MHz to 1 GHz

### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

### 3) Sequence of testing 1 GHz to 18 GHz

#### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

#### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

#### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

#### 4) Sequence of testing above 18 GHz

##### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.


##### Premeasurement:

- The antenna is moved spherical over the EUT in different polarisations of the antenna.


##### Final measurement:

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.


#### 6.8.4 Test Setup Layout



Below 30MHz



Below 1GHz



Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

### 6.8.5 EUT Operation During Test

The EUT was programmed to be in continuously transmitting mode.

### 6.8.6 Test Result

Temperature	25.5℃	Humidity	52.2%
Test Engineer	Emiya Lin	Configurations	IEEE 802.11a/n/ac/ax

Remarks:

1. Only the worst case Main Antenna test data.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

### ■ Results of Radiated Emissions (9 KHz~30MHz)

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dBuV)	Remark
-	-	-	-	See Note

Note:

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);


Limit line = specific limits (dBuV) + distance extrapolation factor.

## Results of Radiated Emissions (30MHz~1GHz)

Pre-scan all modes and recorded the worst case results in this report (IEEE 802.11a VHT20)..

Configuration1+Adapter1:

Model name:	H20	Test Date :	2024-12-31
Polarization :	Vertical	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Measurement Result=Reading Level +Correct Factor;

Over Limit= Measurement Result- Limit;

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		55.8047	27.70	-0.90	26.80	40.00	-13.20	QP
2		144.8418	29.70	-1.24	28.46	43.50	-15.04	QP
3		209.3129	26.88	1.97	28.85	43.50	-14.65	QP
4		261.0583	28.13	-0.12	28.01	46.00	-17.99	QP
5		501.1790	30.12	4.89	35.01	46.00	-10.99	QP
6	*	793.3960	24.27	12.88	37.15	46.00	-8.85	QP



Model name:	H20	Test Date :	2024-12-31
Polarization :	Horizontal	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Measurement Result=Reading Level +Correct Factor;

Over Limit= Measurement Result- Limit;

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		56.1974	25.54	1.28	26.82	40.00	-13.18	QP
2		147.4036	26.03	-0.83	25.20	43.50	-18.30	QP
3	*	411.8240	32.69	6.92	39.61	46.00	-6.39	QP
4		501.1790	30.31	8.44	38.75	46.00	-7.25	QP
5		760.7036	26.27	12.28	38.55	46.00	-7.45	QP
6		952.0937	26.92	12.55	39.47	46.00	-6.53	QP



## Configuration1+Adapter2:

Model name:	H20	Test Date :	2024-12-31
Polarization :	Vertical	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Measurement Result=Reading Level +Correct Factor;

Over Limit= Measurement Result- Limit;

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	44.1202	35.29	1.39	36.68	40.00	-3.32	QP
2		68.1514	34.74	-3.88	30.86	40.00	-9.14	QP
3		98.4866	27.81	-3.05	24.76	43.50	-18.74	QP
4		210.0482	30.27	2.18	32.45	43.50	-11.05	QP
5		501.1790	31.11	4.89	36.00	46.00	-10.00	QP
6		760.7036	27.66	10.89	38.55	46.00	-7.45	QP

Model name:	H20	Test Date :	2024-12-31
Polarization :	Horizontal	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Measurement Result=Reading Level +Correct Factor;

Over Limit= Measurement Result- Limit;

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		31.1798	27.18	1.98	29.16	40.00	-10.84	QP
2		58.2030	26.69	0.51	27.20	40.00	-12.80	QP
3		183.8440	25.15	0.38	25.53	43.50	-17.97	QP
4	*	399.0302	34.30	6.24	40.54	46.00	-5.46	QP
5		501.1790	31.17	8.44	39.61	46.00	-6.39	QP
6		760.7036	27.12	12.28	39.40	46.00	-6.60	QP

## Configuration2+Adapter1:

Model name:	H20	Test Date :	2024-12-31
Polarization :	Vertical	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Measurement Result=Reading Level +Correct Factor;

Over Limit= Measurement Result- Limit;

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		41.4215	26.08	1.56	27.64	40.00	-12.36	QP
2		141.8262	34.84	-1.50	33.34	43.50	-10.16	QP
3		211.5265	29.71	1.73	31.44	43.50	-12.06	QP
4		305.6800	28.56	2.07	30.63	46.00	-15.37	QP
5		501.1790	31.02	4.89	35.91	46.00	-10.09	QP
6	*	793.3960	25.24	12.88	38.12	46.00	-7.88	QP

Model name:	H20	Test Date :	2024-12-31
Polarization :	Horizontal	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Measurement Result=Reading Level +Correct Factor;

Over Limit= Measurement Result- Limit;

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	61.5618	36.66	-1.48	35.18	40.00	-4.82	QP
2		129.9226	28.91	-1.90	27.01	43.50	-16.49	QP
3		264.7457	33.02	-0.38	32.64	46.00	-13.36	QP
4		419.1081	31.18	7.05	38.23	46.00	-7.77	QP
5		501.1790	31.20	8.44	39.64	46.00	-6.36	QP
6		774.1584	25.78	12.57	38.35	46.00	-7.65	QP

## Configuration2+Adapter2:

Model name:	H20	Test Date :	2024-12-31
Polarization :	Vertical	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Measurement Result=Reading Level +Correct Factor;

Over Limit= Measurement Result- Limit;

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		38.8878	24.62	1.53	26.15	40.00	-13.85	QP
2		142.3243	34.68	-1.44	33.24	43.50	-10.26	QP
3		209.3129	30.12	1.97	32.09	43.50	-11.41	QP
4		434.0651	26.57	4.83	31.40	46.00	-14.60	QP
5		501.1790	30.30	4.89	35.19	46.00	-10.81	QP
6	*	807.4291	24.31	12.75	37.06	46.00	-8.94	QP



Model name:	H20	Test Date :	2024-12-31
Polarization :	Horizontal	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Measurement Result=Reading Level +Correct Factor;

Over Limit= Measurement Result- Limit;

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		45.8553	23.86	3.46	27.32	40.00	-12.68	QP
2		58.2030	25.29	0.51	25.80	40.00	-14.20	QP
3		142.3243	26.52	-0.94	25.58	43.50	-17.92	QP
4		263.8190	32.04	-0.32	31.72	46.00	-14.28	QP
5	*	501.1790	31.29	8.44	39.73	46.00	-6.27	QP
6		790.6188	24.15	12.85	37.00	46.00	-9.00	QP

## Results for Radiated Emissions (1- 40 GHz)

Note: All the modes have been tested and recorded worst mode in the report.

### IEEE 802.11a

#### Channel 36 / 5180 MHz

Freq GHz	Read Level dBuV	Correct Factor	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
10360	34.03	12.56	46.59	68.20	-21.61	Peak	Horizontal
15540	20.34	16.45	36.79	54.00	-17.21	Average	Horizontal
10360	32.45	12.56	45.01	68.20	-23.19	Peak	Vertical
15540	20.42	16.45	36.87	54.00	-17.13	Average	Vertical

#### Channel 48 / 5240 MHz

Freq GHz	Read Level dBuV	Correct Factor	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
10480	34.33	12.68	47.01	68.20	-21.19	Peak	Horizontal
15720	21.40	16.54	37.94	54.00	-16.06	Average	Horizontal
10480	31.81	12.68	44.49	68.20	-23.71	Peak	Vertical
15720	20.10	16.54	36.64	54.00	-17.36	Average	Vertical

#### Channel 149 / 5745 MHz

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV/m	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11490	31.08	16.82	47.90	68.20	-20.30	Peak	Horizontal
17235	19.80	22.93	42.73	54.00	-11.27	Average	Horizontal
11490	29.31	16.71	46.02	68.20	-22.18	Peak	Vertical
17235	19.01	22.93	41.94	54.00	-12.06	Average	Vertical

#### Channel 157 / 5785 MHz

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV/m	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11570	32.25	16.71	48.96	68.20	-19.24	Peak	Horizontal
17355	18.63	24.37	43.00	54.00	-11.00	Average	Horizontal
11570	30.60	16.71	47.31	68.20	-20.89	Peak	Vertical
17355	19.91	24.37	44.28	54.00	-9.72	Average	Vertical

**Channel 163 / 5825 MHz**

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV/m	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11650	31.05	16.61	47.66	68.20	-20.54	Peak	Horizontal
17475	20.51	25.01	45.52	54.00	-8.48	Average	Horizontal
11650	29.92	16.61	46.53	68.20	-21.67	Peak	Vertical
17475	18.48	25.01	43.49	54.00	-10.51	Average	Vertical

**IEEE 802.11n HT40**
**Channel 38 / 5190 MHz**

Freq GHz	Read Level dBuV	Correct Factor	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
10380	29.89	12.58	42.47	68.20	-25.73	Peak	Horizontal
15570	20.04	16.48	36.52	54.00	-17.48	Average	Horizontal
10380	29.28	12.58	41.86	68.20	-26.34	Peak	Vertical
15570	20.17	16.48	36.65	54.00	-17.35	Average	Vertical

**Channel 151 / 5755 MHz**

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV/m	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11510	30.44	16.78	47.22	68.20	-20.98	Peak	Horizontal
17265	18.86	23.29	42.15	54.00	-11.85	Average	Horizontal
11510	28.72	16.78	45.50	68.20	-22.70	Peak	Vertical
17265	18.28	23.29	41.57	54.00	-12.43	Average	Vertical

**Channel 159 / 5795 MHz**

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV/m	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11590	30.51	16.69	47.20	68.20	-21.00	Peak	Horizontal
17385	19.38	24.73	44.11	54.00	-9.89	Average	Horizontal
11590	28.75	16.69	45.44	68.20	-22.76	Peak	Vertical
17385	18.20	24.73	42.93	54.00	-11.07	Average	Vertical



# IEEE 802.11ac VHT80

## Channel 42 / 5210 MHz

Freq GHz	Read Level dBuV	Correct Factor	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
10420	27.80	12.62	40.42	68.20	-27.78	Peak	Horizontal
15630	17.73	16.52	34.25	54.00	-19.75	Average	Horizontal
10420	27.08	12.62	39.70	68.20	-28.50	Peak	Vertical
15630	18.23	16.52	34.75	54.00	-19.25	Average	Vertical

## Channel 155 / 5775 MHz

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV/m	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
11550	28.41	16.73	45.14	68.20	-23.06	Peak	Horizontal
17325	18.46	24.01	42.47	54.00	-11.53	Average	Horizontal
11550	27.68	16.73	44.41	68.20	-23.79	Peak	Vertical
17325	18.21	24.01	42.22	54.00	-11.78	Average	Vertical

### Notes:

- 1). Measuring frequencies from 9 KHz ~ 40GHz, No emission found between lowest internal used/generated frequency to 30MHz.
- 2). Radiated emissions measured in frequency range from 9 KHz ~ 40GHz were made with an instrument using Peak detector mode.
- 3). 18~40GHz at least have 20dB margin. No recording in the test report.
- 4). Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11ac VHT20, IEEE 802.11ac VHT40, IEEE 802.11ac VHT80, IEEE 802.11ax HE20, IEEE 802.11ax HE40, IEEE 802.11ax HE80;.
- 5). Data of measurement within this frequency range shown “---” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 6). Margin=Reading level + Factor – Limit

## Results for Radiation Restricted band

Note: All the modes have been tested and recorded worst mode in the report.

5180MHz-5240MHz:

IEEE 802.11a Lowest

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
5150.000	45.02	7.18	52.20	68.20	-16.00	Peak	Horizontal
5150.000	44.19	7.18	51.37	68.20	-16.83	Peak	Vertical
5350.000	43.62	7.20	50.82	68.20	-17.38	Peak	Horizontal
5350.000	42.71	7.20	49.91	68.20	-18.29	Peak	Vertical

IEEE 802.11n HT40 Lowest

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
5150.000	43.11	7.18	50.29	68.20	-17.91	Peak	Horizontal
5150.000	42.66	7.18	49.84	68.20	-18.36	Peak	Vertical
5350.000	45.42	7.20	52.62	68.20	-15.58	Peak	Horizontal
5350.000	44.46	7.20	51.66	68.20	-16.54	Peak	Vertical

IEEE 802.11ac VHT80 Lowest

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
5150.000	47.04	7.18	54.22	68.20	-13.98	Peak	Horizontal
5150.000	45.33	7.18	52.51	68.20	-15.69	Peak	Vertical
5350.000	47.50	7.20	54.70	68.20	-13.50	Peak	Horizontal
5350.000	45.32	7.20	52.52	68.20	-15.68	Peak	Vertical

5745MHz-5825MHz:

IEEE 802.11a Lowest

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
5725	40.48	8.79	49.27	68.20	-18.93	Peak	Horizontal
5741.35	82.71	8.57	91.28	N/A	N/A	Peak	Horizontal
5725	40.77	8.79	49.56	68.20	-18.64	Peak	Vertical
5741.35	84.92	8.57	93.49	N/A	N/A	Peak	Vertical

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
5725	30.83	8.79	39.62	54.00	-14.38	AVG	Horizontal
5741.35	72.03	8.57	80.60	N/A	N/A	AVG	Horizontal
5725	30.42	8.79	39.21	54.00	-14.79	AVG	Vertical
5741.35	75.44	8.57	84.01	N/A	N/A	AVG	Vertical

IEEE 802.11a Highest

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
5826.2	78.26	8.79	87.05	N/A	N/A	Peak	Horizontal
5850	37.94	8.82	46.76	68.20	-21.44	Peak	Horizontal
5826.2	84.78	8.79	93.57	N/A	N/A	Peak	Vertical
5850	39.44	8.82	48.26	68.20	-19.94	Peak	Vertical

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
5826.2	70.24	8.79	79.03	N/A	N/A	AVG	Horizontal
5850	28.84	8.82	37.66	54.00	-16.34	AVG	Horizontal
5826.2	75.92	8.79	84.71	N/A	N/A	AVG	Vertical
5850	28.83	8.82	37.65	54.00	-16.35	AVG	Vertical

### IEEE 802.11n HT40 Lowest

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
5725.000	38.76	8.52	47.28	68.20	-20.92	Peak	Horizontal
5745.000	75.08	8.57	83.65	N/A	N/A	Peak	Horizontal
5725.000	37.58	8.52	46.10	68.20	-22.10	Peak	Vertical
5745.000	84.93	8.57	93.50	N/A	N/A	Peak	Vertical

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
5725.000	30.74	8.52	39.26	54.00	-14.74	AVG	Horizontal
5745.000	68.43	8.57	77.00	N/A	N/A	AVG	Horizontal
5725.000	28.36	8.52	36.88	54.00	-17.12	AVG	Vertical
5745.000	75.03	8.57	83.60	N/A	N/A	AVG	Vertical

### IEEE 802.11n HT40 Highest

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
5784.88.0	79.08	8.68	87.76	N/A	N/A	Peak	Horizontal
5850.000	38.51	8.82	47.33	68.20	-20.87	Peak	Horizontal
5784.880	84.56	8.68	93.24	N/A	N/A	Peak	Vertical
5850.000	43.19	8.82	52.01	68.20	-16.19	Peak	Vertical

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
5784.880	71.16	8.68	79.84	N/A	N/A	AVG	Horizontal
5850.000	29.21	8.82	38.03	54.00	-15.97	AVG	Horizontal
5784.880	74.44	8.68	83.12	N/A	N/A	AVG	Vertical
5850.000	27.78	8.82	36.60	54.00	-17.40	AVG	Vertical

### IEEE 802.11ac VHT80 Lowest

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
5725.000	37.82	8.52	46.34	68.20	-21.86	Peak	Horizontal
5778.180	78.73	8.68	87.41	N/A	N/A	Peak	Horizontal
5850.000	36.26	8.82	45.08	68.20	-23.12	Peak	Horizontal
5725.000	37.88	8.52	46.40	68.20	-21.80	Peak	Vertical
5778.180	82.41	8.68	91.09	N/A	N/A	Peak	Vertical
5850.000	40.56	8.82	49.38	68.20	-18.82	Peak	Vertical

Freq GHz	Read Level dBuV	Correct Factor dB/m	Measured Level dBuV	Limit Line dBuV/m	Over limit dB	Remark	Pol/Phase
5725.000	30.24	8.52	38.76	54.00	-15.24	AVG	Horizontal
5778.180	70.13	8.68	78.81	N/A	N/A	AVG	Horizontal
5850.000	28.75	8.82	37.57	54.00	-16.43	AVG	Horizontal
5725.000	29.26	8.52	37.78	54.00	-16.22	AVG	Vertical
5778.180	71.48	8.68	80.16	N/A	N/A	AVG	Vertical
5850.000	30.03	8.82	38.85	54.00	-15.15	AVG	Vertical

#### Remarks:

- 1). Margin= Emission Level – Limit
- 2). Emission Level = Reading + Factor
- 3). Factor = Antenna Factor + Cable Loss – Pre-amplifie
- 4).The PEAK value is less than the AVG limit, the AVG result no need be show in this report.

## 6.9 Power Line Conducted Emissions


### 6.9.1 Standard requirement

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

\* Decreasing linearly with the logarithm of the frequency

### 6.9.2 Test Setup Layout



### 6.9.3 Test Procedures

The transmitter output is connected to EMI receiver. The resolution bandwidth is set to 9 kHz. The video bandwidth is set to 30 kHz, Sweep time=Auto

The spectrum from 150 kHz to 30MHz is investigated with the transmitter set to the lowest, middle, and highest channels.

### 6.9.4 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

### 6.9.5 Test result

PASS

The test data please refer to following page.


Temperature	25.5°C	Humidity	52.2%
Test Engineer	Emiya Lin	Configurations	IEEE 802.11a/n/ac/ax

**Measurement data:**

**AC Conducted Emission of charge from PC mode @ AC 120V/60Hz @ (IEEE 802.11a HT20)**  
(worst case)

**Configuration1+Adapter1:**

Model name:	H20	Test Date :	2024-12-31
ATM Pressure:	101 kPa	Test by:	Emiya Lin
Phase :	Line	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail



Remark: Factor =insertion loss of LISN + Cable loss +insertion loss of Pulse Limiter +insertion loss of Switch.


Measurement Result=Reading Level +Correct Factor;

Over Limit= Measurement Result- Limit;

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1900	14.39	11.26	25.65	54.03	-28.38	AVG
2		0.1980	28.40	11.16	39.56	63.69	-24.13	QP
3	*	0.3860	32.86	10.13	42.99	58.15	-15.16	QP
4		0.3860	19.27	10.13	29.40	48.15	-18.75	AVG
5		0.6140	18.87	9.99	28.86	56.00	-27.14	QP
6		0.6340	4.36	9.99	14.35	46.00	-31.65	AVG
7		3.0579	17.54	10.03	27.57	56.00	-28.43	QP
8		3.3020	1.24	10.04	11.28	46.00	-34.72	AVG
9		8.1459	5.71	10.19	15.90	50.00	-34.10	AVG
10		8.1820	22.65	10.19	32.84	60.00	-27.16	QP
11		14.0900	26.57	1.38	27.95	60.00	-32.05	QP
12		16.8819	9.75	1.64	11.39	50.00	-38.61	AVG



Model name:	H20	Test Date :	2024-12-31
ATM Pressure:	101 kPa	Test by:	Emiya Lin
Phase :	Neutral	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail



Remark: Factor =insertion loss of LISN + Cable loss +insertion loss of Pulse Limiter +insertion loss of Switch.

Measurement Result=Reading Level +Correct Factor;


Over Limit= Measurement Result- Limit;

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1620	30.86	11.68	42.54	65.36	-22.82	QP
2		0.1620	13.22	11.68	24.90	55.36	-30.46	AVG
3		0.2860	28.77	10.61	39.38	60.64	-21.26	QP
4		0.2980	14.12	10.26	24.38	50.30	-25.92	AVG
5	*	0.3980	32.65	10.13	42.78	57.89	-15.11	QP
6		0.3980	16.37	10.13	26.50	47.89	-21.39	AVG
7		1.8980	16.86	9.99	26.85	56.00	-29.15	QP
8		2.1180	1.38	9.99	11.37	46.00	-34.63	AVG
9		8.3300	22.07	10.20	32.27	60.00	-27.73	QP
10		8.4020	4.02	10.20	14.22	50.00	-35.78	AVG
11		17.9900	25.13	1.78	26.91	60.00	-33.09	QP
12		17.9900	8.87	1.78	10.65	50.00	-39.35	AVG



### Configuration1+Adapter2:

Model name:	H20	Test Date :	2024-12-31
ATM Pressure:	101 kPa	Test by:	Emiya Lin
Phase :	Line	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail




Remark: Factor =insertion loss of LISN + Cable loss +insertion loss of Pulse Limiter +insertion loss of Switch.

Measurement Result=Reading Level +Correct Factor;

Over Limit= Measurement Result- Limit;

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.1500	47.08	11.94	59.02	65.99	-6.97	QP
2		0.1580	32.45	11.75	44.20	55.56	-11.36	AVG
3		0.3220	29.35	10.19	39.54	59.65	-20.11	QP
4		0.3300	19.54	10.18	29.72	49.45	-19.73	AVG
5		0.5260	27.08	10.01	37.09	56.00	-18.91	QP
6		0.5260	22.41	10.01	32.42	46.00	-13.58	AVG
7		1.7660	8.76	9.98	18.74	46.00	-27.26	AVG
8		2.1420	18.24	10.00	28.24	56.00	-27.76	QP
9		7.2500	25.50	10.17	35.67	60.00	-24.33	QP
10		8.3780	17.09	10.20	27.29	50.00	-22.71	AVG
11		16.3900	35.78	1.58	37.36	50.00	-12.64	AVG
12		16.6860	43.53	1.62	45.15	60.00	-14.85	QP

Model name:	H20	Test Date :	2024-12-31
ATM Pressure:	101 kPa	Test by:	Emiya Lin
Phase :	Neutral	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail



Remark: Factor =insertion loss of LISN + Cable loss +insertion loss of Pulse Limiter +insertion loss of Switch.


Measurement Result=Reading Level +Correct Factor;

Over Limit= Measurement Result- Limit;

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.1500	42.58	11.94	54.52	65.99	-11.47	QP
2		0.1500	29.59	11.94	41.53	55.99	-14.46	AVG
3		0.1819	25.37	11.36	36.73	54.39	-17.66	AVG
4		0.2100	37.84	11.06	48.90	63.20	-14.30	QP
5		0.5220	28.09	10.01	38.10	56.00	-17.90	QP
6		0.5220	23.44	10.01	33.45	46.00	-12.55	AVG
7		3.2139	26.83	10.04	36.87	56.00	-19.13	QP
8		3.2380	16.55	10.04	26.59	46.00	-19.41	AVG
9		5.6940	17.57	10.12	27.69	50.00	-22.31	AVG
10		5.9660	24.10	10.12	34.22	60.00	-25.78	QP
11		16.6180	30.03	1.61	31.64	50.00	-18.36	AVG
12		17.4980	39.01	1.72	40.73	60.00	-19.27	QP

### Configuration2+Adapter1:

Model name:	H20	Test Date :	2024-12-31
ATM Pressure:	101 kPa	Test by:	Emiya Lin
Phase :	Line	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail




Remark: Factor =insertion loss of LISN + Cable loss +insertion loss of Pulse Limiter +insertion loss of Switch.

Measurement Result=Reading Level +Correct Factor;

Over Limit= Measurement Result- Limit;

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1539	39.64	11.84	51.48	65.78	-14.30	QP
2		0.1539	25.62	11.84	37.46	55.78	-18.32	AVG
3	*	0.3820	34.01	10.14	44.15	58.23	-14.08	QP
4		0.3820	22.20	10.14	32.34	48.23	-15.89	AVG
5		0.8220	24.85	9.95	34.80	56.00	-21.20	QP
6		0.8220	11.25	9.95	21.20	46.00	-24.80	AVG
7		3.9180	26.95	10.05	37.00	56.00	-19.00	QP
8		3.9180	14.61	10.05	24.66	46.00	-21.34	AVG
9		8.4300	33.12	10.20	43.32	60.00	-16.68	QP
10		8.4300	17.63	10.20	27.83	50.00	-22.17	AVG
11		20.5100	32.99	2.05	35.04	60.00	-24.96	QP
12		20.5100	19.65	2.05	21.70	50.00	-28.30	AVG

Model name:	H20	Test Date :	2024-12-31
ATM Pressure:	101 kPa	Test by:	Emiya Lin
Phase :	Neutral	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail



Remark: Factor =insertion loss of LISN + Cable loss +insertion loss of Pulse Limiter +insertion loss of Switch.

Measurement Result=Reading Level +Correct Factor;


Over Limit= Measurement Result- Limit;

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1580	33.09	11.75	44.84	65.56	-20.72	QP
2		0.1580	24.58	11.75	36.33	55.56	-19.23	AVG
3		0.2180	29.65	11.00	40.65	62.89	-22.24	QP
4		0.2180	19.03	11.00	30.03	52.89	-22.86	AVG
5		0.4140	24.63	10.12	34.75	57.57	-22.82	QP
6		0.4140	14.75	10.12	24.87	47.57	-22.70	AVG
7		1.6420	20.27	9.97	30.24	56.00	-25.76	QP
8		1.6420	7.70	9.97	17.67	46.00	-28.33	AVG
9	*	3.9700	26.96	10.05	37.01	56.00	-18.99	QP
10		3.9700	11.66	10.05	21.71	46.00	-24.29	AVG
11		9.0380	29.80	10.21	40.01	60.00	-19.99	QP
12		9.0380	14.65	10.21	24.86	50.00	-25.14	AVG



### Configuration2+Adapter2:

Model name:	H20	Test Date :	2024-12-31
ATM Pressure:	101 kPa	Test by:	Emiya Lin
Phase :	Line	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail




Remark: Factor =insertion loss of LISN + Cable loss +insertion loss of Pulse Limiter +insertion loss of Switch.

Measurement Result=Reading Level +Correct Factor;

Over Limit= Measurement Result- Limit;

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	*	0.1500	45.14	11.94	57.08	65.99	-8.91	QP
2		0.1500	32.80	11.94	44.74	55.99	-11.25	AVG
3		0.2220	36.78	10.98	47.76	62.74	-14.98	QP
4		0.2220	24.97	10.98	35.95	52.74	-16.79	AVG
5		0.5180	27.54	10.01	37.55	56.00	-18.45	QP
6		0.5180	24.15	10.01	34.16	46.00	-11.84	AVG
7		4.9300	25.38	10.11	35.49	56.00	-20.51	QP
8		4.9300	17.34	10.11	27.45	46.00	-18.55	AVG
9		7.7700	28.88	10.19	39.07	60.00	-20.93	QP
10		7.7700	18.14	10.19	28.33	50.00	-21.67	AVG
11		15.9220	44.87	1.52	46.39	60.00	-13.61	QP
12		15.9220	36.47	1.52	37.99	50.00	-12.01	AVG

Model name:	H20	Test Date :	2024-12-31
ATM Pressure:	101 kPa	Test by:	Emiya Lin
Phase :	Neutral	Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail



Remark: Factor =insertion loss of LISN + Cable loss +insertion loss of Pulse Limiter +insertion loss of Switch.

Measurement Result=Reading Level +Correct Factor;

Over Limit= Measurement Result- Limit;

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.1539	45.74	11.84	57.58	65.78	-8.20	QP
2		0.1539	35.41	11.84	47.25	55.78	-8.53	AVG
3		0.2620	32.57	10.85	43.42	61.36	-17.94	QP
4		0.2620	22.91	10.85	33.76	51.36	-17.60	AVG
5		0.4940	31.81	10.02	41.83	56.10	-14.27	QP
6		0.4940	26.59	10.02	36.61	46.10	-9.49	AVG
7		2.9900	27.20	10.03	37.23	56.00	-18.77	QP
8		2.9900	17.11	10.03	27.14	46.00	-18.86	AVG
9		5.9299	29.15	10.12	39.27	60.00	-20.73	QP
10		5.9299	19.93	10.12	30.05	50.00	-19.95	AVG
11		16.0779	38.94	1.54	40.48	60.00	-19.52	QP
12		16.0779	31.67	1.54	33.21	50.00	-16.79	AVG

#### Notes:

1. Pre-scan all modes and recorded the worst case results in this report (IEEE 802.11n HT20 mode (HCH)).
2. An initial pre-scan was performed on the line and neutral lines with peak detector.
3. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

## 6.10 Frequency Stability

### 6.10.1 Standard requirement

According to FCC §15.407(g) “Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.”

According to FCC §2.1055(a) “The frequency stability shall be measured with variation of ambient temperature as follows:”

- (1) From  $-30^{\circ}$  to  $+50^{\circ}$  centigrade for all equipment except that specified in paragraphs (a) (2) and (3) of this section.
- (2) From  $-20^{\circ}$  to  $+50^{\circ}$  centigrade for equipment to be licensed for use in the Maritime Services under part 80 of this chapter, except for Class A, B, and S Emergency Position Indicating Radiobeacons (EPIRBS), and equipment to be licensed for use above 952 MHz at operational fixed stations in all services, stations in the Local Television Transmission Service and Point-to-Point Microwave Radio Service under part 21 of this chapter, equipment licensed for use aboard aircraft in the Aviation Services under part 87 of this chapter, and equipment authorized for use in the Family Radio Service under part 95 of this chapter.

From  $0^{\circ}$  to  $+50^{\circ}$  centigrade for equipment to be licensed for use in the Radio Broadcast Services under part 73 of this chapter.


### 6.10.2 Measuring Instruments and Setting:

Please refer to equipment list in this report.

### 6.10.3 Test Procedures

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20 degree operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30 degree. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10 degree increased per stage until the highest temperature of +50 degree reached.

### 6.10.4 Test Setup Layout



### 6.10.5 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

### 6.10.6 Test result

PASS

Please refer to Appendix D.7 (5150-5250MHz) and Appendix E.7 (5725-5850MHz)

## **7 Test Setup Photographs of EUT**

Please refer to separated files for Test Setup Photos of the EUT.

## **8 External Photographs of EUT**

Please refer to separated files for External Photos of the EUT.

## **9 Internal Photographs of EUT**

Please refer to separated files for Internal Photos of the EUT.

**----End Of The Report----**