

**Maximum Permissible Exposure Report****1. Product Information**

EUT	:	Interactive touch all-in-one machine
Test Model	:	TV-65810
Additional Model No.	:	TV-*****, TF-*****, TZ-*****, TP-*****, PM-*****(* can represent the numbers 0-9, letters A-Z, a-z, symbols, or blank space, representing different marketing areas; Does not affect product safety and electromagnetic compatibility)
Model Declaration	:	PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Power Supply	:	Input: 100-240V~, 50/60Hz, 2.68A Max
Hardware Version	:	/
Software Version	:	/
Bluetooth		
Frequency Range	:	2402MHz ~ 2480MHz
Channel Number	:	79 channels for Bluetooth V5.0(DSS) 40 channels for Bluetooth V5.0 (DTS)
Channel Spacing	:	1MHz for Bluetooth V5.0 (DSS) 2MHz for Bluetooth V5.0 (DTS)
Modulation Type	:	GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.0(DSS) GFSK for Bluetooth V5.0 (DTS)
Bluetooth Version	:	V5.0
Antenna Description	:	External Antenna, 3.8dBi(Max.)
WIFI(2.4G Band)		
Frequency Range	:	2412MHz~2462MHz
Channel Number	:	11 Channels for 20MHz bandwidth(2412~2462MHz) 7 Channels for 40MHz bandwidth(2422~2452MHz)
Channel Spacing	:	5MHz
Modulation Type	:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	:	Antenna0: External Antenna, 3.8dBi(Max.) Antenna1: External Antenna, 3.8dBi(Max.) Antenna2: External Antenna, 3.8dBi(Max.)
WIFI(5.2G Band)		
Frequency Range	:	5180MHz~5240MHz
Channel Number	:	4 channels for 20MHz bandwidth(5180MHz~5240MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz)
Modulation Type	:	IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)





	IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Antenna0: External Antenna, 5.5dBi(Max.) Antenna1: External Antenna, 5.5dBi(Max.) Antenna2: External Antenna, 5.5dBi(Max.)
WIFI(5.8G Band)	
Frequency Range	: 5745MHz~5825MHz
Channel Number	: 5 channels for 20MHz bandwidth(5745MHz~5825MHz) 2 channels for 40MHz bandwidth(5755MHz~5795MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Antenna0: External Antenna, 5.5dBi(Max.) Antenna1: External Antenna, 5.5dBi(Max.) Antenna2: External Antenna, 5.5dBi(Max.)
Exposure category	: General population/uncontrolled environment
EUT Type	: Production Unit
Device Type	: Mobile Device

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3. 1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Internal/ External Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
External	External Antenna 0	2400MHz ~ 2500MHz	3.8dBi	BT Antenna0
	External Antenna 1	2400MHz ~ 6000MHz	5.5dBi	WIFI Antenna1
	External Antenna 2	2400MHz ~ 6000MHz	5.5dBi	WIFI Antenna2
	External Antenna 3	2400MHz ~ 6000MHz	5.5dBi	WIFI Antenna3



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



6. Conducted Power

< BT >< Ant 0>

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	2.9
	39	2441	3.56
	78	2480	3.03
$\pi/4$ -DQPSK	0	2402	3
	39	2441	3.65
	78	2480	3.04
8-DPSK	0	2402	2.99
	39	2441	3.65
	78	2480	3.03

< BT LE >< Ant 0>

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	-2.12
	19	2440	-1.69
	39	2480	-1.8

< BT 2LE >< Ant 0>

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	-2.12
	19	2440	-1.7
	39	2480	-1.8





[2.4G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Peak Conducted Output Power (dBm)	Ant 2 Peak Conducted Output Power (dBm)	Ant 3 Peak Conducted Output Power (dBm)
11B	1	2412	15.54	15.5	15.24
	6	2437	15.72	15.7	15.34
	11	2462	15.75	15.63	15.38
11G	1	2412	14.49	14.52	14.65
	6	2437	14.66	14.76	14.52
	11	2462	14.84	14.77	14.73
11N20 SISO	1	2412	12.59	12.47	12.37
	6	2437	13.68	13.57	13.74
	11	2462	13.15	13.15	13.66
11N40 SISO	3	2422	12.75	12.3	12.67
	6	2437	13.37	13.33	13.77
	9	2452	13.3	13.3	13.75
11AX20 SISO	1	2412	12.53	12.59	12.45
	6	2437	13.28	13.74	13.64
	11	2462	13.17	13.64	13.61
11AX40 SISO	3	2422	12.48	12.55	12.27
	6	2437	13.45	13.46	13.47
	9	2452	13.56	13.6	13.56



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.2G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)	Ant 3 Max Conducted Power(dBm)
11A	36	5180	12.72	12.99	12.38
	40	5200	12.73	12.2	12.37
	48	5240	11.98	12.09	12.36
11N20 SISO	36	5180	11.87	12	11.95
	40	5200	11.85	11.39	11.67
	48	5240	11.84	11.66	11.62
11N40 SISO	38	5190	11.36	11.47	11.6
	46	5230	11.27	11.62	11.46
11AC20 SISO	36	5180	11.73	11.58	11.45
	40	5200	11.79	11.48	11.68
	48	5240	11.9	11.74	11.68
11AC40 SISO	38	5190	11.64	11.51	11.58
	46	5230	11.47	11.45	11.31
11AX20 SISO	36	5180	11.8	11.96	11.46
	40	5200	11.85	11.94	11.76
	48	5240	11.88	11.63	11.69
11AX40 SISO	38	5190	11.45	11.56	11.47
	46	5230	11.31	11.29	11.41





[5.8G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)	Ant 3 Max Conducted Power(dBm)
11A	149	5745	11.51	11.24	11.66
	157	5785	11.63	11.15	11.48
	165	5825	11.59	11.47	11.36
11N20 SISO	149	5745	10.55	10.75	10.45
	157	5785	10.89	10.62	10.85
	165	5825	10.73	11	10.68
11N40 SISO	151	5755	10.45	10.75	10.65
	159	5795	11.04	10.62	10.7
11AC20 SISO	149	5745	10.41	10.82	10.38
	157	5785	10.88	10.57	10.84
	165	5825	10.55	10.55	10.93
11AC40 SISO	151	5755	10.56	10.09	10.63
	159	5795	10.2	10.44	10.76
11AX20 SISO	149	5745	10.77	10.29	10.36
	157	5785	10.31	10.62	10.62
	165	5825	10.63	10.5	10.96
11AX40 SISO	151	5755	10.47	10.08	10.69
	159	5795	10.26	10.42	10.74



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



7. Manufacturing Tolerance

< BT >< Ant 0>

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	2.0	3.0	3.0
Tolerance ±(dB)	1.0	1.0	1.0
π/4-DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	3.0	3.0	3.0
Tolerance ±(dB)	1.0	1.0	1.0
8-DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	2.0	3.0	3.0
Tolerance ±(dB)	1.0	1.0	1.0

< BT LE >< Ant 0>

GFSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	-2.0	-1.0	-1.0
Tolerance ±(dB)	1.0	1.0	1.0

< BT 2LE >< Ant 0>

GFSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	-2.0	-1.0	-1.0
Tolerance ±(dB)	1.0	1.0	1.0



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[2.4G WIFI Ant1]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	15.0	15.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	12.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX20(Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX40(Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	12.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[2.4G WIFI Ant2]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	15.0	15.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	12.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX20(Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX40(Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	12.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[2.4G WIFI Ant3]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	15.0	15.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	12.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX20(Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX40(Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	12.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.2G WIFI Ant1]

11A(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	12.0	11.0
Tolerance ±(dB)	1.0	1.0	1.0
11N20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance ±(dB)	1.0	1.0	1.0
11N40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	11.0	
Tolerance ±(dB)	1.0	1.0	
11AC20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance ±(dB)	1.0	1.0	1.0
11AC40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	11.0	
Tolerance ±(dB)	1.0	1.0	
11AX20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance ±(dB)	1.0	1.0	1.0
11AX40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	11.0	
Tolerance ±(dB)	1.0	1.0	



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.2G WIFI Ant2]

11A(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	12.0	12.0
Tolerance ±(dB)	1.0	1.0	1.0
11N20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	11.0	11.0
Tolerance ±(dB)	1.0	1.0	1.0
11N40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	11.0	
Tolerance ±(dB)	1.0	1.0	
11AC20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance ±(dB)	1.0	1.0	1.0
11AC40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	11.0	
Tolerance ±(dB)	1.0	1.0	
11AX20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance ±(dB)	1.0	1.0	1.0
11AX40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	11.0	
Tolerance ±(dB)	1.0	1.0	



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.2G WIFI Ant3]

11A(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AX20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.8G WIFI Ant1]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AX20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.8G WIFI Ant2]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.0	10.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AX20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	





[5.8G WIFI Ant3]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AX20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



8. Measurement Results

8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[BT] < Ant 0>

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio0
	dBm	mW					
GFSK	4.0	2.5119	3.8	2.3988	0.0012	1.0000	0.0012
$\pi/4$ -DQPSK	4.0	2.5119	3.8	2.3988	0.0012	1.0000	0.0012
8-DPSK	4.0	2.5119	3.8	2.3988	0.0012	1.0000	0.0012

[BT LE] < Ant 0>

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio0
	dBm	mW					
GFSK	0	1.0000	3.8	2.3988	0.0005	1.0000	0.0005

[BT 2LE] < Ant 0>

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio0
	dBm	mW					
GFSK	0	1.0000	3.8	2.3988	0.0005	1.0000	0.0005

[2.4G WIFI Ant1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio1
	dBm	mW					
IEEE 802.11b	16.0	39.8107	3.8	2.3988	0.0190	1.0000	0.0190
IEEE 802.11g	15.0	31.6228	3.8	2.3988	0.0151	1.0000	0.0151
IEEE 802.11n HT20	14.0	25.1189	3.8	2.3988	0.0120	1.0000	0.0120
IEEE 802.11n HT40	14.0	25.1189	3.8	2.3988	0.0120	1.0000	0.0120
IEEE 802.11AX HT20	14.0	25.1189	3.8	2.3988	0.0120	1.0000	0.0120
IEEE 802.11AX HT40	14.0	25.1189	3.8	2.3988	0.0120	1.0000	0.0120

[2.4G WIFI Ant2]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio2
	dBm	mW					
IEEE 802.11b	16.0	39.8107	3.8	2.3988	0.0190	1.0000	0.0190
IEEE 802.11g	15.0	31.6228	3.8	2.3988	0.0151	1.0000	0.0151
IEEE 802.11n HT20	14.0	25.1189	3.8	2.3988	0.0120	1.0000	0.0120
IEEE 802.11n HT40	14.0	25.1189	3.8	2.3988	0.0120	1.0000	0.0120
IEEE 802.11AX HT20	14.0	25.1189	3.8	2.3988	0.0120	1.0000	0.0120
IEEE 802.11AX HT40	14.0	25.1189	3.8	2.3988	0.0120	1.0000	0.0120



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[2.4G WIFI Ant3]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio3
	dBm	mW					
IEEE 802.11b	16.0	39.8107	3.8	2.3988	0.0190	1.0000	0.0190
IEEE 802.11g	15.0	31.6228	3.8	2.3988	0.0151	1.0000	0.0151
IEEE 802.11n HT20	14.0	25.1189	3.8	2.3988	0.0120	1.0000	0.0120
IEEE 802.11n HT40	14.0	25.1189	3.8	2.3988	0.0120	1.0000	0.0120
IEEE 802.11AX HT20	14.0	25.1189	3.8	2.3988	0.0120	1.0000	0.0120
IEEE 802.11AX HT40	14.0	25.1189	3.8	2.3988	0.0120	1.0000	0.0120

[5.2G WIFI Ant1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio1
	dBm	mW					
IEEE 802.11a	13.0	19.9526	5.5	3.5481	0.0141	1.0000	0.0141
IEEE 802.11n HT20	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11n HT40	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11ac VHT20	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11ac VHT40	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11ax VHT20	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11ax VHT40	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112

[5.2G WIFI Ant2]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio2
	dBm	mW					
IEEE 802.11a	13.0	19.9526	5.5	3.5481	0.0141	1.0000	0.0141
IEEE 802.11n HT20	13.0	19.9526	5.5	3.5481	0.0141	1.0000	0.0141
IEEE 802.11n HT40	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11ac VHT20	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11ac VHT40	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11ax VHT20	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11ax VHT40	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.2G WIFI Ant3]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio3
	dBm	mW					
IEEE 802.11a	13.0	19.9526	5.5	3.5481	0.0141	1.0000	0.0141
IEEE 802.11n HT20	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11n HT40	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11ac VHT20	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11ac VHT40	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11ax VHT20	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11ax VHT40	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112

[5.8G WIFI Ant1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio1
	dBm	mW					
IEEE 802.11a	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11n HT20	11.0	12.5893	5.5	3.5481	0.0089	1.0000	0.0089
IEEE 802.11n HT40	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11ac VHT20	11.0	12.5893	5.5	3.5481	0.0089	1.0000	0.0089
IEEE 802.11ac VHT40	11.0	12.5893	5.5	3.5481	0.0089	1.0000	0.0089
IEEE 802.11ax VHT20	11.0	12.5893	5.5	3.5481	0.0089	1.0000	0.0089
IEEE 802.11ax VHT40	11.0	12.5893	5.5	3.5481	0.0089	1.0000	0.0089

[5.8G WIFI Ant2]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio2
	dBm	mW					
IEEE 802.11a	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11n HT20	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11n HT40	11.0	12.5893	5.5	3.5481	0.0089	1.0000	0.0089
IEEE 802.11ac VHT20	11.0	12.5893	5.5	3.5481	0.0089	1.0000	0.0089
IEEE 802.11ac VHT40	11.0	12.5893	5.5	3.5481	0.0089	1.0000	0.0089
IEEE 802.11ax VHT20	11.0	12.5893	5.5	3.5481	0.0089	1.0000	0.0089
IEEE 802.11ax VHT40	11.0	12.5893	5.5	3.5481	0.0089	1.0000	0.0089



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.8G WIFI Ant3]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio3
	dBm	mW					
IEEE 802.11a	12.0	15.8489	5.5	3.5481	0.0112	1.0000	0.0112
IEEE 802.11n HT20	11.0	12.5893	5.5	3.5481	0.0089	1.0000	0.0089
IEEE 802.11n HT40	11.0	12.5893	5.5	3.5481	0.0089	1.0000	0.0089
IEEE 802.11ac VHT20	11.0	12.5893	5.5	3.5481	0.0089	1.0000	0.0089
IEEE 802.11ac VHT40	11.0	12.5893	5.5	3.5481	0.0089	1.0000	0.0089
IEEE 802.11ax VHT20	11.0	12.5893	5.5	3.5481	0.0089	1.0000	0.0089
IEEE 802.11ax VHT40	11.0	12.5893	5.5	3.5481	0.0089	1.0000	0.0089

Remark:

1. Output power including tune-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

8.2 Simultaneous Transmission MPE Evaluation

Maximum Simultaneous transmission MPE Ratio for WLAN

Mode	MPE Ratio0 (mW/cm ²)	MPE Ratio1 (mW/cm ²)	MPE Ratio2 (mW/cm ²)	MPE Ratio3 (mW/cm ²)	ΣMPE Ratios (mW/cm ²)	Limit (mW/cm ²)	Results
ant0 +ant1+ant2+ant3	0.0012	0.0190	0.0190	0.0190	0.0582	1.0000	Pass

Note:

1. The BT, 2.4G wifi and 5G wifi support simultaneous transmission.
2. According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations; Σ of MPE ratios ≤ 1.0
3. The estimation distance is 20cm

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----

