



REPORT No.: SZ19040180W01

TEST REPORT

APPLICANT : BLU Products, Inc.

PRODUCT NAME : Mobile phone

MODEL NAME : G5 PLUS,STUDIO MEGA 2019

BRAND NAME : BLU

FCC ID : YHLBLUG5PLUS

STANDARD(S) : 47 CFR Part 22 Subpart H
47 CFR Part 24 Subpart E
47 CFR Part 27 Subpart L

RECEIPT DATE : 2019-04-24

TEST DATE : 2019-04-24 to 2019-05-16

ISSUE DATE : 2019-05-16

Edited by: Zhao Zetian
ZhaoZetian (Rapporteur)

Approved by: Peng Huarui
Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.



SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555
Http://www.morlab.cn

Fax: 86-755-36698525
E-mail: service@morlab.cn





DIRECTORY

1. Technical Information	4
1.1. Applicant and Manufacturer Information	4
1.2. Equipment Under Test (EUT) Description	4
1.3. Test Standards and Results	6
1.4. Environmental Conditions	8
2. 47 CFR Part 2, Part 22H , 24E&27L Requirements	9
2.1. Conducted RF Output Power	9
2.2. Peak to Average Ratio	13
2.3. 99% Occupied Bandwidth	22
2.4. Frequency Stability	28
2.5. Conducted Out of Band Emissions	33
2.6. Band Edge	42
2.7. Transmitter Radiated Power (EIRP/ERP)	46
2.8. Radiated Out of Band Emissions	51
Annex A Test Uncertainty	75
Annex B Testing Laboratory Information	76



REPORT No.: SZ19040180W01

Change History		
Version	Date	Reason for change
1	2019-05-16	Initail Version



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	BLU Products, Inc.
Applicant Address:	10814 NW 33rd St # 100 Doral, FL 33172, Doral, Florida, United States
Manufacturer:	BLU Products, Inc.
ManufacturerAddress:	10814 NW 33rd St # 100 Doral, FL 33172, Doral, Florida, United States

1.2. Equipment Under Test (EUT) Description

Product Name:	Mobile phone
Serial No:	(N/A, marked #1 by test site)
Hardware Version:	FS171-MB-V0.1
Software Version:	BLU_G5_Plus_V9.0.01.00_GENERIC
Modulation Type:	GSM/GPRS Mode with GMSK Modulation EDGE Mode with 8PSK Modulation WCDMA Mode with QPSK Modulation HSDPA Mode with QPSK Modulation HSUPA Mode with QPSK Modulation
Operating Frequency Range:	GSM 850MHz: Tx: 824.20 - 848.80MHz Rx: 869.20 - 893.80MHz GSM 1900MHz: Tx: 1850.20 - 1909.80MHz Rx: 1930.20 - 1989.80MHz WCDMA Band V Tx: 826.4 - 846.6MHz Rx: 871.4 - 891.6MHz WCDMA Band II Tx: 1852.4 - 1907.6MHz Rx: 1932.4 - 1987.6MHz



Operating Frequency Range:	WCDMA Band IV Tx: 1712.4 – 1752.6MHz Rx: 2112.4 - 2152.6MHz	
Antenna Type:	PIFA Antenna	
Antenna Gain:	GSM 850:	-0.7 dBi
	GSM1900:	-1.8 dBi
	WCDMA Band V:	-0.7 dBi
	WCDMA Band II:	-1.8 dBi
	WCDMA Band IV:	-1.6 dBi
Accessory Information:	Battery	
	Brand Name:	BLU
	Model No.:	C956439300L
	Serial No.:	(N/A, marked #1 by test site)
	Capacity:	3000mAh
	Rated Voltage:	3.8V
	Charge Limit:	4.35V
	AC Adapter	
	Brand Name:	BLU
	Model No.:	US-NB-1504
	Serial No.:	(N/A, marked #1 by test site)
	Rated Input:	100-240V~50/60Hz 0.3A
	Rated Output:	5V= 1.5A

Note 1: The transmitter (Tx) frequency arrangement of the Cellular 850MHz band used by the EUT can be represented with the formula $F(n)=824.2+0.2*(n-128)$, $128 \leq n \leq 251$; the lowest, middle, highest channel numbers (ARFCHs) used and tested in this report are separately 128 (824.2MHz), 190(836.6MHz) and 251 (848.8MHz).

Note 2: The transmitter (Tx) frequency arrangement of the PCS 1900MHz band used by the EUT can be represented with the formula $F(n)=1850.2+0.2*(n-512)$, $512 \leq n \leq 810$; the lowest, middle and highest channel numbers (ARFCHs) used and tested in this report are separately 512 (1850.2MHz), 661 (1880.0MHz) and 810 (1909.8MHz).

Note 3: The transmitter (Tx) frequency arrangement of the WCDMA Band V used by the EUT can be represented with the formula $F(n)=826.4+0.2*(n-4132)$, $4132 \leq n \leq 4233$; the lowest, middle and highest channel numbers (ARFCHs) used and tested in this report are separately 4132 (826.4MHz), 4182(836.4MHz) and 4233 (846.6MHz).

Note 4: The transmitter (Tx) frequency arrangement of the WCDMA Band II used by the EUT can be represented with the formula $F(n)=1852.4+0.2*(n-9262)$, $9262 \leq n \leq 9538$; the lowest,

middle and highest channel numbers (ARFCHs) used and tested in this report are separately 9262 (1852.4MHz), 9400 (1880MHz) and 9538 (1907.6MHz).

Note 5: The transmitter (Tx) frequency arrangement of the WCDMA 1700MHz band used by the EUT can be represented with the formula $F(n)=1712.4+0.2*(n-1312)$, $1312 \leq n \leq 1513$; the lowest, middle and highest channel numbers (ARFCHs) used and tested in this report are separately 1312 (1712.4MHz), 1413 (1732.6MHz) and 1513 (1752.6MHz).

Note 6: All modes and data rates were considered and evaluated respectively by performing full test. Test modes are chosen to be reported as the worst case below:

GPRS mode and EDGE mode for GSM 850;

GPRS mode and EDGE mode for GSM 1900;

WCDMA mode for WCDMA band V;

WCDMA mode for WCDMA band II;

WCDMA mode for WCDMA band IV;

Note 7: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.3. Maximum ERP/EIRP and Emission Designator

System	Maximum ERP/EIRP (W)	Emission Designator
GSM850	0.944	245KGXW
EDGE850	0.191	250KG7W
GSM1900	1.271	250KGXW
EDGE1900	0.432	246KG7W
WCDMA Band V	0.271	4M18F9W
WCDMA Band II	0.102	4M18F9W
WCDMA Band IV	0.251	4M17F9W

1.4. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 2, Part 22, Part 24 and Part 27 for the EUT FCC ID Certification:

No	Identity	Document Title
1	47 CFR Part 2(10-1-12 Edition)	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 22(10-1-12 Edition)	Public Mobile Services
3	47 CFR Part 24(10-1-12 Edition)	Personal Communications Services
4	47 CFR Part 27(10-1-12 Edition)	Miscellaneous Wireless Communications Services

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result
1	2.1046	Conducted RF Output Power	Apr27, 2019	Gao Mingzhou	PASS
2	24.232(d),27.50(d)	Peak -Average Ratio	May06, 2019	Gao Mingzhou	PASS
3	2.1049	99% Occupied Bandwidth	May06, 2019	Gao Mingzhou	PASS
4	2.1055,22.355, 24.235, 27.54	Frequency Stability	May07&08, 2019	Gao Mingzhou	PASS
5	2.1051,22.917(a),2 4.238(a), 27.53(h)	Conducted Out of Band Emissions	May07&16, 2019	Gao Mingzhou	PASS
6	2.1051,22.917(a),2 4.238(a), 27.53(h)	Band Edge	May06, 2019	Gao Mingzhou	PASS
7	22.913(a),24.232(a)	Transmitter Radiated Power (EIPR/ERP)	Apr28, 2019	Peng Xuwei	PASS
8	2.1051,22.917(a),2 4.238(a), 27.53(h)	Radiated Out of Band Emissions	May09, 2019	Peng Xuwei	PASS

Note 1: The tests were performed according to the method of measurements prescribed in KDB 971168 D01 V03R01 (Oct 27, 2017)and ANSI/TIA-603-E-2016.

Note 2: The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The ref offset 26.5dB contains two parts that cable loss 16.5dB and Attenuator 10dB.



1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106

2.47 CFR Part 2, Part 22H , 24E&27L Requirements


2.1. Conducted RF Output Power

2.1.1. Requirement

According to FCC section 2.1046(a), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in FCC section 2.1033(c)(8).

2.1.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.

**2.1.3. Test Results**

GSM850	Average Power (dBm)		
TX Channel	128	190	251
Frequency (MHz)	824.2	836.6	848.8
GSM 1 Tx slot	32.60	32.58	32.52
GPRS 1 Tx slot	32.61	32.59	32.52
GPRS 2 Tx slots	30.57	30.58	30.75
GPRS 3 Tx slots	28.65	28.64	28.66
GPRS 4 Tx slots	26.76	26.72	26.77
EDGE 1 Tx slot	25.50	25.66	25.57
EDGE 2 Tx slots	24.56	24.61	24.56
EDGE 3 Tx slots	22.64	22.74	22.58
EDGE 4 Tx slots	19.69	19.88	19.80

GSM1900	Average Power (dBm)		
TX Channel	512	661	810
Frequency (MHz)	1850.2	1880	1909.8
GSM 1 Tx slot	29.06	29.24	28.99
GPRS 1 Tx slot	29.08	29.24	28.97
GPRS 2 Tx slots	26.80	27.10	26.99
GPRS 3 Tx slots	25.25	25.58	25.49
GPRS 4 Tx slots	23.23	23.53	23.43
EDGE 1 Tx slot	23.35	24.31	24.55
EDGE 2 Tx slots	21.94	22.87	23.06
EDGE 3 Tx slots	20.34	20.17	21.35
EDGE 4 Tx slots	18.37	19.27	19.41



WCDMA Band V	Average Power (dBm)		
TX Channel	4132	4182	4233
Frequency (MHz)	826.4	836.4	846.6
AMR 12.2Kbps	22.92	22.79	22.89
RMC 12.2Kbps	22.94	22.77	22.89
HSDPA Subtest-1	22.06	21.92	22.06
HSDPA Subtest-2	21.77	21.58	21.78
HSDPA Subtest-3	21.45	21.28	21.44
HSDPA Subtest-4	21.29	21.17	21.35
HSUPA Subtest-1	20.43	20.34	20.44
HSUPA Subtest-2	20.18	19.81	20.01
HSUPA Subtest-3	20.49	20.38	20.48
HSUPA Subtest-4	20.22	19.92	20.11
HSUPA Subtest-5	21.77	21.64	21.76

WCDMA Band II	Average Power (dBm)		
TX Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880.0	1907.6
AMR 12.2Kbps	22.31	22.47	22.52
RMC 12.2Kbps	22.38	22.53	22.50
HSDPA Subtest-1	22.46	22.36	22.52
HSDPA Subtest-2	22.11	22.08	22.15
HSDPA Subtest-3	22.28	22.19	22.27
HSDPA Subtest-4	21.97	21.87	21.97
HSUPA Subtest-1	20.04	20.12	19.97
HSUPA Subtest-2	19.97	20.03	19.85
HSUPA Subtest-3	20.43	20.49	20.31
HSUPA Subtest-4	20.52	20.57	20.35
HSUPA Subtest-5	22.29	22.24	22.38



WCDMA Band IV	Average Power (dBm)		
TX Channel	1312	1413	1513
Frequency (MHz)	1712.4	1732.6	1752.6
AMR 12.2Kbps	23.00	22.39	22.34
RMC 12.2Kbps	23.00	22.40	22.36
HSDPA Subtest-1	23.00	21.06	21.62
HSDPA Subtest-2	23.00	21.57	22.11
HSDPA Subtest-3	22.50	21.53	21.98
HSDPA Subtest-4	22.50	21.56	21.97
HSUPA Subtest-1	20.50	19.82	20.22
HSUPA Subtest-2	20.50	18.93	19.25
HSUPA Subtest-3	21.50	19.78	20.25
HSUPA Subtest-4	21.00	19.38	19.81
HSUPA Subtest-5	22.50	21.47	21.96


2.2. Peak to Average Ratio

2.2.1. Requirement

According to FCC 24.232(d) the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

2.2.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.

2.2.3. Test procedure

1. For GSM/EDGE operating mode:

- Set RBW=1MHz, VBW=3MHz, peak detector in spectrum analyzer.
- Set EUT in maximum output power, and triggered the burst signal.
- Measured respectively the peak level and mean level, and the deviation was recorded as Peak to Average ratio.

2. For UMTS operating mode:

- Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
- The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1%.






2.2.4. Test Result

The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

A. Test Verdict:

Band	Channel	Frequency (MHz)	Peak to Average ratio	Limit	Verdict
			dB	dB	
GSM850M Hz	128	824.2	0.019	13	PASS
	190	836.6	0.013		PASS
	251	848.8	0.021		PASS
GSM 1900MHz	512	1850.2	0.033		PASS
	661	1880.0	0.050		PASS
	810	1909.8	0.015		PASS
EDGE850 MHz	128	824.2	0.016		PASS
	190	836.6	0.018		PASS
	251	848.8	0.012		PASS
EDGE 1900MHz	512	1850.2	0.088		PASS
	661	1880.0	0.081		PASS
	810	1909.8	0.005		PASS

Band	Channel	Frequency (MHz)	Peak to Average ratio	Limit	Verdict
			dB	dB	
WCDMA Band V	4132	826.4	2.97	13	PASS
	4182	836.4	2.89		PASS
	4233	846.6	2.91		PASS
WCDMA Band II	9262	1852.4	2.94		PASS
	9400	1880.0	2.94		PASS
	9538	1907.6	2.73		PASS
WCDMA Band IV	1312	1712.4	2.98		PASS
	1413	1732.6	2.82		PASS
	1513	1752.6	2.97		PASS

**GSM 850MHz CH128 824.2MHz****GSM 850MHz CH190 836.6MHz****GSM 850MHz CH251 848.8MHz**



GSM 1900MHz CH512 1850.2MHz



GSM 1900MHz CH661 1880.0MHz





GSM 1900MHz CH810 1909.8MHz






EDGE 850MHz CH128 824.2MHz



EDGE 850MHz CH190 836.6MHz



EDGE 850MHz CH251 848.8MHz







EDGE 1900MHz CH512 1850.2MHz



EDGE 1900MHz CH661 1880.0MHz



EDGE 1900MHz CH810 1909.8MHz





WCDMA Band V CH4132 826.4MHz







WCDMA Band V CH4182 836.4MHz



WCDMA Band V CH4233 846.6MHz



**WCDMA Band II CH9262 1852.4MHz****WCDMA Band II CH9400 1880.0MHz****WCDMA Band II CH9538 1907.6MHz**

**WCDMA Band IV CH1312 1712.4MHz****WCDMA Band IV CH1413 1732.6MHz****WCDMA Band IV CH1513 1752.6MHz**


2.3.99% Occupied Bandwidth

2.3.1. Requirement

According to FCC section 2.1049, the occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission. Occupied bandwidth is also known as the 99% emission bandwidth.

2.3.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.



2.3.3. Test Result






The lowest, middle and highest channels are selected to perform testing to record the 99% occupied bandwidth.






GSM Test Verdict:

Band	Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26dB Bandwidth (kHz)
GSM 850MHz	128	824.2	243.68	317.4
	190	836.6	245.52	312.5
	251	848.8	244.32	321.0
GSM 1900MHz	512	1850.2	249.89	314.8
	661	1880.0	245.81	314.9
	810	1909.8	243.65	320.0
EDGE 850MHz	128	824.2	250.26	319.3
	190	836.6	241.71	309.2
	251	848.8	247.16	310.6
EDGE 1900MHz	512	1850.2	245.80	313.7
	661	1880.0	236.96	307.2
	810	1909.8	241.91	315.3

WCDMA Test Verdict:

Band	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)
WCDMA Band V	4132	826.4	4.182	4.692
	4182	836.4	4.165	4.686
	4233	846.6	4.144	4.665
WCDMA Band II	9262	1852.4	4.183	4.665
	9400	1880.0	4.144	4.672
	9538	1907.6	4.152	4.658
WCDMA Band IV	1312	1712.4	4.155	4.661
	1413	1732.6	4.175	4.686
	1513	1752.6	4.163	4.681

**GSM 850MHz CH128 824.2MHz****GSM 850MHz CH190 836.6MHz****GSM 850MHz CH251 848.8MHz****GSM 1900MHz CH512 1850.2MHz****GSM 1900MHz CH661 1880.0MHz****GSM 1900MHz CH810 1909.8MHz**

**EDGE 850MHz CH128 824.2MHz****EDGE 850MHz CH190 836.6MHz****EDGE 850MHz CH251 848.8MHz****EDGE 1900MHz CH512 1850.2MHz****EDGE 1900MHz CH661 1880.0MHz****EDGE 1900MHz CH810 1909.8MHz**