

1. RF Exposure Requirements

1.1 General Information

Client Information

Applicant: Xiamen Hanin Electronic Technology Co.,Ltd.
Address of applicant: Room 305A, Angye Building, Pioneering Park,Torch High- tech,Zone,
Xiamen,China

Manufacturer: Xiamen Hanin Electronic Technology Co.,Ltd.
Address of manufacturer: No.96, Rongyuan Road, Tong'an District, Xiamen, China

General Description of EUT:

Product Name: Portable Label Printer
Trade Name /
Model No.: HPL3D2303
Adding Model(s): HM-T300 Pro, HM-T300, HM-T3, HM-T310, HM-T320, HM-T330,
HM-T350, HM-T360, HM-T380, HM-T388, HM-T390, MK3, MK3 Pro,
iM-T3, iMOVE3pro, XT300, M33, MT31, BMT3, BMTU31, BMTU32,
BMTU33, BMTU34, BMTU35, BMTX31, BMTX32, BMTX33, BMTX34,
BMTX35, HM-T3 Pro, HM-T3P, HM-T3M Pro, HM-T3PM, T3 Pro, T3P,
T3M Pro, T3PM, HM-T300P, HM-T300M Pro, HM-T300PM, M300 Pro,
M300P, M300M Pro, M300PM, BMTU30 Pro, BMTU31Pro, BMTU32
Pro, BMTU33 Pro, BMTU34 Pro, BMTU35 Pro
Rated Voltage: DC7.4V
Battery Capacity: 1800mAh
SW-0018
Adapter Model 1: Input:AC100-240 50/60Hz 0.3A
Output:DC5V1.0A
TC331E-5100
Adapter Model 2: Input:AC100-240 50/60Hz 0.25A
Output:DC5V1.0A
FCC ID: 2AUTE-HPL3D2303
Equipment Type: Mobile device

Technical Characteristics of EUT:

Bluetooth (BLE mode)

Bluetooth Version: V5.0(BLE mode)
Frequency Range: 2402-2480MHz
RF Output Power: 2.92dBm (Conducted)
Data Rate: 1Mbps
Modulation: GFSK
Quantity of Channels: 40

Channel Separation:	2MHz
Type of Antenna:	PCB Antenna
Antenna Gain:	0.9dBi
Bluetooth (BR/EDR mode)	
Bluetooth Version:	V5.0(BR/EDR mode)
Frequency Range:	2402-2480MHz
RF Output Power:	3.31dBm (Conducted)
Data Rate:	1Mbps, 2Mbps, 3Mbps
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Quantity of Channels:	79
Channel Separation:	1MHz
Type of Antenna:	PCB Antenna
Antenna Gain:	0.9dBi

1.2 RF Exposure Exemption

According to §1.1307(b)(3) and KDB 447498 D04 Interim General RF Exposure Guidance v01, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

Option A: FCC Rule Part 1.1307 (b)(3)(i)(A): The available maximum time-averaged power is no more than 1mW, regardless of separation distance.

Option B: FCC Rule Part 1.1307 (b)(3)(i)(B): The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option C: FCC Rule Part 1.1307 (b)(3)(i)(C): The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$
1.34-30	$3,450 R^2/f^2$
30-300	$3.83 R^2$
300-1,500	$0.0128 R^2f$
1,500-100,000	$19.2R^2$

For Multiple RF sources: FCC Rule Part 1.1307(b)(3)(ii):

- (A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required).
- (B) In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

1.3 Calculated Result

Radio Access Technology	Prediction Frequency (MHz)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	Tune-Up Time-Averaged Power (dBm)	ERP (dBm)
Bluetooth	2402	3.31	0.9	100	4.00	2.75

Frequency (MHz)	Option	Min. Distance (cm)	Max. Power (dBm) (mW)		Exposure Limit (mW)	Ratio	Result Pass/Fail
2402	B	0.5	4.00	2.51	2.788	0.90	Pass

Note: 1. Time-Averaged Power=Output Power * Duty Cycle; ERP= Time-Averaged Power+ Antenna gain-2.15dB

2. Option A, B and C refers as clause 1.2.

3. For option B, Max (time-averaged power, effective radiated power (ERP)) converts to Max. Power. For option C, ERP converts to Max. Power;

4. For option B, P_{th} (mW) converts to Exposure Limit (mW); For option C, ERP (W) converts to Exposure

Limit (mW).

5. Ratio= Tune-Up ERP (mW)/ Exposure Limit (mW)

Mode for Simultaneous Multi-band Transmission:

Radio Access Technology	Ratio 1	Ratio 2	Simultaneous Ratio	Limit	Result
					Pass/Fail
--	--	--	--	--	--

Result: Pass