

FCC Test Report

Report No. : 1812C40177512501

Applicant : Beijing ManThink Technology Co., Ltd.

Address : Room 904, JingKai Building B DiSheng North
Road No.1, BDA, Beijing, China

Product Name : Out Door Gateway

Report Date : Jan. 14, 2025

Shenzhen Anbotek Compliance Laboratory Limited



Contents

1. General Information	6
1.1. Client Information.....	6
1.2. Description of Device (EUT).....	6
1.3. Auxiliary Equipment Used During Test.....	7
1.4. Description of Test Configuration	7
1.5. Description Of Test Setup	8
1.6. Test Equipment List.....	9
1.7. Measurement Uncertainty	10
1.8. Description of Test Facility	10
1.9.Disclaimer	11
2. Summary of Test Results	12
3. Conducted Emission Test.....	13
3.1. Test Standard and Limit.....	13
3.2. Test Setup.....	13
3.3. Test Procedure.....	13
3.4. Test Data.....	13
4. Radiation Spurious Emission and Band Edge.....	16
4.1. Test Standard and Limit.....	16
4.2. Test Setup.....	16
4.3. Test Procedure.....	17
4.4. Test Data.....	18
5. Maximum Peak Output Power Test.....	24
5.1. Test Standard and Limit.....	24
5.2. Test Setup.....	24
5.3. Test Procedure.....	24
5.4. Test Data.....	24
6. 6dB Emission Bandwidth Test	26
6.1. Test Standard and Limit.....	26
6.2. Test Setup.....	26
6.3. Test Procedure.....	26
6.4. Test Data.....	26
7. Power Spectral Density Test.....	28
7.1. Test Standard and Limit.....	28
7.2. Test Setup.....	28
7.3. Test Procedure.....	28
7.4. Test Data.....	28
8. 100kHz Bandwidth of Frequency Band Edge Requirement	30
8.1. Test Standard and Limit.....	30

8.2. Test Setup.....30

8.3. Test Procedure.....30

8.4. Test Data.....30

9. Antenna Requirement34

9.1. Test Standard and Requirement34

9.2. Antenna Connected Construction34

APPENDIX I -- TEST SETUP PHOTOGRAPH.....35

APPENDIX II -- EXTERNAL PHOTOGRAPH35

APPENDIX III -- INTERNAL PHOTOGRAPH35

TEST REPORT

Applicant : Beijing ManThink Technology Co., Ltd.
Manufacturer : Beijing ManThink Technology Co., Ltd.
Product Name : Out Door Gateway
Model No. : GDO31X
Trade Mark : ManThink
Rating(s) : Input: 48V=0.6A

Test Standard(s) : 47 CFR Part 15.247

Test Method(s) : ANSI C63.10: 2020, KDB 558074 D01 15.247 Meas Guidance v05r02

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the 47 CFR Part 15.247 requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt Dec. 12, 2024

Date of Test Dec. 12, 2024 to Jan. 06, 2025

Prepared By

Haidi Huang

(Haidi Huang)

Approved & Authorized Signer

Kingkong Jin

(Kingkong Jin)



Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Jan. 14, 2025

1. General Information

1.1. Client Information

Applicant	:	Beijing ManThink Technology Co., Ltd.
Address	:	Room 904, JingKai Building B DiSheng North Road No.1, BDA, Beijing, China
Manufacturer	:	Beijing ManThink Technology Co., Ltd.
Address	:	Room 904, JingKai Building B DiSheng North Road No.1, BDA, Beijing, China
Factory	:	Beijing ManThink Technology Co., Ltd.
Address	:	Room 904, JingKai Building B DiSheng North Road No.1, BDA, Beijing, China

1.2. Description of Device (EUT)

Product Name	:	Out Door Gateway
Model No.	:	GDO31X
Trade Mark	:	ManThink
Test Power Supply	:	DC 48V for POE
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
POE	:	Model: DS-2FA4803-POE/Y Input: 100-240V~, 50/60Hz,0.5A Output: 48V=0.32A
RF Specification		
Operation Frequency	:	915.2~916.8MHz
Number of Channel	:	9 Channels
Modulation Type	:	LoRa
Antenna Type	:	Cylindrical antenna
Antenna Gain(Peak)	:	6.09dBi
Remark: 1) All of the RF specification are provided by customer. 2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 3) This product belongs to the custom LoRa protocol.		

1.3. Auxiliary Equipment Used During Test

Title	Manufacturer	Model No.	Serial No.
/	/	/	/

1.4. Description of Test Configuration


Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	915.2	6	916.2
2	915.4	7	916.4
3	915.6	8	916.6
4	915.8	9	916.8
5	916	--	--

Note:


- 1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
- 2. EUT was tested with Channel 1, 4 and 9.

1.5. Description Of Test Setup

CE



RE



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Jan. 18, 2024	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT00 1	Jan. 17, 2024	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Jan. 17, 2024	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Jan. 23, 2024	1 Year
5.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Sept. 09, 2024	1 Year
6.	EMI Preamplifier	SKET Electronic	LNPA-0118G- 45	SKET-PA-002	Jan. 17, 2024	1 Year
7.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	345	Oct. 23, 2022	3 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Sept. 12, 2024	1 Year
10.	Horn Antenna	A-INFO	LB-180400-KF	J211060628	Jan. 22, 2024	3 Year
11.	Pre-amplifier	SONOMA	310N	186860	Jan. 17, 2024	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Sept. 09, 2024	1 Year
14.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Feb. 04, 2024	1 Year
15.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 10, 2024	1 Year
16.	DC Power Supply	IVYTECH	IV3605	1804D360510	Sept. 09, 2024	1 Year
17.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	Oct. 14, 2024	1 Year
18.	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102150	May. 06, 2024	1 Year



1.7. Measurement Uncertainty

Parameter	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	3.8dB
Occupied Bandwidth	925Hz
Conducted Output Power	0.76dB
Conducted Spurious Emission	1.24dB
Radiated spurious emissions (Below 30MHz)	3.53dB
Radiated spurious emissions (30MHz~1GHz)	Horizontal: 3.92dB; Vertical: 4.52dB
Radiated spurious emissions (above 1GHz)	1G-6GHz: 4.78dB; 6G-18GHz: 4.88dB 18G-40GHz: 5.68dB
The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 434132

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 434132.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.

1.9.Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.247(b)(3)	Conducted Peak Output Power	PASS
15.247(a)(2)	6dB Emission Bandwidth	PASS
15.247(e)	Power Spectral Density	PASS
15.247(d)	Band Edge	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		


3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.


3.4. Test Data

During the test, pre-scan all modes, only the worst case is recorded in the report.

Please to see the following pages.

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: 915.2MHz
Test Specification: DC 48V for POE
Comment: Live Line
Temp.(°C)/Hum.(%RH): 24.2°C/54%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	28.82	17.82	46.64	55.99	-9.35	AVG	
2	0.1980	34.13	17.82	51.95	63.69	-11.74	QP	
3	0.2020	25.82	17.82	43.64	53.52	-9.88	AVG	
4	0.3339	24.06	17.83	41.89	59.35	-17.46	QP	
5	0.5780	17.69	17.86	35.55	46.00	-10.45	AVG	
6	0.6100	27.87	17.87	45.74	56.00	-10.26	QP	
7	1.3099	24.18	17.86	42.04	56.00	-13.96	QP	
8	1.3860	13.79	17.86	31.65	46.00	-14.35	AVG	
9	1.6140	19.89	17.85	37.74	56.00	-18.26	QP	
10	1.7180	9.55	17.85	27.40	46.00	-18.60	AVG	
11	2.0500	16.77	17.85	34.62	56.00	-21.38	QP	
12	2.0579	7.42	17.85	25.27	46.00	-20.73	AVG	



Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: 915.2MHz
Test Specification: DC 48V for POE
Comment: Neutral Line
Temp.(°C)/Hum.(%RH): 24.2°C/54%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1539	33.50	17.83	51.33	65.78	-14.45	QP	
2	0.2020	22.15	17.82	39.97	53.52	-13.55	AVG	
3	0.2900	24.77	17.84	42.61	60.52	-17.91	QP	
4	0.4780	14.26	17.85	32.11	46.37	-14.26	AVG	
5	0.6060	23.54	17.87	41.41	56.00	-14.59	QP	
6	0.7780	13.48	17.87	31.35	46.00	-14.65	AVG	
7	0.9340	22.67	17.86	40.53	56.00	-15.47	QP	
8	1.2579	22.31	17.86	40.17	56.00	-15.83	QP	
9	1.3700	13.62	17.86	31.48	46.00	-14.52	AVG	
10	1.6260	19.87	17.85	37.72	56.00	-18.28	QP	
11	1.7060	9.28	17.85	27.13	46.00	-18.87	AVG	
12	2.0500	7.17	17.85	25.02	46.00	-20.98	AVG	

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz~1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz~30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:
(1)The lower limit shall apply at the transition frequency.
(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz,Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz,Set the spectrum analyzer as:

RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW =1MHz, VBW =10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all the modes, only the worst case is recorded in the report.

Test Results (30~1000MHz)

Test Mode:

915.2MHz

Power Source:

DC 48V for POE


Polarization:

Horizontal

Temp.(°C)/Hum.(%RH):

25.3°C/54%RH

Fundamental



Test Results (30~1000MHz)

Test Mode:

915.2MHz

Power Source:

DC 48V for POE


Polarization:

Vertical

Temp.(°C)/Hum.(%RH):

25.3°C/54%RH

Fundamental



Test Results (1GHz-25GHz)

Test channel: Lowest						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1830.40	31.65	17.67	49.32	74.00	-24.68	Vertical
2745.60	31.16	20.94	52.10	74.00	-21.90	Vertical
3660.80	33.11	22.51	55.62	74.00	-18.38	Vertical
4576.00	*			74.00		Vertical
5491.20	*			74.00		Vertical
1830.40	31.04	17.67	48.71	74.00	-25.29	Horizontal
2745.60	32.87	20.94	53.81	74.00	-20.19	Horizontal
3660.80	29.48	22.51	51.99	74.00	-22.01	Horizontal
4576.00	*			74.00		Horizontal
5491.20	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
1830.40	19.92	17.67	37.59	54.00	-16.41	Vertical
2745.60	20.21	20.94	41.15	54.00	-12.85	Vertical
3660.80	22.58	22.51	45.09	54.00	-8.91	Vertical
4576.00	*			54.00		Vertical
5491.20	*			54.00		Vertical
1830.40	19.37	17.67	37.04	54.00	-16.96	Horizontal
2745.60	21.90	20.94	42.84	54.00	-11.16	Horizontal
3660.80	18.99	22.51	41.50	54.00	-12.50	Horizontal
4576.00	*			54.00		Horizontal
5491.20	*			54.00		Horizontal

Test Results (1GHz-25GHz)

Test channel: Middle						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1831.60	31.20	17.70	48.90	74.00	-25.10	Vertical
2747.40	31.13	20.97	52.10	74.00	-21.90	Vertical
3663.20	32.61	22.51	55.12	74.00	-18.88	Vertical
4579.00	*			74.00		Vertical
5494.80	*			74.00		Vertical
1831.60	30.85	17.70	48.55	74.00	-25.45	Horizontal
2747.40	32.74	20.97	53.71	74.00	-20.29	Horizontal
3663.20	29.20	22.51	51.71	74.00	-22.29	Horizontal
4579.00	*			74.00		Horizontal
5494.80	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	
1831.60	20.01	17.70	37.71	54.00	-16.29	polarization
2747.40	20.07	20.97	41.04	54.00	-12.96	Vertical
3663.20	22.43	22.51	44.94	54.00	-9.06	Vertical
4579.00	*			54.00		Vertical
5494.80	*			54.00		Vertical
1831.60	19.48	17.70	37.18	54.00	-16.82	Vertical
2747.40	22.25	20.97	43.22	54.00	-10.78	Horizontal
3663.20	19.29	22.51	41.80	54.00	-12.20	Horizontal
4579.00	*			54.00		Horizontal
5494.80	*			54.00		Horizontal

Test Results (1GHz-25GHz)

Test channel: Highest						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1833.60	31.33	17.74	49.07	74.00	-24.93	Vertical
2750.40	31.29	20.99	52.28	74.00	-21.72	Vertical
3667.20	33.31	22.51	55.82	74.00	-18.18	Vertical
4584.00	*			74.00		Vertical
5500.80	*			74.00		Vertical
1833.60	30.99	17.74	48.73	74.00	-25.27	Horizontal
2750.40	32.95	20.99	53.94	74.00	-20.06	Horizontal
3667.20	29.58	22.51	52.09	74.00	-21.91	Horizontal
4584.00	*			74.00		Horizontal
5500.80	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
1833.60	21.13	17.74	38.87	54.00	-15.13	Vertical
2750.40	21.34	20.99	42.33	54.00	-11.67	Vertical
3667.20	23.08	22.51	45.59	54.00	-8.41	Vertical
4584.00				54.00		Vertical
5500.80				54.00		Vertical
1833.60	20.66	17.74	38.40	54.00	-15.60	Horizontal
2750.40	23.05	20.99	44.04	54.00	-9.96	Horizontal
3667.20	19.44	22.51	41.95	54.00	-12.05	Horizontal
4584.00	*			54.00		Horizontal
5500.80	*			54.00		Horizontal

Remark:

1.Result =Reading + Factor


2. Test frequency are from 1GHz to 25GHz, "*"means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

5. Maximum Peak Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(3)
Test Limit	1W (30dBm) if $GT_x > 6\text{dBi}$, then $P_{out} = 30 - (GT_x - 6)$

5.2. Test Setup



5.3. Test Procedure

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.


1. Set the RBW $\geq$ DTS bandwidth.
2. Set the VBW $\geq 3 \times$ RBW.
3. Set the span $\geq 3 \times$ RBW.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.

5.4. Test Data


Temperature:	25.3 °C	Humidity:	48 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

Test Channel	Peak Power output (dBm)	Limit (dBm)	Results
Low	23.217	29.91	PASS
Middle	23.148	29.91	PASS
High	23.240	29.91	PASS

Limit(dBm)=30-(Directional gain-6.00).



Low Channel



Mid Channel




High Channel

6. 6dB Emission Bandwidth Test

6.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(2)
Test Limit	>500kHz

6.2. Test Setup



6.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
6dB Bandwidth:
 - a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
 - b) Set the VBW $\geq [3 \times \text{RBW}]$.
 - c) Detector = peak.
 - d) Trace mode = max-hold.
 - e) Sweep = No faster than coupled (auto) time.
 - f) Allow the trace to stabilize.
 - g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.


99% Occupied Bandwidth:

RBW=1~5% OBW, VBW=3*RBW, Sweep Time= Auto, Detector= Peak, Trace= Max hold

6.4. Test Data


Temperature:	25.3 °C	Humidity:	48 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

Channel	Bandwidth (kHz)	Limit (kHz)	Results
Low	690.3	>500	PASS
Middle	627.3	>500	PASS
High	676.1	>500	PASS



Low Channel

Mid Channel




High Channel

7. Power Spectral Density Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (e)
Test Limit	8dBm/3KHz if GTx>6dBi, then Pout=8-(GTx-6)

7.2. Test Setup



7.3. Test Procedure


1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 1.5xDTS BW
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

7.4. Test Data


Temperature:	25.3 °C	Humidity:	48 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

Channel	PSD (dBm/3KHz)	Limit (dBm/3KHz)	Results
Low	5.397	7.91	PASS
Middle	5.332	7.91	PASS
High	5.635	7.91	PASS


Limit(dBm/3KHz)=8-(Directional gain-6.00).



Low Channel



Mid Channel




High Channel

8. 100kHz Bandwidth of Frequency Band Edge Requirement

8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in15.209(a).

8.2. Test Setup



8.3. Test Procedure


Using the following spectrum analyzer setting:

1. Set the RBW = 100KHz.
2. Set the VBW = 300KHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.

8.4. Test Data


Temperature:	25.3 °C	Humidity:	48 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

Band edge measurements








Conducted Emission Method

Low Channel





Mid Channel



Conducted Emission Method

High Channel



9. Antenna Requirement

9.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

9.2. Antenna Connected Construction

The antenna is a Cylindrical antenna which permanently attached, and the best case gain of the antenna is 6.09dBi. It complies with the standard requirement.

APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph_RF

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----