The N-Mark is a trademark or registered trademark of NFC Forum, Inc. in the United States and in other countries.



HiRes
This product is conformed to High-Resolution Audio standard defined by Japan Audio Society.
The High-Resolution Audio logo is used under license from Japan Audio Society.

Headphone supplied as accessary of this product is not complied with "Hi-Res Audio Logo" Standard. To experience Hi-Res, you need to purchase an OPPO Hi-Res headset accessory or other Hi-Res headsets. Some content may differ from your device depending on the region, service provider, or software version, and is subject to change without prior notice.







# oppo







2. If you have an old Phone, open Clone Phone on the new phone directly, and follow on-screen instructions to sign in to iCloud account and sync the files. Standard accessories
You are provided with the following standard accessories:
1 Phone, 1 Charger, 1 Earphone, 1 USB data calls, 1 Safety Guide,
1 Durk Guide, 1 SM black Tool. 1 Pretchive Care.

Battery		4890mAh/18.89Wh(Win) 5000mAh/19.35Wh(Typ)	
		48Megapixels+8Megapixels +2Megapixels+2Megapixels 8 16Megapixels Front	
Operating temperature		0°C-35°C	
		0.947W@critiondt	

		16Megapixels Front
ating temp	erature	onc-asino
	CE SAR	0.847W/kg(Head) 0.976W/kg(Body)
Values	RCM SAR	1.432W/kg(Head) 1.093W/kg(Body)

	Radio Waves Specification	1
Radio	Frequency	Max. Output Power
GSM.	850MHz	33±1dBm
GSM	1900MHz	30::1d8m
WCDMA	Bands 2/5	22±1d8m
WCDMA	Band 4	24x1dBm
LTEFDD	Bands 2/4/5/7/26	24±1d8m
LTETOD	Bands 38/41	24±1dBm
Bluetooth	2.4-2.4835GHz	10±2d8m(ERP)
2.4G Wi-Fi	2.4-2.4835GHz	15±1.5dBm(EIRP)
5G Wi-Fi	5.15-5.35GHz; 5.47-5.725GHz	15±1.5d8m(EIRP)
	5.725-5.85GHz	12±1.5d8m(EIRP)



Lors du charpement, placez l'appareil dans un environnement avec une
température ambiante et une bonne ventilation. Il est recommandé de mettre
l'appareil en charge dans un environnement dont la température varie entre 5°



nie entre 5°C	Modifie
infoncis	

Taille de l'écran principal		16,5cm(6,5 pouces)
Dimensions		163,6×75,6×9,1 (mm)
Batterie		4880mAh/18,88Wh(Min) 5000mAh/19,35Wh(Typ)
Appared photo		48-mégapisek+8-mégapisek +2-mégapisek+2-mégapisek 16-mégapisek avant
Température de fonctionnement		0°C-15°C
Valeurs DAS	CE SAR	0.847W/kg (Tase)

	Spécifications concernant les on	des radio
Radio	Fréquence	Puissance de sortie max
GSM	850MHz	33±1d8m
G.MI	1900MHz	30±1dBm
WCDMA	Bands 2/5	22±1dBm
WCDMA	Band 4	24±1dBm
LTE FDD	Bands 2/4/5/7/26	24±1dBm
LTE TOD	Bands 38/41	24:1dBm
Bluetooth	2,4-2,4835GHz	10±2d8m(ERP)
2,4G Wi-Fi	2,4-2,4835GHz	15±1,5d8m(EIRP)
SCWLE	5,15-5,35GHz; 5,47-5,725GHz	15±1,5d8m(EIRP)
SG WI-FI	5,725-5,85GHz	12±1,5d8m(EIRP)
NEC	11 54864	- 473/8-1 (m. 010m)



- No coloque el talafonso o la batería cerca o dentro de equipos el abstrodomísticos prierosendas, cocinas de cualquier topo, hom tipo o calefaciones esci, menja de eccino jol se a penaño esci, batería se sobrecaleme y/o provoque daños en su dispositivo.
   Debe utilizar el cargador, coble y batería originales. Los cangado que no cueránn con la autoriación y/a certificación del fatería.

Al cargar el dispositiva, colóque lo en un entorno que tenga una temperatura ambiente y verel lación normales. El recomendable que el dispositivo sea cargado en un entorno con una temperatura que osole entre 5 °C y 35 °C.

Cómo forzar el reinicio del teléfono
Mentenga presionados los botones de Encendido y Vol. (+) hasta que aparecca la animación de inicio de OPPO para forzar el renicio del tel·Hono.



2. Si tiene un iPhone antigua, abra "Conor Telfora" disectamente en el nuevo delfono y sigal los instrucciones que aparecen en panta la para iniciar sesión en la cuenta de cl'oud y sincreniar los archivos.

Ispecificaciones técr	
-----------------------	--

Producto		CPH1941
Tamaño de la pantalla		16,5cm/6,5 Pulgadas)
Dimensiones		163,6×75,6×9,1 mm)
Bateria		4880mAh/18,88Wh(Min) 5000mAh/19,35Wh(Typ)
Cimara		Cuádrupte cámara trasera de 48 Mpx + 8 Mpx + 2 Mpx + 2 Mpx. Cámara delantera de 16 Mpx
Temperatura para el correcto funcionamiento		0°C-35°C
	CE SAR	0,847W/kg/(Cabeza) 0,976W/kg/(Cuerpo)
Valores CAD		

	Especificaciones de ondas de	radio
Radio	Frecuencia	Potencia máx, de salida
GSM	850MHz	33±1d8m
usw	1900MHz	30±1d8m
WCDMA	Bands 2/5	22±1d8m
WCDMA	Band 4	24±1dBm
LTE FDD	Bands 2/4/5/7/26	24±1dBm
LTE TDD	Bands 38/41	24±1dBm
Bluetooth	2,4-2,4835GHz	10±2d8m(ERP)
2,4G Wi-Fi	2,4-2,4835GHz	15±1,5d8m(EIRP)
56 W.E	5,15-5,35GHz; 5,47-5,725GHz	15±1,5d8m(EIRP)
SG WI-FI	5,725-5,85GHz	12±1,5d8m(ERP)
NFC	13,56MHz	s42d8uA/m @10m



Solben Sie ein altes Phone haben, offnen Sie Clone Phone direkt auf dire

Standard-Zubehör:

# 



- verhindern.

  Es sind das Original Ladegerät, das Original Detenkabel und der Original Aldau zu verwenden. Die Verwendung von nicht genehmigten und vom Henteller nicht.



Questa guida filanta l'utilizzo del tuo smartphone QPPO e le sue funzioni principali, la abtenutiva, è possibile visitare il sito utiliciale di QPPO per avere maggiori informazioni sul telefono.

 Judi twój stary telefon to Phone, otwórz aplikację CPPO Clone Phone na nowym telefonie i postępuj zgodnie z instrukcjami na ekranie, aby zalkomo Kloud i zgynchronizować galiki. Standardowe akcesoria

Dostanczene są rustępujące standardose akcesoria:
1 odęłen, 1 lodosorka, 1 zestaw sluchuwkowy, 1 kabel USB, 1 instrukcja bespie1 sluktora inspulska. 1 marzędzie do wyczgania karty SIM, 1 futeral ochrony.

ambients con una temperatus composito 1972 e 1972. Come interviste al fluorimentario locale discussione e del entire fina quantitate entire such assistante entire such assistante entire such assistante entire such assistante entire entire such assistante entire entre entr

nttps://i.clonephone.coloos.com/download

2. So il veccho talefono è un Phone, apries Clora Telefono direttamente sul nuovo
telefono e seguire la istruzioni sul display per accedere all'account X-load e
sinconizzare. Accessori standard

Vengono forniti i seguenti accessori standanti 1 telefono, 1 caricabatterie, 1 auricalare, 1 cavo USB, 1 strumento di esolubione SM, 1 quida di sicurezza, 1 quida narida, 1 custodia protettina

Product		CPH1941
Hoofdschermafmetingen		16,5cm(6,5°)
Afmetingen		163,6×75,6×9,1(mm)
Accu		4880mAh/18,88Wh(Min) 5000mAh/19,35Wh(Typ)
Camera		48 Megapisel + 8 Megapisel + 2 Megapi + 2 Megapisel Achtercamera 16 Megapisel Voorcamera
Gebruikstemperatuur		01C-35°C
Specifieke absorptionnelfoold (SAII)	CE SAR	0,847W/kg(Head) 0,976W/kg(Body)

Specificaties radiogolven		
Radio	Frequentie	Max. uitgangsvermogen
OSM	850MHz	33±1dBm
CLINI.	1900MHz	30±1dBm
WCDMA	Bands 2/5	22±1dBm
WCDMA	Band 4	24±1dBm
LTE FDD	Bands 2/4/5/7/26	24±1dBm
LTE TDD	Bands 38/41	24±1dBm
Bluetooth	2,4-2,4835GHz	10±2dBm(ERP)
2,4GWi-Fi	2,4-2,4835GHz	15±1,5dBm(EIRP)
SGWLEI	5,15-5,35GHz; 5,47-5,725GHz	15±1,5d8m(EIRP)
July HI-TI	5,725-5,85GHz	12±1,5d8m(EIRP)
NFC	13,56MHz	s42d8uA/m @10m

Produkt		CPH1941	
Bildschirmparameter		16,5cm (6,5 20 <b>8</b> )	
Abmessungen		163,6×75,6×9,1(mm)	
Batterie		4830mAh/18,88Wh(Win) 5000mAh/19,35Wh(Typ)	
Kamera		48-Megapisel+8-Megapisel +2-Megapisel+2-Megapixel 16-Megapisel Front	
V beitstemperatur		0°C-35°C	
SAR-Werte	CE SAR	0,817W/kg (Kopf) 0,976W/kg (Körper)	

funkwellenspezifikationen			
Radio	Frequenz	Max. Ausgangsleistung	
GSM	850MHz	33:1dBm	
GSM	1900MHz	30±1dBm	
WCDMA	Bands 2/5	22±1dBm	
WCDMA	Band 4	24±1dBm	
LTE FDD	Bands 2/4/5/7/26	24±1dBm	
LTE TDD	Bands 38/41	24±1dBm	
Bluetooth	2,4-2,4835GHz	10±2d8m(ERP)	
2,4GWi-Fi	2,4-2,4835GHz	15±1,5d8m(EIRP)	
5G W-Fi	5,15-5,35GHz; 5,47-5,725GHz	15±1,5d8m(EIRP)	
	5,725-5,85GHz	12±1,5d8m(EIRP)	
NFC	13,56MHz	s42d8uA/m @10m	

CPH1941	
16,5cm(6,5°)	
163,6×75,6×9,1(mm)	
4890mAh/18.89Wh(Min) 5000mAh/19.35Wh(Typ)	
48 megapikseli +8 megapikseli +2 megapikseli +2 megapikseli z tylu 16 megapikseli z przodu	
0.038.0	
(HI)	

	Specyfikacje dotyczące fal radiowych			
	Radio	Częstotliwość	Maks. moc wyjściowa	
	OSM	850MHz	33±1dBm	
	LOM	1900MHz	30±1dBm	
	WCDMA	Bands 2/5	22±1dBm	
	WCDMA	Band 4	24±1dBm	
	LTE FDD	Bands 2/4/5/7/26	24±1dBm	
	LTETOD	Bands 38/41	24±1dBm	
	Bluetooth	2,4-2,4835GHz	10±2dBm(ERP)	
	2,4GWi-Fi	2,4-2,4835GHz	15±1,5d8m(EIRP)	
	5G WLEI	5,15-5,35GHz; 5,47-5,725GHz	15±1,5d8m(EIRP)	
ı	SU WI-FI	5,725-5,85GHz	12±1,5d8m(EIRP)	
	NFC	13,56MHz	s42d8uA/m @10m	

Modello		CPH1941	
Parametri Schermo		16,5cm/6,5 poll(ci)	
Dimensioni		163,6×75,6×9,1(mm)	
Batteria		4880mAh/18,88Wh(Min) 5000mAh/19,35Wh(Typ)	
Camera		48 megapisel + 8 megapisel +2 megapisel +2 megapisel di fotocamera anteriore 16 megapisel di fotocamera posteriore	
Temperatur a di utilizzo		0.032.0	
Valori SAR	CE SAR	0,847W/kg (besta) 0,976W/kg (corpo)	

Radio	Frequenza	Potenza uscita max	
OSM	850MHz	33±1dBm	
LOM	1900MHz	30±1dBm	
WCDMA	Bands 2/5	22±1dBm	
WCDMA	Band 4	24±1dBm	
LTE FDD	Bands 2/4/5/7/26 24±1dBm		
LTETDD	Bands 38/41	24±1dBm	
Sturtooth	2,4-2,4835GHz	10±2dBm(EIRP)	
2,4GWi-Fi	2,4-2,4835GHz 15±1,5d8m(EI		
5G Wi-Fi	5,15-5,35GHz; 5,47-5,725GHz	15±1,5d8m(EIRP)	
	5,725-5,85GHz	12±1,5d8m(EIRP)	
1150			

User information (User Monarcion (User Motern) (User Monarcion (Us	Consol and the billetary of connect it with a high violaging power study).  A thirthey on the changed and distribution-banded of tens at last kild.  It will be consult the change of the distribution-banded of tens at last kild.  It will be consultable that the change of the distribution of the last proceeding of the change	Characterist Through Characterist (Characterist (Character	Disampticated by for an appear in other stock, then, or Pequalities an insightening.  It hough be about the control of the product.  It hough be active of the product product of the product.  It hough be active of the product product of the	This sear remail provides the product sidely information.  Before using the person place and the side of sidely and sign.  GPP during this meaning with meaning the side of sidely and sidely s
LEMENTOCI C  LEMEN	Increased, then it no planarises that interferency will not count in a particular involvable, about a not planarises that interferency will not count in a particular whichis in collipsion, which can be compared by a survey the explaned of any of the particular of a compared by the count of the collection of the count of the collection of the count of the collection of t	Based to considerate an amount of the control of th	It considerates for size that as a benefit for tipule and collection II.  When completely the Opportunation from the consormal and is wall differentiated on the source and part and of the own address.  Documentary and control of the own address own address of the own address of the own address own address of the own address of the own address	Exhibitions Medical part has invisit held medical this invision incident by invision incidents of the models proof a front sould incident of the models proof a front sould incident of the models proof a front in the model. The district of the models of the models. The district of the models of t

5211346 V0.1

Safety Guide

	On a marker of extension  - Address with treasulational the equipment and shall be easily accessible.  I are year of the product is not of anyong discontinuous mendality and conscit the extension of a conscit to a story of a conscit to a c	Afterwards in skills determined in the inhighest confided power bank the case will delibe the financiarian level and skill best deliberation and the proceedings of the confidence of the confid	oddo
	Want Backed and Backened Regional WIEI  This world man that consider popularity and product makes in the product make the product makes the product make the product makes	However, learning all compatibility articing devel guarantees that interference to per Area vig. and its earth happen file and the period and period to the compatibility of the compatibility and the	<del>a</del> o