

Protocol Reversion Number: 6

Max Conducted Output PWR of various operation modes of FCS-8010

Radio Configuration	Service Option		Conducted Output Power(dBm)		
			Low Channel(25) 1851.25MHz	Mid Channel(600) 1880.00MHz	High Channel(1175) 1908.75MHz
F1R1	SO2(Loopback)		23.6	23.5	23.4
F2R2	SO9(Loopback)		23.6	23.4	23.4
F3R3	SO55 (Loopback)	9.6 Kbps	23.5	23.4	23.3
		19.2 Kbps	23.6	23.5	23.3
		38.4 Kbps	23.6	23.5	23.3
		76.8 Kbps	23.6	23.5	23.4
		153.6 Kbps	23.6	23.5	23.4
F4R3	SO55 (Loopback)	9.6 Kbps	23.6	23.5	23.5
		19.2 Kbps	23.5	23.5	23.4
		38.4 Kbps	23.6	23.4	23.4
		76.8 Kbps	23.5	23.4	23.4
		153.6 Kbps	23.6	23.5	23.5
F5R4	SO55 (Loopback)	14.4 Kbps	23.5	23.5	23.5
		28.8 Kbps	23.5	23.4	23.5
		57.6 Kbps	23.6	23.4	23.5
		115.2 Kbps	23.6	23.5	23.5
		230.4 Kbps	23.6	23.5	23.5
TEST MODE			23.7	23.6	23.6