

Test report No:
3184ERM.003A1

Assessment report RF EXPOSURE REPORT ACCORDING TO FCC 47 CFR Part 2.1093

| | |
|---|---|
| (*) Identification of item under evaluation | Sense Line Assembly (SLA) |
| (*) Trademark | Visteon |
| (*) Model and /or type reference | SLA8 |
| (*) Other identification of the product | FCC ID: NT8-SLA8 |
| (*) Features | Cell Monitoring Unit in Wireless Battery Management |
| (*) Manufacturer | Visteon Corporation One Village Center Drive, Van Buren Township, MI 48111, USA. |
| Test method requested, standard | FCC 47 CFR Part 2.1093. Radiofrequency radiation exposure evaluation: portable devices |
| Summary | IN COMPLIANCE |
| Approved by (name / position & signature) | Domingo Galvez EMC&RF Lab Manager |
| Date of issue | 11-17-2021 |
| Report template No | FAN24_02 (*) "Data provided by the client" |

Index

Competences and guarantees3

General conditions3

Data provided by the client.....3

Identification of the client.....3

Document history4

Modifications to the reference test report4

Appendix A: FCC RF Exposure assessment result5

General description of the device under evaluation.....6

Assessment summary.....6

Evaluation Results6

Appendix B: FCC RF Exposure information7

FCC SAR test exclusion considerations for portable devices8

Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA Certification Inc. has a calibration and maintenance program for its measurement equipment.

DEKRA Certification Inc. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Certification Inc. at the time of performance of the test.

DEKRA Certification Inc. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Certification Inc.

General conditions

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Certification Inc.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Certification Inc. and the Accreditation Bodies

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested", "General description of the device").
2. Maximum antenna gain and measurement distance information.

DEKRA Certification Inc. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Identification of the client

Visteon Corporation

One Village Center Drive, Van Buren Township, MI 48111, USA.

Document history

| Report number | Date | Description |
|---------------|------------|----------------|
| 3184ERM.003 | 11-11-2021 | First release |
| 3184ERM.003A1 | 11-17-2021 | Second release |

Modifications to the reference test report

It was introduced the following modification in respect to the test report number 3184ERM.003 related with the same samples:

| Clauses/ Sub-Clauses | Modification | Justification |
|--|-------------------------------|---------------|
| Page 6: General description of the device under evaluation / Table 1 | Changed low frequency to 2405 | Typo error |
| Page 6: Assessment summary / Table 2 | Changed low frequency to 2405 | Typo error |
| Page 6: Evaluation Results / Table 3 | Changed low frequency to 2405 | Typo error |

This modification test report cancels and replaces the test report 3184ERM.003.

Appendix A: FCC RF Exposure assessment result

General description of the device under evaluation

The device under evaluation consists of a Cell Monitoring Unit in Wireless Battery Management device.

According to the manufacturer, during its normal use, the separation distance between the radiating structures of the device and nearby users will be greater than distance 5 cm. In order to perform the assessment a conservative evaluation distance of minimum compliance distance (5.67 cm) has been used.

As stated into DEKRA Certification Inc. test report num. 3184ERM.007A1, the maximum measured output power levels for each supported technology are:

| Technology / Mode | Band | Frequency (MHz) | Maximum E.I.R.P. (dBm) | Maximum E.I.R.P. (mW) |
|----------------------|---------|-----------------|------------------------|-----------------------|
| Proprietary Protocol | 2.4 GHz | 2405 - 2480 | 10.20 | 10.47 |

Table 1: Equipment specifications

Assessment summary

The assessment summary according to the radiofrequency radiation exposure limits defined in FCC 47 CFR § 2.1093 is the following:

| Technology / Mode | Band | Frequency (MHz) | Verdict |
|----------------------|---------|-----------------|---------|
| Proprietary Protocol | 2.4 GHz | 2405 - 2480 | Pass |

Table 2: Assessment summary

Evaluation Results

The evaluation according to the minimum intended use distance of 60 mm will be as follow:

| Technology / Mode | Band | Frequency (MHz) | Distance (cm) | Max Output Power (mW) | Limit 1-g SAR (mW) | SAR Test Exclusion |
|----------------------|---------|-----------------|---------------|-----------------------|--------------------|--------------------|
| Proprietary Protocol | 2.4 GHz | 2405 - 2480 | 5.67 | 10.47 | 196 | Pass |

Table 3: FCC Evaluation Result

The computed value(s) are below the limit(s), so according to KDB 447498 D01 – General RF Exposure Guidance, these modes qualify for Standalone SAR test exclusion for 1-g SAR and 10-g Extremity SAR.

Appendix B: FCC RF Exposure information

FCC SAR test exclusion considerations for portable devices

For transmission frequencies below 6GHz, as stated by the FCC (47 CFR §2.1093), human exposure to RF emissions from portable devices, which are defined as transmitting devices to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user, must be evaluated with respect to the FCC-adopted limits for SAR.

According to FCC OET KDB 447498 D01 General RF Exposure Guidance:

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition is satisfied.

- For distances ≤ 50 mm

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

Where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table:

| MHz | 5 | 10 | 15 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | mm |
|------|----|----|-----|-----|-----|-----|-----|-----|-----|-----|--|
| 150 | 39 | 77 | 116 | 155 | 194 | 232 | 271 | 310 | 349 | 387 | SAR Test Exclusion Threshold (mW) |
| 300 | 27 | 55 | 82 | 110 | 137 | 164 | 192 | 219 | 246 | 274 | |
| 450 | 22 | 45 | 67 | 89 | 112 | 134 | 157 | 179 | 201 | 224 | |
| 835 | 16 | 33 | 49 | 66 | 82 | 98 | 115 | 131 | 148 | 164 | |
| 900 | 16 | 32 | 47 | 63 | 79 | 95 | 111 | 126 | 142 | 158 | |
| 1500 | 12 | 24 | 37 | 49 | 61 | 73 | 86 | 98 | 110 | 122 | |
| 1900 | 11 | 22 | 33 | 44 | 54 | 65 | 76 | 87 | 98 | 109 | |
| 2450 | 10 | 19 | 29 | 38 | 48 | 57 | 67 | 77 | 86 | 96 | |
| 3600 | 8 | 16 | 24 | 32 | 40 | 47 | 55 | 63 | 71 | 79 | |
| 5200 | 7 | 13 | 20 | 26 | 33 | 39 | 46 | 53 | 59 | 66 | |
| 5400 | 6 | 13 | 19 | 26 | 32 | 39 | 45 | 52 | 58 | 65 | |
| 5800 | 6 | 12 | 19 | 25 | 31 | 37 | 44 | 50 | 56 | 62 | |

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

- For distances > 50 mm

For 100 MHz to 6 GHz frequencies and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following:

1) [Power allowed at numeric threshold for 50 mm in table 1) + (test separation distance - 50 mm)·(f(MHz)/150)] mW, at 100 MHz to 1500 MHz

2) [Power allowed at numeric threshold for 50 mm in table 1) + (test separation distance - 50 mm)·10] mW, at > 1500 MHz and ≤ 6 GHz

Approximate SAR test exclusion power thresholds at selected frequencies and test separation distances are illustrated in the following table

| MHz | 50 | 60 | 70 | 80 | 90 | 100 | 110 | 120 | 130 | 140 | 150 | 160 | 170 | 180 | 190 | mm |
|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|-----------------------------------|
| 100 | 474 | 481 | 487 | 494 | 501 | 507 | 514 | 521 | 527 | 534 | 541 | 547 | 554 | 561 | 567 | SAR Test Exclusion Threshold (mW) |
| 150 | 387 | 397 | 407 | 417 | 427 | 437 | 447 | 457 | 467 | 477 | 487 | 497 | 507 | 517 | 527 | |
| 300 | 274 | 294 | 314 | 334 | 354 | 374 | 394 | 414 | 434 | 454 | 474 | 494 | 514 | 534 | 554 | |
| 450 | 224 | 254 | 284 | 314 | 344 | 374 | 404 | 434 | 464 | 494 | 524 | 554 | 584 | 614 | 644 | |
| 835 | 164 | 220 | 275 | 331 | 387 | 442 | 498 | 554 | 609 | 665 | 721 | 776 | 832 | 888 | 943 | |
| 900 | 158 | 218 | 278 | 338 | 398 | 458 | 518 | 578 | 638 | 698 | 758 | 818 | 878 | 938 | 998 | |
| 1500 | 122 | 222 | 322 | 422 | 522 | 622 | 722 | 822 | 922 | 1022 | 1122 | 1222 | 1322 | 1422 | 1522 | |
| 1900 | 109 | 209 | 309 | 409 | 509 | 609 | 709 | 809 | 909 | 1009 | 1109 | 1209 | 1309 | 1409 | 1509 | |
| 2450 | 96 | 196 | 296 | 396 | 496 | 596 | 696 | 796 | 896 | 996 | 1096 | 1196 | 1296 | 1396 | 1496 | |
| 3600 | 79 | 179 | 279 | 379 | 479 | 579 | 679 | 779 | 879 | 979 | 1079 | 1179 | 1279 | 1379 | 1479 | |
| 5200 | 66 | 166 | 266 | 366 | 466 | 566 | 666 | 766 | 866 | 966 | 1066 | 1166 | 1266 | 1366 | 1466 | |
| 5400 | 65 | 165 | 265 | 365 | 465 | 565 | 665 | 765 | 865 | 965 | 1065 | 1165 | 1265 | 1365 | 1465 | |
| 5800 | 62 | 162 | 262 | 362 | 462 | 562 | 662 | 762 | 862 | 962 | 1062 | 1162 | 1262 | 1362 | 1462 | |

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and > 50 mm

- For frequencies below 100 MHz

The following may be considered for SAR test exclusion:

1) For test separation distances > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by [1 + log(100/f(MHz))]

2) For test separation distances ≤ 50 mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by ½

Approximate SAR test exclusion power thresholds at selected frequencies and test separation distances are illustrated in the following table

| MHz | < 50 | 50 | 60 | 70 | 80 | 90 | 100 | 110 | 120 | 130 | 140 | 150 | 160 | 170 | 180 | 190 | mm |
|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|----|
| 100 | 237 | 474 | 481 | 487 | 494 | 501 | 507 | 514 | 521 | 527 | 534 | 541 | 547 | 554 | 561 | 567 | mW |
| 50 | 308 | 617 | 625 | 634 | 643 | 651 | 660 | 669 | 677 | 686 | 695 | 703 | 712 | 721 | 729 | 738 | |
| 10 | 474 | 948 | 961 | 975 | 988 | 1001 | 1015 | 1028 | 1041 | 1055 | 1068 | 1081 | 1095 | 1108 | 1121 | 1135 | |
| 1 | 711 | 1422 | 1442 | 1462 | 1482 | 1502 | 1522 | 1542 | 1562 | 1582 | 1602 | 1622 | 1642 | 1662 | 1682 | 1702 | |
| 0.1 | 948 | 1896 | 1923 | 1949 | 1976 | 2003 | 2029 | 2056 | 2083 | 2109 | 2136 | 2163 | 2189 | 2216 | 2243 | 2269 | |
| 0.05 | 1019 | 2039 | 2067 | 2096 | 2125 | 2153 | 2182 | 2211 | 2239 | 2268 | 2297 | 2325 | 2354 | 2383 | 2411 | 2440 | |
| 0.01 | 1185 | 2370 | 2403 | 2437 | 2470 | 2503 | 2537 | 2570 | 2603 | 2637 | 2670 | 2703 | 2737 | 2770 | 2803 | 2837 | |

SAR Test Exclusion Thresholds for frequencies < 100 MHz