



RF Exposure Evaluation Declaration

FCC ID: PIDAV2700
Applicant: Airspan Networks Inc
Product: AirVelocity2700, 3.55-3.7GHz (n48),FM,PoE/DC
Model No.: AV27-N48-P4CXP-FM-C
Brand Name: Airspan
Test Procedure(s): FCC part 2.1091

Reviewed By:

Kevin Guo

Approved By:

Robin Wu



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2203RSU006-U2	Rev. 01	Initial Report	05-24-2022	Valid

CONTENTS

Description	Page
1. General Information	4
1.1. Applicant.....	4
1.2. Manufacturer	4
1.3. Testing Facility.....	4
1.4. Product Information	5
1.5. Antenna Details	5
2. RF Exposure Evaluation.....	6
2.1. Test Limits	6
2.2. Test Result.....	7
Appendix A - EUT Photograph	8

1. General Information

1.1. Applicant

Airspan Networks Inc

777 Yamato Road Suite 310 Boca Raton FL 33431 USA

1.2. Manufacturer

Airspan Networks Inc

777 Yamato Road Suite 310 Boca Raton FL 33431 USA

1.3. Testing Facility

☒	Test Site – MRT Suzhou Laboratory				
	Laboratory Location (Suzhou - Wuzhong)				
	D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China				
	Laboratory Location (Suzhou - SIP)				
	4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China				
	Laboratory Accreditations				
A2LA: 3628.01		CNAS: L10551			
FCC: CN1166		ISED: CN0001			
VCCI:	☐ R-20025	☐ G-20034	☐ C-20020	☐ T-20020	
	☐ R-20141	☐ G-20134	☐ C-20103	☐ T-20104	
☐	Test Site – MRT Shenzhen Laboratory				
	Laboratory Location (Shenzhen)				
	1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China				
	Laboratory Accreditations				
	A2LA: 3628.02		CNAS: L10551		
	FCC: CN1284		ISED: CN0105		
☐	Test Site – MRT Taiwan Laboratory				
	Laboratory Location (Taiwan)				
	No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)				
	Laboratory Accreditations				
	TAF: L3261-190725				
FCC: 291082, TW3261		ISED: TW3261			

1.4. Product Information

Product Name	AirVelocity2700, 3.55-3.7GHz (n48),FM,PoE/DC
Model No.	AV27-N48-P4CXP-FM-C
Operating Band	5G NR n48
CBSD Category	Category A CBSD
Antenna Information	Refer to section 1.6
Emission Designator	Refer to Section 1.7
Voltage Range	DC 42-57V/1A PoE 41.1-57V/1A
Remark: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	

1.5. Antenna Details

Band Support	Antenna Type	Manufacturer	Antenna Gain
n48	Omni Internal	Galtronics	5.00 dBi
Remark: 1. This device can operate with 2Tx and 4Tx mode. 2. This device operates with Multiple Antennas Using Multiple-input, Multiple-output (MIMO) Technology for Uncorrelated Transmission. 3. The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.			

2. RF Exposure Evaluation

2.1. Test Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result

Product	AirVelocity2700, 3.55-3.7GHz (n48),FM,PoE/DC
Test Item	RF Exposure Evaluation

Test Mode	Frequency Band (MHz)	Maximum EIRP (dBm)	Tune-up Factor	Pd (mW/cm ²)	Limit (mW/cm ²)	Compliance Distance (cm)
n48	3550 ~ 3700	28.75	2	0.2364	1	20

CONCLUSION:

The Power Density at R (20 cm) = $0.2364\text{mW/cm}^2 < 1\text{mW/cm}^2$.

So the compliance distance is 20cm for device installed without any other radio equipment.

Appendix A - EUT Photograph

Refer to “2203RSU006-UE” file.

_____ The End _____