

## RF Exposure Evaluation

### Limits

KDB 447498 D01 General RF Exposure Guidance v06; Part2.1091.

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula:  $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

**R** = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

$$EIRP = E_{Meas} + 20 \log(d_{Meas}) - 104.7$$

EIRP is the equivalent isotropically radiated power, in dBm

E<sub>Meas</sub> is the field strength of the emission at the measurement distance, in dB μV/m

d<sub>Meas</sub> is the measurement distance, in m

## Test Result of RF Exposure Evaluation

wifi 2.4G mode

Channel	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
802.11b	13.887	24.4737	0.00844	1.0	PASS
802.11g	13.24	21.0863	0.00727	1.0	PASS
802.11n HT20	14.604	28.8669	0.00996	1.0	PASS
802.11n HT40	13.783	23.8946	0.00824	1.0	PASS

Remark: antenna gain=2.39cdBi

wifi 5G mode:

Band	Channel	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
Band 1	802.11a	15.335	34.1586	0.01518	1.0	PASS
	802.11ac HT20	15.226	33.3119	0.01480	1.0	PASS
	802.11ac HT40	15.313	33.9860	0.01510	1.0	PASS
	802.11ac HT80	14.588	28.7607	0.01278	1.0	PASS
	802.11n HT20	15.144	32.6889	0.01453	1.0	PASS
	802.11n HT40	15.252	33.5120	0.01489	1.0	PASS

Band	Channel	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
Band 4	802.11a	14.727	29.6961	0.01320	1.0	PASS
	802.11ac HT20	14.569	28.6352	0.01272	1.0	PASS
	802.11ac HT40	14.164	26.0856	0.01159	1.0	PASS
	802.11ac HT80	14.126	25.8583	0.01149	1.0	PASS
	802.11n HT20	14.52	28.3139	0.01258	1.0	PASS
	802.11n HT40	14.208	26.3512	0.01320	1.0	PASS

Remark: antenna gain=3.49dBi

---

For BLE

Field strength (dBuV/m)	EIRP (dBm)	Max tune-up (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
85.07	-10.09	0.097	0.00002	1.0	PASS

Remark: antenna gain= -0.08dBi

For EDR

Field strength (dBuV/m)	EIRP (dBm)	Max tune-up (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
86.47	-8.69	0.135	0.00003	1.0	PASS

Remark: antenna gain= -0.08dBi

For Simultaneous transmitting, 1): The sum of the ratios of the spatially averaged results to the applicable frequency dependent MPE limits =  $0.00996/1 + 0.01518/1 + 0.00003/1 = 0.02517 < 1$  Since the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in the device is  $\leq 1.0$ , the EUT is considered to satisfy MPE compliance for simultaneous transmission operations.