

TEST REPORT

For

Mobile Phone

Model Number: CPH2711

FCC ID: R9C-OP24283

Test Laboratory : Shenzhen Academy of Metrology and Quality Inspection
Site Location : No.4, Tongfa Road, Xili Street, Nanshan District,
Shenzhen, Guangdong, China
Tel : 0086-755-86928965
Fax : 0086-755-86009898-31396
Web : www.smq.com.cn
Email : emcrf@smq.com.cn

The "important statement" on the back of report's homepage is an element of the report, and any copy that does not contain the "important statement" is incomplete.

重 要 声 明

Important statement

1. 本院是深圳市人民政府依法设置的产品质量监督检验机构，系社会公益型非营利性技术机构，为各级政府执法部门进行监督管理提供技术支持和接受社会各界的委托检验。

SMQ is a legal non-profit technical institute established by Shenzhen Municipal Government to undertake the quality supervision and inspection of products, and to provide technical support to relevant supervision and administration and also conduct commission test from the society.

2. 本院保证检验的科学性、公正性和准确性，对检验的数据负责，并对委托单位所提供的样品和技术资料保密。

SMQ is committed to assuring the scientificness, impartiality and accuracy of all tests carried out, responsibility for test data gained, and keeping confidential of all test samples and technical documents provided.

3. 抽样按照本院程序文件《抽样程序》和相应产品的检验细则的规定执行。

The sampling should be carried out according to the "sampling procedure" defined in the Procedure Document and relevant testing specifications.

4. 报告/证书无主检、审核、批准人签字，或涂改，或未盖本院报告/证书专用章及骑缝章无效。未经本院许可，不得部分复印、摘用或篡改本报告/证书内容。复印证书/报告未重新加盖本院证书/报告专用章无效。

Any report/certificate having not been signed by relevant responsible engineer, reviewer or authorized approver, or having been altered without authorization, or without both the Dedicated Report/Certificate Seal and its across-page seal is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report/certificate is not permitted without the written authorization of SMQ. Any copy of certificates/reports without the Dedicated Report/Certificate Seal is deemed to be invalid.

5. 送样委托检验结果仅对来样有效：委托检验的样品、样品及委托方信息均由委托方提供，本院不对样品的代表性、真实性及信息的完整性和准确性负责。

The test results presented in the report apply only to the tested sample. The customer provides thier own information, the sample, and the sample information. Thus, SMQ assumes no responsibility for representativeness , authenticity of the sample and validity and accuracy of the information..

6. 未经检验机构同意，样品委托人不得擅自使用检验结果进行不当宣传。

Any use of SMQ test result for advertisement of the tested material or product must be approved in writing by SMQ.

7. 无 CMA 标志的报告/证书，仅作为科研、教学或内部质量控制之用。含粤字编号的 CAL 标志仅适用于产品标准和判定标准。

The non-CMA report/certificate issued by SMQ is only permitted to be used for research, teaching or internal quality control. CAL logo with symbol "Yue" is only relevant to product standards and reference of standards.

8. 委托方对报告/证书有异议的，应于报告发出之日起十五日内向本院提出。政府行政管理部门下达的监督检验任务，受检方对报告/证书有异议的，应按政府行政管理部门文件规定及国家相关法律、法规进行。Any objection to report/certificate issued by SMQ should be submitted to SMQ within 15 days after the issuance of the test. The mandatory inspection assigned by government administrative departments shall be carried out in accordance with the documents and regulations of the government administrative department and relevant national laws and regulations if inspected parties raise any objection to the inspection.

9. 报告/证书更改后，发出的电子版报告/证书、报告/证书的扫描件及传真件将不被追回，委托方有义务将更改后的报告/证书提供给使用原报告/证书的相关方。

SMQ is not responsible for recalling the electronic version of the original report/certificate when any revision is made to them. The applicant assumes the responsibility of providing the revised version to any interested party who uses them.

10. 只申领电子报告时，相关内容和效力以电子报告为准；电子报告和纸质报告同时申领时，电子报告仅作为纸质报告的副本，相关内容和效力以同编号纸质报告为准。

The relevant content and effectiveness is subject to the electronic version of the original report which was only applied for. When an electronic report and a paper report are applied for at the same time, the electronic report is only a copy of the paper report, and the relevant content and effectiveness is subject to the paper report.

11. 检验报告二维码具浏览和下载完整报告功能，是应委托方要求所设，该二维码及其复制图能使任何人扫描获取完整的检验报告电子版，本报告持有人如需限制他人经该二维码获取检验报告内容，应自行遮盖或消除检验报告及其复制件所附二维码，我院对委托方选择检验报告二维码功能所致的信息泄露概不负责（适用于附二维码报告）。

The QR code has the function of browsing and downloading complete report. Setting this function or not is chosen by the customer. The QR code and its copy enable anyone to scan and obtain the complete electronic version of the test report. Thus, if the owner of this report needs to restrict others from obtaining the content of the test report through the QR code, he shall cover or remove the QR code attached to the test report and its copies by himself. SMQ assumes no responsibility for the information leakage caused by the customer's selection of the QR code function of the test report (This clause applies to reports with QR code attached) .

投诉及报告/证书真伪查询电话

Complaint hotline : 400-900-8999 按 5

Email : complaint@smq.com.cn

Revision History

No	Date	Remark
V1.0	2024-12-13	Initial issue

TEST REPORT DECLARATION

Applicant : Guangdong OPPO Mobile Telecommunications Corp., Ltd.
Address : NO.18 Haibin Road, Wusha Village, Chang'an Town,
Dongguan City, Guangdong, China
Manufacturer : Guangdong OPPO Mobile Telecommunications Corp., Ltd.
Address : NO.18 Haibin Road, Wusha Village, Chang'an Town,
Dongguan City, Guangdong, China
EUT Description : Mobile Phone
Model No. : CPH2711
Trade mark : OPPO
Serial Number : ---
Date of EUT : 2024-11-4
Receive
Test Standards: : FCC Part 15 Subpart C

The EUT described above is tested by Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory to determine the maximum emissions from the EUT and ensure the EUT to be compliance with the immunity requirements of the EUT. Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory is assumed full responsibility for the accuracy of the test results, unless they depend on the manufacturer information.

The test report is valid for above tested sample only and shall not be reproduced in part without written approval of the laboratory.

Project
Engineer: 陈司林 Date: 2024-12-6
(陈司林 Chen SiLin)
Checked by: 万晓婧 Date: 2024-12-13
(万晓婧 Wan XiaoJing)
Approved by: 林斌 Date: 2024-12-13
(林斌 Lin Bin)

TABLE OF CONTENTS

TEST REPORT DECLARATION	3
1. TEST RESULTS SUMMARY	6
2. GENERAL INFORMATION	7
2.1. Report information	7
2.2. Laboratory Accreditation and Relationship to Customer	7
2.3. Measurement Uncertainty	8
3. PRODUCT DESCRIPTION	9
3.1. EUT Description	9
3.2. Related Submittal(s) / Grant (s)	9
3.3. Block Diagram of EUT Configuration	9
3.4. Operating Condition of EUT	10
3.5. Directional Antenna Gain	10
3.6. Support Equipment List	10
3.7. Special Accessories	10
3.8. Equipment Modifications	10
4. 6DB BANDWIDTH	11
4.1. Test Limit	11
4.2. Test Procedure	11
4.3. Test Setup	11
4.4. Test Equipment	11
4.5. Test Condition	11
4.6. Test Data	12
5. MAXIMUM PEAK CONDUCTED OUTPUT POWER	13
5.1. Test Limit	13
5.2. Test Procedure	13
5.3. Test Setup	14
5.4. Test Equipment	14
5.5. Test Condition	15
5.6. Test Data	15
6. POWER SPECTRAL DENSITY	16
6.1. Test Limit	16
6.2. Test Procedure	16
6.3. Test Setup	16
6.4. Test Equipment	16
6.5. Test Condition	17
6.6. Test Data	17
7. CONDUCTED BANDEDGE AND SPURIOUS	18
7.1. Test Limit	18

7.2.	Test Procedure	18
7.3.	Test Setup	19
7.4.	Test Equipment	19
7.5.	Test Condition	19
7.6.	Test Data	19
8.	RADIATED EMISSION.....	20
8.1.	Test Limit	20
8.2.	Test Procedure	21
8.3.	Test Equipment	21
8.4.	Test Condition	22
8.5.	Test Data	22
9.	AC POWER-LINE CONDUCTION EMISSIONS	23
9.1.	Test Standard and Limit	23
9.2.	Test Procedure	23
9.3.	Test Arrangement	23
9.4.	Test Equipment	23
9.5.	Test Condition	24
9.6.	Test Data	24
10.	ANTENNA REQUIREMENTS	26
10.1.	Test Limit	26
10.2.	Antenna Connector	26

1. TEST RESULTS SUMMARY

Table 1 Test Results Summary

Test Items	Test Results
6dB bandwidth	PASS
Maximum Peak Conducted Power	PASS
Power spectral density	PASS
Conducted Bandedge and Spurious	PASS
Radiated emission	PASS
Conducted Emission	PASS
Antenna Requirement	PASS

Remark: "N/A" means "Not applicable."

2. GENERAL INFORMATION

2.1. Report information

This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that SMQ approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that SMQ in any way guarantees the later performance of the product/equipment.

The sample/s mentioned in this report is/are supplied by Applicant, SMQ therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.

Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through SMQ, unless the applicant has authorized SMQ in writing to do so.

The lab will not be liable for any loss or damage resulting for false, inaccurate, inappropriate or incomplete product information provided by the applicant/manufacturer.

2.2. Laboratory Accreditation and Relationship to Customer

The testing report were performed by the Shenzhen Academy of Metrology and quality Inspection EMC Laboratory (Guangdong EMC compliance testing center), in their facilities located at NETC Building, No.4 Tongfa Rd., Xili, Nanshan, Shenzhen, China. At the time of testing, Laboratory is accredited by the following organizations:

China National Accreditation Service for Conformity Assessment (CNAS) accredits the Laboratory for conformance to FCC standards, EMC international standards and EN standards. The Registration Number is CNAS L0579.

The Laboratory is Accredited Testing Laboratory of FCC with Designation number CN1165 and Site registration number 582918.

The Laboratory is registered to perform emission tests with Innovation, Science and Economic Development (ISED), and the registration number is 11177A.

The Laboratory is registered to perform emission tests with VCCI, and the registration number are C-20048, G20076, R-20077, R-20078 and T-20047.

The Laboratory is Accredited Testing Laboratory of American Association for Laboratory Accreditation (A2LA) and certificate number is 3292.01.

2.3.Measurement Uncertainty

Conducted Emission

9 kHz~150 kHz $U=3.7$ dB $k=2$

150 kHz~30 MHz $U=3.3$ dB $k=2$

Radiated Emission

30 MHz~1000 MHz $U=4.3$ dB $k=2$

1 GHz~6 GHz $U=4.6$ dB $k=2$

6 GHz~40 GHz $U=5.1$ dB $k=2$

3. PRODUCT DESCRIPTION

3.1.EUT Description

Operate Frequency : 2.402 GHz~2.480 GHz

Antenna Designation : IFA 0 dBi

Modulation : GFSK

Operating Voltage : DC 3.92 V (Li-ion, battery)
AC 120 V/60 Hz (Adapter)

Software Version : ColorOS 15.0.0

Hardware Version : 11

Remark: There are 4 adapters, only the worst data of VCB4JAUH (2#) shown in this report.

Bluetooth Low Energy:


Table 2 Working Frequency List

Regulatory Range	RF Channels
2.400-2.4835 GHz	f=2402+k*2 MHz, k=0, ... ,39

3.2.Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: **R9C-OP24283** filing to comply with Section 15.207,15.209, 15.247 of the FCC Part 15, Subpart C Rules.

3.3.Block Diagram of EUT Configuration



3.4. Operating Condition of EUT

Worst-case mode and channel used for 30-1000 MHz radiated and power line conducted emissions was the mode and channel with the highest output power.

Worst-case data rates as provided by the client were:

Bluetooth low energy

3.5. Directional Antenna Gain

Not available for this EUT intended for grant.

3.6. Support Equipment List

Table 3 Support Equipment List

Name	Model No.	S/N	Manufacturer
Adapter 1# for EUT	VCB4JAUH	---	HUIZHOU GOLDEN LAKE INDUSTRIAL CO., LTD
Adapter 2# for EUT	VCB4JAUH	---	Jiangsu ChenYang Electronics Co., Ltd.
Adapter 3# for EUT	VCB4HAUH	---	ShenZhen Huntkey Electronics Co.,Ltd.
Adapter 4# for EUT	VCB4HAUH	---	HUIZHOU GOLDEN LAKE INDUSTRIAL CO., LTD.

3.7. Special Accessories

Not available for this EUT intended for grant.

3.8. Equipment Modifications

Not available for this EUT intended for grant.

4. 6DB BANDWIDTH

4.1. Test Limit

The minimum 6 dB bandwidth shall be 500 kHz.

4.2. Test Procedure

ANSI C63.10-2013 Clause 11.8

The transmitter output was connected to the spectrum analyzer.

- a) Set RBW = 100 kHz.
- b) Set the VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3. Test Setup



4.4. Test Equipment

No.	Equipment	Manufacturer	Model No.	LAST CALIB	Period
SB9060	Signal Analyzer	Rohde & Schwarz	SB9060	2024-04-22	12 Months

4.5. Test Condition

Date of test: Dec.6,2024

Temperature: 26 °C

Relative Humidity: 36 %RH
Atmospheric Pressure: 101.3 kPa

4.6. Test Data

Please refer to the Annex A.

5. MAXIMUM PEAK CONDUCTED OUTPUT POWER

5.1. Test Limit

Compliance with part CFR 47 (FCC) part 15.247 (b)

(1) For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

(2) For frequency hopping systems operating in the 902–928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

(3) For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the *maximum conducted output power* is the highest total transmit power occurring in any mode.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.2. Test Procedure

For FHSs

ANSI C63.10-2013 Clause 7.8.5

a) Use the following spectrum analyzer settings:

1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.

2) RBW > 20 dB bandwidth of the emission being measured.

3) VBW ≥ RBW.

- 4) Sweep: Auto.
- 5) Detector function: Peak.
- 6) Trace: Max hold.
 - b) Allow trace to stabilize.
 - c) Use the marker-to-peak function to set the marker to the peak of the emission.
 - d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
 - e) A plot of the test results and setup description shall be included in the test report.

For DTSs

ANSI C63.10-2013 Clause 11.9

The following procedure can be used when the maximum available RBW of the instrument is less than the DTS bandwidth:

- a) Set the RBW = 1 MHz.
- b) Set the VBW $\geq [3 \times \text{RBW}]$.
- c) Set the span $\geq [1.5 \times \text{DTS bandwidth}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select the peak detector). If the instrument does not have a band power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS channel

5.3. Test Setup



5.4. Test Equipment

No.	Equipment	Manufacturer	Model No.	LAST CALIB	Period
SB9060	Signal Analyzer	Rohde & Schwarz	FSQ40	2024-04-22	12 Months

5.5. Test Condition

Date of test: Dec.6,2024

Temperature: 26 °C

Relative Humidity: 36 %RH

Atmospheric Pressure: 100.7 kPa

5.6. Test Data

Please refer to the Annex A.

6. POWER SPECTRAL DENSITY

6.1. Test Limit

CFR 47 (FCC) part 15.247 (e) , For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

6.2. Test Procedure

ANSI C63.10-2013 Clause 11.10

The transmitter output was connected to the spectrum analyzer.

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
- d) Set VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3. Test Setup



6.4. Test Equipment

No.	Equipment	Manufacturer	Model No.	LAST CALIB	Period
SB9060	Signal Analyzer	Rohde & Schwarz	FSQ40	2024-04-22	12 Months

6.5. Test Condition

Date of test: Dec.6,2024

Temperature: 26 °C

Relative Humidity: 36 %RH

Atmospheric Pressure: 101.3 kPa

6.6. Test Data

Please refer to the Annex A.

7. CONDUCTED BANDEDGE AND SPURIOUS

7.1. Test Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.

7.2. Test Procedure

ANSI C63.10-2013

The transmitter output was connected to the spectrum analyzer.

Establish a reference level by using the following procedure:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to ≥ 1.5 times the DTS bandwidth.
- c) Set the RBW = 100 kHz.
- d) Set the VBW $\geq 3 \times$ RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.

Emission level measurement

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq 3 \times$ RBW.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

The bandedges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal

Test Result : All emission outside of 2400-2483.5 are lower at least 20dB than fundamental frequency.

7.3. Test Setup



7.4. Test Equipment

No.	Equipment	Manufacturer	Model No.	LAST CALIB	Period
SB9060	Signal Analyzer	Rohde & Schwarz	FSQ40	2024-04-22	12 Months

7.5. Test Condition

Date of test: Dec.6,2024
Temperature: 26 °C
Relative Humidity: 36 %RH
Atmospheric Pressure: 101.3 kPa

7.6. Test Data

Please refer to the Annex A.

8. RADIATED EMISSION

8.1. Test Limit

CFR 47 (FCC) part 15.205, 15.209

Table 4 Radiation Emission Test Limit

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.

Table 5 Restricted frequency bands

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 -	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.17775	73 - 74.6	1645.5 -	9.3 - 9.5
4.20725 -	74.8 - 75.2	1646.5	
4.20775	108 - 121.94	1660 - 1710	
6.215 - 6.218	123 - 138	1718.8 -	
6.26775 -	149.9 - 150.05	1722.2	
6.26825	156.52475 -	2200 - 2300	
6.31175 -	156.52525	2310 - 2390	
6.31225	156.7 - 156.9	2483.5 - 2500	
8.291 - 8.294	162.0125 - 167.17	2655 - 2900	
8.362 - 8.366	167.72 - 173.2	3260 - 3267	
8.37625 -	240 - 285	3332 - 3339	
8.38675	322 - 335.4	3345.8 - 3358	
8.41425 -		3600 - 4400	
8.41475			
12.29 - 12.293			
12.51975 -			
12.52025			

12.57675	-		
12.57725			
13.36 - 13.41			

8.2. Test Procedure

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. For measurement below 1GHz, the EUT was placed on a turntable with 0.8meter, above ground. For measurement above 1 GHz, test at FAR, the EUT is placed on a non-conductive table, which is 1.5 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f > 1$ GHz for peak measurement. Set RBW = 1 MHz, and 1/T (on time) for average measurement.

8.3. Test Equipment

No.	Equipment	Manufacturer	Model No.	LAST CALIB	Period
SB15044/01	Test Receiver	ROHDE&SCHWARZ	ESW8	2024-03-15	12 Months
SB18844	Anechoic chamber	Albatross	3mSAC	2024-03-19	12 Months
SB18856	Broadband Antenna	SCHWARZBECK	VULB9163	2024-08-26	12 Months
SB3345	Loop antenna	SCHWARZBECK	FMZB1516	2024-01-12	12 Months
SB3435	Horn Antenna	ROHDE&SCHWARZ	HF906	2024-11-19	12 Months
SB8501/09	Test Receiver	ROHDE&SCHWARZ	ESU40	2024-01-17	12 Months
SB8501/11	Horn Antenna	ETS-Lindgren	3160-09	2023-02-22	36 Months
SB8501/16	Low Noise Amplifier	ROHDE&SCHWARZ	SCU-26	2024-01-16	12 Months

SB9054/08	Broadband Antenna	SCHWARZBECK	VULB 9163	2023-12-27	12 Months
SB9058/03	Low Noise Amplifier	ROHDE&SCHWARZ	SCU18	2024-01-16	12 Months
SB9555/02	Anechoic chamber	Albatross	/	2024-08-08	12 Months

8.4. Test Condition

Date of test: Nov.5,2024-Nov.22,2024
Temperature: (21 ~ 24) °C
Relative Humidity: (46 ~ 56) %RH
Atmospheric Pressure: (100.4 ~ 101.5) kPa

8.5. Test Data

Please refer to the Annex A.

9. AC POWER-LINE CONDUCTION EMISSIONS

9.1. Test Standard and Limit

9.1.1. Test Standard

CFR 47 (FCC) part 15.207

9.1.2. Test Limit

Table 6 AC Power-line Conduction Emissions Test Limit

Frequency (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 ¹	56 to 46 ¹
0.5 - 5	56	46
5 - 30	60	50

Note¹: The level decreases linearly with the logarithm of the frequency.

9.2. Test Procedure

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver is used to test the emissions from both sides of AC line. According to the requirements in Section 7 and 13 of ANSI C63.4a-2017. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

The bandwidth of EMI test receiver is set at 9 kHz.

9.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

9.4. Test Equipment

No.	Equipment	Manufacturer	Model No.	LAST CALIB	Period
SB4357	AMN	ROHDE&SCHW ARZ	ENV216	2024-05-21	12 Months
SB9058/05	Test Receiver	ROHDE&SCHW ARZ	ESCI3	2024-09-03	12 Months
SB9549	Shielded Room	Albatross	SR	2024-08-28	12 Months

9.5. Test Condition

Date of test: Nov.5,2024
Temperature: 23 °C
Relative Humidity: 49 %RH
Atmospheric Pressure: 101.4 kPa

9.6. Test Data


Note: Emissions not reported below are too low against the prescribed limits. “/” means the test data is too low against the limit.

Table 7 AC Power-line Conduction Emissions Test Data


Test mode: Charging and Transmitting										
Port	Frequency (MHz)	Emission Level QP (dBuV/m)	Limit QP (dBuV/m)	Margin QP (dB)	Emission Level AV (dBuV/m)	Limit AV (dBuV/m)	Margin AV (dB)	Reading QP (dBuV/m)	Reading AV (dBuV/m)	Correction Factor (dB)
L	0.150	60.1	66.0	5.9	33.8	56.0	22.2	50.0	23.7	10.1
L	0.185	53.8	64.3	10.5	25.8	54.3	28.5	43.7	15.7	10.1
L	0.480	38.7	56.3	17.6	29.1	46.3	17.2	28.6	19.0	10.1
L	3.210	31.2	56.0	24.8	21.3	46.0	24.7	21.1	11.2	10.1
L	2.280	33.6	56.0	22.4	25.8	46.0	20.2	23.5	15.7	10.1
L	6.280	35.9	60.0	24.1	28.6	50.0	21.4	25.9	18.6	10.0
N	0.150	60.4	66.0	5.6	32.6	56.0	23.4	50.3	22.5	10.1
N	0.205	51.8	63.4	11.6	23.8	53.4	29.6	41.7	13.7	10.1
N	0.375	34.2	58.4	24.2	20.1	48.4	28.3	24.1	10.0	10.1
N	2.036	31.6	56.0	24.4	22.4	46.0	23.6	21.5	12.3	10.1
N	3.725	36.3	56.0	19.7	27.7	46.0	18.3	26.3	17.7	10.0
N	5.935	37.4	60.0	22.6	29.9	50.0	20.1	27.4	19.9	10.0

Test Mode: Charging and Transmitting

L:



N:



10. ANTENNA REQUIREMENTS

10.1. Test Limit

15.203 requirements:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

10.2. Antenna Connector

Antenna Connector is on the PCB within enclosure and not accessible to user.

-----End of Report-----