



Bundesrepublik Deutschland
Federal Republic of Germany

Bundesamt für Seeschifffahrt und Hydrographie
Federal Maritime and Hydrographic Agency



**BUNDESAMT FÜR
SEESCHIFFFAHRT
UND
HYDROGRAPHIE**

Conformance test report of an

AIS Class B SO System

Equipment under test:

SRT

Type:

Cobalt II

Applying test standards:

IEC 62287-2 Ed.2.0:2017 [Sections 10, 12, 13]

Test Report No.:

BSH/4542/001/4323102/17-1

Applicant:

**SRT Marine Systems
Wireless House, Westfield Industrial Estate,
Midsomer Norton
Bath, BA3 4BS
United Kingdom**

Hamburg, 02 August 2017
For the Federal Maritime and Hydrographic Agency

Daniel Meyszies

Test engineer

Hans-Karl von Arnim

Head of section

Federal Maritime and Hydrographic Agency
Bernhard-Nocht-Str. 78
20359 Hamburg
Germany



DAkkS
Deutsche
Akkreditierungsstelle
D-PL-12084-01-00



Deutsche Akkreditierungsstelle GmbH

Beliehene gemäß § 8 Absatz 1 AkkStelleG i.V.m. § 1 Absatz 1 AkkStelleGBV
Unterzeichnerin der Multilateralen Abkommen
von EA, ILAC und IAF zur gegenseitigen Anerkennung

Akkreditierung



Die Deutsche Akkreditierungsstelle GmbH bestätigt hiermit, dass das Prüflaboratorium

Bundesamt für Seeschifffahrt und Hydrographie
Bernhard-Nocht-Straße 78, 20359 Hamburg


die Kompetenz nach DIN EN ISO/IEC 17025:2005 besitzt, Prüfungen in folgenden Bereichen durchzuführen:

Schiffsausrüstung (Navigationsausrüstung, Funkausrüstung, Rettungsmittel)

Die Akkreditierungsurkunde gilt nur in Verbindung mit dem Bescheid vom 20.04.2017 mit der Akkreditierungsnummer D-PL 12084-01 und ist gültig bis 19.04.2022. Sie besteht aus diesem Deckblatt, der Rückseite des Deckblatts und der folgenden Anlage mit insgesamt 11 Seiten.

Registrierungsnummer der Urkunde: **D-PL-12084-01-00**

Frankfurt am Main, 20.04.2017



Im Auftrag Dipl.-Ing. (FH) Ralf Egner
Abteilungsleiter

Siehe Hinweise auf der Rückseite

Table of contents:

1	GENERAL	6
1.1	SUMMARY	6
1.2	EQUIPMENT HISTORY	8
1.2.1	EUT system no 1.....	8
1.2.2	EUT system no 2.....	8
1.3	TEST ENVIRONMENT.....	9
1.4	COMPOSITION.....	10
1.5	LEGEND.....	11
1.6	GENERAL OBSERVATIONS.....	11
2	9 POWER SUPPLY, ENVIRONMENTAL AND EMC TESTS	12
2.1	9.5 UNDER VOLTAGE TEST (BROWN OUT).....	12
2.2	9.6 UNDER VOLTAGE TEST (SHORT TERM).....	13
3	10 OPERATIONAL TESTS.....	14
3.1	10.1 GENERAL.....	14
3.1.1	10.1.1 Tests by inspection	14
3.1.2	10.1.2 Safety of operation	16
3.1.3	10.1.3 Additional features	16
3.2	10.2 MODES OF OPERATION	17
3.2.1	10.2.1 Autonomous mode.....	17
3.2.1.1	10.2.1.1 Transmit position reports	17
3.2.1.2	10.2.1.2 Receive AIS Class A position reports.....	18
3.2.1.3	10.2.1.3 Receive AIS Class B "SO" position reports	19
3.2.1.4	10.2.1.4 Receive AIS Class B "CS" position reports	20
3.2.1.5	10.2.1.5 Receive in time slot adjacent to own transmission.....	21
3.2.1.6	10.2.1.6 High VDL loading reception test.....	21
3.2.2	10.2.2 Single messages.....	22
3.2.2.1	10.2.2.1 Transmit an addressed binary message	22
3.2.2.2	10.2.2.2 Transmit an addressed safety related Message 12	27
3.2.2.3	10.2.2.3 Acknowledgement of addressed Messages.....	28
3.2.2.4	10.2.2.4 Transmit a broadcast binary Message 8	30
3.2.2.5	10.2.2.5 Transmit a broadcast safety related Message 14	34
3.2.2.6	10.2.2.6 ITDMA and RATDMA transmission.....	35
3.2.3	10.2.3 Polled mode / Interrogation response	36
3.3	10.3 CHANNEL SELECTION	38
3.3.1	10.3.1 Valid channels.....	38
3.3.2	10.3.2 Invalid channels	39
3.4	10.4 INTERNAL GNSS RECEIVER	39
3.5	10.5 AIS INFORMATION	40
3.5.1	10.5.1 Information content	40
3.5.2	10.5.2 Information update intervals.....	42
3.5.2.1	10.5.2.1 Autonomous reporting interval.....	42
3.5.2.2	10.5.2.2 Polite behavior.....	45
3.5.2.3	10.5.2.3 Static data reporting interval.....	47
3.6	10.6 INITIALISATION PERIOD	49
3.7	10.7 ALARMS AND INDICATIONS, FALL-BACK ARRANGEMENTS	50
3.7.1	10.7.1 Built in integrity test	50
3.7.2	10.7.2 Transceiver protection.....	50
3.7.3	10.7.3 Transmitter shutdown procedure	51
3.7.4	10.7.4 Position sensor fallback conditions	52
3.8	10.8 USER INTERFACE	54
3.8.1	10.8.1 Status indication.....	54
3.8.2	10.8.2 Message display	55
3.8.3	10.8.3 Static data input.....	57

4	11 PHYSICAL TESTS.....	59
5	12 SPECIFIC TESTS OF LINK LAYER	60
5.1	12.1 TDMA SYNCHRONISATION	60
5.1.1	12.1.1 Synchronisation test using UTC direct and indirect	60
5.1.2	12.1.2 Synchronisation test without UTC, EUT receiving semaphore	61
5.2	12.2 TIME DIVISION (FRAME FORMAT)	62
5.3	12.3 SYNCHRONISATION JITTER	63
5.4	12.4 DATA ENCODING (BIT STUFFING)	64
5.5	12.5 FRAME CHECK SEQUENCE	65
5.6	12.6 SLOT ALLOCATION (CHANNEL ACCESS PROTOCOLS).....	66
5.6.1	12.6.1 Network entry	66
5.6.2	12.6.2 Autonomous scheduled transmissions (SOTDMA)	67
5.6.3	12.6.3 Autonomous scheduled transmissions (ITDMA).....	68
5.6.4	12.6.4 Transmission of Messages 24A and 24B (ITDMA).....	69
5.6.5	12.6.5 Assigned operation	70
5.6.5.1	12.6.5.1 Message 16 with slot assignment	70
5.6.5.2	12.6.5.2 Message 16 with rate assignment.....	72
5.6.5.3	12.6.5.3 Assigned mode using invalid reporting rates.....	74
5.6.5.4	12.6.5.4 Slot assignment to FATDMA reserved slots.....	75
5.6.6	12.6.6 Group assignment.....	76
5.6.6.1	12.6.6.1 Entering interval assignment	76
5.6.6.2	12.6.6.2 Assignment by region.....	78
5.6.6.3	12.6.6.3 Assignment by station type.....	79
5.6.6.4	12.6.6.4 Addressing by ship and cargo type	81
5.6.6.5	12.6.6.5 Quiet time command	82
5.6.6.6	12.6.6.6 Reverting from interval assignment.....	83
5.6.6.7	12.6.6.7 Assignment priority test – Message 16 and 23	84
5.6.6.8	12.6.6.8 Assignment priority test – Message 22 and 23	85
5.6.7	12.6.7 Base station reservations.....	87
5.7	12.7 MESSAGE FORMATS	88
5.7.1	12.7.1 Received messages.....	88
5.7.2	12.7.2 Transmitted messages.....	91
6	13 SPECIFIC TESTS OF NETWORK LAYER.....	93
6.1	13.1 REGIONAL AREA DESIGNATION BY VDL MESSAGE	93
6.2	13.2 CHANNEL MANAGEMENT BY ADDRESSED MESSAGE 22	99
6.3	13.3 INVALID REGIONAL OPERATING AREAS.....	100
6.4	13.4 CONTINUATION OF AUTONOMOUS MODE REPORTING INTERVAL	101
6.5	13.5 SLOT REUSE AND FATDMA RESERVATIONS	102
6.6	13.6 LONG-RANGE APPLICATION BY BROADCAST	104
6.6.1	13.6.1 Long-range broadcast.....	104
6.6.2	13.6.2 Multiple assignment operation	106
6.7	13.6 OTHER FEATURES.....	107
7	ANNEX D DSC FUNCTIONALITY	108
7.1	A.4 DSC FUNCTIONALITY TESTS.....	108
7.1.1	A.4.1 General.....	108
7.1.2	A.4.4 Regional area designation	109
7.1.3	A.4.5 Scheduling.....	109
7.1.4	A.4.6 DSC flag in Message 18.....	110
7.1.5	A.4.7 DSC monitoring time plan.....	111
7.1.6	A.4.8 Replacement or erasure of dated or remote regional operating settings	112
7.1.7	A.4.9 Test of addressed telecommand	114
7.1.8	A.4.10 Invalid regional operating areas.....	115
ANNEX A	TEST EQUIPMENT	116
A.1	TEST EQUIPMENT SUMMARY	116
A.1.1	VDL Analyser / Generator	116
A.1.2	Target simulator	117
A.1.3	Presentation Interface Monitor	117
A.1.4	Sensor Data Simulator	117

A.1.5	DSC Test box.....	117
A.1.6	Serial Interface Server.....	118
A.1.7	Laboratory Network.....	118
A.1.8	GPS Re-transmitter.....	118
A.2	TEST ENVIRONMENT OVERVIEW	119
ANNEX B	TEST SENTENCES.....	120
B.1	IEC 61162 TEST SENTENCES	120
B.1.1	Messages (ABM, BBM).....	120
ANNEX C	PHOTOS OF EQUIPMENT UNDER TEST	122
C.1	TRANSPONDER UNIT.....	122
C.2	GPS ANTENNA.....	124

1 General

1.1 Summary

Applicant:	SRT Marine Systems, Wireless House, Westfield Industrial Estate, Midsomer Norton, Bath, BA3 4BS, United Kingdom
<u>Equipment under test:</u>	
Type:	Cobalt II
Manufacturer:	SRT Marine Systems, Wireless House, Westfield Industrial Estate, Midsomer Norton, Bath, BA3 4BS, United Kingdom
Place of test:	BSH test laboratory Hamburg, Room 916
Start of test:	02 May 2017
End of test:	01 August 2017

Test standards¹:

IEC 62287-2 Ed. 2.0 : 2017

Maritime navigation and radiocommunication equipment and systems – Class B shipborne equipment of the automatic identification systems (AIS) –

Part 2: Self-organising time division multiple access (SOTDMA) techniques –

IEC 61162-1 Ed. 5.0 : 2016

Maritime navigation and radiocommunication equipment and systems – Digital Interfaces –

Part 1: Single talker and multiple listeners /

IEC 61162-2 : 1998

Maritime navigation and radiocommunication equipment and systems – Digital Interfaces –

Part 2: Single talker and multiple listeners, high speed transmission

Other relevant standards:

Recommendation ITU-R M.1371-5 (2014)

Technical characteristics for an automatic identification system using time division multiple access in the VHF maritime mobile band

¹ Numbers listed in the titles of the test sections of this report refer to the respective sections of IEC 62287-2 if not stated otherwise.

Test No.	Reference IEC 61993-2 Ed. 2	Section	Result (passed / not passed / not applicable / not tested)
1	10	Operational tests	Passed
2	11	Physical tests	not included
3	12	Specific tests of link layer	Passed
4	13	Specific tests of network layer	Passed
5	A.4	DSC functionality tests	Passed

1.2 Equipment history

For each transponder unit under test a numbered entry is provided here.

1.2.1 EUT system no 1

Transponder				
Type	Cobalt II SOTDMA		Part no.	--
Delivery date	2017-04-28		Serial no.	41100023510428
HW Version:	Delivery date	2017-04-28	Version no.	--
	Installation date	2017-04-28		
SW Version:	Delivery date	2017-05-10	Version no.	15010004
	Installation date	2017-05-11		
SW Version:	Delivery date	2017-05-22	Version no.	15010005
	Installation date	2017-05-23		
SW Version:	Delivery date	2017-07-31	Version no.	15010007
	Installation date	2017-08-01		
SW Version:	Delivery date		Version no.	
	Installation date			

GPS antenna				
Type	GPS antenna		Part no.	GPS antenna
Delivery date	2017-03-17		Serial no.	2017-03-17
HW Version:	Delivery date	2017-03-17	Version no.	
	Installation date	2017-03-17		

1.3 Test environment

Here it is intended to record:

- lab room conditions,
- equipment under test conditions and type,
- for which period of time which EUT system is under test.

This test environment is completely equipped as described in Annex A.

Location	
Lab room no.	BSH Room 916 (9 th floor)
Geographical location	9° 59,103 E 53° 32,822 N (WGS84)
Lab room air temperature	Within the specification of IEC 60945, Section 5.2.1
Lab room air pressure	980 – 1030 mBar
Lab room relative air humidity	Within the specification of IEC 60945, Section 5.2.1

Equipment under test	
Position in lab room	
<input type="checkbox"/> relevant	<input checked="" type="checkbox"/> not relevant
Mounting at test bed	
<input type="checkbox"/> relevant	<input checked="" type="checkbox"/> not relevant
Type of equipment	
1 Component 1	production sample
2 Component 2	prototype
...	...
Refer to Annex A – Photos of Equipment under Test	
Remarks	

Test engineer	Meyszies (Me)

Equipment no	Start of test	End of test	Test engineer
1	2017-05-02	2017-08-01	Meyszies

1.4 Composition

Minimum Keyboard and Display (MKD)

☒ No display ☐ Internal ☐ Remote

Channel management by DSC

☐ Time sharing ☐ Dedicated receiver

Differential GNSS

☐ No differential GNSS ☒ Differential GNSS by Message 17

1.5 Legend

Result marking (in the “result” column):

Passed	Item is ok, test was successful
Not passed	Test of a required item was not successful, change required
N/T	Not tested
N/A	Not applicable

Specific remarks (in the “remark” column, marked “bold italic”):

REC	Recommendation (in terms of IEC17025 “opinion”): an improvement or change is recommended
Note	Note or comment (in terms of IEC17025 “interpretation”): rationale for specific results or interpretation of requirements as appropriate

Template for additional test notes (copy if required):

Date	Sign	Result	Status

Date of test report template: 2017-01-11

1.6 General observations

General observations not specific to any test item of the test standard are listed here:

	General problems		
Date	Item	Remark	Result

2 9 Power supply, Environmental and EMC tests

Test 9.1 to 9.4 are part of the environmental tests and performed by other labs.

2.1 9.5 Under voltage test (brown out)

9.5.1 Purpose

This test simulates the situation where the nominal supply voltage drops to below acceptable levels and then recovers over a medium time-period.

9.5.2 Method of test

Operate the EUT at the nominal supply voltage as indicated by the manufacturer.

- a) Gradually reduce the supply voltage to 40 % of the nominal supply voltage over 30 s.*
- b) Gradually increase the supply voltage back to 80 % of the nominal supply voltage over 30 s.*

9.5.3 Required result

Confirm that

- a) the unit shall not enter into any undefined or undesirable state as verified by a performance check,*
- b) the EUT shall recover and be fully operational as verified by a performance check.*

2017-05-02	Tester: Me	Test details: Under voltage test (brown out)		
Test item		Check	Remark	Result
Operate the EUT at the nominal supply voltage as indicated by the manufacturer.				
Reduce voltage down to 40% over 30 s,		Check that the EUT does not enter an undefined or undesirable state		Passed
Increasing voltage back to 80% of the nominal voltage over 30 s		Check that the EUT recovers to full operation		Passed

2.2 9.6 Under voltage test (short term)

9.6.1 Purpose

This test simulates the situation where the nominal supply voltage drops to below acceptable levels for a short period and then recovers.

9.6.2 Method of test

Operate the EUT at the nominal supply voltage as indicated by the manufacturer.

- a) Reduce the supply voltage to 40 % of the nominal supply voltage over 1 s.*
- b) Increase the supply voltage back to 80 % of the nominal supply voltage over 1 s.*

9.6.3 Required result

The following results are required.

- a) The unit shall not enter into any undefined or undesirable state as verified by a performance check.*
- b) The EUT shall recover and be fully operational as verified by a performance check.*

2017-05-02	Tester: Me	Test details: Under voltage test (short term)		
Test item		Check	Remark	Result
Operate the EUT at the nominal supply voltage as indicated by the manufacturer.				
Reduce voltage down to 40% over 1 s,		Check that the EUT does not enter an undefined or undesirable state		Passed
Increasing voltage back to 80% of the nominal voltage over 1 s		Check that the EUT recovers to full operation		Passed

3 10 Operational tests

3.1 10.1 General

3.1.1 10.1.1 Tests by inspection

(See 4.1.2, 4.2, 4.3, 6.1)

10.1.1.1 Method of measurement

By inspection of documentation.

10.1.1.2 Required results

The relevant requirements shall be met.

2017-05-02	Tester: Me	Test details: Tests by inspection	
Test item	Check	Remark	Result
4.1.2 Quality assurance			
Quality control system	Check the manufacturer's quality control system.		Passed
4.2 Manuals			
Type of external connectors	Check that information about external connectors is provided, if applicable.		Passed
Installation	Check that information for correct installation is provided.		Passed
	Check that information for correct positioning of the antennas is provided.		Passed
Compass safe distance	Check that the Compass safe distance value is provided.		Passed
4.3 Marking and identification (in addition to IEC 60945, 4.9)			
Power supply	Check that details of the power supply are provided.		Passed
Battery replacement	If applicable, check that the date for replacement of batteries is provided.	No batteries are implemented	NA

6.1 Internal processes			
Inspect the documentation that the following internal processes are implemented	A communication processor, capable of operating in the VHF Maritime Mobile Service band		Passed
	One TDMA transmitter		Passed
	Two TDMA receiving processes		Passed
	One DSC receiving process		Passed
	Means for automatic channel switching in the maritime mobile band by Message 22		Passed
	Means for automatic channel switching in the maritime mobile band by DSC		Passed
	Manual channel switching shall not be provided.		Passed
	An internal GNSS position sensor, resolution 1/10 000 minute, using WGS-84 datum only		Passed

3.1.2 10.1.2 Safety of operation

(See 4.1.3)

10.1.2.1 Purpose

To ensure the safety of operation.

10.1.2.2 Method of measurement

By inspection.

10.1.2.3 Required result

The requirements of 4.1.3 shall be met.

2017-05-02	Tester: Me	Test details: Safety of operation		
Test item		Check	Remark	Result
Verify by inspection				
Software modification		It shall not be possible for the operator to augment, amend or erase any program software required for operation in accordance with this equipment standard.		Passed
Modification of data		Data used during operation and stored in the system shall be protected in such a way that necessary modifications and amendments by the user cannot endanger its integrity and correctness.		Passed

3.1.3 10.1.3 Additional features

(See 4.1.4)

10.1.3.1 Purpose

To ensure that any additional or optional features do not adversely affect operation of the EUT.

10.1.3.2 Method of measurement

Operate the EUT in standard test environment and enable any additional features provided. Repeat tests that might be affected by the additional feature.

10.1.3.3 Required results

The requirements of 4.1.4 shall be met.

2017-07-26	Tester: Me	Test details: Additional features	
Test item	Check	Remark	Result
Enable all additional features. Repeat tests that might be affected by the additional features			
Repetition of test	Check that the additional features do not degrade the performance of the equipment.		Passed
Repetition of test	Check that the additional features do not degrade the performance of the equipment.		Passed

3.2 10.2 Modes of operation

(See 6.4)

3.2.1 10.2.1 Autonomous mode

3.2.1.1 10.2.1.1 Transmit position reports

10.2.1.1.1 Purpose

The purpose of this test is to ensure that the EUT transmits in the autonomous mode.

10.2.1.1.2 Method of measurement

Set up standard test environment. Record the VDL communication and check for messages transmitted by the EUT.

10.2.1.1.3 Required result

Confirm that the EUT transmits Messages 18 and 24 part A and B following the autonomous continuous schedules, alternating between channels A and B.

2017-05-02	Tester: Me	Test details: Transmission of position reports	
Test item	Check	Remark	Result
Setup standard environment			
Message 18	Check that the Message 18 is transmitted continuously.		Passed
Message 24 A	Check that the Message 24 A is transmitted continuously.		Passed
Message 24 B	Check that the Message 24 B is transmitted continuously.		Passed
Message 27	Check that the Message 27 is not transmitted when the default setting is used		Passed
Channels	Check that the transmissions alternate between channel A and B.		Passed

3.2.1.2 10.2.1.2 Receive AIS Class A position reports

10.2.1.2.1 Purpose

The purpose of this test is to ensure that the EUT receives AIS Class A position reports in the autonomous mode.

10.2.1.2.2 Method of measurement

Set up standard test environment. Perform the tests below and validate the required result for each test.

- Switch on test targets, and then start operation of the EUT.
- Start operation of the EUT, and then switch on test targets.
- Transmit test targets using same time slots on channels A and B.
- Transmit test targets that are not synchronised to time slot boundaries on channels A and B.

Check the VDL communication and external interface of the EUT and, where provided, display.

10.2.1.2.3 Required result

Confirm that the EUT receives continuously under the conditions above and outputs the received messages on the external interface in accordance with IEC 61162 and, where provided, on the display.

2017-05-02	Tester: Me	Test details: Receive Class A position reports		
Test item	Check	Remark	Result	
Switch on test targets, and then start operation of EUT.				
Check the following items on VDM output of the PI compared with the transmitted values.				
Received targets	Check that the received targets are continuously output as VDM.		Passed	
	Check that the VDM sentences are correct according to IEC 61162.		Passed	
Optional display	Check that the targets are displayed on the display.	No display implemented	N/A	
Targets on same slots on A and B	Check that both targets which use the same slots on A and B are output as VDM.		Passed	
Unsynchronized targets	Check that unsynchronized targets are output as VDM.		Passed	
Start operation of EUT, and then switch on test targets.				
Check the following items on VDM output of the PI compared with the transmitted values.				
Received targets	Check that the received targets are continuously output as VDM.		Passed	

3.2.1.3 10.2.1.3 Receive AIS Class B "SO" position reports

10.2.1.3.1 Purpose

The purpose of this test is to ensure that the EUT receives AIS Class B "SO" position reports in the autonomous mode.

10.2.1.3.2 Method of measurement

Set up standard test environment. Simulate at least one additional Class B "SO" test target (bit stuffing shall not exceed 4 bits). Perform the tests below and validate the required result for each test.

- Switch on test targets, and then start operation of the EUT.
- Start operation of the EUT, and then switch on test targets.
- Transmit test targets using same time slots on channels A and B.
- Transmit test targets that are not synchronised to time slot boundaries on channels A and B.

Check the VDL communication and external interface of the EUT and, where provided, display.

10.2.1.3.3 Required result

Confirm that the EUT receives continuously under the conditions above and outputs the received messages on the external interface and, where provided, on the display.

2017-05-02	Tester: Me	Test details: Receive Class B SO position reports	
Test item	Check	Remark	Result
a) Switch on test targets, and then start operation of the EUT. Check the following items on VDM output of the PI compared with the transmitted values.			
Received targets	Check that the received targets are continuously output as VDM.		Passed
	Check that the VDM sentences are correct according to IEC 61162.		Passed
Optional display	Check that the targets are displayed on the display.	No display is implemented	N/A
Targets on same slots on A and B	Check that both targets which use the same slots on A and B are output as VDM.		Passed
Unsynchronized targets	Check that unsynchronized targets are output as VDM.		Passed
b) Start operation of the EUT, and then switch on test targets. Check the following items on VDM output of the PI compared with the transmitted values.			
Received targets	Check that the received targets are continuously output as VDM.		Passed

3.2.1.4 10.2.1.4 Receive AIS Class B "CS" position reports

10.2.1.4.1 Purpose

The purpose of this test is to ensure that the EUT receives AIS Class B "CS" position reports in the autonomous mode.

10.2.1.4.2 Method of measurement

Set up standard test environment. Simulate at least one additional Class B "SO" test target (bit stuffing shall not exceed 4 bits). Perform the tests below and validate the required result for each test.

- Switch on test targets, and then start operation of the EUT.
- Start operation of the EUT, and then switch on test targets.
- Transmit test targets using same time slots on channels A and B.
- Transmit test targets that are not synchronised to time slot boundaries on channels A and B.

Check the VDL communication and external interface of the EUT and, where provided, display.

10.2.1.4.3 Required result

Confirm that the EUT receives continuously under the conditions above and outputs the received messages on the external interface and, where provided, on the display.

2017-05-02	Tester: Me	Test details: Receive Class B CS position reports	
Test item	Check	Remark	Result
a) Switch on test targets, and then start operation of the EUT. Check the following items on VDM output of the PI compared with the transmitted values.			
Received targets	Check that the received targets are continuously output as VDM.		Passed
	Check that the VDM sentences are correct according to IEC 61162.		Passed
Optional display	Check that the targets are displayed on the display.	No display is implemented	N/A
Targets on same slots on A and B	Check that both targets which use the same slots on A and B are output as VDM.		Passed
Unsynchronized targets	Check that unsynchronized targets are output as VDM.		Passed
b) Start operation of the EUT, and then switch on test targets. Check the following items on VDM output of the PI compared with the transmitted values.			
Received targets	Check that the received targets are continuously output as VDM.		Passed

3.2.1.5 10.2.1.5 Receive in time slot adjacent to own transmission

10.2.1.5.1 Purpose

The purpose of this test is to ensure that the EUT receives position reports in the slot adjacent to own transmission in the autonomous mode.

10.2.1.5.2 Method of measurement

Set up standard test environment. Simulate 80 % VDL loading. The reporting interval of the EUT may be decreased for the purpose of this test.

Check the external Interface of the EUT.

10.2.1.5.3 Required result

Confirm that the EUT continuously receives messages in the slots before and after own transmission with an acceptable loss of 5 %.

2017-07-24	Tester: Me	Test details: Receive in adjacent slots		
Test item	Check	Remark	Result	
Setup standard environment. Simulate 80% VDL load. Test scenario: The EUT is operated in slot assigned mode. Specific targets are transmitted in the slots before and after the EUT Tx slots. The receiving probability of these targets is evaluated.				
Target transmissions in slots adjacent to own Tx slots	Check that target reports are received in the slot before the own Tx slot with < 5% loss.		Passed	
	Check that target reports are received in the slot after the own Tx slot with < 5% loss.		Passed	

3.2.1.6 10.2.1.6 High VDL loading reception test

10.2.1.6.1 Purpose

The purpose of this test is to ensure that the EUT receives position reports under high VDL loading in the autonomous mode.

10.2.1.6.2 Method of measurement

Set up standard test environment. Simulate 90 % VDL loading.

Check the external Interface of the EUT.

10.2.1.6.3 Required result

Confirm that the EUT continuously receives messages and outputs the received messages on the external interface with a loss of not more than 2 %.

2017-07-24	Tester: Me	Test details: High VDL loading test	
Test item	Check	Remark	Result
Setup standard environment.			
Simulate 90% VDL load.	Check that target reports are received with < 2% loss.		Passed

3.2.2 10.2.2 Single messages

3.2.2.1 10.2.2.1 Transmit an addressed binary message

10.2.2.1.1 Method of measurement

Set up standard test environment and operate EUT in autonomous mode.

- a) Initiate the transmission of an addressed binary Message 6 by the EUT using an ABM sentence input. An acknowledgement Message 7 shall be applied. Record the transmitted messages.
- b) Repeat the test without acknowledgement.
- c) Repeat test with a Message 6 exceeding 2 slots.
- d) Apply more than 3 ABM sentences with 1 slot Message 6 to the EUT.
- e) Repeat test a) with the addressed unstructured binary Message 25.
- f) Repeat tests a), b) and d) with the addressed structured binary Message 25.
- g) Repeat test a) with a single addressed unstructured binary Message 26.
- h) Repeat tests a), b), c) and d) with a single addressed structured binary Message 26.

10.2.2.1.2 Required results

Check that

- a) the EUT transmits Message 6 as appropriate within 30 s. Check the content of Message 6. Check that the EUT outputs the appropriate ABK sentence.
- b) the EUT transmits Message 6 as appropriate. Check that the EUT outputs the appropriate ABK sentence indicating that no acknowledgment has been received. Check that the EUT does not retransmit Message 6.
- c) the EUT does not transmit Message 6. Check that the EUT outputs the appropriate ABK sentence indicating that the message could not be sent.
- d) the EUT transmits the first 3 Message 6s and does not transmit all following Message 6s within one frame. Check that the EUT outputs the appropriate ABK sentence indicating that the message could not be sent.
- e) the EUT transmits Message 25 as appropriate.
- f) the EUT transmits Message 25 as appropriate.
- g) the EUT transmits Message 26 as appropriate.
- h) the EUT transmits Message 26 as appropriate.

2017-05-03	Tester: Me	Test details: a) Addressed binary Message 6 with acknowledgement		
Test item		Check	Remark	Result
Transmit an addressed binary message 6 by sending an ABM sentence to the PI				
PI sentence: File AIABM_bin.sst:				
Apply an acknowledgement Message 7 on the VDL				
Transmission	Check that message 6 is transmitted within 30 s.			Passed
	Check the VDO output on PI for correct format and content.			Passed
	Check the VDL transmission for correct content.			Passed
Message sequence number	Check that sequence number in VDL message = Sequential message identifier of ABM sentence.			Passed
Repetition	Check that message 6 is not repeated.			Passed
AIABK acknowledgement	Check AIABK sentence, status = 0.			Passed

2017-05-03	Tester: Me	Test details: b) Addressed binary message 6 without acknowledgement		
Test item		Check	Remark	Result
Transmit an addressed binary message 6 by sending an ABM sentence to the PI PI sentence: File AIABM_bin.sst: No acknowledgement Message 7 on the VDL				
Transmission		Check that message 6 is transmitted within 30 s.		Passed
Repetition		Check that message 6 is not repeated.		Passed
AIABK acknowledgement		Check AIABK sentence, status = 1.		Passed

2017-05-03	Tester: Me	Test details: c) Addressed binary message 6 exceeding 2 slots		
Test item		Check	Remark	Result
Transmit an addressed binary message 6 exceeding 2 slots by ABM to the PI PI sentence: File AIABM_long.sst:				
Transmission	Check that message 6 is not transmitted.			Passed
	Check that there is no VDO output on PI.			Passed
AIABK acknowledgement	Check AIABK sentence, status = 2.			Passed

2017-05-03	Tester: Me	Test details: d) More than 3 Message 6 within one frame		
Test item		Check	Remark	Result
Apply more than 3 ABM sentences per frame for transmission of Messages 6 (1 slot) PI sentence: File AIABM_multi.sst:				
First 3 Messages	Check that the first 3 Messages 6 are transmitted within 30 s after the ABM input.			Passed
	Check AIABK sentence, status = 0.			Passed
Further messages within a frame	Check that the further Messages 6 are not transmitted.			Passed
	Check that there is an AIABK sentence for each ABK, status = 2.			Passed

2017-05-03	Tester: Me	Test details: e) Addressed unstructured binary message 25	
Test item	Check	Remark	Result
Transmit an addressed unstructured binary message 25 by sending an ABM sentence with Message type 70 to the PI. No acknowledgement is applied PI sentence: File AIABM_msg70.sst			
Transmission	Check that message 25 is transmitted within 30 s.		Passed
	Check the VDO output on PI for correct format and content.		Passed
	Check the VDL transmission for correct content.		Passed
Repetition	Check that message 25 is not repeated.		Passed
AIABK acknowledgement	Check AIABK sentence, status = 3.		Passed
	Check that Message sequence number in ABK = Sequential message identifier of ABM sentence.		Passed

2017-05-29	Tester: Me	Test details: f) Addressed structured binary message 25		
Test item		Check	Remark	Result
(a, b) Transmit an addressed structured binary message 25 by sending an ABM sentence to the PI PI sentence: File AIABM_msg25.sst No acknowledgement is applied				
Transmission	Check that message 25 is transmitted within 30 s.			Passed
	Check the VDO output on PI for correct format and content.			Passed
	Check the VDL transmission for correct content...			Passed
Repetition	Check that message 25 is not repeated.			Passed
AIABK acknowledgement	Check AIABK sentence, status = 3.			Passed
	Check that Message sequence number in ABK = Sequential message identifier of ABM sentence.			Passed
(d) Apply more than 3 ABM sentences per frame for transmissions of one slot structured Messages 25 PI sentence: File AIABM_msg25_multi.sst:				
First 3 Messages	Check that the first 3 Messages 25 are transmitted within 30 s after the ABM input.			Passed
	Check AIABK sentence, status = 3			Passed
Further messages within a frame	Check that the further Messages 25 are not transmitted.			Passed
	Check that there is an AIABK sentence for each ABK, status = 2.			Passed

2017-05-29	Tester: Me	Test details: g) Addressed unstructured binary message 26		
Test item	Check	Remark	Result	
Transmit an addressed unstructured binary message 26 by sending an ABM sentence with Message type 71 to the PI.				
PI sentence: File AIABM_msg71.sst				
Transmission	Check that message 26 is transmitted within 30 s.		Passed	
	Check the VDO output on PI for correct format and content.		Passed	
	Check the VDL transmission for correct content.		Passed	
Repetition	Check that message 26 is not repeated.		Passed	
AIABK acknowledgement	Check AIABK sentence, status =3.		Passed	
	Check that Message sequence number in ABK = Sequential message identifier of ABM sentence.		Passed	

2017-05-29	Tester: Me	Test details: h) Addressed structured binary message 26		
Test item	Check	Remark	Result	
(a, b) Transmit an addressed structured binary message 26 by sending an ABM sentence to the PI PI sentence: File AIABM_msg26.sst No acknowledgement				
Transmission	Check that message 26 is transmitted within 30 s.		Passed	
	Check the VDO output on PI for correct format and content.		Passed	
	Check the VDL transmission for correct content.		Passed	
Repetition	Check that message 26 is not repeated.		Passed	
AIABK acknowledgement	Check AIABK sentence, status = 3.		Passed	
	Check that Message sequence number in ABK = Sequential message identifier of ABM sentence.		Passed	
(c) Transmit an addressed binary message 26 exceeding 2 slots by ABM to the PI PI sentence: File AIABM_long.sst:				
Transmission	Check that message 26 is not transmitted.		Passed	
	Check that there is no VDO output on PI.		Passed	
AIABK acknowledgement	Check AIABK sentence, status = 2.		Passed	

(d) Apply more than 3 ABM sentences per frame for transmissions of one slot structured Messages 26 PI sentence: File AIABM_msg26_multi.sst:			
First 3 Messages	Check that the first 3 Messages 26 are transmitted within 30 s after the ABM input.		Passed
	Check AIABK sentence, status = 3		Passed
Further messages within a frame	Check that the further Messages 26 are not transmitted.		Passed
	Check that there is an AIABK sentence for each ABK, status = 2.		Passed

3.2.2.2 10.2.2.2 Transmit an addressed safety related Message 12

10.2.2.2.1 Method of measurement

Set up standard test environment and operate EUT in autonomous mode.

Initiate the transmission of an addressed binary Message 12 by the EUT using an ABM sentence input.

10.2.2.2.2 Required results

Check that the EUT does not transmit Message 12.

2017-05-03	Tester: Me	Test details: c) Addressed safety related Message 12	
Test item	Check	Remark	Result
Transmit an addressed safety related text message 2 by ABM to the PI PI sentence: File AIABM_bin.sst:			
Transmission	Check that message 12 is not transmitted.		Passed
	Check that there is no VDO output on PI.		Passed
AIABK acknowledgement	Check AIABK sentence, status = 2.		Passed

3.2.2.3 10.2.2.3 Acknowledgement of addressed Messages

10.2.2.3.1 Purpose

The purpose of this test is to ensure that the EUT acknowledges addressed messages in the autonomous mode.

10.2.2.3.2 Method of measurement

Operate standard test environment and the EUT in autonomous mode.

- a) Apply an addressed binary Message 6 with the EUT as destination to the VDL on Channel A.
Record transmitted messages on both channels.
- b) Repeat for Message 12.
- c) Repeat the test a) on channel B.

10.2.2.3.3 Required results

Confirm that

- a) the EUT transmits a binary acknowledge Message 7, with the appropriate sequence numbers within 4 s on the channel where the Message 6 was received.
- b) the EUT transmits a binary acknowledge Message 13, with the appropriate sequence numbers within 4 s on the channel where the Message 12 was received.
- c) the EUT transmits a binary acknowledge Message 7 on channel B.

2017-05-02	Tester: Me	Test details: a) Acknowledgement of binary message 6		
Test item	Check	Remark	Result	
Transmit an addressed binary Message 6 with EUT as destination on channel A of the VDL				
RX of messages (VDM)	Check by VDM output on PI of EUT that Message 6 is received.		Passed	
Transmission of ackn. Message 7	Check transmission of ackn. Message 7 by the EUT.		Passed	
	Check the content of Message 7.		Passed	
	Check that Message 7 is transmitted within 4 s.		Passed	
Sequence numbers	Check that sequence number in ackn. = sequence number of R _x message.		Passed	
Ackn. channel	Check that ackn. T _x channel = channel A (= Rx channel).		Passed	

2017-05-02	Tester: Me	Test details: b) Acknowledgement of safety related Message 12		
Test item		Check	Remark	Result
Transmit an addressed safety related Message 12 with EUT as destination on the VDL				
RX of messages (VDM)	Check by VDM output on PI of EUT that Message 12 is received.			Passed
Transmission of ackn. Message 13	Check transmission of ackn Message 13 by the EUT.			Passed
	Check the content of Message 13.			Passed
	Check that Message 13 is transmitted within 4 s.			Passed
Sequence numbers	Check that sequence number in ackn. = sequence number of R_x message.			Passed
Ackn. channel	Check that ackn. T_x channel = channel A (= Rx channel).			Passed

2017-05-02	Tester: Me	Test details: c) Acknowledgement on channel B		
Test item		Check	Remark	Result
Transmit an addressed binary		Message 6 with EUT as destination on channel B of the VDL		
RX of messages (VDM)		Check by VDM output on PI of EUT that Message 6 is received.		Passed
Transmission of ackn. Message 7		Check transmission of ackn. Message 7 by the EUT.		Passed
Ackn. channel		Check that ackn. T _x channel = channel B.		Passed

3.2.2.4 10.2.2.4 Transmit a broadcast binary Message 8

10.2.2.4.1 Method of measurement

Set up standard test environment and operate EUT in autonomous mode.

- a) *Initiate the transmission of a broadcast binary Message 8 by the EUT using a BBM sentence input. Record the transmitted messages.*
- b) *Repeat test with a Message 8 exceeding 2 slots.*
- c) *Apply more than 3 BBM sentences with 1 slot Message 8 to the EUT.*
- d) *Repeat test a) with the broadcast unstructured binary Message 25.*
- e) *Repeat tests a) and c) with the broadcast structured binary Message 25.*
- f) *Repeat test a) with a single broadcast unstructured binary Message 26.*
- g) *Repeat tests a), b) and c) with a single broadcast structured binary Message 26.*

10.2.2.4.2 Required results

Check that

- a) *the EUT transmits Message 8 as appropriate within 30 s. Check the content of Message 8. Check that the EUT outputs the appropriate ABK sentence.*
- b) *the EUT does not transmit Message 8. Check that the EUT outputs the appropriate ABK sentence indicating that the message could not be sent.*
- c) *the EUT transmits the first 3 Message 8s and does not transmit all following Message 8s. Check that the EUT outputs the appropriate ABK sentence indicating that the message could not be sent.*
- d) *the EUT transmits Message 25 as appropriate.*
- e) *the EUT transmits Message 25 as appropriate.*
- f) *the EUT transmits Message 26 as appropriate.*
- g) *the EUT transmits Message 26 as appropriate.*

2017-05-03	Tester: Me	Test details: a) Message 8		
Test item		Check	Remark	Result
Apply a BBM sentence with message type 8 for transmission of a binary message to the PI. PI sentence: File AIBBM_bin.sst:				
Transmission of Message 8	Check the VDO output on PI.			Passed
	Check that Message 8 is transmitted within 30 s after BBM input.			Passed
Channel	Check T _x on channel according to BBM.			Passed
AIABK acknowledgement	Record and check the AIABK acknowledgement with message type 8, status = 3			Passed
	Check that Message sequence number in ABK = Sequential message identifier of BBM sentence.			Passed
Message content	Check message content.			Passed

2017-05-03	Tester: Me	Test details: b) Message 8 exceeding 2 slots		
Test item		Check	Remark	Result
Transmit an broadcast binary message 8 exceeding 2 slots by BBM to the PI				
PI sentence: File AIBBM_long.sst:				
Transmission	Check that message 8 is not transmitted.			Passed
	Check that there is no VDO output on PI.			Passed
AIABK acknowledgement	Check AIABK sentence, status = 2.			Passed

2017-05-03	Tester: Me	Test details: c) More than 3 Message 8 within one frame		
Test item		Check	Remark	Result
Apply more than 3 BBM sentences per frame for transmission of Messages 8 (1 slot)				
PI sentence: File AIBBM_multi.sst:				
First 3 Messages	Check that the first 3 Messages 8 are transmitted within 30 s after the BBM input.			Passed
	Check AIABK sentence, status = 3.			Passed
Further messages within a frame	Check that the further Messages 8 are not transmitted.			Passed
	Check that there is an AIABK sentence for each ABK, status = 2.			Passed

2017-05-03	Tester: Me	Test details: d) Broadcast unstructured binary message 25		
Test item	Check	Remark	Result	
Transmit a broadcast unstructured binary message 25 by sending a BBM sentence with Message type 70 to the PI.				
PI sentence: File AIBBM_msg70.sst				
Transmission	Check that message 25 is transmitted within 30 s.		Passed	
	Check the VDO output on PI for correct format and content.		Passed	
	Check the VDL transmission for correct content.		Passed	
AIABK acknowledgement	Check AIABK sentence, status = 3.		Passed	
	Check Message type = 70		Passed	
	Check that Message sequence number in ABK = Sequential message identifier of BBM sentence.		Passed	

2017-05-29	Tester: Me	Test details: e) Broadcast structured binary message 25		
Test item		Check	Remark	Result
(a) Transmit a broadcast structured binary message 25 by sending an BBM sentence to the PI PI sentence: File AIABM_msg25.sst No acknowledgement				
Transmission	Check that message 25 is transmitted within 30 s.			Passed
	Check the VDO output on PI for correct format and content.			Passed
	Check the VDL transmission for correct content.			Passed
AIABK acknowledgement	Check AIABK sentence, status = 3.			Passed
	Check Message type = 25			Passed
	Check that Message sequence number in ABK = Sequential message identifier of ABM sentence.			Passed
(c) Apply more than 3 ABM sentences per frame for transmissions of structured Messages 25 (1 slot) PI sentence: File AIABM_msg25_multi.sst:				
First 3 Messages	Check that the first 3 Messages 25 are transmitted within 30 s after the ABM input.			Passed
	Check AIABK sentence, status = 3.			Passed
Further messages within a frame	Check that the further Messages 25 are not transmitted.			Passed
	Check that there is an AIABK sentence for each ABK, status = 2.			Passed

2017-05-29	Tester: Me	Test details: f) Broadcast unstructured binary message 26		
Test item	Check	Remark	Result	
Transmit a broadcast unstructured binary message 26 by sending a BBM sentence with Message type 71 to the PI.				
PI sentence: File AIBBM_msg71.sst				
Transmission	Check that message 26 is transmitted within 30 s.		Passed	
	Check the VDO output on PI for correct format and content.		Passed	
	Check the VDL transmission for correct content.		Passed	
AIABK acknowledgement	Check AIABK sentence, status = 3.		Passed	
	Check Message type = 71		Passed	
	Check that Message sequence number in ABK = Sequential message identifier of ABM sentence.		Passed	

	Tester: Ba	Test details: g) Broadcast structured binary message 26		
Test item	Check	Remark	Result	
(a) Transmit a broadcasts structured binary message 26 by sending a BBM sentence to the PI. PI sentence: File AIBBM_msg26.sst				
Transmission	Check that message 26 is transmitted within 30 s.		Passed	
	Check the VDO output on PI for correct format and content.		Passed	
	Check the VDL transmission for correct content.		Passed	
AIABK acknowledgement	Check AIABK sentence, status = 3.		Passed	
	Check Message type = 26		Passed	
	Check that Message sequence number in ABK = Sequential message identifier of BBM sentence.		Passed	
(b) Apply a BBM sentence to the PI for a broadcast binary message 26 exceeding 2 slots. PI sentence: File AIBBM_Msg26_long.sst:				
Transmission	Check that message 26 is not transmitted.		Passed	
	Check that there is no VDO output on PI.		Passed	
AIABK acknowledgement	Check AIABK sentence, status = 2.		Passed	

(c) Apply more than 3 BBM sentences per frame for transmissions of structured Messages 26 (1 slot). PI sentence: File AIBBM_msg26_multi.sst:			
First 3 Messages	Check that the first 3 Messages 26 are transmitted within 30 s after the ABM input.		Passed
	Check AIABK sentence, status = 3.		Passed
Further messages within a frame	Check that the further Messages 26 are not transmitted.		Passed
	Check that there is an AIABK sentence for each ABK, status = 2.		Passed

3.2.2.5 10.2.2.5 Transmit a broadcast safety related Message 14

10.2.2.5.1 Method of measurement

Set up standard test environment and operate EUT in autonomous mode.

Initiate the transmission of a broadcast binary Message 14 by the EUT using a BBM sentence input.

10.2.2.5.2 Required results

Check that the EUT does not transmit Message 14.

2017-05-03	Tester: Me	Test details: Broadcast safety related Message 14	
Test item	Check	Remark	Result
Apply a BBM sentence to transmit a broadcast safety related text message 14. PI sentence: File AIBBM_safety.sst:			
Transmission	Check that message 14 is not transmitted.		Passed
	Check that there is no VDO output on PI.		Passed
AIABK acknowledgement	Check AIABK sentence, status = 2.		Passed

3.2.2.6 10.2.2.6 ITDMA and RATDMA transmission

(See 7.3.4.2, 7.6)

10.2.2.6.1 Method of measurement

Set up standard test environment and operate EUT in autonomous mode.

- a) Apply a 1 slot binary broadcast message (Message 8) to the PI of the EUT less than 30 s before the next scheduled transmission. Record transmitted messages.
- b) Apply a 1 slot binary broadcast message (Message 8) to the PI of the EUT more than 30 s before the next scheduled transmission. Record transmitted messages.

10.2.2.6.2 Required results

Confirm that

- a) the EUT transmits this Message 8 within 30 s using ITDMA.
- b) the EUT transmits this Message 8 within 30 s using RATDMA.

2017-05-03	Tester: Me	Test details: ITDMA and RATDMA transmission		
Test item	Check	Remark	Result	
Apply binary broadcast Messages 8 to the PI port of the EUT. File name: AIBBM_bin.sst.				
a) Transmissions < 30 s before next scheduled position report. Reporting interval = 15 s	Check that Message 8 is transmitted within 30 s.		Passed	
	Check that ITDMA is used for slot allocation.		Passed	
b) Transmissions > 30 s before next scheduled position report. Reporting interval = 3 min	Check that Message 8 is transmitted within 30 s.	See Note)	Passed	
	Check that RADMA is used for channel access.		Passed	

Note)

With 30s, 15s and 5 s reporting interval the time from the BBM input to the next scheduled Message 18 is always shorter than 30 s.

Therefore test b) has to be performed with 3 minutes reporting interval.

With 3 minutes reporting interval a slot allocation for Message 8 is generally not possible, because Message 18 is already running in ITDMA mode to allocate the next Message 18.

Therefore with 3 minutes reporting interval always RATDMA is used, independent if the BBM is more or less than 30 s before the next scheduled transmission of message 18.

3.2.3 10.2.3 Polled mode / Interrogation response

(See 4.1.5, 7.3.4.3.4)

10.2.3.1 Purpose

The purpose of this test is to ensure that the EUT responds to interrogations.

10.2.3.2 Method of measurement

Set up standard test environment and operate the EUT in autonomous mode. Apply interrogation Message 15 with the EUT as destination:

- a) interrogation for Message 19 with transmission offset = 0;
- b) interrogation for Message 19 with transmission offset = 10;
- c) interrogation for Message 18 with transmission offset = 0;
- d) interrogation for Message 24 with transmission offset = 0.

Record transmitted messages and frame structure.

10.2.3.3 Required results

Confirm that

- a) the EUT transmits the appropriate interrogation response message within 30 s.
- b) the EUT transmits the appropriate interrogation response message as requested after defined transmission offset.
- c) the EUT transmits the appropriate interrogation response Message 18 within 30 s.
- d) the EUT transmits the appropriate interrogation response Messages 24A within 30 s and 24B within 1 min of Message 24A.

Confirm that the EUT transmits the response on the same channel as the interrogation was received.

2017-05-03	Tester: Me	Test details: Interrogation responses		
Test item	Check	Remark	Result	
a) Apply an interrogation Message 15 requesting Message 19 with slot offset = 0 on the VDL. The request is transmitted on channel A.				
R _x of request by EUT	Check that the request message is received by the EUT (VDM).		Passed	
T _x of response (VDO)	Check that response is transmitted by EUT.		Passed	
Response on VDL	Check that the response is transmitted within 30 s.		Passed	
Response channel	Check that the response is transmitted on the request channel.		Passed	

b) Apply an interrogation Message 15 requesting Message 19 with given slot offset = 10. The request is transmitted on channel B.			
R _x of request by EUT	Check that the request message is received by the EUT (VDM).		Passed
T _x of response (VDO)	Check that response is transmitted by EUT.		Passed
Response on VDL	Check that the response is transmitted with the defined slot offset.		Passed
Response channel	Check that the response is transmitted on the request channel.		Passed
c) Apply an interrogation Message 15 requesting Message 18 with slot offset = 0. The request is transmitted on channel A.			
R _x of request by EUT	Check that the request message is received by the EUT (VDM).		Passed
T _x of response (VDO)	Check that response is transmitted by EUT.		Passed
Response on VDL	Check that the response is transmitted within 30 s.		Passed
Response channel	Check that the response is transmitted on the request channel.		Passed
d) Apply an interrogation Message 15 requesting Message 24 with slot offset = 0. The request is transmitted on channel B.			
R _x of request by EUT	Check that the request message is received by the EUT (VDM).		Passed
T _x of response (VDO)	Check that response Message 24 A and 24B is transmitted by EUT.		Passed
Response on VDL	Check that Message 24 A is transmitted within 30 s after the interrogation.		Passed
	Check that Message 24 B is transmitted within 1 min after 24 A		Passed
Response channel	Check that Message 24 A and 24 B are transmitted on the request channel.		Passed

3.3 10.3 Channel selection

(See 6.2)

3.3.1 10.3.1 Valid channels

10.3.1.1 Purpose

The purpose of this test is to ensure that the EUT responds appropriately when given instructions to change to valid channels.

10.3.1.2 Method of measurement

Set up standard test environment and operate the EUT in autonomous mode. Switch the EUT to different channels within the operating band as specified in 6.2 by transmission of channel management Message 22, broadcast and addressed to the EUT.

Record the VDL Messages on the designated channels and check "band flag" and "Message 22 flag" in Message 18.

10.3.1.3 Required results

Confirm that the EUT switches to the correct channel and uses the correct "band flag" and "Message 22 flag".

2017-05-29	Tester: Me	Test details: Valid channels		
Test item		Check	Remark	Result
Apply a Message 4 and a broadcast Message 22 with area settings and valid channels to the VDL. Position is inside the channel management area.				
Broadcast Message 22	Check that channels are used.		Passed	
	Check that the Band flag in Message 18 = 1 (whole band).		Passed	
	Check that the Message 22 flag in Message 18 = 1 (Message 22 is supported).		Passed	
	Check TXT output at PI.		Passed	
	Check ACA output at PI.		Passed	
Apply a Message 4 and a broadcast Message 22 with area settings and other valid channels to the VDL.				
Other valid channels	Check that channels are used.		Passed	
	Check TXT output at PI.		Passed	
	Check ACA output at PI.		Passed	
Apply an addressed Message 22 with valid channels to the VDL. Position inside a valid area.				
Addressed Message 22	Check that channels are used.		Passed	
	Check TXT output at PI.		Passed	
	Check ACA output at PI.		Passed	

Note)

For an addressed message 22 a Message 4 is not required because the message is addressed explicitly to a specific station. Different to a broadcast message the 120 NM evaluation is not necessary for an addressed messages.

In ITU-R M.1371-5, Annex 8, section 3.20 there are 2 alternatives:

- As a broadcast message, accompanied by a Message 4 for evaluation of the message within 120 NM
- Alternatively as an addressed message. For this alternative Message 4 is not mentioned

3.3.2 10.3.2 Invalid channels

10.3.2.1 Purpose

The purpose of this test is to ensure that the EUT responds appropriately when given instructions to change to invalid channels.

10.3.2.2 Method of measurement

Set up standard test environment and operate the EUT in autonomous mode. Apply a Message 22 with 25 kHz channels not specified in Recommendation ITU-R M. 1084-5.

Record the VDL messages on the designated channels.

10.3.2.3 Required results

Confirm that the EUT disregards Message 22.

2017-05-29	Tester: Me	Test details: Invalid channels		
Test item		Check	Remark	Result
Apply an addressed Message 22 with invalid channels with 25 kHz spacing to the VDL. Position is inside a valid channel management area.				
Addressed Message 22, Invalid channels		Check that channels are not used.		Passed
		Check that there is no TXT ID 36 output on PI.		Passed
		Check that there is no ACA output on PI.		Passed

3.4 10.4 Internal GNSS receiver

(See 6.3)

The following relevant tests according to the IEC 61108 series shall be performed:

- *position accuracy, static;*
- *position accuracy, dynamic;*
- *COG/SOG accuracy;*
- *position update;*
- *status indications (including RAIM, when implemented);*
- *differential mode.*

The test of the Internal GNSS receiver is not part of this test report.

3.5 10.5 AIS information

3.5.1 10.5.1 Information content

(See 6.5.1)

10.5.1.1 Purpose

The purpose of this test is to ensure that the EUT transmits all parameters in static and dynamic Class B AIS Messages.

10.5.1.2 Method of measurement

Set up standard test environment and operate the EUT in autonomous mode. Apply all static data to the EUT.

Record all Messages on VDL and check the content of position report Message 18 and static data reports, Messages 24A and 24B.

10.5.1.3 Required results

Confirm that data transmitted by the EUT complies with static data and position sensor data.

2017-05-29	Tester: Me	Test details: Content of Message 18		
Test item		Check	Remark	Result
Internal GNSS is in use, no external position/speed sensor inputs. Apply Heading sensor data if the optional heading input is implemented.				
MMSI	Check MMSI.		Passed	
Speed	Check the SOG value.		Passed	
Position accuracy flag	Check PA flag.		Passed	
Position	Check the values of LAT and LON.		Passed	
Heading	Check that the values of heading.		Passed	
COG	Check the COG value.		Passed	
Time stamp	Check time stamp.		Passed	
Class B unit flag	Check that the Class B unit flag = 0 (Class B SOTDMA).		Passed	
Display flag	Check that the Class B Display flag is according to the composition.		Passed	
DSC flag	Check that the DSC flag is set to 1.		Passed	
Band flag	Check that the Band flag is set to 1.		Passed	
Message 22 flag	Check that the Message 22 flag is set to 1.		Passed	
RAIM flag	Check the RAIM flag.		Passed	
Other content	Other content of message 18 like mode flag or comm state are checked in separate tests.			

2017-05-29	Tester: Me	Test details: Content of Message 24		
Test item		Check	Remark	Result
Content of message 24 A				
MMSI	Check value in Message 24A.			Passed
Part number	Check part number = 0.			Passed
Name of ship	Check value in Message 24A.			Passed
Content of message 24 B				
MMSI	Check value in Message 24B.			Passed
Part number	Check part number = 1.			Passed
Type of ship and cargo type	Check value in Message 24B.			Passed
Vendor ID	Check Manufacturer's ID.			Passed
	Check Unit model code.			Passed
	Check Unit serial number.			Passed
Call sign	Check Call sign.			Passed
Dimension of ship/ reference for position	Check dim/ref A value.			Passed
	Check dim/ref B value.			Passed
	Check dim/ref C value.			Passed
	Check dim/ref D value.			Passed
Type of EPFS	Check Type of EPFS.			Passed

3.5.2 10.5.2 Information update intervals

(See 6.5.2)

3.5.2.1 10.5.2.1 Autonomous reporting interval

10.5.2.1.1 Purpose

The purpose of this test is to ensure that the EUT adopts the correct reporting interval for its SOG.

10.5.2.1.2 Method of measurement

Set up standard test environment and operate the EUT in autonomous mode.

- a) *Start with own SOG of 1 kn; record all Messages on VDL for at least 30 min and evaluate reporting interval for position report of the EUT by calculating average transmission offset over test period.*
- b) *Increase speed to 3 kn.*
- c) *Increase speed to 15 kn.*
- d) *Increase speed to 24 kn.*
- e) *Reduce speed to 22 kn.*
- f) *Reduce speed to 13 kn.*
- g) *Reduce speed to 1 kn.*

Record all messages on VDL and check transmission offset between two consecutive transmissions.

10.5.2.1.3 Required results

Confirm that

- a) *the reporting interval is 3 min (± 10 s);*
- b) *the reporting interval is 30 s (± 3 s);*
- c) *the reporting interval is 15 s ($\pm 1,5$ s);*
- d) *the reporting interval is 5 s ($\pm 0,5$ s);*
- e) *the reporting interval is 15 s;*
- f) *the reporting interval is 30 s;*
- g) *the reporting interval is 3 min.*

This test is performed in two steps:

- *one test sequence to evaluate the rescheduling to the different reporting intervals*
- *one test sequence to evaluate the average transmission offset and transmission intervals. In this test the EUT is operated with each reporting interval for at least 30 minutes.*

2017-07-24	Tester: Me	Test details: Change of reporting rate by speed		
Test item		Check	Remark	Result
Increase speed according to the test items.				
a) Speed = 1 kn		Check that reporting interval is 3 minutes.		Passed
b) Speed = 3 kn		Check releasing slot of the old reporting interval.		Passed
		Check slot allocation for new reporting interval.		Passed
		Check that reporting interval is 30 s.		Passed
c) Speed = 15 kn		Check releasing slot of the old reporting interval.		Passed
		Check slot allocation for new reporting interval.		Passed
		Check that reporting interval is 15 s.		Passed
d) Speed = 24 kn		Check releasing slot of the old reporting interval.		Passed
		Check slot allocation for new reporting interval.		Passed
		Check that reporting interval is 5 s.		Passed
Decrease speed according to the test items.				
e) Speed = 22 kn		Check releasing slot of the old reporting interval.		Passed
		Check slot allocation for new reporting interval.		Passed
		Check that reporting interval is 15 s.		Passed
f) Speed = 13 kn		Check releasing slot of the old reporting interval.		Passed
		Check slot allocation for new reporting interval.		Passed
		Check that reporting interval is 30 s.		Passed
g) Speed = 1 kn		Check releasing slot of the old reporting interval.		Passed
		Check slot allocation for new reporting interval.		Passed
		Check that reporting interval is 3 minutes.		Passed

2017-07-24	Tester: Ba	Test details: Average values		
Test item	Check	Remark	Result	
Modify speed to establish the required reporting intervals. Run the test of each reporting interval for at least 30 min.				
a) Speed = 1 kn	Check that the average reporting interval is 3 minutes +/- 10s.		Passed	
	Check that the transmission slots are randomly distributed over the selection interval of 20% of 180 s = 36 s = 1350 slot.		Passed	
	Check that the slot offsets are in a range of 180 s +/- 36s = 6750 +/- 1350 slots = 5400...8100 slots.		Passed	
b) Speed = 3 kn	Check that the average reporting interval is 30 s +/- 3 s.		Passed	
	Check that the transmission slots are randomly distributed over the selection interval 20% of 30s = 6 s = 225 slots.		Passed	
	Check that the slot offsets are in a range of 30 s +/- 6 s = 1125 +/- 450 slots = 900...1350 slots.		Passed	
b) Speed = 15 kn	Check that the average reporting interval is 15 s +/- 1.5 s		Passed	
	Check that the transmission slots are randomly distributed over the selection interval 20% of 15s = 3 s = 112.5 slots.		Passed	
	Check that the slot offsets are in a range of 15 s +/- 3 s = 562.5 +/- 112.5 slots = 450...675 slots.		Passed	
b) Speed = 24 kn	Check that the average reporting interval is 5 s +/- 0.5 s.		Passed	
	Check that the transmission slots are randomly distributed over the selection interval 20% of 5s = 1 s = 37.5 slots.		Passed	
	Check that the slot offsets are in a range of 5 s +/- 1 s = 178.5 +/- 37.5 slots = 150...225 slots.		Passed	

3.5.2.2 10.5.2.2 Polite behavior

10.5.2.2.1 Purpose

The purpose of this test is to ensure that the EUT adopts the correct reporting interval dependent on VDL loading and SOG.

10.5.2.2.2 Method of measurement

Set up standard test environment and operate the EUT in autonomous mode. Simulate a VDL loading of 55 %. Record all messages.

- a) Start with own SOG of 1 kn.*
- b) Increase speed to 20 kn.*
- c) Reduce VDL loading to 40 %.*
- d) Reduce VDL loading to 30 %.*
- e) Increase VDL loading to 45 %.*
- f) Increase VDL loading to 55 %.*
- g) Increase speed to 30 kn.*
- h) Reduce VDL loading to 40 %.*
- i) Reduce VDL loading to 30 %.*
- j) Increase VDL loading to 45 %.*
- k) Increase VDL loading to 55 %.*
- l) Reduce speed to 10 kn.*
- m) Reduce VDL loading to 30 %.*

Record all messages on the VDL.

10.5.2.2.3 Required results

Confirm that

- a) the reporting interval is 3 min,*
- b) the reporting interval of 30 s has been established,*
- c) the reporting interval of 30 s is maintained,*
- d) the reporting interval decreases to 15 s within 4 min to 5 min,*
- e) the reporting interval of 15 s is maintained,*
- f) the reporting interval increases to 30 s within 4 min to 5 min,*
- g) the reporting interval decreases to 15 s,*
- h) the reporting interval of 15 s is maintained,*
- i) the reporting interval decreases to 5 s within 4 min to 5 min,*
- j) the reporting interval of 5 s is maintained,*
- k) the reporting interval increases to 15 s within 4 min to 5 min,*
- l) the reporting interval increases to 30 s,*

m) the reporting interval of 30 s is maintained.

2017-07-27		Tester: Me		Test details: Test of polite behaviour			
Apply speed and VDL load according to the test items. Check the required reporting interval							
No.	SOG (kn)	VDL load (%)	Interval			Remark	Result
			Norm.	Redu.	Required		
a	1	55	3 min	3 min	3 min		Passed
b	20	55	15 s	30 s	30s		Passed
c	20	40	15 s	30 s	30s		Passed
d	20	30	15 s	30 s	15 s within 4...5 min		Passed
e	20	45	15 s	30 s	15 s		Passed
f	20	55	15 s	30 s	30 s within 4...5 min		Passed
g	30	55	5 s	15 s	15 s		Passed
h	30	40	5 s	15 s	15 s		Passed
i	30	30	5 s	15 s	5 s within 4...5 min		Passed
j	30	45	5 s	15 s	5 s		Passed
k	30	55	5 s	15 s	15 s within 4...5 min		Passed
l	10	55	30 s	30 s	30 s		Passed
m	10	30	30 s	30 s	30 s		Passed

3.5.2.3 10.5.2.3 Static data reporting interval

10.5.2.3.1 Purpose

The purpose of this test is to ensure that the EUT maintains the static data-reporting interval.

10.5.2.3.2 Method of measurement

Set up standard test environment and operate the EUT in autonomous mode. Record the transmitted messages and check for static data Messages 24A and 24B.

Repeat the test at an assigned reporting interval of 5 s for Message 18.

10.5.2.3.3 Required results

Confirm that the EUT transmits Messages 24A and 24B every 6 min. Confirm that Message 24B is transmitted within 1 min of transmission of Message 24A, and on the same channel. Transmissions shall alternate between channels A and B, and shall be independent of the Message 18 reporting interval.

2017-07-27	Tester: Me	Test details: ITDMA transmission of Message 24	
Test item	Check	Remark	Result
Set the reporting interval of message 18 to 30 s.			
Reporting interval	Check that the reporting interval of Message 24A and 24B is 6 min.		Passed
	Check that Message 24B is transmitted within 1 min after 24A.		Passed
	Check that Message 24B is transmitted on the same channel as 24A.		Passed
Message type for allocation	Check that the slots for Message 24A and 24B are allocated by Message 18 with ITDMA comm state.		Passed
Number of slots	Check that the number of slots = 1 (value in comm state = 0).		Passed
Slot allocation	Check that the slots allocated by Message 18 are used for Tx of Message 24A and 24B.		Passed
Alternating channels	Check that the pairs of Message 24A/24B are transmitted on alternating channels.		Passed
Independent transmission schedule	Check that the transmission schedule of Message 24A/24B is independent of the Tx schedule of Message 18.		Passed

Set the reporting interval of message 18 by rate assignment to 5 s.			
Reporting interval	Check that the reporting interval of Message 24A and 24B is 6 min.		Passed
	Check that Message 24B is transmitted within 1 min after 24A.		Passed
	Check that Message 24B is transmitted on the same channel as 24A.		Passed
Message type for allocation	Check that the slots for Message 24A and 24B are allocated by Message 18 with ITDMA comm state.		Passed
Number of slots	Check that the number of slots = 1 (value in comm state = 0).		Passed
Slot allocation	Check that the slots allocated by Message 18 are used for Tx of Message 24A and 24B.		Passed
Alternating channels	Check that the pairs of Message 24A/24B are transmitted on alternating channels.		Passed
Independent transmission schedule	Check that the transmission schedule of Message 24A/24B is independent of the Tx schedule of Message 18.		Passed

3.6 10.6 Initialisation period

(See 6.5.2, 6.5.4)

10.6.1 Purpose

The purpose of this test is to ensure that the EUT starts to transmit within the permissible initialisation period.

10.6.2 Method of measurement

Set up standard test environment with SOG > 2 kn.

- Switch on the EUT from cold (off-time minimum 1 h) with the EUT operating in autonomous mode.
- Switch off the EUT for between 15 min to 60 min and switch on again.
- Make the GNSS sensor position unavailable.

Record transmitted messages.

10.6.3 Required results

Confirm that the EUT

- starts regular transmission of Message 18 within 2 min and valid position within 30 min after switch on,
- starts regular transmission of Message 18 within 2 min and valid position within 5 min after switch on,
- continues transmission with last known position and time stamp "63" (positioning system inoperative) with a reporting interval of 3 min. Change to default position values (91, 181) after 30 min.

2017-05-29	Tester: Me	Test details: Initialisation period		
Test item	Check	Remark	Result	
Power is off for at least 1 hour				
Apply a speed > 2 kn.				
a) Switch power on.	Check that EUT starts transmission of Message 18 within 2 min.		Passed	
	Check that EUT has a valid position within 30 min.		Passed	
b) Switch power off for 15 ... 60 min.	Check that EUT starts transmission of Message 18 within 2 min.		Passed	
	Check that EUT has a valid position within 5 min.		Passed	
c) Make GNSS unavailable.	Check that EUT continues transmission with last known position.		Passed	
	Check that time stamp = 63.		Passed	
	Check that reporting interval = 3 min.		Passed	
After 30 min	Check that position = default.		Passed	

3.7 10.7 Alarms and indications, fall-back arrangements

(See 6.6)

3.7.1 10.7.1 Built in integrity test

10.7.1.1 Purpose

The purpose of this test is to ensure that the EUT has a BIIT.

10.7.1.2 Method of measurement

Check manufacturer's documentation on BIIT.

10.7.1.3 Required result

Verify that an indication is provided if a malfunction is detected and the appropriate ALR sentence is output on the PI.

2017-07-25	Tester: Me	Test details: Built in integrity test		
Test item		Check	Remark	Result
Check manufacturer's documentation on BIIT.		Check that a malfunction indication is provided.		Passed
		Check that an appropriate ALR sentence is output on the PI if a malfunction is detected.		Passed

3.7.2 10.7.2 Transceiver protection

(See 7.6)

10.7.2.1 Purpose

The purpose of this test is to ensure that the EUT is capable of withstanding open and short circuit to the VHF-antenna terminals.

10.7.2.2 Method of measurement

Set up standard test environment and operate the EUT in autonomous mode with SOG > 23 kn.

- Open circuit VHF-antenna terminals of the EUT for at least 5 min.
- Short circuit VHF-antenna terminals of the EUT for at least 5 min.
- Reconnect the VHF-antenna.

10.7.2.3 Required results

Check that

- an alarm sentence ALR with alarm ID 002 is sent to the PI,
- an alarm sentence ALR with alarm ID 002 is sent to the PI,
- the EUT shall be operative again after refitting the antenna, without damage to the transceiver and check that an alarm sentence ALR with a deactivated alarm ID 002 is sent to the PI.

2017-05-29	Tester: Me	Test details: Transceiver protection		
Test item		Check	Remark	Result
Apply a speed > 23 kn (5 s reporting interval).				
a) open circuit the VHF antenna terminal for at least 5 min.		Check that ALR ID 002 is output.		Passed
		Check that the malfunction indication is activated.		Passed
b) short circuit the VHF antenna terminal for at least 5 min.		Check that ALR ID 002 is output.		Passed
		Check that the malfunction indication is activated.		Passed
c) Reconnect the VHF antenna.		Check that ALR ID 002 is output indicating the deactivation.		Passed
		Check that the EUT is not damaged and continuous normal operation.		Passed
		Check that the malfunction indication is deactivated.		Passed

3.7.3 10.7.3 Transmitter shutdown procedure

10.7.3.1 Purpose

The purpose of this test is to ensure that the EUT has a shutdown procedure that is independent of the operating system software.

10.7.3.2 Method of measurement

Check manufacturer's documentation on transmitter shutdown procedure.

10.7.3.3 Required result

Verify that a transmitter shutdown procedure, independent of the operating software, is provided (see 6.6.2).

2017-07-27	Tester: Me	Test details: Transmitter shutdown procedure		
Test item		Check	Remark	Result
Check manufacturer's documentation on Transmitter shutdown procedure.		Verify the transmitter shutdown procedure.		Passed
		Verify that the transmitter shutdown procedure is independent of software.		Passed

3.7.4 10.7.4 Position sensor fallback conditions

10.7.4.1 Purpose

The purpose of this test is to ensure that the EUT uses position source, position accuracy flag, RAIM flag and position information in accordance with Table 3.

10.7.4.2 Method of measurement

Set up standard test environment and operate the EUT in autonomous mode.

Apply position sensor data such that the EUT operates as follows:

- internal DGNSS in use (corrected by Message 17);
- internal DGNSS in use (corrected by a beacon), if implemented;
- internal GNSS in use;
- no sensor position in use.

Check the position accuracy and RAIM flag in the VDL Message 18 and, where provided, the ALR sentence.

10.7.4.3 Required result

Verify that the use of position source, position accuracy flag, RAIM flag and position information complies with Table 3.

Verify that the position sensor status is maintained for the next scheduled report and changed for subsequent reports.

Verify that the EUT does not accept Message 17 from a station using a non-base station MMSI.

2017-05-29	Tester: Me	Test details: Check of position sensor fall-back conditions	
Test item	Check	Remark	Result
Provide GNSS signal according to the test items, changing upwards			
No GNSS signal available	Check that position = default.		Passed
	Check that PA flag = 0.		Passed
	Check the RAIM flag = 0.		Passed
	Check that ALR ID 007 is output.		Passed
	Check that ALR ID 026 is output.		Passed
	Check that ALR ID 029 is output.		Passed
	Check that ALR ID 030 is output.		Passed
Provide a GNSS signal	Check that position is correct.		Passed
	Check that PA flag = 0.		Passed
	Check the RAIM flag (0 or 1 if RAIM is optionally implemented).		Passed
	Check that ALR ID 026 is output indicating inactivation of alarm.		Passed
	Check that ALR ID 026 is output indicating inactivation of alarm.		Passed
	Check that ALR ID 029 is output indicating inactivation of alarm.		Passed

	Check that ALR ID 030 is output indicating inactivation of alarm.		Passed
	Check that the status is changed after the next scheduled position report		Passed
Provide a beacon signal (Optional)	Check that position is correct.		N/A
	Check that PA flag = 1.		N/A
	Check the RAIM flag (0 or 1 if RAIM is optionally implemented).		N/A
	Check that the status is changed		N/A
Provide Message 17 on VDL (Optional)	Check that position is correct.		N/A
	Check that PA flag = 1.		N/A
	Check the RAIM flag (0 or 1 if RAIM is optionally implemented).		N/A
	Check that the status is changed after the next scheduled position report		N/A
Provide GNSS signal according to the test items, changing upwards			
Remove Message 17 on VDL (Optional)	Check that position is correct		N/A
	Check that PA flag = 0		N/A
	Check the RAIM flag (0 or 1 if RAIM is optionally implemented).		N/A
	Check that the status is changed after the next scheduled position report		N/A
Remove the beacon signal (Optional)	Check that position is correct.		N/A
	Check that PA flag = 0.		N/A
	Check the RAIM flag (0 or 1 if RAIM is optionally implemented).		N/A
	Check that the status is changed		N/A
Remove the GNSS signal	Check that time stamp = 63		Passed
	Check that PA flag = 0.		Passed
	Check the RAIM flag = 0.		Passed
	Check that the status is changed after the next scheduled position report		Passed

2017-05-29	Tester: Me	Test details: Check of Message 17 from an non-base station MMSI		
Test item		Check	Remark	Result
Connect sensor inputs and correction data according to the test items.				
<ul style="list-style-type: none">GNSS is available.Apply correction data by Message 17 from a non-base station MMSI.		Check that PA flag = 0.		Passed

3.8 10.8 User interface

3.8.1 10.8.1 Status indication

(See 6.7.1)

10.8.1.1 Purpose

The purpose of this test is to ensure that the status indicators provided on the EUT function correctly.

10.8.1.2 Method of measurement

Perform the following.

- Set up standard test environment and operate the EUT in autonomous mode.
- Send Message 23 with a quiet time to EUT.
- Disable GNSS reception.

Check status indications.

10.8.1.3 Required results

Check that

- power indicator is on and the no transmission indicator is off,
- no transmission indicator is on and reverts to off after quiet time elapse,
- the error indicator is on.

2017-05-29	Tester: Me	Test details: Status indication		
Test item		Check	Remark	Result
Operate the EUT according to the test items.				
a) Operate under normal conditions in autonomous mode.	Check that the power indicator is on.		Passed	
	The “No transmission” indicator is off.		Passed	
	Check that the “Error” indicator is off.		Passed	
b) Disable transmission by message 23 with quiet time.	Check that the power indicator is on.		Passed	
	The “No transmission” indicator is on.		Passed	
	Check that the “Error” indicator is off.		Passed	
c) Disable GNSS reception (quiet time is finished).	Check that the power indicator is on.		Passed	
	The “No transmission” indicator is off.		Passed	
	Check that the “Error” indicator is on.		Passed	

3.8.2 10.8.2 Message display

(See 6.7.1)

This test is only applicable if a message display is provided.

10.8.2.1 Purpose

The purpose of this test is to ensure that, if a display is provided, the EUT displays the required information.

10.8.2.2 Method of measurement

Set up standard test environment and operate the EUT in autonomous mode.

- Apply to the VDL Message 12 addressed to EUT.*
- Apply to the VDL Message 12 not addressed to EUT.*
- Apply to the VDL Message 14 to EUT.*
- Apply an active AIS- SART position report to EUT.*
- Apply a test mode AIS-SART position report to EUT.*
- Disable VHF antenna.*

10.8.2.3 Required results

Verify that

- the EUT displays Message 12,*
- the EUT does not display Message 12,*
- the EUT displays Message 14,*
- the EUT displays the AIS- SART position report Message 1, at least ID and position,*
- the EUT displays the AIS-SART position report Message 1, at least ID and position only if unit set to AIS-SART test mode,*
- the EUT displays the alarm status and that the error indicator is on.*

	Tester: Me	Test details: Test of optional Message display		
Test item		Check	Remark	Result
Apply messages according to the test items.				
a) Apply message 12 addressed to the EUT		Check that the message is displayed.	No display is provided	N/A
		Check that the content is correct.		N/A
b) Apply message 12 not addressed to the EUT		Check that the message is not displayed.		N/A
c) Apply message 14		Check that the message is displayed.		N/A
		Check that the content is correct.		N/A
d) Apply an active SART message 1		Check that the SART is displayed.		N/A
		Check that the MMSI is displayed.		N/A
		Check that the position is displayed.		N/A
e) Apply an SART test message 1 EUT in SART test mode		Check that the SART is displayed.		N/A
		Check that the MMSI is displayed.		N/A
		Check that the position is displayed.		N/A
e) Apply an SART test message 1 EUT not in SART test mode		Check that the SART is not displayed.		N/A
f) Disconnect VHF antenna		Check that the alarm status is displayed.		N/A
		Check that the error indicator is on.		N/A

3.8.3 10.8.3 Static data input

(See 6.4, 6.7.2)

10.8.3.1 Purpose

The purpose of this test is to ensure that static data can be input to the EUT according to the manufacturer's documentation and the MMSI cannot be changed once input.

10.8.3.2 Method of measurement

Set up standard test environment and operate the EUT in autonomous mode.

- a) Enter all static data except MMSI.*
- b) Enter an MMSI outside the valid range.*
- c) Enter an MMSI according to the manufacturer's initialisation procedure.*
- d) Enter a new MMSI.*
- e) Enter all other static data.*

10.8.3.3 Required results

Verify that

- a) the static data is correctly stored according to the manufacturer's initialisation procedure,*
- b) the unit does not accept the MMSI,*
- c) the unit accepts the MMSI as entered by the user,*
- d) the unit does not accept the MMSI as entered by the user,*
- e) static data can be changed.*

2017-05-29	Tester: Me	Test details: Static data input		
Test item		Check	Remark	Result
Input static data according to manufacturer's documentation. At test start no valid MMSI is stored in the EUT.				
a) Enter all static data except MMSI and check that they are correctly stored.	Enter and check ships name.		Passed	
	Enter and check type of ship and cargo.		Passed	
	Enter and check call sign.		Passed	
	Enter and check dimension of ship/ reference for position.		Passed	
b) Enter an MMSI outside the valid range.	Check that the MMSI is not accepted.		Passed	
c) Enter an MMSI inside the valid range.	Check that the MMSI is accepted and correctly stored.		Passed	
d) Enter a new MMSI inside the valid range.	Check that the new MMSI is not accepted.		Passed	
e) Enter all static data except MMSI and check that they are correctly stored.	Enter and check ships name.		Passed	
	Enter and check type of ship and cargo.		Passed	
	Enter and check call sign.		Passed	
	Enter and check dimension of ship/ reference for position.		Passed	

4 11 Physical tests

The physical radio tests are not part of this test report.

5 12 Specific tests of link layer

5.1 12.1 TDMA synchronisation

5.1.1 12.1.1 Synchronisation test using UTC direct and indirect

12.1.1.1 Purpose

The purpose of this test is to ensure that the EUT can operate UTC direct and indirect.

12.1.1.2 Method of measurement

Set up standard test environment; choose test conditions in a way that the EUT operates in the following synchronisation modes:

- a) *UTC direct;*
- b) *UTC indirect (internal synchronisation source disabled; at least one other station UTC direct synchronised);*
- c) *BASE direct (internal GNSS disabled; base station with UTC direct synchronisation within range);*
- d) *UTC indirect (internal GNSS receiver disabled; only Class B SO station UTC direct synchronised).*

Check all CommState parameters in position report. Check reporting interval.

12.1.1.3 Required results

Confirm that

- a) *the SynchState = 0;*
- b) *the SynchState = 1;*
- c) *the SynchState = 1;*
- d) *the SynchState = 1.*

2017-05-29	Tester: Me	Test details: TDMA Synchronisation		
Test item		Check	Remark	Result
Operate the EUT in an environment according to the test items and check the synchronisation state.				
a) Operate with GPS.		Check that sync state is 0 (UTC direct).		Passed
b) Disable GPS. At least one AIS Class A station with UTC direct.		Check that sync state is 1 (UTC indirect).		Passed
c) GPS disabled, one base station with UTC direct within range.		Check that sync state is 1 (UTC indirect).		Passed
d) GPS disabled, At least one AIS Class B SO station with UTC direct.		Check that sync state is 1 (UTC indirect).		Passed

5.1.2 12.1.2 Synchronisation test without UTC, EUT receiving semaphore

12.1.2.1 Purpose

The purpose of this test is to ensure that the EUT can synchronise to a semaphore.

12.1.2.2 Method of measurement

Set up standard test environment; choose test conditions such that the EUT operates with other units acting as follows.

- The EUT is receiving a mobile station that is acting as semaphore with no Base Stations being received.
- Introduce a Base Station that is acting as a semaphore with different timing.
- Enable internal synchronisation source.

Check all CommState parameters in position report. Check reporting interval.

12.1.2.3 Required results

Confirm that

- transmitted SynchState = 3;
- the EUT shall change synchronisation source to the Base Station;
- synchronisation mode shall revert to UTC direct, SynchState = 0.

2017-05-29	Tester: Me	Test details: TDMA Synchronisation		
Test item		Check	Remark	Result
Operate the EUT in an environment according to the test items and check the synchronisation state.				
a) GPS disabled At least one AIS Class A station as semaphore.	Check that sync state is 3.		Passed	
	Check that the EUT synchronizes to the Class A station.		Passed	
b) GPS disabled, Class A without UTC and one base station as semaphore, different timing.	Check that sync state is 2 (Base direct)		Passed	
	Check that the EUT synchronizes to the base station.		Passed	
c) Enable GPS.	Check that sync state is 0 (UTC direct)		Passed	

5.2 12.2 Time division (frame format)

12.2.1 Purpose

The purpose of this test is to ensure that the EUT uses SOTDMA correctly.

12.2.2 Method of measurement

Set the EUT to maximum reporting interval of 5 s by applying a speed of >23 kn. Record VDL Messages and check for used slots. Check parameter slot number in CommState of position report. Check slot length (transmission time).

12.2.3 Required results

Slot number used and slot number indicated in CommState shall match. Slot number shall not exceed 2249. Slot length shall not exceed 26,67 ms.

2017-05-29	Tester: Me	Test details: TDMA Synchronisation		
Test item		Check	Remark	Result
Operate the EUT with 5 s reporting interval (SOG > 23 kn).				
Slot number		Check that slot number used and slot number indicated in CommState match.		Passed
Slot count		Check that slot number does not exceed 2249.		Passed
Slot length		Check that slot length does not exceed 26.67 ms.		Passed

5.3 12.3 Synchronisation jitter

12.3.1 Definition

Synchronisation jitter (transmission timing error) is the time between nominal slot start as determined by the UTC synchronisation source and the initiation of the "transmitter on" function.

12.3.2 Purpose

The purpose of this test is to ensure that the synchronisation jitter is within the allowable tolerances.

12.3.3 Method of measurement

Set up standard test environment. Set the EUT to 5 s reporting interval using:

- a) UTC direct synchronisation;*
- b) UTC indirect synchronisation by disconnecting the synchronisation source of the EUT.*

Record VDL Messages and measure the time between the nominal beginning of the slot (Nominal T_0) and the start flag and calculate it back to T_0 .

12.3.4 Required results

The synchronisation jitter shall not exceed:

- a) $\pm 104 \mu s$ using UTC direct synchronisation;*
- b) $\pm 312 \mu s$ using UTC indirect synchronisation.*

2017-05-29	Tester: Me	Test details: Synchronisation jitter		
Test item		Check	Remark	Result
Operate the EUT with a reporting interval of 5 s (speed > 23 kn). Record the time T ₂ using the VDL analyser and and calculate it back to T ₀ .				
a) UTC direct		Check that T ₀ is in the range of +/- ±104 μs.		Passed
b) UTC indirect		Check that T ₀ is in the range of +/- ±312 μs.		Passed

5.4 12.4 Data encoding (bit stuffing)

(See 7.2.3.6)

12.4.1 Purpose

The purpose of this test is to ensure that the EUT conforms to the data encoding requirements.

12.4.2 Method of measurement

Set up standard test environment.

Set ship's name to HEX-Values "7E 3B 3C 3E 7E" so that bit stuffing will be applied and check the VDL (note that this might require that the manufacturer provides means to input this data).

12.4.3 Required results

Confirm that transmitted VDL Messages 24A and 24B conform to data input.

Data in Hex	7E 3B 3C 3E 7E
Binary (Bytes)	01111110_00111010_00111100_00111110_01111110
Binary (6 bit)	011111_100011_101000_111100_001111_100111_1110xx _ # (< O ' 8
Name in 6 bit ASCII text (Table 47 of 1371)	_#(<O'8 ('= 27h, Apostrophe) (xx bits set to 0
Binary (after 40 bit header)	xxxx01_111110_001110_100011_110000_111110_011111_10xxxx v > S h v O
Coded in 6 bit ASCII in VDM/ VDO (IEC 61162-1 Table C.1)	XXXXXXxv>ShvOx

Note: the ship's name does not affect message 24 B. Therefore there is no need to check 24 B.

2017-05-29	Tester: Me	Test details: Data encoding (bit stuffing)		
Test item	Check	Remark	Result	
Input name “_#(<O'8” to the EUT.				
Evaluate Message 24A	Check that the VDO is according to the ships name (sequence “v>ShvO”).		Passed	
	Check that the VDM is according to the ships name (sequence “v>ShvO”).		Passed	
	Check that receiver shows name as “_#(<O'8”.		Passed	

5.5 12.5 Frame check sequence

12.5.1 Purpose

The purpose of this test is to ensure that the EUT rejects Messages with invalid CRC.

12.5.2 Method of measurement

Apply simulated position report Messages with wrong CRC bit sequence to the VDL.

- a) Check test output; if a display interface is provided, check this.
- b) Repeat test 12.1.2 and check that a station transmitting Messages with wrong CRC are not used for synchronisation.

12.5.3 Required results

Confirm that Messages with invalid CRC are not accepted by the EUT in cases a) and b).

2017-05-29	Tester: Me	Test details: Frame check sequence		
Test item		Check	Remark	Result
Transmit position report message from VDL generator.				
a) Set CRC bit sequence to valid.	Check that the position reports are output as VDM on the PI port.		Passed	
	If implemented: Check that the target is displayed on the MKD.	No display implemented	N/A	
a) Set CRC bit sequence to wrong.	Check that the position reports are not output as VDM on the PI port.		Passed	
	If implemented: Check that the target is not displayed on the MKD.	No display implemented	N/A	
b) GPS disabled One AIS Class A with UTC direct, with incorrect CRC	Check that sync state is 3.		Passed	
	Check that the EUT does not synchronize to the Class A station.		Passed	
b) GPS disabled, One Class A without UTC and one base station as semaphore, both with incorrect CRC	Check that sync state is 3.		Passed	
	Check that the EUT does not synchronize to the Class A station and to the base station.		Passed	

5.6 12.6 Slot allocation (Channel access protocols)

5.6.1 12.6.1 Network entry

12.6.1.1 Method of measurement

Set up standard test environment; switch on EUT. Record transmitted scheduled position reports for the first 3 min of transmission after initialisation period. Check CommState for channel access mode.

12.6.1.2 Required results

EUT shall start autonomous transmissions of Message 18 (position report) with ITDMA CommState with Keep Flag set true for first minute of transmission and Message 18 with SOTDMA CommState thereafter.

2017-05-29	Tester: Me	Test details: Channel access protocol		
Test item		Check	Remark	Result
Switch on EUT and record data with VDL analyser.				
Operate the EUT with 5 s reporting interval (speed > 23 kn).				
Initial message type	Check that the network entry is done with Message 18 with ITDMA comm state.			Passed
Keep flag	Check that the keep flag is set in the ITDMA comm state.			Passed
Slot offsets	Check that the slot offsets the ITDMA comm state are in the range 375 +/- 37.5= 337.5 ... 412.5.			Passed
Slot use	Check that the allocated slots are used.			Passed
Comm state	Check that the Comm state is changed to SOTDMA after the first frame.			Passed
Timeout	Check that the timeout in the 2 nd frame is between 2 and 6 (Decrementd from initial 3...7).			Passed

5.6.2 12.6.2 Autonomous scheduled transmissions (SOTDMA)

12.6.2.1 Method of measurement

Set up standard test environment and operate EUT in autonomous mode.

- a) Record transmitted scheduled position reports Message 18 and check frame structure. Check CommState of transmitted messages for channel access mode and parameters number of received stations, slot timeout, slot number and slot offset.
- b) Repeat the test with 50 % channel loading ensuring there are at least 4 free slots in each SI.

12.6.2.2 Required results

Check that

- a) nominal reporting interval is achieved $\pm 20\%$ (allocating slots in selection interval SI). Confirm that the EUT allocates new slots NTS within SI after 3 min to 8 min. Check that slot offset indicated in CommState matches slots used for transmission. Check that Class B "CS" are not included in the number of received stations. Check that during DSC monitoring periods there are no time out values of "0";
- b) only free slots are used for transmission.

2017-06-13	Tester: Me	Test details: Autonomous scheduled transmissions (SOTDMA)		
Test item		Check	Remark	Result
a) Record the VDL data of 10 frames operating with autonomously scheduled transmissions. Evaluate the following test items using the recorded data. Set the condition so that the reporting rate is 5 s (SOG > 23 kn).				
Reporting rate		Check that the reporting rate is 5 s, 12 messages per frame.		Passed
Nominal increment and selection interval		Check that the allocated slots match the nominal and selection interval of 5 s reporting interval.		Passed
Slot interval		Check that the slot intervals are in the range 187.5 +/- 37.5 = 150 ... 225.		Passed
Timeout		Check that the timeout is counting down from 3...7 to 0.		Passed
Slots used		Check that the slots indicated in CommState match the slots used.		Passed
Slots allocated at timeout 0		Check that the slots are used in the next frame.		Passed
		Check the slot offset is 2250 +/-SI (2212.5...2287.5).		Passed
CommState sub message		Check that for timeout 3,5,7 the number of received stations is included.		Passed
		Check that Class B CS stations are not counted as received stations.		Passed
		Check that for timeout 2, 4, 6 the correct slot number is included.		Passed

	Check that for timeout 1 the correct value of UTC is included.		Passed
	Check that for timeout 0 the slot increment is included.		Passed
Alternating channels	Check that the position reports are transmitted on alternating channels.		Passed
b) Apply 50 % channel load on both channels			
Free slots	Check that only free slots are used for transmission		Passed

5.6.3 12.6.3 Autonomous scheduled transmissions (ITDMA)

12.6.3.1 Method of measurement

Set up standard test environment and operate EUT in autonomous mode. Set NavStatus of EUT to "at anchor" giving a reporting interval of 3 min. Record transmitted scheduled position reports.

12.6.3.2 Required results

Check that EUT transmits Message 18 with ITDMA CommState and allocates slots using ITDMA and that slot offset indicated in CommState matches slots used for transmission. Check that nominal reporting interval is achieved $\pm 20\%$.

2017-05-13	Tester: Me	Test details: Autonomous scheduled transmissions (ITDMA)		
Test item		Check	Remark	Result
Record the VDL data of at least 20 frames operating with autonomously scheduled transmissions. Evaluate the following test items using the recorded data.				
Set the condition so that the reporting rate is 3 min (SOG < 2 kn).				
Reporting rate	Check that the reporting rate is 3 min.	See test 10.5.2.1		Passed
Message type	Check that ITDMA comm state is used.			Passed
Slot interval	Check that the slot intervals are 3 min +/- 20 %.			Passed
Slot increment	Check that the slot increment = 13500 +/- 10 %.			Passed
Number of slots	Check that the number of slots = 1 (value in comm state = 5).			Passed
Keep flag	Check that the keep flag = 0.			Passed
Alternating channels	Check that the position reports are transmitted on alternating channels.			Passed

5.6.4 12.6.4 Transmission of Messages 24A and 24B (ITDMA)

12.6.4.1 Method of measurement

Set up standard test environment and operate EUT in autonomous mode. Record transmitted messages.

12.6.4.2 Required results

Confirm that EUT transmits Messages 24A and 24B using the ITDMA access scheme. The SOTDMA CommState of Messages 18 shall, as far as possible, be changed to ITDMA CommState to allocate slots for Messages 24A and 24B.

2017-05-13	Tester: Me	Test details: ITDMA transmission of Message 24		
Test item		Check	Remark	Result
Record the VDL data of at least 20 frames operating with autonomously scheduled transmissions. Set the condition so that the reporting rate is 30 s.				
Reporting interval	Check that the reporting rate of msg 24A and 24B is 6 min.	See also test 10.5.2.3	Passed	
	Check that msg 24A and 24B are transmitted on the same channel.		Passed	
Message type for allocation	Check that the comm state of 2 Message 18 are changed to ITDMA to allocate the slots for message 24 A and 24 B.		Passed	
Number of slots	Check that the number of slots = 1 (value in comm state = 0).		Passed	
Keep flag	Check that the keep flag = 1.		Passed	
Slot allocation	Check that the slots allocated by Message 18 are used for T _x of Message 24A and 24 B.		Passed	
Alternating channels	Check that the pairs of Message 24A and 24B are transmitted on alternating channels.		Passed	

5.6.5 12.6.5 Assigned operation

(See 4.1.5, 7.3.4.3.3)

5.6.5.1 12.6.5.1 Message 16 with slot assignment

12.6.5.1.1 Purpose

The purpose of this test is to ensure that the EUT can be assigned to use specific slots.

12.6.5.1.2 Method of measurement

Set up standard test environment and operate the EUT in autonomous mode (SOG < 2 kn).

- a) Transmit an assigned mode command Message 16 to the EUT with initial slot offset and increment.*
- b) Increase speed to 25 kn while still assigned to a reporting interval of 10 s.*
- c) Every 3 min send further assignment Messages with the same slot assignment.*
- d) Transmit an assigned mode command Message 16 with a non-base station MMSI to the EUT with initial slot offset and increment.*
- e) Transmit an assigned mode command Message 16 to an MMSI different to the MMSI of the EUT with initial slot offset and increment.*

Record transmitted Messages.

12.6.5.1.3 Required results

Confirm that

- a) the EUT transmits a Message 18 in the designated slots. Check that the assigned mode flag is set to 1,*
- b) the EUT stays in assigned mode using the assigned slots,*
- c) the EUT continues in assigned mode when it receives a further assignment commands by Message 16. Verify that the slot timeout value is updated for every received Message 16,*
- d) the EUT ignores Message 16 and continues autonomous mode operation,*
- e) the EUT ignores Message 16 and continues autonomous mode operation. Confirm that the EUT reverts to autonomous mode with autonomous reporting interval 4 min to 8 min after the last Message 16.*

2017-05-13	Tester: Me	Test details: Slot offset and increment		
Test item		Check	Remark	Result
a) Operate the EUT with SOG < 2 kn, autonomous reporting interval = 3 min. Apply an assignment Message 16 on channel A with offset to first assigned slot = 40 and slot increment parameter = 2 (increment = 375, interval = 10s).				
VDM output		Check VDM output of Message 16.		Passed
First message		Check that the first Message in assigned mode is sent 40 slots after Message 16.		Passed
Assigned mode flag		Check that the assigned mode flag is set to 1.		Passed
Initialisation phase (First frame)		Check that EUT continues after the first Message of the assigned mode with the network entry phase.		Passed
		Check that an ITDMA comm state is used.		Passed
Alternating channels		Check that position reports are transmitted alternating on channel A and B.		Passed
Increment		Check that the increment is 375 slots.		Passed
Timeout		Check that all slots of the first frame have the same timeout.		Passed
		Check that the timeout is between 3 and 7.		Passed
		Check that the timeout is decremented after 1 min.		Passed
CommState		Check that after the first frame a SOTDMA comm state is used.		Passed
b) Increase SOG to 25 kn (autonomous reporting interval = 5s)				
Mode		Check that the assigned mode continues.		Passed
c) Repeat Message 16 with same assignment every 3 min				
Mode		Check that the assigned mode continues.		Passed
Timeout		Check that the time-out value is updated for every received Message 16.		Passed
c) Stop transmission of Message 16				
End of assigned mode		Check that EUT reverts to autonomous mode after time-out (4...8 min after last received Message 16).		Passed
		Check that the assigned mode flag in autonomous mode is set to 0.		Passed
		Check that the Slot offset of all messages with time-out 0 is set to 0 to release the old slots.		Passed

	Check that EUT initialises autonomous mode like network entry.		Passed
d) Transmit Message 16 with slot assignment from a non-base station MMSI			
Mode	Check that the EUT ignores Message 16.		Passed
e) Transmit Message 16 with slot assignment addressed to an MMSI different to the EUT			
Mode	Check that the EUT ignores Message 16.		Passed

5.6.5.2 12.6.5.2 Message 16 with rate assignment

12.6.5.2.1 Purpose

The purpose of this test is to ensure that the EUT can be assigned reporting intervals.

12.6.5.2.2 Method of measurement

Set up standard test environment and operate the EUT in autonomous mode (SOG < 2 kn).

- Transmit an assigned mode command Message 16 to the EUT with a designated reporting interval of 5 s.
- Transmit an assigned mode command Message 16 to the EUT with the assigned reporting interval of 10 s.
- Increase speed to 25 kn while still assigned to a reporting interval of 10 s.
- Every 3 min send further assignment Messages with a reporting interval of 10 s.
- Transmit an assigned mode command Message 16 to the EUT with a non-base station MMSI.

Record transmitted Messages.

12.6.5.2.3 Required results

Confirm that

- the EUT transmits with the designated reporting interval of 5 s. Check that the assigned mode flag is set to 1,
- the reporting interval is 10 s,
- the EUT stays in assigned mode with a reporting interval of 10 s,
- the EUT continues in assigned mode when it receives a further assignment commands by Message 16. Verify that the slot timeout value in the CommState is not updated by the received Message 16,
- confirm that the EUT ignores Message 16 and continues autonomous mode operation. Confirm that the EUT reverts to autonomous mode with autonomous reporting interval 4 min to 8 min after the last Message 16.

2017-05-13	Tester: Me	Test details: Rate assignment	
Test item	Check	Remark	Result
a) Operate the EUT with SOG < 2 kn, autonomous reporting interval = 3 min. Apply an assignment message 16 with offset = 120 (reporting interval = 5s).			
VDM output	Check VDM output of Message 16.		Passed
Assigned mode flag	Check that the assigned mode flag is set to 1.		Passed
Initialisation phase (First frame)	Check that EUT starts the assigned mode with a network entry phase.		Passed
	Check that an ITDMA comm state is used.		Passed
Alternating channels	Check that position reports are transmitted alternating on channel A and B.		Passed
Increment	Check that the reporting interval is 5 s.		Passed
Timeout	Check that the timeout of the first frame is between 3 and 7.		Passed
	Check that the timeout is decremented after 1 min.		Passed
CommState	Check that after the first frame a SOTDMA comm state is used.		Passed
b) Send an assignment message 16 with offset = 60 (reporting interval = 10s)			
Reporting interval	Check that the reporting interval is 10 s.		Passed
c) Increase SOG to 25 kn (autonomous reporting interval = 5s)			
Mode	Check that the assigned mode with 10 s interval continues.		Passed
d) Repeat Message 16 with same assignment every 3 min			
Mode	Check that the assigned mode continues.		Passed
Timeout	Check that the time-out values are not updated for every received Message 16.		Passed
d) Stop transmission of Message 16			
End of assigned mode	Check that reverts to autonomous mode after time-out (4...8 min).		Passed
	Check that the assigned mode flag in autonomous mode is set to 0.		Passed
	Check that the slots of the assigned mode schedule are released with time-out 0 and slot offset = 0.		Passed
	Check that EUT initialises autonomous mode like network entry.		Passed
e) Transmit Message 16 with rate assignment from a non-base station MMSI			
Mode	Check that the EUT ignores Message 16.		Passed

5.6.5.3 12.6.5.3 Assigned mode using invalid reporting rates

12.6.5.3.1 Method of measurement

Operate standard test environment and EUT in autonomous mode. Transmit an assigned mode command Message 16 using a base station MMSI to the EUT with

- a) the number of reports per 10 min which is not a multiple of 20,
- b) the number of reports per 10 min which is higher than 120.

12.6.5.3.2 Required results

Confirm that

- a) the EUT transmits position reports Message 18 at a reporting rate that corresponds to the next highest multiple of 20 reports per 10 min,
- b) the EUT transmits position reports Message 18 at a reporting interval of 5 s.

2017-05-13	Tester: Me	Test details: Assigned Mode		
Test item		Check	Remark	Result
Send a Message 16 rate assignment with invalid offset values.				
a) Offset value = 110 (not a multiple of 20) EUT = destination ID A		Check that the reporting rate is 120/10min = 12/min = 5 s .		Passed
b) Offset value = 300 (> 120 messages/10 min) EUT = destination ID B		Check that the reporting interval is 5 s.		Passed

5.6.5.4 12.6.5.4 Slot assignment to FATDMA reserved slots

12.6.5.4.1 Definition

This test checks the operation of Message 16 assignment of slots reserved by Message 20.

12.6.5.4.2 Method of measurement

Set up the standard test environment and operate EUT in autonomous mode. Transmit a Data Link Management message (Message 20) using a base station MMSI to the EUT with slot offset and increment. Transmit an Assigned Mode Command (Message 16) using a base station MMSI to the EUT and command it to use one or more of those FATDMA allocated slots.

Record transmitted messages.

12.6.5.4.3 Required results

Confirm that the EUT uses the slots commanded by Message 16 for own transmissions.

2017-07-24	Tester: Me	Test details: Slot assignment to FATDMA reserved slots		
Test item		Check	Remark	Result
Apply a Message 4 and 20 from VDL Generator with slot offset and increment for slot reservation: Offset = 23, slots = 5, time-out = 7, incr. = 25. Apply a Message 16 from VDL Generator assigning one or more of these reserved slots: Offset = 25, incr. = 5 (= 75 slots).				
R _x of Message 4		Check that Message 4 has been received by EUT (VDM output).		Passed
R _x of Message 20		Check that Message 20 has been received by EUT (VDM output).		Passed
Slot use		Check that slots assigned by the Message 16 are used by the EUT.		Passed

5.6.6 12.6.6 Group assignment

NOTE In the tests of the following subclauses use a base station MMSI to transmit Message 23 with a geographic region so that the EUT is inside this region, unless mentioned otherwise.

5.6.6.1 12.6.6.1 Entering interval assignment

12.6.6.1.1 Method of measurement

Set up standard test environment and operate EUT in autonomous mode with a reporting interval of 15 s (SOG = 15 kn). Perform the following tests after time-out of the previous test.

- Transmit a Group Assignment command (Message 23) to the EUT with a reporting interval of 30 s assigned.
- Transmit a Group Assignment command (Message 23) to the EUT with a reporting interval of 5 s assigned.
- Using a non-base station MMSI, transmit a Group Assignment command (Message 23) to the EUT with a reporting interval of 5 s assigned.
- Transmit a Group Assignment command (Message 23) to the EUT with a reporting interval of 2 s assigned.
- Transmit a Group Assignment command (Message 23) to the EUT with a reporting interval field setting 9 (next shorter autonomous reporting interval).
- Transmit a Group Assignment command (Message 23) to the EUT with a reporting interval field setting 10 (next longer autonomous reporting interval).

Monitor the VDL.

12.6.6.1.2 Required result

Verify that

- EUT enters assigned operation mode and transmits position report Message 18 with 30 s reporting interval. Verify that EUT builds up the assigned transmission scheduled according to the network entry procedure. Verify that unused slots of the previous reporting schedule are released. Verify that the EUT reverts to autonomous mode after a time out of 4 min to 8 min building up the autonomous transmission schedule according to the network entry procedure and releases unused slots from previous schedule.
- EUT enters assigned operation mode and transmits position report Message 18 with 5 s reporting interval. Verify that EUT builds up the assigned transmission scheduled according to network entry procedure. Verify that unused slots of the previous reporting schedule are released. Verify that the EUT reverts to autonomous mode after a time out of 4 min to 8 min building up the autonomous transmission schedule according to the network entry procedure and releases unused slots from the previous schedule.
- EUT does not react on Message 23.
- EUT does not react on Message 23.
- EUT enters assigned operation mode and transmits position report Message 18 with 5 s reporting interval.
- EUT enters assigned operation mode and transmits position report Message 18 with 30 s reporting interval.

2017-05-13	Tester: Me	Test details: Entering interval assignment		
Test item		Check	Remark	Result
a) Operate the EUT with an autonomous reporting interval of 15 s. Apply a group assignment Message 23 with a reporting interval of 30 s (value 5).				
VDM output	Check VDM output of Message 23.			Passed
Initialisation phase	Check that EUT starts immediately with rescheduling to the new reporting rate.	New reporting rate starts after 1 min		Passed
Assigned mode flag	Check that Assigned mode flag = 1.			Passed
Reporting rate	Check that the reporting interval = 30 s.			Passed
Alternating channels	Check that position reports are transmitted alternating on channel A and B.			Passed
Slot deallocation	Check that the slot of the autonomous reporting interval are released using time-out = 0 and slot offset = 0.			Passed
Initialisation/ Slot allocation	Check that the slots of the assigned reporting interval are allocated according to the network entry procedure.			Passed
Timeout	Check that the assigned timeout is between 2 and 6 in the next frame.			Passed
End of assigned mode	Check that the EUT reverts to autonomous mode after 4...8 min.			Passed
b) Apply a group assignment message 23 with a reporting interval of 5 s (value 8).				
VDM output	Check VDM output of Message 23.			Passed
Initialisation phase	Check that EUT starts immediately with rescheduling to the new reporting rate.	New reporting rate starts after 30s		Passed
Assigned mode flag	Check that Assigned mode flag = 1.			Passed
Reporting rate	Check that the reporting interval = 5 s.			Passed
Alternating channels	Check that position reports are transmitted alternating on channel A and B.			Passed
Slot deallocation	Check that the slot of the autonomous reporting interval are released using time-out = 0 and slot offset = 0.			Passed
Initialisation/ Slot allocation	Check that the slots of the assigned reporting interval are allocated according to the network entry procedure.			Passed
Timeout	Check that the assigned timeout is between 2 and 6 in the next frame.			Passed
End of assigned mode	Check that the reverts to autonomous mode after 4...8 min.			Passed

c) Apply a group assignment message 23 with a reporting interval of 5 s (value 8) from a non-base station MMSI.			
Mode	Check that the EUT ignores message 23.		Passed
d) Apply a group assignment message 23 with a reporting interval of 2 s (value 11).			
Mode	Check that the EUT ignores message 23.		Passed
e) Apply a group assignment message 23 with reporting interval = next shorter interval (value 9).			
VDM output	Check VDM output of Message 23.		Passed
Mode	Check that the EUT enters assigned mode.		Passed
Reporting interval	Check that the reporting interval = 5 s.		Passed
f) Apply a group assignment message 23 with reporting interval = next longer interval (value 10).			
VDM output	Check VDM output of Message 23.		Passed
Mode	Check that the EUT enters assigned mode.		Passed
Reporting interval	Check that the reporting interval = 30 s.		Passed

5.6.6.2 12.6.6.2 Assignment by region

12.6.6.2.1 Method of measurement

Set up standard test environment and operate EUT in autonomous mode with a reporting interval of 15 s and use a base station MMSI to transmit Message 23.

- Transmit a Group Assignment command (Message 23) to the EUT (define station type 0 and geographic region so that the EUT is inside this region). Set the reporting rate to 5 s and apply message to VDL.
- Transmit a Group Assignment command (Message 23) to the EUT (define station type 0 and geographic region so that the EUT is outside this region). Set the reporting rate to 5 s and apply message to VDL.

12.6.6.2.2 Required result

Verify that

- EUT switches to assigned mode and transmits position reports with 5 s interval. Verify that EUT reverts to normal operation mode after timeout period,
- EUT declines Message 23.

2017-05-13	Tester: Me	Test details: Assignment by region		
Test item		Check	Remark	Result
Set up the standard test environment and operate EUT in autonomous mode. Operate the EUT with a reporting interval is 15 seconds (SOG = 15 kn).				
a) Transmit Message 23, EUT inside region (Reporting interval value = 8 = 5s)	Check that Message 23 is received (VDM output).		Passed	
	Check that the EUT enters assigned mode.		Passed	
	Check that the reporting interval is changed to 5 s.		Passed	
	Verify that EUT reverts to normal operation mode after 4... 8 min.		Passed	
EUT outside the addressed region				
Transmit Message 23, EUT outside region (Reporting interval = 5 s)	Verify that EUT declines Message 23. Reporting interval = 15 s.		Passed	

5.6.6.3 12.6.6.3 Assignment by station type

12.6.6.3.1 Method of measurement

Set up standard test environment and operate EUT in autonomous mode with a reporting interval of 15 s and transmit Message 23 with a reporting interval of 5 s.

- Transmit a Group Assignment command with a station type to 0 (all stations).
- Transmit a Group Assignment command with a station type to 1 (Class A).
- Transmit a Group Assignment command with a station type to 2 (All Class B).
- Transmit a Group Assignment command with a station type to 3 (SAR aircraft).
- Transmit a Group Assignment command with a station type to 4 (Class B SO).
- Transmit a Group Assignment command with a station type to 5 (Class B CS).
- Transmit a Group Assignment command with a station type to 6 (Inland AIS).

12.6.6.3.2 Required result

Verify that

- EUT switches to assigned mode with 5 s reporting interval,
- EUT declines Message 23,
- EUT switches to assigned mode with 5 s reporting interval,
- EUT declines Message 23,
- EUT switches to assigned mode with 5 s reporting interval,
- EUT declines Message 23,
- EUT declines Message 23.

2017-05-13	Tester: Me	Test details: Assignment by station type		
Test item		Check	Remark	Result
Set up the standard test environment and operate EUT in autonomous mode. Apply sensor information in that way that reporting interval is 15 s (SOG = 15 kn). Transmit Message 23 with different station types according to the test item, Type of ship and cargo = 0, Reporting interval = 5 s, position of EUT inside the addressing area.				
a) Station type = 0	Check that EUT enters assigned mode.			Passed
	Check reporting interval = 5 s.			Passed
Transmit Message 23 with different station types according to the test item,				
b) Station type = 1 (Class A),	Check that Message 23 is ignored.			Passed
	Check reporting interval = 15 s.			Passed
c) Station type = 2 (all types of Class B mobile stations),	Check that EUT enters assigned mode.			Passed
	Check reporting interval = 5 s.			Passed
d) Station type = 3 (SAR airborne mobile station),	Check that Message 23 is ignored.			Passed
	Check reporting interval = 15 s.			Passed
e) Station type = 4 (Class B SO mobile stations only),	Check that EUT enters assigned mode.			Passed
	Check reporting interval = 5 s.			Passed
f) Station type = 5 (Class B CS mobile stations only),	Check that Message 23 is ignored.			Passed
	Check reporting interval = 15 s.			Passed
g) Station type = 6 (Inland Waterways)	Check that Message 23 is ignored.			Passed
	Check reporting interval = 15 s.			Passed

5.6.6.4 12.6.6.4 Addressing by ship and cargo type

12.6.6.4.1 Method of measurement

Set up standard test environment and operate EUT in autonomous mode with a reporting interval of 15 s and use a base station MMSI to transmit Message 23.

- Transmit a Group Assignment command (Message 23) to the EUT. Set the reporting interval to 5 s and the ship and cargo value to the value which is configured in the EUT.
- Transmit a Group Assignment command (Message 23) to the EUT. Set the reporting interval to 5 s and the ship and cargo value to a value different to the value which is configured in the EUT.
- Configure the ship and cargo type of the EUT to 72. Transmit a Group Assignment command (Message 23) to the EUT. Set the reporting interval to 5 s and the ship and cargo type value to 70.

12.6.6.4.2 Required result

Verify that

- EUT switches to assigned mode and transmits position reports with 5 s reporting interval,
- EUT declines Message 23,
- EUT switches to assigned mode and transmits position reports with 5 s reporting interval.

2017-07-24	Tester: Me	Test details: Addressing by ship and cargo type		
Test item	Check	Remark	Result	
Operate EUT in autonomous mode with 15 s reporting interval (SOG = 15 kn).				
Set EUT to ship and cargo type =36.				
Set station type of Message 23 = 0, reporting interval = 5s and position of EUT inside the addressing area.				
Transmit Message 23 Ship and cargo type = 36	Check that EUT enters assigned mode.		Passed	
	Check reporting interval = 5 s.		Passed	
Transmit Message 23 Ship and Cargo type not 36	Check that Message 23 has been received (VDM output).		Passed	
	Check that message 23 is ignored and the reporting interval is 15 s.		Passed	
Set EUT to ship and cargo type = 72				
Transmit Message 23 Ship and Cargo type = 70	Check that EUT enters assigned mode.		Passed	
	Check reporting interval = 5 s.		Passed	

5.6.6.5 12.6.6.5 Quiet time command

12.6.6.5.1 Method of measurement

Set up the standard test environment and operate EUT in autonomous mode with 15s reporting interval.

Transmit a Group Assignment message (Message 23) to the EUT with a quiet time command.

Record transmitted messages.

12.6.6.5.2 Required results

Confirm that the EUT continues transmission for one frame to release the allocated slots and then stops transmission. Confirm that the EUT starts transmission after the quiet time according to the network entry procedure. The quiet time period starts with the reception of Message 23.

2017-05-13	Tester: Me	Test details: Addressing by ship and cargo type		
Test item	Check	Remark	Result	
Set up the standard test environment and operate EUT in autonomous mode with 15 s reporting interval (SOG = 15 kn).				
Transmit Message 23 EUT inside area, station type = 0 Quiet time = 8 min	Check that EUT releases all slots with time-out = 0 and Slot offset = 0.		Passed	
	Check that the EUT stops transmission after one frame.		Passed	
After end of quiet time	Check that the EUT starts transmission after end of quiet time.		Passed	
	Check that the EUT starts transmission with a network entry procedure.		Passed	

5.6.6.6 12.6.6.6 Reverting from interval assignment

12.6.6.6.1 Method of measurement

Set up standard test environment and operate EUT in autonomous mode. Transmit a Group Assignment command (Message 23) to the EUT with a reporting interval of 5 s assigned. Monitor the VDL until at least 1 min after timeout occurred. Repeat 10 times (transmissions of Message 23 shall not be synchronised to the initial transmission schedule of the EUT).

Measure the time T_{rev} between the reception of Message 23 and the first transmission after timeout.

12.6.6.6.2 Required result

Verify that the time out is randomly distributed between 4 min and 8 min.

2017-05-13	Tester: Me	Test details: Reverting from interval assignment	
Test item	Check	Remark	Result
Set up the standard test environment and operate EUT in autonomous mode with 15 s reporting interval. Repeat the following test 10 times			
Transmit Message 23 EUT inside area, station type = 0 Reporting interval = 5 s	Check that Message 23 has been received. Record R_x time		Passed
	Check that EUT transmits position reports with reporting interval of 5 s.		Passed
End of assigned mode	Check that the slots of the assigned reporting interval are released using time-out = 0 and slot offset = 0		Passed
	Check that the slot of the autonomous reporting interval (15 s) are allocated according to the network entry procedure		Passed
After 10 times group assignment			
Time-out	Check that the time-out time is randomly distributed between 4 and 8 minutes		Passed

5.6.6.7 12.6.6.7 Assignment priority test – Message 16 and 23

12.6.6.7.1 Purpose

The purpose of this test is to ensure that the EUT selects the correct assignment Message when given both addressed and group assignments.

12.6.6.7.2 Method of Measurement

Set up standard test environment and operate the EUT in autonomous mode.

- a) Transmit a Message 23, addressed to the EUT, to assign a reporting interval of 15 s. Check that the EUT reporting interval is 15 s. Transmit a Message 16, addressed to the EUT, assigning a reporting interval of 10 s while still assigned by Message 23.
- b) Transmit a Message 16, addressed to the EUT, to assign a reporting interval of 15 s. Check that the EUT reporting interval is 15 s. Transmit a Message 23, addressed to the EUT, assigning a reporting interval of 10 s while still assigned by Message 16.

12.6.6.7.3 Required result

Confirm that:

- a) the EUT adopts the reporting interval of Message 16;
- b) the EUT continues with the reporting interval of Message 16.

2017-05-13	Tester: Me	Test details: Assignment priority – Message 16 and 23		
Test item		Check	Remark	Result
a) Operate EUT in autonomous mode, reporting interval = 30 s				
Transmit Message 23 with reporting interval = 15 s		Verify that EUT enters assigned mode with 15 s reporting interval.		Passed
During assigned mode: Transmit Message 16 with 10 s reporting interval		Check that EUT changes the reporting interval to 10 s.		Passed
b) Message 23 during Message 16 assignment				
Transmit Message 16 with reporting interval = 15 s		Verify that EUT enters assigned mode with 15 s reporting interval.		Passed
During assigned mode: Transmit Message 23 with 10 s reporting interval		Check that EUT continues with 15 s reporting interval.		Passed

5.6.6.8 12.6.6.8 Assignment priority test – Message 22 and 23

12.6.6.8.1 Purpose

The purpose of this test is to ensure that the EUT selects the correct assignment Message when given group assignments by Messages 22 and 23.

12.6.6.8.2 Method of measurement

Set up standard test environment and operate the EUT in autonomous mode. Transmit a Message 22 defining a region with the EUT inside that region Tx/Rx mode = 0.

- a) Transmit an Assigned mode command (Message 23) to the EUT with Tx/Rx mode 1.
- b) Transmit Message 22 to the EUT with regional settings specifying Tx/Rx mode 2.
- c) Transmit an Assigned mode command (Message 23) to the EUT with Tx/Rx mode 1.
- d) During assigned mode transmit a Message 22 to the EUT individually addressed and specifying Tx/Rx mode 2.
- e) Within 10 min transmit a Message 22 with regional area settings specifying Tx/Rx mode 0.
- f) Transmit an Assigned mode command (Message 23) to the EUT with Tx/Rx mode 1 every min for 15 min.
- g) After timeout of the last Message 23 transmit a Message 22 with regional settings specifying Tx/Rx mode 0.

Record transmitted messages.

12.6.6.8.3 Required result

The following results are required.

- a) Check that Tx/Rx mode = 1. The Tx/Rx mode field setting of Message 23 takes precedence over the Tx/Rx mode field setting of Message 22.
- b) Check that Tx/Rx mode = 1. The EUT reverts to the Tx/Rx mode = 2 defined by Message 22 after the timeout of Message 23.
- c) Verify that Tx/Rx mode = 1.
- d) Check that Tx/Rx mode = 2. The Tx/Rx mode field setting of Message 22 takes precedence over the Tx/Rx mode field setting of Message 23.
- e) Check that Tx/Rx mode = 2. The Tx/Rx mode setting of Message 22 are ignored.
- f) Check that the Tx/Rx mode remains at 2 min for 10 min after applying Message 22. Check that the Tx/Rx mode is changed to 1 when receiving Message 23 later than 10 min after Message 22. Check that after timeout of the last Message 23 the Tx/Rx mode reverts to 2 according to the individually addressed Message 22.
- g) Check that Tx/Rx mode = 0. The Tx/Rx mode setting of Message 22 are accepted.

2017-05-13	Tester: Me	Test details: Assignment priority – Message 22 and 23		
Test item		Check	Remark	Result
Operate EUT in autonomous mode with 15 s reporting interval. Apply a channel management area with Tx/Rx mode = 0. Test for priority of Message 22 to an area				
a) Transmit Message 23 with Tx/Rx mode = 1.	Verify that Message 23 is received and content is correct.		Passed	
	Check that reporting interval is 15 s on channel A (Tx/Rx mode = 1).		Passed	
b) Transmit Message 22 with Tx/Rx mode = 2.	Verify that Message 22 is received (ACA output).		Passed	
	Check T _x /R _x mode = 1 as defined by Message 23.		Passed	
Wait for Assigned mode time-out.	Check that reporting rate = autonomous reporting rate.		Passed	
	Check T _x /R _x mode = 2 =mode of Message 22 (T _x on channel B).		Passed	
Test for priority of Message 22 individually addressed				
c) Transmit Message 23 with T _x /R _x mode = 1.	Verify that Message 23 is received and content is correct.		Passed	
	Confirm that EUT transmit position reports on channel A with 15 s reporting interval (Tx/Rx mode = 1).		Passed	
d) Transmit Message 22 individually addressed (MMSI) with T _x /R _x mode = 2.	Verify that Message 22 is received and content is correct.		Passed	
	Check T _x /R _x mode = 2 = mode of Message 22 (T _x on channel B).		Passed	
e) Within 10 min transmit Message 22 to an area with T _x /R _x mode 0.	Verify that Message 22 is received and content is correct.		Passed	
	Check that Tx/Rx mode = 2, the mode of Message 22 is ignored.		Passed	
f) Transmit Message 23 with T _x /R _x mode 1 every minute for 15 min.	Verify that Message 23 is received and content is correct.		Passed	
	Check that Message 23 is ignored for the first 10 minute.		Passed	
	Confirm that EUT changes to Tx/Rx mode 1 after 10 minutes.		Passed	
Wait for Assigned mode time-out.	Check that reporting rate = autonomous reporting rate.		Passed	
	Check T _x /R _x mode = 2 = mode of Message 22 (T _x on channel B).		Passed	
g) Transmit Message 22 to an area with Tx/Rx mode = 0.	Verify that Message 22 is received (ACA output).		Passed	
	Check T _x /R _x mode = 0.		Passed	

5.6.7 12.6.7 Base station reservations

12.6.7.1 Method of measurement

Set up standard test environment and operate EUT in autonomous mode with 5 s reporting interval (SOG = 25 kn). Apply a Message 4 to the VDL using a base station MMSI.

- Transmit a Data Link Management message (Message 20) on Channel A from a Base Station within 120 NM to the EUT with slot offset = 5 and increment = 10. Record transmitted messages.
- Repeat the test with a Base Station beyond 120 NM.
- Repeat the test without Base Station Report (Message 4).
- Repeat the test reserving 100 % of the slots.
- Repeat the test with a Base Station within 120 NM and maintain transmission of Message 20. Stop transmission Message 4.
- Repeat test a) using a non-base station MMSI.

12.6.7.2 Required results

The following results are required.

- For the Base Station within 120 NM, confirm that EUT does not use slots allocated by Message 20 for own transmissions until timeout of 4 min to 8 min. Confirm that the EUT does not use the same slots on Channel B.
- For the Base Station beyond 120 NM confirm that the EUT treats the slots as free.
- Confirm that the EUT treats the slots as free.
- Confirm that the EUT stops transmission.
- Confirm that the EUT ignores the slot reservations of a Message 20 which is received after the normal target time-out of Message 4.
- Confirm that the EUT treats the slots as free.


Test scenario:

Message 20 is transmitted in slot 0 of each frame

Message 20 parameters:

Offset number 1: 25
Number of slots: 5
Time out 1: 7
Increment: 10

FATDMA reservation:



2017-05-13	Tester: Me	Test details: FATDMA reserved slots		
Test item		Check	Remark	Result
Operate EUT with 5 s reporting interval (SOG = 25 kn) according to the description below.				
a) Transmit base station report Message 4 with distance < 120 NM. Transmit Message 20 for 5 frames on channel B with slot reservations.	Check that the reserved slots on channel B are not used by the EUT.		Passed	
	Check that the reserved slots on channel A are not used because of priority rules.		Passed	
After time-out of Message 20 of 4...8 minutes.	Check that all slots are used again.		Passed	
b) Repeat test with base station distance > 120 NM.	Check that all slots are used.		Passed	
c) Repeat test without Message 4.	Check that all slots are used.		Passed	
d) Repeat test with 100% slot reservation.	Check that EUT stops transmission.		Passed	
e) Transmit Message 4, distance < 120 NM, and Message 20 with slot reservation.	Check that the reserved slots are not used.		Passed	
Stop message 4, Continue Message 20.	Check that messages 20 which are received after normal target time-out of Message 4 are ignored and all slots are used.		Passed	
f) Repeat test a) using a non-base station MMSI.	Check that the reservation is ignored and all slots are used.		Passed	

5.7 12.7 Message formats

5.7.1 12.7.1 Received messages

(See 7.6)

12.7.1.1 Method of measurement

Set up standard test environment and operate EUT in autonomous mode. Apply messages according to Table 8 to the VDL including multiple slot messages up to 5 slots. Record messages output by the PI of EUT.

12.7.1.2 Required results

Confirm that EUT outputs corresponding message with correct field contents and format via the PI or responds as appropriate.

For the VDM frame the following items shall be checked:

Field	Value for single sentence	Values for multi sentences
Number of sentences	1	Number of sentences
Check sentence number	1	1, 2, ...
Sequential message identifier	Null field	0...9, counting up for each multi sentence group
Channel	A, B	
Fill bits	Depending on message type, in most cases 0	

2017-05-12	Tester: Me	Test details: Received messages		
Test item		Check	Remark	Result
Apply all Messages of table 8 to the VDL. Evaluate the VDM output				
Message 1		Check single sentence frame.		Passed
		Check message content.		Passed
Message 2		Check single sentence frame.		Passed
		Check message content.		Passed
Message 3		Check single sentence frame.		Passed
		Check message content.		Passed
Message 4		Check single sentence frame.		Passed
		Check message content.		Passed
Message 5		Check multi (2) sentence frame.		Passed
		Check message content.		Passed
Message 6 Addressed to EUT		Check single sentence frame.		Passed
		Check message content.		Passed
Message 6 Addressed to other station		Check that there is no VDM output.		Passed
Message 7 Addressed to EUT		Check single sentence frame.		Passed
		Check message content.		Passed
Message 7 Addressed to other station		Check that there is no VDM output.		Passed
Message 8		Check single sentence frame.		Passed
		Check message content.		Passed
Message 9		Check single sentence frame.		Passed
		Check message content.		Passed
Message 10		Check that there is no VDM output.		Passed
Message 11		Check single sentence frame.		Passed
		Check message content.		Passed
Message 12 Addressed to EUT		Check single sentence frame.		Passed
		Check message content.		Passed
Message 12 Addressed to other station		Check that there is no VDM output.		Passed

Message 13	Check single sentence frame.		Passed
Addressed to EUT	Check message content.		Passed
Message 13	Check that there is no VDM output.		Passed
Addressed to other station			
Message 14	Check single sentence frame.		Passed
Single slot	Check message content.		Passed
Message 15	Check single sentence frame.		Passed
EUT as destination	Check message content.		Passed
Message 15	Check that there is no VDM output.		Passed
EUT is not destination			
Message 16	Check single sentence frame.		Passed
Addressed to EUT	Check message content.		Passed
Message 16	Check that there is no VDM output.		Passed
Addressed to other station			
Message 17	Check multi (2) sentence frame.		Passed
	Check message content.		Passed
Message 18	Check single sentence frame.		Passed
	Check message content.		Passed
Message 19	Check single sentence frame.		Passed
	Check message content.		Passed
Message 20	Check single sentence frame.		Passed
	Check message content.		Passed
Message 21	Check single or multi sentence frame.		Passed
	Check message content.		Passed
Message 22	Check single sentence frame.		Passed
for an area	Check message content.		Passed
Message 22	Check single sentence frame.		Passed
Addressed to the EUT	Check message content.		Passed
Message 22	Check that there is no VDM output.		Passed
Addressed to other station			
Message 23	Check single sentence frame.		Passed
	Check message content.		Passed
Message 24 A	Check single sentence frame.		Passed
	Check message content.		Passed
Message 24 B	Check single sentence frame.		Passed
	Check message content.		Passed
Message 25	Check single sentence frame.		Passed
Broadcast	Check message content.		Passed
Message 25	Check single sentence frame.		Passed
Addressed to EUT	Check message content.		Passed
Message 25	Check that there is no VDM output.		Passed
Addressed to other station			
Message 26	Check single sentence frame.		Passed
Broadcast	Check message content.		Passed

Message 26	Check single sentence frame.		Passed
Addressed to EUT	Check message content.		Passed
Message 26	Check that there is no VDM output.		Passed
Addressed to other station			
Message 26	Check multi sentence frame.		Passed
Maximum length (1064 bit)	Check message content.		Passed
Message 27	Check that there is no VDM output.		Passed
Message of undefined type	Check single sentence frame.		Passed
	Check message content.		Passed

5.7.2 12.7.2 Transmitted messages

12.7.2.1 Method of measurement

Set up standard test environment and operate EUT in autonomous mode. Initiate the transmission of messages relevant for a mobile station according to Table 8 by the EUT.

Record transmitted messages.

12.7.2.2 Required results

Confirm that EUT transmits messages with correct field contents and format or responses as defined in Table 8.

For the VDM frame the following items shall be checked:

Field	Value for single sentence	Values for multi sentences
Number of sentences	1	Number of sentences
Check sentence number	1	1, 2, ...
Sequential message ident.	Null field	0...9, counting up for each multi sentence group
Channel	A, B	
Fill bits	Depending on message type, in most cases 0	

The messages not listed in the following table cannot be transmitted by a Class B SO.

2017-05-12	Tester: Me	Test details: Transmitted messages		
Test item		Check	Remark	Result
Apply all Messages of table 8 to the VDL. Evaluate the VDM output				
Message 6	Check single sentence frame.	See test 10.2.2.1	Passed	
Apply ABM sentence	Check message content.		Passed	
Message 7	Check single sentence frame.	See test 10.2.2.3	Passed	
Apply Msg 6 to VDL	Check message content.		Passed	
Message 8	Check single sentence frame.	See test 10.2.2.4	Passed	
Apply BBM sentence	Check message content.		Passed	
Message 13	Check single sentence frame.	See test 10.2.2.3	Passed	
Apply Msg 12 to the VDL	Check message content.		Passed	
Message 18	Check single sentence frame.	See test 10.2.1.1	Passed	
Automatically transmitted	Check message content.		Passed	
Message 19	Check multi (2) sentence frame.	See test 10.2.3	Passed	
Apply Msg 15 interrogation on VDL	Check message content.		Passed	
Message 24 A	Check single sentence frame.	See test 12.6.4	Passed	
Automatically transmitted	Check message content.		Passed	
Message 24 B	Check single sentence frame.	See test 12.6.4	Passed	
Automatically transmitted	Check message content.		Passed	
Message 25 broadcast	Check single sentence frame.	See test 10.2.2.4	Passed	
Apply BBM sentence	Check message content.		Passed	
Message 25 addressed	Check single sentence frame.	See test 10.2.2.1	Passed	
Apply ABM sentence	Check message content.		Passed	
Message 26 broadcast	Check single sentence frame.	See test 10.2.2.4	Passed	
Apply BBM sentence	Check message content.		Passed	
Message 26 addressed	Check single sentence frame.	See test 10.2.2.1	Passed	
Apply ABM sentence	Check message content.		Passed	

6 13 Specific tests of network layer

6.1 13.1 Regional area designation by VDL Message

13.1.1 Purpose

The purpose of this test is to ensure that the EUT transmits on the correct channels when transiting adjacent regional areas.

13.1.2 Method of measurement

Set up the standard test environment.

- With no Message 4. Apply channel management messages (Message 22) to the VDL defining two adjacent regional areas, 1 and 2, with different channel assignments for both regions and a transitional zone extending 4 NM either side of the regional boundary,
- With a Base Station within 120 NM transmitting Message 4. Apply the same channel management Messages as in a). Make the EUT approach region 1 from outside region 2 more than 5 NM away from the region boundary, transmitting on default channels. Record transmitted Messages on all 6 channels. This can be accomplished by either using a dedicated test input for simulated position information or a GNSS simulator




Figure 11 – Regional transitional zones

Table 14 – Regional area scenario

	Primary channel	Secondary channel
Region 1	CH A 1	CH B 1
Region 2	CH A 2	CH B 2
Default region	AIS 1	AIS 2

- c) *Operate the unit in an area with Tx/Rx mode 1.*
- d) *Operate the unit in an area with Tx/Rx mode 2.*
- e) *Transmit Message 22 using a non-base station MMSI.*

13.1.3 Required results

The following results are required.

- a) *Check that the channel management regions are not stored and not used by the EUT.*
- b) *Check that the EUT transmits and receives on the primary channels assigned for each region, alternating channels and halving the reporting interval when passing through the transitional zones (see Table 15). Check that the EUT reverts to default autonomous operation on the regional channels after leaving the transitional zones. Check that TXT and ACA sentences are output when defining the area, crossing the boundary of the area and on request. The In-use flag shall be set to "1" if the position is inside the area which is defined by the two corner points of the area setting (e.g. the grey area defining region 2 in Figure 11).*

Table 15 – Required channels in use

	Area	Channels in use
1	<i>Default region</i>	<i>AIS 1, AIS 2</i>
2	<i>First transitional zone</i>	<i>AIS 1, CH A 2</i>
3	<i>Region 2</i>	<i>CH A 2, CH B 2</i>
4	<i>Second transitional zone</i>	<i>CH A 2, CH A 1</i>
5	<i>Region 1</i>	<i>CH A 1, CH B 1</i>

- c) *Check that the EUT transmits on only channel A with the nominal reporting interval (the number of transmissions doubles on the active channel when transmitting on one channel only).*
- d) *Check that the EUT transmits on channel B only with the nominal reporting rate.*
- e) *When using a non-base station MMSI, verify that the EUT does not accept the channel management.*

2017-05-12	Tester: Me	Test details: Check of message 22 acceptance		
Test item		Check	Remark	Result
Transmit message 22 with a new area settings for area 1 and 2				
a) Transmit message 22 from a base station not transmitting message 4		Check that the area setting is not stored		Passed
Transmit message 22 from a base station transmitting message 4, distance > 120 NM		Check that the area setting is not stored		Passed
e) Transmit message 22 from a base station transmitting message 4, distance < 120 NM MMSI of message 4 and 22 is a non-base station MMSI		Check that the area setting is not stored		Passed

Test b) is performed in 2 parts:

- The first part checks the general behaviour including check of ACA and TXT output, check of the borders of area a transitional zone, check of the correct frequency use.

2017-07-24	Tester: Me	Test details: b) Part 1 - Channel management by VDL message 22		
Test item		Check	Remark	Result
Set up EUT in autonomous mode transmitting on channel AIS 1/AIS 2, apply 2 Messages 22 on the VDL, defining 2 adjacent areas with channels A 1, B 1 and A 2, B 2. <i>The position is outside of both areas.</i>				
PI output	Check that the Messages 22 are output as VDM on PI.			Passed
	Check ACA and TXT output on PI when the areas are stored.			Passed
	Check ACA and TXT output on PI on request.			Passed
<u>Item 1:</u> Position in high sea area	Check that channels AIS 1 and AIS 2 are in use.			Passed

<u>Item 2:</u> Move position into outer TZ of region 2	Check the limit of the TZ (5 NM = 8.8 minutes).		Passed
	Check that channels AIS 1 and A 2 are used.		Passed
	Check that reporting rate is doubled.		Passed
<u>Item 3:</u> Move position into inner TZ of region 2 (crossing the area border)	Check ACA and TXT output.		Passed
	ACA: check in use flag of area 2 = 1.		Passed
	ACA: check time of in use flag.		Passed
<u>Item 4:</u> Move position into region 2 (out of TZ)	Check the limit of the TZ (4 NM = 7 minutes).		Passed
	Check that channels A 2 and B 2 are used.		Passed
	Check that reporting rate is changed back to normal reporting rate.		Passed
<u>Item 5:</u> Move position into TZ between region 1 and 2, inside area 2	Check that channels A 2 and A 1 are used.		Passed
	Check the limit of the TZ (4 NM = 7 minutes).		Passed
	Check that reporting rate is doubled.		Passed
<u>Item 6:</u> Move position into area 1 (inside the TZ) (crossing the area border)	Check ACA and TXT output.		Passed
	Check the border of area.		Passed
<u>Item 7:</u> Move position into region 1 (out of TZ)	Check that channels A 1 and B 1 are used.		Passed
	Check the limit of the TZ (4 NM = 7 minutes).		Passed
	Check that reporting rate is changed back to normal reporting rate.		Passed
<u>Item 8:</u> Move position into TZ of region 1 to high sea	Check that channels A 1 and AIS 1 are used.		Passed
	Check that reporting rate is doubled.		Passed
<u>Item 9:</u> Move position out of area 1 (inside the TZ) (crossing the area border)	Check ACA and TXT output.		Passed
	Check the border of area.		Passed
Move position out of the TZ, into high sea	Check that channels AIS 1 and AIS 2 are used.		Passed
	ACA: check in use flags of area 1 = 0 and time of in use flag.		Passed
	Check that reporting rate is changed back to normal reporting rate.		Passed

- The second part concentrates on the correct slot allocation and usage during a transition from one (high sea) area into another on the different channels.

2017-07-24	Tester: Me	Test details: b) Part 2 - Channel management by VDL message 22		
Test item		Check	Remark	Result
The same area and movement is used as in test part 1.				
Item 1: In high sea area		Check that channels AIS 1 and AIS 2 are in use.		Passed
Item 2: Move position into transitional area of region 2, first frame after transition		Check that EUT continues T _x on AIS 1 and AIS 2 for 1 frame.		Passed
		Check that EUT releases the slots on AIS 2 by Message 1 with time-out 0 and no slot offset.		Passed
		Check that channels AIS 1 and A 2 are used for R _x .		Passed
Item 3: In outer transitional area of region 2, next frames after transition		Check allocation of additional slots on channel A (AIS 1) using ITDMA comm state		Passed
		Check complete slot allocation on channel B (A 2) using ITDMA comm state.		Passed
		Check that channels AIS 1 and A 2 are used for T _x .		Passed
		Check that channels AIS 1 and A 2 are used for R _x .		Passed
		Check that reporting rate is doubled.		Passed
		Check that messages on AIS 1 are output on PI (VDM/VDO) as channel "A" and A 2 as channel "B".		Passed
Item 4: Move into inner transitional area of region 2, crossing the area border		Check that messages on AIS 1 are output on PI (VDM/VDO) as channel "B" and A 2 as channel "A" (channels reverted).		Passed
		Check that the usage of slots continues		Passed
Item 5: Move position into the area of region 2 (out of TZ), first frame after transition		Check that EUT continues T _x on AIS 1 and A 2 for 1 frame.		Passed
		Check that EUT releases all slots on AIS 1.		Passed
		Check that EUT releases every second slot on channel A 2(for reversion to normal reporting rate).		Passed
		Check that channels A 2 and B 2 are used for R _x .		Passed

Item 6: Inside area of region 2, next frames after transition	Check allocation of slots on channel B (B 2) using ITDMA comm state.		Passed
	Check that channels A 2 and B 2 are used for T _x .		Passed
	Check that channels A 2 and B 2 are used for R _x .		Passed
	Check that reporting rate is back to normal reporting rate.		Passed
	Check that messages on A 2 are output on PI (VDM/VDO) as channel "A" and B 2 as channel "B".		Passed

Note)

The channels on the diagram are:

Column	Colour	Channel
Left (Channel A)	Black	A2 (channel A of area 2)
Left (Channel A)	Orange	AIS1 (channel A of high sea)
Right (Channel B)	Black	B2 (channel B of area 2)
Right (Channel B)	Orange	AIS2 (channel B of high sea)

2017-07-24	Tester: Me	Test details: Check of T _x /R _x -Mode		
Test item	Check	Remark	Result	
Transmit message 22 to an area with T _x /R _x mode according to the test item.				
c) Set T _x /R _x -Mode in Message 22 to 1.	Check that mode is correctly stored.		Passed	
	Check that channel A only is used for T _x .		Passed	
	Check that channels A and B are used for R _x .		Passed	
	Check that the reporting rate is correct.	15 s	Passed	
d) Set T _x /R _x -Mode in Message 22 to 2.	Check that mode is correctly stored.		Passed	
	Check that channel B only is used for T _x .		Passed	
	Check that channels A and B are used for R _x .		Passed	

6.2 13.2 Channel management by addressed Message 22

13.2.1 Purpose

The purpose of this test is to ensure that the EUT uses the regional operating settings of an addressed Message 22.

13.2.2 Method of measurement

Set up a standard test environment and operate the EUT in autonomous mode.

- Send Message 4 within 120 NM and Message 22 with valid regional operating settings that are different from the default operating settings to the EUT. The regional operating area includes the current position of own station.
- Send an addressed Message 22 to the EUT with regional operating settings different from the previous command.
- Move the EUT out of the regional operating area defined by the previous addressed command and into an area without regional operating settings.

13.2.3 Required results

Check that

- the EUT uses the regional operating settings commanded to it in a),
- the EUT uses the regional operating settings commanded to it in b),
- the EUT reverts to default.

2017-07-25	Tester: Me	Test details: Test of addressed Message 22		
Test item		Check	Remark	Result
a) Send a valid Message 22, position inside.		Check, that the EUT uses the regional operating settings.		Passed
b) Send an addressed message 22 to the EUT with different regional operating settings.		Check, that the EUT uses the regional operating settings.		Passed
b) Send an addressed Message 22, addressed as ID 2, to the EUT with different regional operating settings.		Check, that the EUT uses the regional operating settings.		Passed
c) Move the EUT out of the regional operating area defined by the previous addressed telecommand.		Check, that the EUT reverts to default.		Passed

Note)

The purpose of the 10 minutes protection of an addressed Message 22 is to protect this individual station from being overwritten by a broadcast Message 22 which is normally regularly transmitted every few minutes.

It shall not inhibit an addressed Message 22.

6.3 13.3 Invalid regional operating areas

13.3.1 Purpose

The purpose of this test is to ensure that the EUT rejects invalid regional operating areas (three regional operating areas with same corner).

13.3.2 Method of measurement

Set up standard test environment and operate the EUT in autonomous mode. Perform, after completion of all other tests related to change of regional operating settings, the following.

- Send three different valid regional operating settings with adjacent regional operating areas, their corners within 8 NM of each other, to the EUT using Message 22. The current own position of the EUT shall be within the regional operating area of the third regional operating setting.*
- Move current own position of the EUT consecutively to the regional operating areas of the first two valid regional operating settings.*

13.3.3 Required test results

Check that:

- the EUT uses the operating settings that were in use prior to receiving the third regional operating setting,*
- the EUT consecutively uses the regional operating settings of the first two received regional operating areas.*

2017-07-25	Tester: Me	Test details: Test for invalid regional operating areas		
Test item		Check	Remark	Result
Msg 22 input				
a) Send three different valid regional with adjacent corners by message 22, Position inside third area.		Check, that the third area is refused and settings are not used.		Passed
b) Move own position to the first 2 areas.		Check, that the EUT uses the operational settings of these areas.		Passed

6.4 13.4 Continuation of autonomous mode reporting interval

13.4.1 Purpose

The purpose of this test is to ensure that the EUT maintains autonomous reporting interval in a transitional zone.

13.4.2 Method of test

When in the presence of an assigned mode command, and in a transition zone, check that the EUT continues to report at the autonomous reporting interval.

13.4.3 Required result

Ensure that the autonomous reporting interval is maintained.

2017-07-25	Tester: Me	Test details: Continuation of autonomous mode reporting rate		
Test item		Check	Remark	Result
Set the EUT into a transitional zone. Send assignment commands message 16 to the EUT.				
Rate assignment command in a transitional zone.		Check that the rate assignment command is ignored in a transitional zone.		Passed
Slot assignment command in a transitional zone.		Check that the slot assignment command is ignored in a transitional zone.		Passed

6.5 13.5 Slot reuse and FATDMA reservations

(See 7.3.2.4)

13.5.1 Method of measurement

Set up standard test environment and operate EUT in autonomous mode. Assure that at test receiver location the signal level received from EUT exceeds the signal level received from test transmitter.

- a) Transmit test targets on channel A with 50 % channel load. Channel B is free. This test covers Rule 0 and 1.
- b) Transmit near and distant test targets with 100 % channel load on channel A in all selection intervals which are under observation. Channel B is free. There shall be enough different targets to allow the EUT to meet the requirement to reuse only one slot of each target per frame.
- c) Transmit near and distant test targets with 100 % channel load on channel B in all selection intervals which are under observation. Channel A is free.
- d) Transmit Message 4 with a position distance < 120 NM and Message 20 with slot reservations on channel A. Transmit near and distant test targets in the unreserved slots on channel A. Channel B is free.

13.5.2 Required results

Confirm that

- a) only free slots are used for transmission on channel A, confirm that only slots which are free on channel A are used for transmissions on channel B,
- b) slots of the most distant test targets are used for transmission on channel A. Check that not more than one slot of a station is reused in a frame,
- c) for transmission on channel A that the candidate slots on channel A are organized according to the most distance station on channel B,
- d) only unreserved slots are used on channel A. Confirm that slots of the most distant test targets are used for transmission. Confirm that for transmissions on channel B only slots which are not reserved on channel A are used after the next regular time-out 0.

2017-07-26	Tester: Me	Test details: Slot reuse		
Test item		Check	Remark	Result
Operate the EUT with 5 s reporting interval.				
a) Test for using free slots if they are available.				
<ul style="list-style-type: none">• Apply 50% VDL load on channel A.• Apply 0% VDL load on channel B.	Check that only free slots are used on channel A.		Passed	
	Check that only slots which are free on channel A are used on channel B.		Passed	
b) Test for using slots of most distant targets				
<ul style="list-style-type: none">• Apply 100% VDL load on channel A.• Apply 0% VDL load on channel B.	Check that only the slots of odd numbered targets are used.		Passed	
	Check that the slot of a target is not used twice in a frame.		Passed	
c) Test for using slots of most distant targets				
<ul style="list-style-type: none">• Apply 0% VDL load on channel A.• Apply 100% VDL load on channel B.	Check that only the slots of odd numbered targets are used on channel A.		Passed	
d) Check for slot reservation by message 20 < 120 NM in combination with near and distant targets				
<ul style="list-style-type: none">• Apply message 20 with slot reservations on channel A and message 4 with distance < 120 NM.• Transmit near and distant test targets in the unreserved slots on channel A.	Check that only unreserved slots are used on channel A.		Passed	
	Check that the most distant targets are reused on channel A.		Passed	
	Check that on channel B only slots which are not reserved on channel A are selected at time-out 0.		Passed	

6.6 13.6 Long-range application by broadcast

(See 7.8)

6.6.1 13.6.1 Long-range broadcast

Method of measurement

Set up standard test environment, enable the EUT to transmit Message 27 and operate EUT in autonomous mode. Use base stations MMSI to transmit Message 4 and Message 23. Record the transmitted messages from the EUT. The designated long-range channels are defined in 8.3.

- a) Do not apply Message 4 and Message 23.
- b) Apply the Message 4 with the long range control bit set to 1 and 0. Place the EUT inside the RF footprint (Message 4 receiving area) of a base station.
- c) Apply the Message 4 with the long range control bit set to 1 and 0. Using the same MMSI as the Message 4, broadcast the Message 23 with station type 10 to define the base station coverage area. Place the EUT inside the RF footprint area, but outside the base station coverage area.
- d) Apply the Message 4 with the long range control bit set to 1 and 0. Using the same MMSI as the Message 4, broadcast the Message 23 with station type 10 to define the base station coverage area. Place the EUT inside the base station coverage area..
- e) Repeat the test d) using different MMSIs for Message 4 and Message 23.
- f) Apply the Message 4 with the long range control bit set to 0. Using the same MMSI as the Message 4, broadcast the Message 23 with station type 10 to define the base station coverage area. Place the EUT inside the base station coverage area. After 6 minutes, remove transmissions of Message 23.
- g) Apply the Message 4 with the long range control bit set to 0. Using the same MMSI as the Message 4, broadcast the Message 23 with station type 10 to define the base station coverage area. Place the EUT inside the base station coverage area. After 6 min. remove transmissions of Message 4.

Required results

Check that EUT transmits the appropriate messages, e.g. in addition to the normal transmission of Messages 1 and 5 with adequate reporting interval on AIS 1 and AIS2, confirm that:

- a) EUT transmits Message 27 alternating on the designated long-range channels with 3 min reporting interval.
- b) Irrespective of the Message 4 long range control bit status, EUT transmits Message 27 alternating on the designated long-range channels with 3 min reporting interval.
- c) Irrespective of the Message 4 long range control bit status, EUT transmits Message 27 alternating on the designated long-range channels with 3 min reporting interval.
- d) EUT transmits Message 27 alternating on the designated long-range channels with 3 min reporting interval when the Message 4 long-range control bit is set to 1. EUT stops transmitting Message 27 when the Message 4 long-range control bit is set to 0. Verify fields after station type in received Message 23 are ignored.
- e) Irrespective of the Message 4 long range control bit status, EUT transmits Message 27 alternating on the designated long-range channels with 3 min reporting interval.
- f) EUT begins transmission of Message 27 no sooner than 4 minutes and no later than 8 minutes after Message 23 was removed.
- g) EUT begins transmission of Message 27 beyond 3 minutes after Message 4 was removed.

2017-08-01	Tester: Me	Test details: Long range broadcast		
Test item		Check	Remark	Result
Set up the standard test environment and operate EUT in autonomous mode. Enable the EUT to transmit Message 27, e.g. by configuring the long range broadcast channels, Message 4 and 23 in the following test steps are transmitted from the same base station MMSI.				
a) no message 4 and message 23	Check that message 27 is transmitted		Passed	
	Check Tx channels C and D		Passed	
	Check that the transmission is alternating between C and D		Passed	
	Check reporting interval = 3 min		Passed	
	Check message 27 content		Passed	
a) Apply 50% VDL channel load This test has been added to verify that the requirement of ITU-R M.1371-5, Annex 4, section 3.3.2 "Access scheme" for slot selection are fulfilled considering the slot reservation on the AIS channels AIS1 and AIS2.				
Apply the channel load on channel A with message 1	Check that only slots which are free on channel A are used		Passed	
Apply the channel load on channel B with message 26	Check that only slots which are free on channel B are used		Passed	
b) Apply message 4 only without message 23				
Apply message 4 with long range control bit set to 0	Check that message 27 is transmitted with 3 min interval		Passed	
Apply message 4 with long range control bit set to 1	Check that message 27 is transmitted with 3 min interval		Passed	
c) Apply message 4 and message 23 with station type 10 (long range coverage area), EUT outside the coverage area				
Apply message 4 with long range control bit set to 0	Check that message 27 is transmitted with 3 min interval		Passed	
Apply message 4 with long range control bit set to 1	Check that message 27 is transmitted with 3 min interval		Passed	
d) Apply message 4 and message 23 with station type 10 (long range coverage area), EUT inside the coverage area				
Apply message 4 with long range control bit set to 0	Check that EUT stops transmission of message 27		Passed	
	Verify that the information (Tx/Rx mode, Reporting interval) of message 23 after station type is ignored		Passed	
Apply message 4 with long range control bit set to 1	Check that message 27 is transmitted with 3 min interval		Passed	
e) Apply message 23 with station type 10, EUT inside the coverage area, apply message 4 with a different MMSI than message 23				
Apply message 4 with long range control bit set to 0	Check that message 27 is transmitted with 3 min interval		Passed	
Apply message 4 with long range control bit set to 1	Check that message 27 is transmitted with 3 min interval		Passed	

f) Apply message 4 and message 23 with station type 10 (long range coverage area), EUT inside the coverage area			
Apply message 4 with long range control bit set to 0	Check that message 27 is not transmitted		Passed
Stop messages 23 after 6 minutes	Check that EUT starts transmission of Message 27 after the time-out of message 23 (4... 8 min)		Passed
g) Apply message 23 with station type 10 (long range coverage area), EUT inside the coverage area			
Apply message 4 with long range control bit set to 0	Check that message 27 is not transmitted		Passed
Stop message 4 after 6 minutes	Check that EUT starts transmission of Message 27 later than 3 minutes after end of message 4		Passed

6.6.2 13.6.2 Multiple assignment operation

Method of measurement

Set up standard test environment, enable the EUT to transmit Message 27 and operate EUT in autonomous mode with a reporting interval of 10 s. Use base stations MMSI to transmit Message 4 and Message 23. Record the transmitted messages from the EUT.

- Using different MMSIs, apply the Message 4 with long range control bit set to 1 and 0 from multiple base stations partially overlapping their RF footprints. Broadcast the Message 23 from multiple base stations with station type 10 to define the base station coverage areas not overlapping. Place the EUT inside the overlapped RF footprint area but outside the coverage area of both base stations.
- Using different MMSIs, apply the Message 4 with long range control bit set to 1 and 0 from multiple base stations partially overlapping their RF footprints. Broadcast the Message 23 from multiple base stations with station type 10 to define the base station coverage areas not overlapping. Place the EUT inside the overlapped RF footprint area.
- Using different MMSIs, apply the Message 4 with long range control bit set to 1 and 0 from multiple base stations partially overlapping RF footprints. Broadcast the Message 23 from one base station with station type 10 to define the base station coverage areas. Do not broadcast Message 23 from other base stations. Place the EUT inside the RF footprint area of base station not broadcasting Message 23 but outside the coverage area of the base station transmitting Message 23.

Required results

Verify that:

- Irrespective of the Message 4 long-range control bit status of both base stations, EUT transmits Message 27 alternating on the long-range channels with 3 min reporting interval.
- EUT transmits Message 27.
- Irrespective of the Message 4 long range control bit status of both base stations, EUT transmits Message 27 alternating on the long-range channels with 3 min reporting interval.

2017-08-01	Tester: Me	Test details: Multiple assignments		
Test item		Check	Remark	Result
Set up the standard test environment and operate EUT in autonomous mode. Enable the EUT to transmit Message 27, e.g. by configuring the long range broadcast channels, reporting interval = 10 s				
a) Apply message 4 and 23 with station type 10 (long range coverage area) from two different base station, the coverage area not overlapping EUT outside the coverage areas				
<ul style="list-style-type: none">Long range control bit of station 1 is set to 0Long range control bit of station 2 is set to 1	Check that message 27 is transmitted with 3 min interval	See test 13.6.1 c)	Passed	
b) Apply message 4 and 23 with station type 10 (long range coverage area) from two different base station, the coverage areas are overlapping EUT inside the overlapping part of the coverage areas				
<ul style="list-style-type: none">Long range control bit of station 1 is set to 0Long range control bit of station 2 is set to 1	Check that message 27 is transmitted with 3 min interval		Passed	
c) Apply message 4 and 23 with station type 10 (long range coverage area) from one base station and message 4 from a second base station EUT is outside the message 23 coverage area of base station 1				
<ul style="list-style-type: none">Long range control bit of station 1 is set to 0Long range control bit of station 2 is set to 1	Check that message 27 is transmitted with 3 min interval	See test 13.6.1 c)	Passed	
<ul style="list-style-type: none">Long range control bit of station 1 is set to 1Long range control bit of station 2 is set to 0	Check that message 27 is transmitted with 3 min interval	See test 13.6.1 b)	Passed	

6.7 13.6 Other features

(See 4.1.4)

The performance of other features provided shall be self-certified by the manufacturer.

7 Annex D DSC functionality

(normative)

7.1 A.4 DSC functionality tests

7.1.1 A.4.1 General

For the tests in this subclause, set the EUT into assigned mode using channels AIS 1 and AIS 2 with a reporting interval of 10 s.

A.4.2 Method of measurement

Send a sequence of valid calls consisting of:

- DSC test signal number 2;
- DSC test signal number 3;
- DSC test signal number 2;
- DSC test signal number 4;
- DSC test signal number 2.

A.4.3 Required results

Check that the EUT AIS operation is not affected by the interleaved calls.

2017-04-28	Tester: Me	Test details: Sequence of 5 calls		
Test item	Check	Remark	Result	
Activate DSC function. Set reporting interval by rate assignment to 10 s and record VDL.				
Start DSC transmission of test sequence.	Check that the transmission schedule of the AIS position reports is not affected by the transmission of the DSC calls.		Passed	

7.1.2 A.4.4 Regional area designation

Perform the following tests using DSC test signal number 2.

Send DSC test signal number 2 to the EUT but with symbol numbers appropriate to the geographical regions and channels specified in the test. Note the transition boundary is 5 NM in this test.

7.1.3 A.4.5 Scheduling

A.4.5.1 General

The purpose of this test is to confirm that the EUT's AIS reporting is not affected during the DSC monitoring times and a response is not transmitted.

A.4.5.2 Method of measurement

Send DSC test signal number 2 to the EUT, with EOS = 127 and another signal with EOS=117 (RQ).

A.4.5.3 Required results

Check that the EUT's AIS reporting is not affected during the DSC monitoring times. Check that the EUT accepts the channel management, but a response is not transmitted in either case of EOS = 127 and 117.

2017-04-28	Tester: Me	Test details: Scheduling		
Test item		Check	Remark	Result
Set reporting interval to 15 s and record VDL				
Send DSC call test signal number 2.		Check that the AIS reporting is not affected during the DSC monitoring times.		Passed
		Check that not response is transmitted.		Passed
Send a DSC call with EOS=117 (RQ).		Check that not response is transmitted.		Passed

7.1.4 A.4.6 DSC flag in Message 18

A.4.6.1 General

The purpose of this test is to confirm that the DSC flag is set properly when DSC functionality is available.

A.4.6.2 Method of measurement

Perform the following:

- a) *enable DSC monitoring;*
- b) *disable DSC monitoring.*

A.4.6.3 Required results

Check that

- a) *the DSC flag is set to one,*
- b) *the DSC flag is set to zero.*

2017-04-28	Tester: Me	Test details: DSC flag		
Test item		Check	Remark	Result
Record Message 18 on VDL				
DSC enabled		Check that the DSC flag is set.		Passed
DSC disabled		Check that the DSC flag is not set.		Passed

7.1.5 A.4.7 DSC monitoring time plan

A.4.7.1 General

The purpose of this test is to confirm that DSC commands are received during DSC monitoring times and, if time-sharing is used, are not received outside those times.

A.4.7.2 Method of measurement

Perform the following:

- a) transmit DSC test signal 2 during monitoring time,
- b) transmit DSC test signal 2 outside monitoring time.

A.4.7.3 Required results

Check that

- a) the DSC call is received,
- b) the DSC call is not received.

2017-04-28	Tester: Me	Test details: DSC monitoring time plan		
Test item		Check	Remark	Result
Delete all area settings				
Send a DSC area setting outside the monitoring time.	If time-sharing is used: Check that the channels are not changed.		Passed	
	If time-sharing is not used: Check that the channels are changed according to the area setting.		Passed	
Send a DSC area setting inside the monitoring time.	Check that the channels are changed according to the area setting.		Passed	

7.1.6 A.4.8 Replacement or erasure of dated or remote regional operating settings

A.4.8.1 Method of measurement

Set up standard test environment. Send a valid regional operating setting to the EUT by Message 22 with the regional operating area including the own position of the EUT. Consecutively send a further seven (7) valid regional operating settings to EUT, using both Message 22 and DSC test signal number 2, with regional operating areas not overlapping to the first and to each other. Perform the following in the order shown:

- a) send a ninth Message 22 to the EUT with valid regional operating areas not overlapping with the previous eight regional operating areas;
- b) Step 1: set own position of EUT into any of the regional operating areas defined by the second to the ninth telecommands sent to the EUT previously;

Step 2: send a tenth telecommand to the EUT, with a regional operating area which partly overlaps the regional operating area to which the EUT was set by Step 1 but which does not include the own position of the EUT;
- c) Step 1: move own position of EUT to a distance of more than 500 NM from all regions defined by previous commands;

Step 2: consecutively set own position of EUT to within all regions defined by the previous telecommands.

A.4.8.2 Required results

After the initialisation, the EUT shall operate according to the regional operating settings defined by the first Message 22 sent.

- a) Check that the most distant area is removed.
- b) Step 1: check that the EUT changes its operating settings to those of that region which includes own position of the EUT.

Step 2: check that the EUT reverts to the default operating settings.

NOTE Since the regional operating settings to which the EUT was set in Step 1 are erased due to Step 2, and since there is no other regional operating setting due to their non-overlapping definition, the EUT returns to default.

- c) Step 1: check that the EUT operates with the default settings.

Step 2: check that the EUT operates with the default settings.

2017-04-28	Tester: Me	Test details: Test of replacement or erasure of dated or remote regional operating settings	
Test item	Check	Remark	Result
Send by DSC and msg 22			
<ul style="list-style-type: none"> 1 area including own position by MSG 22 (Msg: B Msg 22 Test 13.3.1 Area 1) 7 areas not overlapping, not including own position, first 3 by msg 22, last 4 by DSC 			
Check active area.	Check that EUT uses the channels of area 1.		Passed
a) Send a 9. msg 22 to the EUT not overlapping the previous areas .	Check that the most distant area is deleted.		Passed
b) step 1: Set own position to any of the 7 areas.	Check channels of area 2.		Passed
	Check channels of area 3.		Passed
	Check channels of area 4.		Passed
	Check channels of area 5.		Passed
	Check channels of area 6.		Passed
	Check channels of area 7.		Passed
	Check channels of area 8.		Passed
	Check channels of area 9.		Passed
b) step 2: Send an area 10 by DSC, overlapping the area 2 of step 1 not including own position.	Check that the EUT returns to the default operating settings (the area is deleted).		Passed
c) Step 1: Erasure by distance: Move own position of EUT to a distance of more than 500 miles from all regions defined by previous commands.	Check that the EUT operates with the default settings.		Passed
Step 2: Check of erasure: Set own position of EUT to within all regions defined by the previous telecommands.	Check area 2 = default.		Passed
	Check area 3 = default.		Passed
	Check area 4 = default.		Passed
	Check area 5 = default.		Passed
	Check area 6 = default.		Passed
	Check area 7 = default.		Passed
	Check area 8 = default.		Passed
	Check area 10 = default.		Passed

7.1.7 A.4.9 Test of addressed telecommand

A.4.9.1 Method of measurement

Set up a standard test environment and operate EUT in autonomous mode. Perform the following tests in the following order:

- a) send a DSC test signal number 2 with valid regional operating settings that are different from the default operating settings, to the EUT with a regional operating area, which contains the current position of own station;
- b) send an addressed DSC channel management command to the EUT with different regional operating settings than the previous command;
- c) move the EUT out of the regional operating area defined by the previous addressed telecommand into an area without regional operating settings.

A.4.9.2 Required results

Check that

- a) the EUT uses the regional operating settings commanded to it in a),
- b) the EUT uses the regional operating settings commanded to it in b),
- c) the EUT reverts to default.

2017-04-28	Tester: Me	Test details: Test of addressed telecommand		
Test item		Check	Remark	Result
All areas are erased by the previous test.				
a) Send a DSC call with a new area, position inside.		Check that the EUT uses the regional operating settings.		Passed
b) Send an addressed DSC call to the EUT with different regional operating settings.		Check that the EUT uses the settings of the new message.		Passed
c) Move the position out of the area.		Check that the EUT uses the default channels.		Passed

7.1.8 A.4.10 Invalid regional operating areas

A.4.10.1 General

Test for invalid regional operating areas (three regional operating areas with same corner).

A.4.10.2 Method of measurement

Set up standard test environment and operate EUT in autonomous mode. Perform the following tests in the following order after completion of all other tests related to change of regional operating settings:

- a) send three different valid regional operating settings with adjacent regional operating areas, their corners within eight miles of each other, to the EUT by DSC test signal number 2. The current own position of the EUT shall be within the regional operating area of the third regional operating setting;
- b) move current own position of the EUT consecutively to the regional operating areas of the first two valid regional operating settings.

A.4.10.3 Required results

Check that

- a) the EUT uses the operating settings that were in use prior to receiving the third regional operating setting,
- b) the EUT consecutively uses the regional operating settings of the first two received regional operating areas.

2017-04-28	Tester: Me	Test details: Test for invalid regional operating areas		
Test item		Check	Remark	Result
a) Send three different valid regional with adjacent corners by DSC area call, Position inside 3 rd area.		Check that the default channels are used.		Passed
b) Move own position to the first area.		Check that the EUT uses the operational settings of the first area.		Passed
Move own position to the second area.		Check that the EUT uses the operational settings of the second area.		Passed

Annex A Test equipment

A.1 Test equipment summary

#	description	type	identification
1	VDL Analyser / Generator	AIS Test unit MKII	S/N AA08PN Bund BSH/2012, 7200002112 BSH PC10745 AISLog
2	Target simulator software	Furuno Navintra	BSH PC 14731
3	Presentation Interface Monitor	BSH	BSH PC 10756 BSH VC 13416 SW NewMoni V3.2
4	GMDSS-AIS-Testbox (DSC)	Futronic I/S	200 30 405
5	16 Port Serial Device Server	Moxa NPort 5610 RS232	S/N 756
6	16 Port Serial Device Server	Moxa NPort 5630 RS485/RS422	S/N 9440
7	Active retransmitting GPS antenna	RA - 48	4800199
8	Trimble GPS reference receiver	4000RS, Part number 21000-76	S/N 3428A06700
	Auxiliaries:		
9	True RMS Multimeter DMM 916	Tektronix	S/N 138531
11	Unbalanced Standard Attenuator	Rhode & Schwarz DPR BN 18024/50	BUND KK 11201
12	2 fixed voltage power supply (24 V/10A)	SITOP	BUND 102452, 102453
14	2 adjustable power supplies (30 V/5 A)	PS 405 D	S/N 2737, 2768

A.1.1 VDL Analyser / Generator

The VDL analyser/generator:

- receives the radio data telegrams transmitted by the AIS under test, slot wise evaluates their radio parameters (field strength, SNR, etc.) and provides a transparent display of the decoded radio data telegrams (VDL messages).
- transmits radio data telegrams which have been entered/edited via a control panel. The AIS under test receives these messages and either passes the received data to it's presentation interface and/or responds as appropriate.
- records all data contained in the received radio telegrams and radio parameters in a data base for offline evaluation and documentation purposes.
- simulates AIS targets by transmitting position reports of virtual targets up to the maximum channel capacity of 100% channel load on both channels (4500 messages / minute). The data are provided via serial interface to the VDL analyser/ Generator.

The VDL analyser is controlled by a user interface software running on a standard PC. This user interface software composes the transmission messages and decodes and displays the received messages.

A.1.2 Target simulator

The target simulator consists of a standard PC with special AIS Target Simulator software.

For tests of AIS transponders the data of up to 75 moving targets defined in text file in plain language are transferred to the „TS“ input of the VDL Analyser/ Generator as VDM sentences and transmitted on the VHF data link (VDL). Thus the AIS VHF data link is loaded with simulated AIS targets in fixed slots or in slots selected by the VDL Analyser/ Generator.

A.1.3 Presentation Interface Monitor

The Presentation Interface Monitor is a PC software running on four standard PCs. It is used to

- analyse the AIS high speed input / output
- analyse the AIS long range function
- generate DSC calls for the DSC test box and to display, log and evaluate the received DSC calls from EUT.

For that purpose it includes the functions:

- coding / decoding of NMEA 6-bit data fields
- online AIS message filtering
- online AIS message editing
- load and transmit predefined sequences
- online modification of transmitted sequences

A.1.4 Sensor Data Simulator

The Sensor Data Simulator provides simulated sensor data to the serial sensor data inputs of the EUT. The sensor data are provided in text files to the Sensor Data Simulator which modifies the sensor data sentences e.g. adding the actual UTC time, modify some time-varying data and by adding a checksum.

The Sensor Data Simulator is basically the same software as the Presentation Interface Monitor using a special part of the functionality of the software.

A.1.5 DSC Test box

The DSC test box is a standard GMDSS-AIS Test box used for the survey of ship stations.

For the DSC testing of AIS equipment includes a software extension that provides a remote control input/output facility

- to transmit DSC calls according to ITU 825-3 generated in an external PC on DSC channel 70 and
- to output received DSC calls from the EUT to the external PC.

Special PC software is used to generate the DSC calls and to display, log and evaluate received DSC calls. It communicates via the serial remote control interface to the DSC Test box.

A.1.6 Serial Interface Server

The Serial Interface Server consists on two Serial Interface boxes which provides 16 serial lines each which can be connected in a flexible way to the EUT and to equipment of the test environment like the DSC Test box.

The Serial Interface Server is connected to the controlling PCs via Ethernet Network. It includes:

- One interface box with 16 serial lines according to RS-422 and IEC 61162-1/2
- One interface box with 16 serial lines according to RS-232

A.1.7 Laboratory Network


A special laboratory network connects controlling PCs with equipment of the test environment (VDL Generator/ analyser) and with EUT if equipped with an Ethernet interface.

A.1.8 GPS Re-transmitter

All AIS equipment includes a GPS receiver for the exact timing and for getting position and speed information.

To avoid the need to connect all AIS equipment to GPS antennas outside the laboratory a re-transmitting GPS antenna is installed in the lab. It amplifies and radiates a GPS signal in the laboratory which is received by active GPS antenna on the roof.

A.2 Test environment overview



Annex B Test sentences

B.1 IEC 61162 Test Sentences

Many of the test sentences are modified manually during the test according to the requirements of the actual test items.

Mainly the MMSI in all addressed sentences are adapted to the actual MMSI of the EUT or of the unit the EUT communicates with.

In addition the files containing these sentences contain also some control information used by the monitor program like:

<UTC> is replaced by the actual UTC time at time of output

<WAIT EVENT> waiting for user action before next output

<WAIT xxxx> waiting xxx ms before next output

This control information is not shown in the following sentence examples because it is not sent to the EUT.

B.1.1 Messages (ABM, BBM)

The addressed messages include a MMSI number which is changed according to the actual MMSI number of the EUT

Messages (ABM, BBM)	
File name	Description
Sentences	
AIABM_bin.sst	Standard addressed binary message
!AIABM,1,1,2,211001028,1,6,07i@E=@,2	
AIABM_safety.sst	Standard addressed safety related message
!AIABM,1,1,2,211001028,1,12,D5CD,0	
AIABM_4_bin.sst	Set of 4 addressed binary messages
!AIABM,1,1,3,211001028,1,6,07i@E=B34,2	
!AIABM,1,1,0,211001028,2,6,07i@E=B38,2	
!AIABM,1,1,1,211001028,1,6,07i@E=B3<,2	
!AIABM,1,1,2,211001028,2,6,07i@E=B3@,2	
AIBBM_bin.sst	Standard binary broadcast message
!AIBBM,1,1,6,1,8,07i@E=@,2	
AIBBM_safety.sst	Standard safety related broadcast message
!AIBBM,1,1,6,1,14,D5CD,0	

AIABM_BBM_msg25_26.sst	Collecton of addressed and broadcast message 25/26
<pre> <WAIT_EVENT> !AIABM,1,1,0,211001028,1,70,upGd45L22B2J2B2H,0 <WAIT,10000> !AIABM,1,1,1,211001028,2,25,upGd45L22B2J2B2H,0 <WAIT,10000> !AIABM,1,1,2,211001028,1,71,ur3d45L0h`S0,0 <WAIT,10000> !AIABM,1,1,3,211001028,2,26,ur3d45L0h`S0,0 <WAIT,10000> !AIBBM,1,1,4,1,70,up?d45L2N`UKPF1>o8?`00,4 <WAIT,5000> !AIBBM,1,1,5,2,25,up?d45L2N`UKPF1>o8?`00,4 <WAIT,5000> !AIBBM,1,1,6,1,71,upkd45L1E9PR200JGP,4 <WAIT,5000> !AIBBM,1,1,7,2,26,upkd45L1E9PR200JGP,4 </pre>	
AIBBM_multi_bin_3_slot.sst	Long 3 slot binary broadcast message
<pre> !AIBBM,3,1,6,2,8,07i@456789012345678901234567890123456789,0 !AIBBM,3,2,6,2,8,0123456789012345678901234567890123456789,0 !AIBBM,3,3,6,2,8,01234567890,2 </pre>	

Annex C Photos of equipment under test

C.1 Transponder unit





C.2 GPS antenna

