

FCC Test Report

Report No.: RWAZ202300086A

Applicant: Shenzhen Qianyan Technology LTD

Address: No.3301, Block C, Section 1, Chuangzhi Yuncheng Building,

Liuxian Avenue, Xili Community, Xili Street, Nanshan District,

Shenzhen, China

Product Name: Govee Outdoor Ground Lights 2

Product Model: H7053

Multiple Models: H7052

Trade Mark: Govee

FCC ID: 2A7VD-H7053

Standards: FCC CFR Title 47 Part 15C (§15.247)

Test Date: 2023-12-21 to 2023-12-29

Test Result: Complied

Report Date: 2024-01-08

Reviewed by:

Approved by:

Abel Chen

Project Engineer

Jacob Kong

Jacob Gong

Manager

Prepared by:

World Alliance Testing and Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen, Guangdong, People's Republic of China



This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★"

Report Template: TR-4-E-009/V1 Page 1 of 39





Announcement

- 1. This test report shall not be reproduced in full or partial, without the written approval of World Alliance Testing and Certification (Shenzhen) Co., Ltd
- 2. The results in this report apply only to the sample tested.
- 3. This sample tested is in compliance with the limits of the above regulation.
- 4. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.
- 5. The information marked "#" is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

Revision History

Version No.	Issued Date	Description
00	2024-01-08	Original

Report Template: TR-4-E-009/V1 Page 2 of 39



Contents

1	Gene	rai inio	ormation	4
	1.1	Client	t Information	4
	1.2	Produ	uct Description of EUT	4
	1.3	Anter	nna information	4
	1.4	Relat	ed Submittal(s)/Grant(s)	5
	1.5	Meas	urement Uncertainty	5
	1.6	Labor	ratory Location	5
	1.7	Test N	Methodology	5
2	Desc	ription	of Measurement	6
	2.1	Test (Configuration	6
	2.2	Test A	Auxiliary Equipment	6
	2.3	Test S	Setup	7
	2.4	Test F	Procedure	9
	2.5	Meas	urement Method	10
	2.6	Meas	urement Equipment	11
3	Test	Results	S	12
	3.1		Summary	
	3.2		, 	
	3.3	AC Li	ne Conducted Emissions Test Data	14
	3.4		ated emission Test Data	
	3.5		onducted Test Data	
		3.5.1	6 dB Emission Bandwidth and 99% Occupied Bandwidth	
		3.5.2	Maximum Conducted Peak Output Power	
	;	3.5.3	Maximum Conducted Average Output Power	28
	;	3.5.4	Power Spectral Density	28
	;	3.5.5	100 kHz Bandwidth of Frequency Band Edge	29
	;	3.5.6	Duty Cycle	
4	Test	Setup F	Photo	38
5	FIIT	· Photo		30



1 General Information

1.1 Client Information

Applicant:	Shenzhen Qianyan Technology LTD	
Address:	No.3301, Block C, Section 1, Chuangzhi Yuncheng Building, Liuxian Avenue, Xili Community, Xili Street, Nanshan District, Shenzhen, China	
Manufacturer:	Shenzhen Qianyan Technology LTD	
Address:	No.3301, Block C, Section 1, Chuangzhi Yuncheng Building, Liuxian Avenue, Xili Community, Xili Street, Nanshan District, Shenzhen, China	

1.2 Product Description of EUT

The EUT is Govee Outdoor Ground Lights 2 that contains 2.4G and BLE(1M), this report covers the full testing of the 2.4G WLAN radio.

Sample Serial Number	10-3 & 10-4 test, 10-1 & 10-3 & 10-4 for RE test, 10-2 for RF test conducted test(assigned by WATC)
Sample Received Date	2023-12-20
Sample Status	Good Condition
Frequency Range	2412MHz - 2472MHz(802.11b, g, n-HT20)
Maximum Conducted Peak Output Power	13.83dBm
Modulation Technology	DSSS, OFDM
Antenna Gain#	3.85dBi
Spatial Streams [#]	SISO (1TX, 1RX)
Operating Temperature#	-20 deg. C~45 deg. C
Power Supply	H7053: DC 24V/3A from adapter
	H7052: DC 24V/1.5A from adapter
Adapter Information	For H7053: Model: SOY-2400300US-306 Input: AC100-240V, 50/60Hz, 1.8A Output: DC 24.0V/3.0A For H7052: Model: B136L-240150-AdU Input: AC100-240V, 50/60Hz, 1.2A Output: DC 24.0V/1.5A
Modification	Sample No Modification by the test lab

1.3 Antenna information

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Device Antenna information:

The Wi-Fi antenna is an internal antenna which cannot replace by end-user. Please see product internal photos for details.

Report Template: TR-4-E-009/V1 Page 4 of 39



1.4 Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s)

1.5 Measurement Uncertainty

Para	meter	Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
AC Power Lines Condu	ucted Emissions	±3.14dB
Emissions, Radiated	Below 30MHz	±2.78dB
	Below 1GHz	±4.84dB
	Above 1GHz	±5.44dB
Emissions, Conducted		1.75dB
Conducted Power		0.74dB
Frequency Error		150Hz
Bandwidth		0.34%
Power Spectral Density		0.74dB

Note 1: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Note 2: The Decision Rule is based on simple acceptance with ISO Guide 98-4:2012 Clause 8.2 (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

1.6 Laboratory Location

World Alliance Testing and Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen, Guangdong, People's Republic of China

Tel: +86-755-29691511, Email: qa@watc.com.cn

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 463912, the FCC Designation No. : CN5040.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0160.

1.7 Test Methodology

FCC CFR 47 Part 2

FCC CFR 47 Part 15

KDB 558074 D01 DTS Meas Guidance v05r02

KDB 662911 D01 Multiple Transmitter Output v02r01

ANSI C63.10-2020

Report Template: TR-4-E-009/V1 Page 5 of 39



2 Description of Measurement

2.1 Test Configuration

Operating channels:						
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	
1	2412	6	2437	11	2462	
2	2417	7	2442	12	2467	
3	2422	8	2447	13	2472	
4	2427	9	2452	/	/	
5	2432	10	2457	/	/	

According to ANSI C63.10-2020 chapter 5.6.1 Table 11 requirement, select lowest channel, middle channel, and highest channel in the frequency range in which device operates for testing. The detailed frequency points are as follows:

802.11b, 802.11g, 802.11n-HT20							
Lowe	Lowest channel Middle channel Highest channel						
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)		
1	2412	7	2442	13	2472		

Test Mode:						
Transmitting mode:	Keep the EUT in	Keep the EUT in continuous transmitting with modulation				
Exercise software#:	AmebaZ2_mpto	AmebaZ2_mptool_1V3				
Mode	Worst-case Power Level Setting [#]					
Wode	Data rate	Low Channel	Middle Channel	High Channel		
802.11b	1Mbps	55	55	55		
802.11g	6Mbps	32	32	32		
802.11n-HT20	6.5Mbps	25	25	25		
The exercise softwar	re and the maximum	power setting that pro	vided by manufacture	er.		

Worst-Case Configuration:

For radiated emissions, EUT was investigated in three orthogonal orientation, the worst-case orientation was recorded in report

For AC power line conducted emission and radiated emission 9kHz-1GHz and above 18GHz were performed with the EUT transmits at the channel with highest output power as worst-case scenario.

For model H7053 and H7052, they have same control box(RF circuitry), difference for the lights and adapter, AC power line conducted emission and radiated emission 9kHz-1GHz test both two models, other items was select model H7053 to test.

2.2 Test Auxiliary Equipment


Manufacturer	Manufacturer Description		Serial Number
1	/	1	1

Report Template: TR-4-E-009/V1 Page 6 of 39



2.3 Test Setup


1) Conducted emission measurement:




Note: The 0.8 m distance specified between EUT/AE/PSU and AMN/AAN, is applicable only to the EUT being measured. If the device is AE then it shall be >0.8 m.

2) Radiated emission measurement:


Below 30MHz (3m SAC)











2.4 Test Procedure

Conducted emission:

- 1. The E.U.T is placed on a non-conducting table 40cm from the vertical ground plane and 80cm above the horizontal ground plane (Please refer to the block diagram of the test setup and photographs).
- Both sides of A.C. line are checked for maximum conducted interference. In order to find the
 maximum emission, the relative positions of equipment and all of the interface cables must be
 changed according to ANSI C63.10 on conducted measurement.
- 3. Line conducted data is recorded for both Line and Neutral

Radiated Emission Procedure:

a) For below 30MHz

- 1. All measurements were made at a test distance of 3 m. The measured data was extrapolated from the test distance (3m) to the specification distance (300 m from 9-490 kHz and 30 m from 490 kHz- 30 MHz) to clearly show the relative levels of fundamental and spurious emissions and demonstrate compliance with the requirement that the level of any spurious emissions be below the level of the intentionally transmitted signal. The extrapolation factor for the limits were 40*Log (test distance / specification distance).
- 2. Loop antenna use, investigation was done on the three antenna orientations (parallel, perpendicular, gound-parallel)

b) For 30MHz-1GHz:

- 1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m.
- 2. EUT works in each mode of operation that needs to be tested. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.

c) For above 1GHz:

1. The EUT was placed on the tabletop of a rotating table 1.5 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m (1-18GHz) and 1.5 m (above 18GHz).



- 2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.
- 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.
- 4. Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

RF Conducted Test:

- 1. The antenna port of EUT was connected to the RF port of the test equipment (Power Meter or Spectrum analyzer) through Attenuator and RF cable.
- 2. The cable assembly insertion loss of 7.0dB (including 6.0 dB Attenuator and 1.0 dB cable) was entered as an offset in the power meter. Note: Actual cable loss was unavailable at the time of testing, therefore a loss of 1.0dB was assumed as worst case. This was later verified to be true by laboratory. (if the RF cable provided by client, the cable loss declared by client)
- 3. The EUT is keeping in continuous transmission mode and tested in all modulation modes.

2.5 Measurement Method

Description of Test	Measurement Method	
AC Line Conducted Emissions	ANSI C63.10-2020 Section 6.2	
Maximum Conducted Output Power	ANSI C63.10-2020 Section 11.9.1.2 PKPM1 Peak power meter method or ANSI C63.10-2020 Section 11.9.2.3.2 Method AVGPM-G	
Power Spectral Density	ANSI C63.10-2020 Section 11.10.2 Method PKPSD (peak PSD)	
6 dB Emission Bandwidth	ANSI C63.10-2020 Section 11.8.1	
99% Occupied Bandwidth	ANSI C63.10-2020 Section 6.9.3	
100kHz Bandwidth of Frequency Band Edge	ANSI C63.10-2020 Section 6.10	
Radiated emission	ANSI C63.10-2020 Section 11.11&11.12	
Duty Cycle	ANSI C63.10-2020 Section 11.6	

Report Template: TR-4-E-009/V1 Page 10 of 39



2.6 Measurement Equipment

Manufacturer	Description	Model	Management	Calibration	Calibration
Manufacturer	Description	Model	No.	Date	Due Date
	AC	Line Conducted Em	nission Test		
ROHDE&	EMI TEST	ESR	101817	2023/7/3	2024/7/2
SCHWARZ	RECEIVER	LOIX	101017	2023/173	2024/1/2
R&S	LISN	ENV216	101748	2023/8/1	2024/7/31
N/A	Coaxial Cable	NO.12	N/A	2023/7/3	2024/7/2
Farad	Test Software	EZ-EMC	Ver. EMEC-3A1	1	/
	T	Radiated Emissio	n Test		
R&S	EMI test receiver	ESR3	102758	2023/7/3	2024/7/2
ROHDE& SCHWARZ	SPECTRUM ANALYZER	FSV40-N	101608	2023/7/3	2024/7/2
SONOMA INSTRUMENT	Low frequency amplifier	310	186014	2023/7/12	2024/7/11
COM-POWER	preamplifier	PAM-118A	18040152	2023/8/21	2024/8/20
COM-POWER	Amplifier	PAM-840A	461306	2023/8/8	2024/8/7
ETS	Passive Loop Antenna	6512	29604	2023/7/7	2024/7/6
SCHWARZBECK	Log - periodic wideband antenna	VULB 9163	9163-872	2023/7/7	2024/7/6
Astro Antenna Ltd	Horn antenna	AHA-118S	3015	2023/7/6	2024/7/5
Ducommun technologies	Horn Antenna	ARH-4223-02	1007726-03	2023/7/10	2024/7/9
Oulitong	Band Reject Filter	OBSF-2400-248 3.5-50N	OE02103119	2023/9/15	2024/9/14
N/A	Coaxial Cable	N/A	NO.9	2023/8/8	2024/8/7
N/A	Coaxial Cable	N/A	NO.10	2023/8/8	2024/8/7
N/A	Coaxial Cable	N/A	NO.11	2023/8/8	2024/8/7
Audix	Test Software	E3	191218 V9	/	/
		RF Conducted	Test		
ROHDE&	SPECTRUM	ESIL OC	200680/020	2022/7/42	2024/7/44
SCHWARZ	ANALYZER	FSU-26	200680/026	2023/7/12	2024/7/11
ANRITSU	USB Power Sensor	MA24418A	12620	2023/7/12	2024/7/11
narda	6dB attenuator	603-06-1	N/A	2023/7/26	2024/7/25

Note: All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or International standards.



3 Test Results

3.1 Test Summary

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
-	99% Occupied Bandwidth	Report only
§15.247(d)	100kHz Bandwidth of Frequency Band Edge	Compliance
§15.205, §15.209, §15.247(d)	Radiated emission	Compliance
-	Duty Cycle	Report only



3.2 Limit


Test items	Limit
AC Line Conducted Emissions	See details §15.207 (a)
Conducted Output Power	For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.
6dB Emission Bandwidth	The minimum 6 dB bandwidth shall be at least 500 kHz.
Power Spectral Density	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
Spurious Emissions, 100kHz Bandwidth of Frequency Band Edge	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.205(c)).



3.3 AC Line Conducted Emissions Test Data


Test Date:	2023-12-21	Test By:	Lirou Li
Environment condition:	Temperature: 23.1°C; Relative	Humidity:32%; ATM Pres	ssure: 101.6kPa

Model: H7053




Report Template: TR-4-E-009/V1







Model: H7052



Report Template: TR-4-E-009/V1

*:Maximum data


x:Over limit

!:over margin

Engineer Signature:

Lirou





Remark:

Measurement (dBuV)= Reading Level (dBuV) + Correct Factor(dB)

Correct Factor (dB)= LISN Voltage Division Factor (dB)+ Cable loss(dB)

Over Limit= Measurement – Limit



3.4 Radiated emission Test Data

9 kHz-30MHz:

Test Date:	2023-12-29	Test By:	Luke Li
Environment condition:	Temperature: 23.8°C; Relative	Humidity:48%; ATM Pres	ssure: 101.5kPa

For radiated emissions below 30MHz, there were no emissions found within 20dB of limit.


Report Template: TR-4-E-009/V1 Page 18 of 39



30MHz-1GHz:

Test Date:	2023-12-29	Test By:	Luke Li
Environment condition:	Temperature: 23.8°C; Relative	Humidity:48%; ATM Pres	ssure: 101.5kPa





Project No. : RWAZ202300086

EUT/Model No.: H7053 Test Mode : Transmitting Test Voltage : AC 120V/60Hz


Environment : 23.8℃/48%R.H./101.5kPa Tested by : Luke Li

Polarization : horizontal

Remark : 802.11b High Channel

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector	
1	44.333	38.73	-12.27	26.46	40.00	-13.54	Peak	
2	72.623	43.26	-17.30	25.96	40.00	-14.04	Peak	
3	119.331	46.42	-15.72	30.70	43.50	-12.80	Peak	
4	132.337	51.15	-17.40	33.75	43.50	-9.75	Peak	
5	183.040	51.51	-15.39	36.12	43.50	-7.38	Peak	
6	216.403	47.67	-13.78	33.89	46.00	-12.11	Peak	





Project No. : RWAZ202300086

EUT/Model No.: H7053

Test Mode : Transmitting Test Voltage : AC 120V/60Hz

Environment : 23.8℃/48%R.H./101.5kPa Tested by : Luke Li


Polarization : vertical

Remark : 802.11b High Channel

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector	
1	44.217	50.60	-12.28	38.32	40.00	-1.68	QP	
2	50.210	47.60	-12.16	35.44	40.00	-4.56	QP	
3	56.420	45.77	-12.97	32.80	40.00	-7.20	Peak	
4	76.177	51.91	-18.13	33.78	40.00	-6.22	QP	
5	90.498	41.35	-15.59	25.76	43.50	-17.74	Peak	
6	168.193	44.03	-16.44	27.59	43.50	-15.91	Peak	



Model: H7052



Project No. : RWAZ202300086

EUT/Model No.: H7052

Test Mode : Transmitting Test Voltage : AC 120V/60Hz


Environment : 23.8℃/48%R.H./101.5kPa

Tested by : Luke Li Polarization : horizontal

Remark : 802.11b High Channel

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector	
1	123.753	45.00	-16.58	28.42	43.50	-15.08	Peak	
2	180.017	45.91	-15.71	30.20	43.50	-13.30	Peak	
3	210.325	44.89	-13.91	30.98	43.50	-12.52	Peak	
4	245.198	39.96	-12.51	27.45	46.00	-18.55	Peak	
5	258.666	38.79	-12.27	26.52	46.00	-19.48	Peak	
6	276.124	36.55	-11.91	24.64	46.00	-21.36	Peak	





Project No. : RWAZ202300086

EUT/Model No.: H7052

Test Mode : Transmitting Test Voltage : AC 120V/60Hz

Environment : 23.8℃/48%R.H./101.5kPa

Tested by : Luke Li Polarization : vertical

Remark : 802.11b High Channel

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBµV/m)	Over Limit (dB)	Detector	
1	47.160	42.88	-12.18	30.70	40.00	-9.30	Peak	
2	53.201	42.90	-12.33	30.57	40.00	-9.43	Peak	
3	60.254	46.49	-13.70	32.79	40.00	-7.21	Peak	
4	64.320	44.53	-14.29	30.24	40.00	-9.76	Peak	
5	96.648	39.24	-14.63	24.61	43.50	-18.89	Peak	
6	179.701	40.79	-15.71	25.08	43.50	-18.42	Peak	

Remarks: Factor = Antenna factor + Cable loss - Preamp gain

Remark:

Level = Reading + Factor

Factor = Antenna factor + Cable loss - Amplifier gain

 $Over\ Limit = Level - Limit$



Above 1GHz:

Test Date:	2023-12-22	Test By:	Luke Li
Environment condition:	Temperature: 23.0°C; Relative	Humidity:60%; ATM Pres	ssure: 100.7kPa

Frequency (MHz)	Reading level (dBµV)	Polar	Corrected Factor (dB/m)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Remark		
802.11b									
			Low Ch	annel					
2390.000	37.50	horizontal	8.25	45.75	54.00	-8.25	Average		
2390.000	49.93	horizontal	8.25	58.18	74.00	-15.82	Peak		
2390.000	37.43	vertical	8.25	45.68	54.00	-8.32	Average		
2390.000	50.30	vertical	8.25	58.55	74.00	-15.45	Peak		
4824.000	49.80	horizontal	0.26	50.06	74.00	-23.94	Peak		
4824.000	50.05	vertical	0.26	50.31	74.00	-23.69	Peak		
			Middle C	hannel					
4884.000	48.96	horizontal	0.46	49.42	74.00	-24.58	Peak		
4884.000	49.46	vertical	0.46	49.92	74.00	-24.08	Peak		
			High Ch	annel					
2484.052	42.23	horizontal	8.25	50.48	54.00	-3.52	Average		
2484.052	54.01	horizontal	8.25	62.26	74.00	-11.74	Peak		
2483.500	37.85	vertical	8.25	46.10	54.00	-7.90	Average		
2483.500	50.87	vertical	8.25	59.12	74.00	-14.88	Peak		
4944.000	49.19	horizontal	0.83	50.02	74.00	-23.98	Peak		
4944.000	50.59	vertical	0.83	51.42	74.00	-22.58	Peak		
			802.1	1g					
			Low Cha	annel					
2390.000	37.57	horizontal	8.25	45.82	54.00	-8.18	Average		
2390.000	51.05	horizontal	8.25	59.30	74.00	-14.70	Peak		
2390.000	37.43	vertical	8.25	45.68	54.00	-8.32	Average		
2390.000	50.49	vertical	8.25	58.74	74.00	-15.26	Peak		
4824.000	49.59	horizontal	0.26	49.85	74.00	-24.15	Peak		
4824.000	49.46	vertical	0.26	49.72	74.00	-24.28	Peak		
			Middle C	hannel					
4884.000	49.70	horizontal	0.46	50.16	74.00	-23.84	Peak		
4884.000	48.92	vertical	0.46	49.38	74.00	-24.62	Peak		



	High Channel									
2483.500	40.13	horizontal	8.25	48.38	54.00	-5.62	Average			
2483.500	60.85	horizontal	8.25	69.10	74.00	-4.90	Peak			
2483.500	38.42	vertical	8.25	46.67	54.00	-7.33	Average			
2483.500	54.67	vertical	8.25	62.92	74.00	-11.08	Peak			
4944.000	48.43	horizontal	0.83	49.26	74.00	-24.74	Peak			
4944.000	50.01	vertical	0.83	50.84	74.00	-23.16	Peak			
			802.11	n20						
			Low Ch	annel						
2390.000	37.59	horizontal	8.25	45.84	54.00	-8.16	Average			
2390.000	50.28	horizontal	8.25	58.53	74.00	-15.47	Peak			
2390.000	37.50	vertical	8.25	45.75	54.00	-8.25	Average			
2390.000	49.36	vertical	8.25	57.61	74.00	-16.39	Peak			
4824.000	48.92	horizontal	0.26	49.18	74.00	-24.82	Peak			
4824.000	49.65	vertical	0.26	49.91	74.00	-24.09	Peak			
			Middle C	hannel						
4884.000	48.83	horizontal	0.46	49.29	74.00	-24.71	Peak			
4884.000	48.50	vertical	0.46	48.96	74.00	-25.04	Peak			
			High Ch	annel						
2483.500	39.50	horizontal	8.25	47.75	54.00	-6.25	Average			
2483.500	62.50	horizontal	8.25	70.75	74.00	-3.25	Peak			
2483.500	38.26	vertical	8.25	46.51	54.00	-7.49	Average			
2483.500	54.73	vertical	8.25	62.98	74.00	-11.02	Peak			
4944.000	48.78	horizontal	0.83	49.61	74.00	-24.39	Peak			
4944.000	50.19	vertical	0.83	51.02	74.00	-22.98	Peak			

Remark:

Corrected Amplitude= Reading level + corrected Factor

Corrected Factor = Antenna factor + Cable loss – Amplifier gain

Margin = Corrected Amplitude - Limit


For the test result of PK was more than 20dB below the PK limit, which can compliance with the average limit, just the PK level was recorded.

The emission levels of other frequencies that were lower than the limit 20dB not show in test report.

For emissions in 18GHz-25GHz range, all emissions were investigated and in the noise floor level.



Test plot for example as below:



Project No. : RWAZ202300086

EUT/Model No.: H7053 Test Mode : Transmitting Test Voltage : AC 120V/60Hz

Environment : $23.0\,^{\circ}\text{C}/60\%\text{R.H.}/100.7\text{kPa}$ Tested by : Luke Li

Polarization : horizontal


Remark : 802.11b High Channel

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector
1	4944.000	49.19	0.83	50.02	74.00	-23.98	Peak
2	15610.300	37.61	8.05	45.66	54.00	-8.34	Average
3	15610.300	49.88	8.05	57.93	74.00	-16.07	Peak
4	17923.460	38.15	8.20	46.35	54.00	-7.65	Average
5	17923.460	50.56	8.20	58.76	74.00	-15.24	Peak

2472MHz



Mode:



Channel:

Project No. : RWAZ202300086

EUT/Model No.: H7053 Test Mode : Transmitting Test Voltage : AC 120V/60Hz


Environment : 23.0℃/60%R.H./100.7kPa

802.11b

Tested by : Luke Li Polarization : vertical

Remark : 802.11b High Channel

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector
1	4944.000	50.59	0.83	51.42	74.00	-22.58	Peak
2	15610.300	37.47	8.05	45.52	54.00	-8.48	Average
3	15610.300	50.83	8.05	58.88	74.00	-15.12	Peak
4	17923.460	38.30	8.20	46.50	54.00	-7.50	Average
5	17923.460	50.85	8.20	59.05	74.00	-14.95	Peak





3.5 RF Conducted Test Data

Test Date:	2023-12-27	Test By:	Ryan Zhang	
Environment condition:	Temperature: 18°C; Relative Humidity: 41.5%; ATM Pressure: 102.3kPa			

3.5.1 6 dB Emission Bandwidth and 99% Occupied Bandwidth

Test Mode	Antenna	Channel[MHz]	6dB BW [MHz]	99% OBW[MHz]	6dB BW Limit[MHz]	Verdict	
	Ant1	2412	9.103	14.103	0.5	pass	
11B		2442	9.154	14.167	0.5	pass	
		2472	9.154	14.167	0.5	pass	
	Ant1	2412	16.577	16.731	0.5	pass	
11G		2442	16.679	16.731	0.5	pass	
		2472	16.577	16.795	0.5	pass	
	Ant1		2412	17.885	17.885	0.5	pass
11N20		2442	17.923	17.949	0.5	pass	
		2472	17.821	17.885	0.5	pass	

Report Template: TR-4-E-009/V1 Page 27 of 39



3.5.2 Maximum Conducted Peak Output Power

Test Mode	Antenna	Channel [MHz]	Result [dBm]	Limit [dBm]	Verdict
	Ant1	2412	13.30	30	Pass
11B SISO		2442	13.63	30	Pass
		2472	13.83	30	Pass
	Ant1	2412	7.20	30	Pass
11G SISO		2442	7.54	30	Pass
		2472	7.72	30	Pass
	Ant1	2412	6.02	30	Pass
11N20 SISO		2442	6.36	30	Pass
		2472	6.55	30	Pass

3.5.3 Maximum Conducted Average Output Power

Note: Report only

N/A

3.5.4 Power Spectral Density

Test Mode	Antenna	Channel [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
	Ant1	2412	-12.92	8	Pass
11B SISO		2442	-13.45	8	Pass
		2472	-13.15	8	Pass
	Ant1	2412	-29.66	8	Pass
11G SISO		2442	-29.49	8	Pass
		2472	-28.89	8	Pass
11N20 SISO	Ant1	2412	-30.64	8	Pass
		2442	-30.48	8	Pass
		2472	-30.34	8	Pass

Report Template: TR-4-E-009/V1 Page 28 of 39



3.5.5 100 kHz Bandwidth of Frequency Band Edge

Test Mode	Antenna	Channel	Result	Limit	Verdict
	A n+1	2412	Refer test plot	Refer test plot	Pass
11B SISO	Ant1	2472	Refer test plot	Refer test plot	Pass
	Ant1	2412	Refer test plot	Refer test plot	Pass
11G SISO		2472	Refer test plot	Refer test plot	Pass
	Ant1	2412	Refer test plot	Refer test plot	Pass
11N20 SISO		2472	Refer test plot	Refer test plot	Pass

3.5.6 Duty Cycle

Test Mode	Antenna	Channel	Ton (ms)	Ton+off (ms)	Duty Cycle [%]	1/Т	VBW setting* [Hz]
11B	Ant1	2442	100	100	100	/	10
11G	Ant1	2442	100	100	100	/	10
11N20	Ant1	2442	100	100	100	/	10


Note*: Radiated emission test with average value, the Spectrum analyzer VBW setting information.

Report Template: TR-4-E-009/V1 Page 29 of 39




Test Plots:

6 dB Emission Bandwidth:











99% Occupied Bandwidth:











Power Spectral Density:











100kHz Bandwidth of Frequency Band Edge:





Duty Cycle:





4 Test Setup Photo

Please refer to the attachment RWAZ202300086 Test Setup photo.



5 E.U.T Photo

Please refer to the attachment:

- (1) RWAZ202300086 H7053 External photo;
- (2) RWAZ202300086 H7053 Internal photo;
- (3) RWAZ202300086 H7052 External photo;
- (4) RWAZ202300086 H7052 Internal photo

---End of Report---

Report Template: TR-4-E-009/V1 Page 39 of 39