

## RF Exposure Evaluation Report

**Report Reference No.**..... : **MTEB24120133/1-H**

**FCC ID**..... : **2AB2Q13A21150WRGBWH**

Compiled by

( position+printed name+signature)..: File administrators Alisa Luo



Supervised by

( position+printed name+signature)..: Test Engineer Sunny Deng



Approved by

( position+printed name+signature)..: Manager Yvette Zhou



Date of issue.....: Jan.16,2025

**Representative Laboratory Name.:** **Shenzhen Most Technology Service Co., Ltd.**

Address.....: No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park,  
Nanshan, Shenzhen, Guangdong, China.

**Applicant's name**.....: **LEEDARSON LIGHTING CO., LTD.**

Address.....: Xingda Road, Xingtai Industrial Zone,  
Changtai County, Zhangzhou, Fujian, China

**Test specification/ Standard**.....: **47 CFR Part 1.1307**

**47 CFR Part 2.1093**

TRF Originator.....: Shenzhen Most Technology Service Co., Ltd.

**Shenzhen Most Technology Service Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description**.....: Smart LED Lamp

Trade Mark .....: N/A

Model/Type reference.....: 14cSA-A2550ST-Q1G-01,

Listed Models .....: 14ySA-A2550ST-Q1G-xx, 13A21150WRGBWHx  
Where "y" may be "a" to "z", which designates for different enclosure pattern design;  
"x and xx" may be "0" to "99", which designates for different package of style.

Modulation Type.....: GFSK

b: DSSS

g/n: OFDM

Operation Frequency.....: From 2402MHz to 2480MHz,2412MHz~2462MHz

Hardware Version.....: V2.0

Software Version.....: 1.0.2

Rating.....: AC 120V/60Hz

Result.....: PASS

**TEST REPORT**

Equipment under Test	:	Smart LED Lamp
Model /Type	:	14cSA-A2550ST-Q1G-01
Listed Models	:	14ySA-A2550ST-Q1G-xx, 13A21150WRGBWHx Where “y” may be “a” to “z”, which designates for different enclosure pattern design; “x and xx” may be “0” to “99”, which designates for different package of style.
Remark		Only model number and enclosure pattern design is different for these model.
Applicant	:	LEEDARSON LIGHTING CO., LTD.
Address	:	Xingda Road, Xingtai Industrial Zone, Changtai County, Zhangzhou, Fujian, China
Manufacturer 1	:	LEEDARSON LIGHTING CO., LTD.
Address 1	:	Xingtai Industrial Zone, Economic Development Zone, Changtai County, Zhangzhou city, Fujian Province, P.R.China
Manufacturer 2	:	LEEDARSON IOT TECHNOLOGY (THAILAND) CO., LTD.
Address 2	:	71, Moo5, Wellgrow Industrial Estate. Bang Samak, Bang Pakong District, Chachoengsao 24130

<b>Test Result:</b>	<b>PASS</b>
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

1. Revision History

Revision	Issue Date	Revisions	Revised By
00	2024.12.12	Initial Issue	Alisa Luo
01	2025.01.16	Filing case	Alisa Luo

Note:On the basis of the original report **MTEB24120133-R1**, report the spare shrapnel, which is connected to the rivet cover and mainly used for discharge without affecting RF performance. Re evaluate the radiation interference.

## 2. SAR Evaluation

### 2.1 RF Exposure Compliance Requirement

#### 2.1.1 Standard Requirement

According to §1.1307(e)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

#### 2.1.2 Limits

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	* (100)	6
3.0–30 .....	1842/f	4.89/f	* (900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	* (100)	30
1.34–30 .....	824/f	2.19/f	* (180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in

MHz Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where  $P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in

mW  $G$  = gain of antenna in linear

scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

## 2.1.3 EUT RF Exposure

## Measurement Data

## BLE

GFSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402MHz)	6.106	$6.106 \pm 1$	7.106
Middle(2441MHz)	7.803	$7.803 \pm 1$	8.803
Highest(2480MHz)	8.710	$8.710 \pm 1$	9.710

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Maximum Peak Conducted Output Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
Highest(2480 MHz)	9.710	9.35	-0.33	0.0017	1.0	Pass

Note: 1) Refer to report **MTEB24120133-R1** for EUT test Max Conducted average Output Power value.

Note: 2)  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2) = (9.35 \cdot 0.93) / (4 \cdot 3.1416 \cdot 20^2) = 0.0017$

Note: 3) EUT's Bluetooth module is more than 20cm away from the human body.

WIFI 2.4G

Antenna Gain: -0.33dBi

IEEE for 802.11b mode			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2412MHz)	17.27	$17.27 \pm 1$	18.27
Middle(2437MHz)	17.63	$17.63 \pm 1$	18.63
Highest(2462MHz)	17.96	$17.96 \pm 1$	18.96

IEEE for 802.11g mode			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2412MHz)	16.95	$16.95 \pm 1$	17.95
Middle(2437MHz)	17.94	$17.94 \pm 1$	18.94
Highest(2462MHz)	16.89	$16.89 \pm 1$	17.89

IEEE for 802.11n(HT20) mode			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2412MHz)	18.45	$18.45 \pm 1$	19.45
Middle(2437MHz)	17.37	$17.37 \pm 1$	18.37
Highest(2462MHz)	17.32	$17.32 \pm 1$	18.32

IEEE for 802.11n(HT40) mode			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2412MHz)	17.45	$17.45 \pm 1$	18.45
Middle(2437MHz)	17.28	$17.28 \pm 1$	18.28
Highest(2462MHz)	17.25	$17.25 \pm 1$	18.25

Worst case: 802.11n(HT20)						
Channel	Maximum Peak Conducted Output Power (dBm)	Maximum Peak Conducted Output Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
Highest(2412 MHz)	19.45	88.1	-0.33	0.0163	1.0	Pass

Note: 1) Refer to report **MTEB24120133-R2** for EUT test Max Conducted average Output Power value.

Note: 2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (88.1 * 0.93) / (4 * 3.1416 * 20^2) = 0.0163$

Note: 3) EUT's Bluetooth module is more than 20cm away from the human body.

.....**THE END OF REPORT**.....