

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	Digital Wireless Baby Monitor With Storage Capacity
Model Name	GD8220
FCC ID	TW5GD8220

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

$$P_t = 8.41 \text{ dBm} = 6.93 \text{ mW}$$

The result for RF exposure evaluation

$$\text{SAR} = (6.93 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.473875(\text{GHz})}] = 2.18 < 3.0 \text{ for 1-g SAR}$$

4. CONCLUSION

The SAR evaluation is not required.