

TEST REPORT

Product Name : Tablet pc
Brand Mark : tibuta
Model No. : T100
Extension mode : T101,T102
FCC ID : 2AXUI-T100
Report Number : BLA-EMC-202106-A2502
Date of Sample Receipt : 2021/6/8
Date of Test : 2021/6/8 to 2021/7/22
Date of Issue : 2021/7/22
Test Standard : 47 CFR Part 15, Subpart C 15.247
Test Result : Pass

Prepared for:

CHITECH SHENZHEN TECHNOLOGY CO.,LTD
Chitech industrial Park, NO.48, Xiashijia Road, Gongming Town,
Guangming New Dist., Shenzhen, China

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by:

Jozu.

Review by:

Sueels

Approved by:

Blue Zhong

Date:

2021/7/22



REPORT REVISE RECORD

Version No.	Date	Description
00	2021/7/22	Original

BlueAsia

TABLE OF CONTENTS

1	TEST SUMMARY	5
2	GENERAL INFORMATION	6
3	GENERAL DESCRIPTION OF E.U.T.	6
4	TEST ENVIRONMENT	7
5	TEST MODE	7
6	MEASUREMENT UNCERTAINTY	7
7	DESCRIPTION OF SUPPORT UNIT.....	8
8	LABORATORY LOCATION.....	8
9	TEST INSTRUMENTS LIST	9
10	POWER SPECTRUM DENSITY.....	13
10.1	LIMITS	13
10.2	BLOCK DIAGRAM OF TEST SETUP	13
10.3	TEST DATA.....	13
11	CONDUCTED PEAK OUTPUT POWER	14
11.1	LIMITS	14
11.2	BLOCK DIAGRAM OF TEST SETUP	14
11.3	TEST DATA.....	15
12	CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ).....	16
12.1	LIMITS	16
12.2	BLOCK DIAGRAM OF TEST SETUP	16
12.3	PROCEDURE	16
12.4	TEST DATA.....	18
13	ANTENNA REQUIREMENT	20
13.1	CONCLUSION	20
14	RADIATED SPURIOUS EMISSIONS.....	21
14.1	LIMITS	21
14.2	BLOCK DIAGRAM OF TEST SETUP	22
14.3	PROCEDURE	22
14.4	TEST DATA.....	24

15	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....	33
15.1	LIMITS	33
15.2	BLOCK DIAGRAM OF TEST SETUP	34
15.3	PROCEDURE	34
15.4	TEST DATA.....	36
16	CONDUCTED SPURIOUS EMISSIONS	52
16.1	LIMITS	52
16.2	BLOCK DIAGRAM OF TEST SETUP	52
16.3	TEST DATA.....	53
17	CONDUCTED BAND EDGES MEASUREMENT.....	54
17.1	LIMITS	54
17.2	BLOCK DIAGRAM OF TEST SETUP	54
17.3	TEST DATA.....	55
18	MINIMUM 6DB BANDWIDTH	56
18.1	LIMITS	56
18.2	BLOCK DIAGRAM OF TEST SETUP	56
18.3	TEST DATA.....	56
19	APPENDIX.....	57
19.1	MAXIMUM CONDUCTED OUTPUT POWER	57
19.2	-6DB BANDWIDTH	64
19.3	OCCUPIED CHANNEL BANDWIDTH.....	71
19.4	MAXIMUM POWER SPECTRAL DENSITY LEVEL	78
19.5	BAND EDGE.....	85
19.6	CONDUCTED RF SPURIOUS EMISSION	94
APPENDIX A: PHOTOGRAPHS OF TEST SETUP		107
APPENDIX B: PHOTOGRAPHS OF EUT		109

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5 & Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(1) & 15.247(b)(3)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass

2 GENERAL INFORMATION

Applicant	CHITECH SHENZHEN TECHNOLOGY CO.,LTD
Address	Chitech industrial Park,NO.48,Xiashijia Road,Gongming Town,Guangming New Dist.,Shenzhen,China
Manufacturer	CHITECH SHENZHEN TECHNOLOGY CO.,LTD
Address	Chitech industrial Park,NO.48,Xiashijia Road,Gongming Town,Guangming New Dist.,Shenzhen,China
Factory	CHITECH SHENZHEN TECHNOLOGY CO.,LTD
Address	Chitech industrial Park,NO.48,Xiashijia Road,Gongming Town,Guangming New Dist.,Shenzhen,China
Product Name	Tablet pc
Test Model No.	T100

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	863A_MB_V5.1
Software Version	Tibuta_MasterPad-T100_20210717
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Channel Spacing:	5MHz
Number of Channels:	802.11b/g/n(HT20):11 802.11n(HT40):7
Antenna Type:	Internal Antenna
Antenna Gain:	1.62dBi

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	DC3.7V

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
Transmitting mode	Keep the EUT in continuously transmitting mode with modulation. (Duty cycle≥98%)
Remark: Only the data of the worst mode would be recorded in this report.	

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
N/A	N/A	N/A	N/A	N/A

8 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

9 TEST INSTRUMENTS LIST

Test Equipment Of Power Spectrum Density					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Conducted Peak Output Power					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Shield room	SKET	833	N/A	2020/11/25	2023/11/24
Receiver	R&S	ESPI3	101082	2020/10/12	2021/10/11
LISN	R&S	ENV216	3560.6550.15	2020/10/12	2021/10/11
LISN	AT	AT166-2	AKK1806000003	2020/10/12	2021/10/11
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A

Test Equipment Of Antenna Requirement					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due

Test Equipment Of Radiated Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25

Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Conducted Spurious Emissions

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Conducted Band Edges Measurement

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Minimum 6dB Bandwidth

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11

Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

BlueAsia


10 POWER SPECTRUM DENSITY

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.10.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

10.1 LIMITS

Limit: $\leq 8\text{dBm}$ in any 3 kHz band during any time interval of continuous transmission

10.2 BLOCK DIAGRAM OF TEST SETUP



10.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details


11 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5 & Section 11.9.1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

11.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq \text{hopping channels} < 50$
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

11.2 BLOCK DIAGRAM OF TEST SETUP



11.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

12 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	Transmitting mode
Test Mode (Final Test)	Transmitting mode
Tester	Jozu
Temperature	25℃
Humidity	60%

12.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

12.2 BLOCK DIAGRAM OF TEST SETUP



12.3 PROCEDURE

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.


- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: $LISN = Read\ Level + Cable\ Loss + LISN\ Factor$

12.4 TEST DATA

[TestMode: Transmitting mode]; [Line: Neutral]

Conducted Emission Measurement



Site: Limit: FCC Class B Conduction(QP) EUT: Tablet pc M/N: Tibuta_MasterPad_T100 Mode: Wifi TX mode Note:

Phase: **N** Power: AC120V 60Hz Temperature: Humidity: %

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.3379	24.00	9.77	33.77	59.25	-25.48	QP	
2	0.3379	17.42	9.77	27.19	49.25	-22.06	AVG	
3	0.5140	35.28	9.79	45.07	56.00	-10.93	QP	
4 *	0.5140	29.49	9.79	39.28	46.00	-6.72	AVG	
5	0.6660	22.41	9.81	32.22	56.00	-23.78	QP	
6	0.6660	15.80	9.81	25.61	46.00	-20.39	AVG	
7	1.0540	24.79	9.84	34.63	56.00	-21.37	QP	
8	1.0540	17.30	9.84	27.14	46.00	-18.86	AVG	
9	2.0940	21.54	9.86	31.40	56.00	-24.60	QP	
10	2.0940	13.59	9.86	23.45	46.00	-22.55	AVG	
11	2.8260	20.40	9.89	30.29	56.00	-25.71	QP	
12	2.8260	12.43	9.89	22.32	46.00	-23.68	AVG	


*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMode: Transmitting mode]; [Line: Line]

Conducted Emission Measurement



Site: Phase: **L1** Temperature:
Limit: FCC Class B Conduction(QP) Power: AC120V 60Hz Humidity: %
EUT: Tablet pc
M/N: Tibuta_MasterPad_T100
Mode: Wifi TX mode
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1900	30.52	9.83	40.35	64.04	-23.69	QP	
2		0.1900	22.03	9.83	31.86	54.04	-22.18	AVG	
3		0.3620	21.36	9.85	31.21	58.68	-27.47	QP	
4		0.3620	15.66	9.85	25.51	48.68	-23.17	AVG	
5		0.5180	41.22	9.87	51.09	56.00	-4.91	QP	
6	*	0.5180	34.63	9.87	44.50	46.00	-1.50	AVG	
7		0.9540	31.85	9.92	41.77	56.00	-14.23	QP	
8		0.9540	23.35	9.92	33.27	46.00	-12.73	AVG	
9		2.0780	29.60	9.94	39.54	56.00	-16.46	QP	
10		2.0780	20.05	9.94	29.99	46.00	-16.01	AVG	
11		2.4260	28.67	9.95	38.62	56.00	-17.38	QP	
12		2.4260	19.19	9.95	29.14	46.00	-16.86	AVG	

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

13 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A


13.1 CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 1.62dBi.



14 RADIATED SPURIOUS EMISSIONS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

14.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

14.2 BLOCK DIAGRAM OF TEST SETUP



14.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

14.4 TEST DATA

Remark: During the test, pre-scan the 802.11b/g/n mode, and found the 802.11b mode which it is worse case.

[TestMode: TX 11B low channel]; [Polarity: Horizontal]



*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

BlueAsia

[TestMode: TX 11B low channel]; [Polarity: Vertical]


Radiated Emission Measurement

File: WIF12
80.0 dBuV/m

Data: #4

Date: 2021/7/12 星期

Time: 下午 4:36:06



Site

Polarization: **Vertical**

Temperature:

Limit: FCC Part15 (PK)

Power:

Humidity: %

EUT: Tablet pc

Distance:

M/N: Tibuta-MasterPad-T100

Mode: B-TX-L

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1	*	4824.000	49.35	3.62	52.97	74.00	-21.03	peak		
2		4830.500	49.39	3.58	52.97	74.00	-21.03	peak		
3		7326.000	41.16	6.44	47.60	74.00	-26.40	peak		
4		9648.000	40.50	9.37	49.87	74.00	-24.13	peak		

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX 11B mid channel]; [Polarity: Vertical]

Radiated Emission Measurement


File: WIF12

Data: #5

Date: 2021/7/12 星期

Time: 下午 4:39:02

80.0 dBuV/m



Site

Polarization: **Vertical**

Temperature:

Limit: FCC Part15 (PK)

Power:

Humidity: %

EUT: Tablet pc

Distance:

M/N: Tibuta-MasterPad-T100

Mode: B-TX-M

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1	*	4877.500	48.08	3.37	51.45	74.00	-22.55	peak		
2		7311.000	41.14	6.37	47.51	74.00	-26.49	peak		
3		9748.000	40.86	9.59	50.45	74.00	-23.55	peak		

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX 11B mid channel]; [Polarity: Horizontal]

Radiated Emission Measurement


File: WIFI2

Data: #6

Date: 2021/7/12 星期

Time: 下午 4:41:25

80.0 dBuV/m



Site

Polarization: **Horizontal**

Temperature:

Limit: FCC Part15 (PK)

Power:

Humidity: %

EUT: Tablet pc

Distance:

M/N: Tibuta-MasterPad-T100

Mode: B-TX-M

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		4877.500	46.57	3.37	49.94	74.00	-24.06	peak		
2		7311.000	41.08	6.37	47.45	74.00	-26.55	peak		
3	*	9748.000	40.63	9.59	50.22	74.00	-23.78	peak		

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX 11B high channel]; [Polarity: Horizontal]

Radiated Emission Measurement


File: WIF12

Data: #7

Date: 2021/7/12 星期

Time: 下午 4:46:24

80.0 dBuV/m



Site

Polarization: **Horizontal**

Temperature:

Limit: FCC Part15 (PK)

Power:

Humidity: %

EUT: Tablet pc

Distance:

M/N: Tibuta-MasterPad-T100

Mode: B-TX-H

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1	*	4924.500	46.92	3.47	50.39	74.00	-23.61	peak		
2		7386.000	41.46	6.68	48.14	74.00	-25.86	peak		
3		9848.000	39.76	9.88	49.64	74.00	-24.36	peak		

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMode: TX 11B high channel]; [Polarity: Vertical]

Radiated Emission Measurement


File: WIF12

Data: #8

Date: 2021/7/12 星期

Time: 下午 4:49:11

80.0 dBuV/m



Site

Polarization: **Vertical**

Temperature:

Limit: FCC Part15 (PK)

Power:

Humidity: %

EUT: Tablet pc

Distance:

M/N: Tibuta-MasterPad-T100

Mode: B-TX-H

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		4924.000	45.39	3.46	48.85	74.00	-25.15	peak		
2	*	7386.000	42.65	6.68	49.33	74.00	-24.67	peak		
3		9848.000	39.16	9.88	49.04	74.00	-24.96	peak		

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX mode (SE) below 1G]; [Polarity: Horizontal]

Radiated Emission Measurement


File: REL

Data: #4

Date: 2021/7/20

Time: 15:45:51

80.0 dBuV/m



Site

Polarization: **Horizontal**

Temperature:

Limit: FCC Part15 Class B

Power:

Humidity: %

EUT: Tablet pc

Distance:

M/N: Tibuta-MasterPad-T100

Mode: WIFI mode

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		31.9438	39.25	-20.29	18.96	40.00	-21.04	QP		
2	*	63.0461	44.12	-19.90	24.22	40.00	-15.78	QP		
3		140.8015	35.45	-19.06	16.39	43.50	-27.11	QP		
4		311.8636	43.18	-18.06	25.12	46.00	-20.88	QP		
5		630.6612	33.31	-10.54	22.77	46.00	-23.23	QP		
6		986.3927	37.40	-5.37	32.03	54.00	-21.97	QP		

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX mode (SE) below 1G]; [Polarity: Vertical]

Radiated Emission Measurement


File:REL

Data :#3

Date: 2021/7/20

Time: 15:43:32

80.0 dBuV/m



Site

Polarization: **Vertical**

Temperature:

Limit: FCC Part15 Class B

Power:

Humidity: %

EUT: Tablet pc

Distance:

M/N: Tibuta-MasterPad-T100

Mode: WIFI mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1	*	45.5511	50.84	-18.89	31.95	40.00	-8.05	QP		
2		61.1022	45.22	-19.49	25.73	40.00	-14.27	QP		
3		123.3066	45.81	-19.75	26.06	43.50	-17.44	QP		
4		154.4088	48.04	-19.17	28.87	43.50	-14.63	QP		
5		311.8637	37.23	-18.06	19.17	46.00	-26.83	QP		
6		677.3146	35.31	-10.16	25.15	46.00	-20.85	QP		

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

15 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

15.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

15.2 BLOCK DIAGRAM OF TEST SETUP



15.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamplifier Factor}$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

15.4 TEST DATA

[TestMode: TX 11B low channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: Tablet pc
M/N: Tibuta-MasterPad-T100
Mode: B-TX-L
Note:

Polarization: **Horizontal** Temperature:
Power: Humidity: %
Distance:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		2310.000	49.79	-4.61	45.18	74.00	-28.82	peak		
2		2387.660	68.62	-4.29	64.33	74.00	-9.67	peak		
3	*	2387.660	53.03	-4.29	48.74	54.00	-5.26	AVG		
4		2390.000	68.10	-4.27	63.83	74.00	-10.17	peak		
5		2390.000	49.48	-4.27	45.21	54.00	-8.79	AVG		

*:Maximum data x:Over limit !:over margin

〈Reference Only

Test Result: Pass

[TestMode: TX 11B low channel]; [Polarity: Vertical]

Radiated Emission Measurement

File: WIF12
107.0 dBuV/m

Data :#2

Date: 2021/7/12 星期

Time: 下午 3:56:21



Site
Limit: FCC Part15 (PK)
EUT: Tablet pc
M/N: Tibuta-MasterPad-T100
Mode: B-TX-L
Note:

Polarization: **Vertical**
Power:
Distance:

Temperature:
Humidity: %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		2310.000	53.71	-4.61	49.10	74.00	-24.90	peak		
2		2388.540	72.44	-4.29	68.15	74.00	-5.85	peak		
3	*	2388.540	53.25	-4.29	48.96	54.00	-5.04	AVG		
4		2390.000	68.68	-4.27	64.41	74.00	-9.59	peak		
5		2390.000	50.61	-4.27	46.34	54.00	-7.66	AVG		

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMode: TX 11B high channel]; [Polarity: Vertical]


Radiated Emission Measurement

File: WIFI2
107.0 dBuV/m

Data :#9

Date: 2021/7/12 星期

Time: 下午 4:53:10



Site

Polarization: **Vertical**

Temperature:

Limit: FCC Part15 (PK)

Power:

Humidity: %

EUT: Tablet pc

Distance:

M/N: Tibuta-MasterPad-T100

Mode: B-TX-H

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2483.500	70.76	-3.84	66.92	74.00	-7.08	peak		
2		2483.500	49.09	-3.84	45.25	54.00	-8.75	AVG		
3	*	2487.400	76.15	-3.84	72.31	74.00	-1.69	peak		
4		2487.400	52.80	-3.84	48.96	54.00	-5.04	AVG		
5		2500.000	62.33	-3.78	58.55	74.00	-15.45	peak		
6		2500.000	49.15	-3.78	45.37	54.00	-8.63	AVG		

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX 11B high channel]; [Polarity: Horizontal]


Radiated Emission Measurement

File: WIFI2
107.0 dBuV/m

Data :#10

Date: 2021/7/12 星期

Time: 下午 4:59:43



Site

Polarization: **Horizontal**

Temperature:

Limit: FCC Part15 (PK)

Power:

Humidity: %

EUT: Tablet pc

Distance:

M/N: Tibuta-MasterPad-T100

Mode: B-TX-H

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		2483.500	69.05	-3.84	65.21	74.00	-8.79	peak		
2		2483.500	49.82	-3.84	45.98	54.00	-8.02	AVG		
3		2486.770	70.35	-3.84	66.51	74.00	-7.49	peak		
4	*	2486.770	52.71	-3.84	48.87	54.00	-5.13	AVG		
5		2500.000	59.76	-3.78	55.98	74.00	-18.02	peak		
6		2500.000	50.12	-3.78	46.34	54.00	-7.66	AVG		

*:Maximum data x:Over limit !:over margin


<Reference Only

Test Result: Pass

[TestMode: TX 11G high channel]; [Polarity: Horizontal]

Radiated Emission Measurement

File: WIFI2 Data: #11 Date: 2021/7/12 星期 Time: 下午 5:06:37
107.0 dBuV/m



Site: Polarization: **Horizontal** Temperature:
Limit: FCC Part15 (PK) Power: Humidity: %
EUT: Tablet pc Distance:
M/N: Tibuta-MasterPad-T100
Mode: G-TX-H
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2483.500	67.88	-3.84	64.04	74.00	-9.96	peak		
2		2483.500	51.17	-3.84	47.33	54.00	-6.67	AVG		
3		2490.370	71.56	-3.81	67.75	74.00	-6.25	peak		
4	*	2490.370	52.38	-3.81	48.57	54.00	-5.43	AVG		
5		2500.000	60.72	-3.78	56.94	74.00	-17.06	peak		
6		2500.000	50.03	-3.78	46.25	54.00	-7.75	AVG		

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMode: TX 11G high channel]; [Polarity: Vertical]


Radiated Emission Measurement

File: WIFI2
107.0 dBuV/m

Data :#12

Date: 2021/7/12 星期

Time: 下午 5:09:26



Site

Polarization: **Vertical**

Temperature:

Limit: FCC Part15 (PK)

Power:

Humidity: %

EUT: Tablet pc

Distance:

M/N: Tibuta-MasterPad-T100

Mode: G-TX-H

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		2483.500	71.88	-3.84	68.04	74.00	-5.96	peak		
2		2483.500	51.23	-3.84	47.39	54.00	-6.61	AVG		
3	*	2491.720	74.49	-3.81	70.68	74.00	-3.32	peak		
4		2491.720	52.40	-3.81	48.59	54.00	-5.41	AVG		
5		2500.000	62.58	-3.78	58.80	74.00	-15.20	peak		
6		2500.000	50.12	-3.78	46.34	54.00	-7.66	AVG		


*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMode: TX 11G low channel]; [Polarity: Horizontal]

Radiated Emission Measurement



Site: Polarization: **Horizontal** Temperature:
Limit: FCC Part15 (PK) Power: Humidity: %
EUT: Tablet pc Distance:
M/N: Tibuta-MasterPad-T100
Mode: G-TX-L
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2310.000	53.00	-4.61	48.39	74.00	-25.61	peak		
2		2381.300	68.18	-4.32	63.86	74.00	-10.14	peak		
3	*	2381.300	52.28	-4.32	47.96	54.00	-6.04	AVG		
4		2390.000	67.82	-4.27	63.55	74.00	-10.45	peak		
5		2390.000	51.61	-4.27	47.34	54.00	-6.66	AVG		

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMode: TX 11G low channel]; [Polarity: Vertical]


Radiated Emission Measurement

File: WIFI2
107.0 dBuV/m

Data :#20

Date: 2021/7/12 星期

Time: 下午 5:45:19



Site

Polarization: **Vertical**

Temperature:

Limit: FCC Part15 (PK)

Power:

Humidity: %

EUT: Tablet pc

Distance:

M/N: Tibuta-MasterPad-T100

Mode: G-TX-L

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		2310.000	55.62	-4.61	51.01	74.00	-22.99	peak		
2		2381.530	72.51	-4.32	68.19	74.00	-5.81	peak		
3	*	2381.530	52.71	-4.32	48.39	54.00	-5.61	AVG		
4		2390.000	67.57	-4.27	63.30	74.00	-10.70	peak		
5		2390.000	67.57	-4.27	63.30	74.00	-10.70	peak		
6		2390.000	51.56	-4.27	47.29	54.00	-6.71	AVG		

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX N20 high channel]; [Polarity: Vertical]


Radiated Emission Measurement

File: WIF12
107.0 dBuV/m

Data: #21

Date: 2021/7/20

Time: 16:25:29



Site

Polarization: **Vertical**

Temperature:

Limit: FCC Part15 (PK)

Power:

Humidity: %

EUT: Tablet pc

Distance: 3m

M/N: Tibuta-MasterPad-T100

Mode: N20-TX-H

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1	*	2483.500	46.71	-3.84	42.87	74.00	-31.13	peak		
2		2500.000	45.76	-3.78	41.98	74.00	-32.02	peak		

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX N20 high channel]; [Polarity: Horizontal]


Radiated Emission Measurement

File: WIFI2
107.0 dBuV/m

Data :#22

Date: 2021/7/20

Time: 16:27:18



Site

Polarization: **Horizontal**

Temperature:

Limit: FCC Part15 (PK)

Power:

Humidity: %

EUT: Tablet pc

Distance: 3m

M/N: Tibuta-MasterPad-T100

Mode: N20-TX-H

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		2483.500	59.37	-3.84	55.53	74.00	-18.47	peak		
2	*	2483.500	52.20	-3.84	48.36	54.00	-5.64	AVG		
3		2500.000	45.63	-3.78	41.85	74.00	-32.15	peak		

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX N20 low channel]; [Polarity: Vertical]


Radiated Emission Measurement

File: WIF12
107.0 dBuV/m

Data: #23

Date: 2021/7/20

Time: 16:38:22



Site

Polarization: **Vertical**

Temperature:

Limit: FCC Part15 (PK)

Power:

Humidity: %

EUT: Tablet pc

Distance: 3m

M/N: Tibuta-MasterPad-T100

Mode: N20-TX-L

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2310.000	45.75	-4.61	41.14	74.00	-32.86	peak		
2	*	2390.000	45.74	-4.27	41.47	74.00	-32.53	peak		

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX N20 low channel]; [Polarity: Horizontal]


Radiated Emission Measurement

File: WIFI2
107.0 dBuV/m

Data :#24

Date: 2021/7/20

Time: 16:40:31



Site

Polarization: **Horizontal**

Temperature:

Limit: FCC Part15 (PK)

Power:

Humidity: %

EUT: Tablet pc

Distance: 3m

M/N: Tibuta-MasterPad-T100

Mode: N20-TX-L

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2310.000	45.91	-4.61	41.30	74.00	-32.70	peak		
2		2390.000	58.55	-4.27	54.28	74.00	-19.72	peak		
3	*	2390.000	53.23	-4.27	48.96	54.00	-5.04	AVG		

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX N40 low channel]; [Polarity: Horizontal]


Radiated Emission Measurement

File: WIFI2
107.0 dBuV/m

Data :#25

Date: 2021/7/20

Time: 16:44:07



Site
Limit: FCC Part15 (PK)
EUT: Tablet pc
M/N: Tibuta-MasterPad-T100
Mode: N40-TX-L
Note:

Polarization: **Horizontal**
Power:
Distance: 3m

Temperature:
Humidity: %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		2310.000	46.39	-4.61	41.78	74.00	-32.22	peak		
2	*	2390.000	62.18	-4.27	57.91	74.00	-16.09	peak		
3		2390.000	42.06	-4.27	37.79	54.00	-16.21	AVG		

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMode: TX N40 low channel]; [Polarity: Vertical]


Radiated Emission Measurement

File: WIF12
107.0 dBuV/m

Data :#26

Date: 2021/7/20

Time: 16:47:19



Site

Polarization: **Vertical**

Temperature:

Limit: FCC Part15 (PK)

Power:

Humidity: %

EUT: Tablet pc

Distance: 3m

M/N: Tibuta-MasterPad-T100

Mode: N40-TX-L

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		2310.000	46.16	-4.61	41.55	74.00	-32.45	peak		
2	*	2390.000	52.66	-4.27	48.39	74.00	-25.61	peak		

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX N40 high channel]; [Polarity: Vertical]


Radiated Emission Measurement

File: WIF12
107.0 dBuV/m

Data: #27

Date: 2021/7/20

Time: 16:50:24



Site

Polarization: **Vertical**

Temperature:

Limit: FCC Part15 (PK)

Power:

Humidity: %

EUT: Tablet pc

Distance: 3m

M/N: Tibuta-MasterPad-T100

Mode: N40-TX-H

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1	*	2483.500	55.42	-3.84	51.58	74.00	-22.42	peak		
2		2500.000	50.36	-3.78	46.58	74.00	-27.42	peak		

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX N40 high channel]; [Polarity: Horizontal]


Radiated Emission Measurement

File: WIFI2
107.0 dBuV/m

Data: #28

Date: 2021/7/20

Time: 16:52:02



Site

Polarization: **Horizontal**

Temperature:

Limit: FCC Part15 (PK)

Power:

Humidity: %

EUT: Tablet pc

Distance: 3m

M/N: Tibuta-MasterPad-T100

Mode: N40-TX-H

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		2483.500	62.89	-3.84	59.05	74.00	-14.95	peak		
2	*	2483.500	52.61	-3.84	48.77	54.00	-5.23	AVG		
3		2500.000	57.32	-3.78	53.54	74.00	-20.46	peak		
4		2500.000	51.13	-3.78	47.35	54.00	-6.65	AVG		

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass


16 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

16.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

16.2 BLOCK DIAGRAM OF TEST SETUP



16.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia


17 CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

17.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

17.2 BLOCK DIAGRAM OF TEST SETUP



17.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia


18 MINIMUM 6DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.8.1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

18.1 LIMITS

Limit:	≥ 500 kHz
--------	----------------

18.2 BLOCK DIAGRAM OF TEST SETUP



18.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details