


Prüfbericht-Nr.: <i>Test report no.:</i>	IN25YR31 001	Auftrags-Nr.: <i>Order no.:</i>	146966291 010	Seite 1 von 7 Page 1 of 7	
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	2390953	Auftragsdatum: <i>Order date:</i>	2024-09-24		
Auftraggeber: <i>Client:</i>	Proxim Wireless Corporation 2114 Ringwood Avenue, San Jose, California 95131				
Prüfgegenstand: <i>Test item:</i>	EdgeAX 5GHz Radio Module				
Bezeichnung <i>Identification</i>	Edge AX5				
Auftrags-Inhalt: <i>Order content:</i>	Maximum Permissible Exposure				
Prüfgrundlage: <i>Test specification:</i>	FCC 1.1310, and RSS 102 Issue 6 KDB 447498 D01				
Wareneingangsdatum: <i>Date of sample receipt:</i>	2024-07-02				
Prüfmuster-Nr.: <i>Test sample no:</i>	A003759215-012				
Serien -Nr.: <i>Serial no.:</i>	A003759215-005				
Prüfzeitraum: <i>Testing period:</i>	2024-08-05 - 2024-12-30				
Ort der Prüfung: <i>Place of testing:</i>	Wireless laboratory, Bangalore				
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (India) Pvt. Ltd. 27/B, 2nd cross road, Electronic city Phase 1, Bangalore-560100, India FCC Test Site Registration No: 496599 IC Test Site Registration No: 27711				
Prüfergebnis*: <i>Test result*:</i>	Pass				
geprüft von: <i>tested by:</i>	genehmigt von: <i>authorized by:</i>				
Datum: <i>Date:</i> 2025-02-18	Ausstellatum: <i>Issue date:</i> 2025-02-18				
Stellung / Position:	M.V.Naveen Kumar Senior Engineer	Stellung / Position:	Madhu K.N Assistant Manager		
Sonstiges / Other:	FCC ID: HZB-MEGA5 IC: 1856A-MEGA5 HVIN: Megabit 5 dual				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>				
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	4 = ausreichend N/A = nicht anwendbar	5 = mangelhaft N/T = nicht getestet
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory F(ail) = failed a.m. test specification(s)	4 = sufficient N/A = not applicable	5 = poor N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>					

V05

Prüfbericht - Nr.:

Test Report No.:

IN25YR31 001

Seite 2 von 7

Page 2 of 7

- | | |
|---|---|
| 1 | <p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.</p> <p>Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p> |
| 2 | <p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben.</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged.</i></p> |
| 3 | <p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben.</p> <p>Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i></p> <p><i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p> |
| 4 | <p>Die Entscheidungsregel für Konformitätserklärungen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird.</p> <p><i>The decision rule for statements of conformity in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report.</i></p> |

1 Maximum Permissible Exposure

1.1 RF Exposure Compliance Requirement

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

1.2 RF Exposure Limits:

1.2.1 For FCC

1. According to FCC Part 1 Subpart I 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b) showed in Table 1.

Table 1: Limits for Maximum Permissible Exposure (MPE) as per FCC			
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	F/300
1500 - 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	F/1500
1500 - 100000	--	--	1.0

F or f = Frequency in MHz

Friss Formula

Friss Transmission Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation.

Prüfbericht - Nr.:

Test Report No.:

IN25YR31 001

Seite 4 von 7

Page 4 of 7

Test Results:

Antenna details:

Manufacturer	Antenna Name	Antenna Model	Antenna Gain/used Frequency range
Telimart India	Omni Directional Antenna	TM55D-HVOMNI-12	2 X 12±0.5/ 5.15 to 5.850GHz
Telimart India	Dual Polarization Sector Antenna	TM55D-HVSCTR-21	2 X 21±0.5/ 5.15 to 5.850GHz
Telimart India	Dual Polarization Directional Antenna	MT-466010/NVH	2 X 28±1.0/ 5.15 to 5.850GHz
Kingnet	15dBi Plane Antenna For NGP_LCP	XD1C-B180B15D-01A	15dBi 5.15-585GHz
SIGNAL PLUS TECHNOLOGY	Dual Polarization Integrated Panel Antenna	4900-5900MHz Panel Antenna	23dBi

Note:

The Conducted output power including Tune-up Tolerance for each antenna/bands as below, which was declared by manufacturer.

Antenna Model	Frequency Range (MHz)	Conducted Output Power including tune-up Tolerance (dBm)
TM55D-HVOMNI-12	5250MHz to 5350MHz	11.96
	5470MHz to 5725MHz	12.44
TM55D-HVSCTR-21	5250MHz to 5350MHz	1.88
	5470MHz to 5725MHz	2.42
MT-466010/NVH	5250MHz to 5350MHz	-6.60
	5470MHz to 5725MHz	-5.76
XD1C-B180B15D-01A	5250MHz to 5350MHz	10.99
	5470MHz to 5725MHz	11.53
4900-5900MHz Panel Antenna	5250MHz to 5350MHz	-2.32
	5470MHz to 5725MHz	-1.60

Prüfbericht - Nr.:
Test Report No.:

IN25YR31 001

Seite 5 von 7
Page 5 of 7

Antenna Model	Frequency (MHz)	Maximum measured RF output power with tune-up tolerance (dBm)	Max power Including tune-up tolerance * (mW)	Antenna Gain in linear	Min Separation distance (CM)	Power Density (Pd) (mW/cm²)	FCC Limit (mW/cm²)
TM55D-HVOMNI-12	5250MHz to 5350	11.96	15.7036	15.8489	20	0.0495	1
	5470MHz to 5725MHz	12.44	17.5388	15.8489	20	0.0553	1
TM55D-HVSCTR-21	5250MHz to 5350	11.88	15.4170	125.8925	20	0.3861	1
	5470MHz to 5725MHz	12.42	17.4582	125.8925	20	0.4372	1
MT-466010/NVH	5250MHz to 5350	3.4	2.1878	630.9573	20	0.2746	1
	5470MHz to 5725MHz	4.24	2.6546	630.9573	20	0.3332	1
XD1C-B180B15D-01A	5250MHz to 5350	10.99	12.5603	31.6228	20	0.0790	1
	5470MHz to 5725MHz	11.53	14.2233	31.6228	20	0.0895	1
4900-5900MHz Panel Antenna	5250MHz to 5350	5.68	3.6983	199.5262	20	0.1468	1
	5470MHz to 5725MHz	6.4	4.3652	199.5262	20	0.1733	1

***Note:** Maximum conducted output power taken from test Reports: **IN25YR31 001**

Prüfbericht - Nr.:
Test Report No.:

IN25YR31 001

Seite 6 von 7
Page 6 of 7

1.2.2 For IC

According to IC RSS 102 Issue 6: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radiofrequency (RF) radiation as specified in section 5.3.2 showed in Table 7.

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ <i>f</i>	-	6**
1.1-10	87/ <i>f</i> ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ <i>f</i> ^{0.25}	0.1540/ <i>f</i> ^{0.25}	8.944/ <i>f</i> ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 <i>f</i> ^{0.3417}	0.008335 <i>f</i> ^{0.3417}	0.02619 <i>f</i> ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ <i>f</i> ^{1.2}
150000-300000	0.158 <i>f</i> ^{0.5}	4.21 x 10 ⁻⁴ <i>f</i> ^{0.5}	6.67 x 10 ⁻⁵ <i>f</i>	616000/ <i>f</i> ^{1.2}

Note: *f* is frequency in MHz.
*Based on nerve stimulation (NS).
** Based on specific absorption rate (SAR).

Antenna Model	Frequency (MHz)	Maximum measured RF output power with tune-up tolerance (dBm)	Max power including tune-up tolerance * (mW)	Antenna Gain in linear	Min Separation distance (CM)	Power Density (Pd) (W/m ²)	IC Limit (W/m ²)
TM55D-HVOMNI-12	5250MHz to 5350	11.96	15.7036	15.8489	20	0.4951	9.1305
	5470MHz to 5725MHz	12.44	17.5388	15.8489	20	0.5530	9.3902
TM55D-HVSCTR-21	5250MHz to 5350	11.88	15.4170	125.8925	20	3.8613	9.1305
	5470MHz to 5725MHz	12.42	17.4582	125.8925	20	4.3725	9.3902
MT-466010/NVH	5250MHz to 5350	3.4	2.1878	630.9573	20	2.7462	9.1305
	5470MHz to 5725MHz	4.24	2.6546	630.9573	20	3.3322	9.3902
XD1C-B180B15D-01A	5250MHz to 5350	10.99	12.5603	31.6228	20	0.7902	9.1305
	5470MHz to 5725MHz	11.53	14.2233	31.6228	20	0.8948	9.3902
4900-5900MHz Panel Antenna	5250MHz to 5350	5.68	3.6983	199.5262	20	1.4680	9.1305
	5470MHz to 5725MHz	6.4	4.3652	199.5262	20	1.7327	9.3902

Prüfbericht - Nr.:
Test Report No.:

IN25YR31 001

Seite 7 von 7
Page 7 of 7

1.3 Conclusion

The Power density of the EUT is less than defined limit as shown above, hence EUT is exempted from routine SAR.